

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P853612

Luminaire Tested: SQ2-BBN-075D-935-UNV-STD-W-4

Issue Date: 7/12/2024

Test Information

Test Method: LM-79-2019
Report Number: P853612
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2308-130-1)
Test Lab: INNOVATION CENTER
Issue Date: 7/12/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ2-BBN-075D-935-UNV-STD-W-4
Description: CORELITE SQ2 SURFACE LED LUMINAIRE
DOWNLIGHT 750 LUMENS PER FOOT
DIRECT ONLY
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3001.8 lumens
Efficiency: N/A
Efficacy: 108.8 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.62
Luminous Opening: Rectangular (W 0.17' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 27.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P853612
CATALOG NUMBER: SQ2-BBN-075D-935-UNV-STD-W-4

Luminous Intensity Polar Plot





TEST NUMBER: P853612

CATALOG NUMBER: SQ2-BBN-075D-935-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94
2	108	104	100	97	106	102	99	96	99	96	94	96	94	92	93	91	90	88
3	103	97	93	89	101	96	92	88	93	90	87	91	88	85	89	86	84	82
4	98	91	86	82	97	90	85	82	88	84	81	86	83	80	84	81	79	77
5	94	86	80	76	92	85	80	76	83	79	75	82	78	75	80	77	74	73
6	90	81	75	71	88	80	75	71	79	74	71	77	73	70	76	73	70	68
7	85	77	71	67	84	76	71	67	75	70	66	74	69	66	72	69	66	64
8	82	73	67	63	80	72	67	63	71	66	63	70	66	62	69	65	62	61
9	78	69	63	60	77	69	63	60	68	63	59	67	62	59	66	62	59	58
10	75	66	60	57	74	65	60	57	64	60	56	64	59	56	63	59	56	55

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	89663	89663	89663
5°	86663	85592	86712
10°	74376	74425	74376
15°	57728	56809	57595
20°	41665	40804	40770
25°	29543	28365	28418
30°	21979	21420	21215
35°	17103	16667	16312
40°	12657	12338	11559
45°	6466	7930	5211
50°	1407	4373	1030
55°	394	1773	310
60°	65	355	32
65°	0	38	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 45°
 Vertical Angle: 45°
 Luminance: 7930 cd/sqm



TEST NUMBER: P853612

CATALOG NUMBER: SQ2-BBN-075D-935-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	480.2	16.0
10°-20°	946.7	31.5
20°-30°	763.7	25.4
30°-40°	530.5	17.7
40°-50°	245.1	8.2
50°-60°	34.4	1.1
60°-70°	1.2	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2190.6	73.0
0°-40°	2721.1	90.6
0°-60°	3000.6	100.0
0°-90°	3001.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3001.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	5553	5553	5553	5553	5553	
5°	5347	5319	5281	5346	5350	481
15°	3454	3498	3399	3447	3446	951
25°	1658	1621	1592	1616	1595	776
35°	868	868	846	831	828	543
45°	283	338	347	315	228	229
55°	14	22	63	18	11	18
65°	0	0	1	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P853612

CATALOG NUMBER: SQ2-BBN-075D-935-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	5553.3	5553.3	5553.3	5553.3	5553.3
2.5°	5550.1	5529.7	5481.2	5524.9	5511.6
5°	5347.1	5318.7	5281.0	5346.2	5350.1
7.5°	4899.2	4908.4	4873.3	4945.2	4937.6
10°	4536.5	4543.3	4539.5	4562.9	4536.5
12.5°	4116.2	4143.4	4091.9	4128.2	4139.4
15°	3453.6	3497.7	3398.6	3446.6	3445.6
17.5°	2832.4	2827.9	2776.7	2785.7	2782.7
20°	2424.9	2418.0	2374.8	2367.9	2372.8
22.5°	2075.8	2064.2	2049.0	2031.7	2038.2
25°	1658.3	1621.1	1592.2	1615.8	1595.2
27.5°	1331.0	1330.4	1306.6	1309.3	1313.2
30°	1178.9	1172.1	1148.9	1149.6	1137.9
32.5°	1043.6	1048.5	1020.0	1014.3	1002.6
35°	867.7	867.7	845.6	830.6	827.6
37.5°	704.5	702.8	687.1	665.7	658.1
40°	600.5	595.6	585.4	559.2	548.4
42.5°	482.0	495.1	485.4	459.0	442.7
45°	283.2	338.0	347.3	315.3	228.2
47.5°	121.7	182.0	231.8	151.1	78.7
50°	56.0	103.0	174.1	74.3	41.0
52.5°	32.8	56.3	129.3	43.4	25.8
55°	14.0	21.8	63.0	17.9	11.0
57.5°	5.2	9.5	23.8	7.7	4.2
60°	2.0	4.0	11.0	3.0	1.0
62.5°	0.4	1.6	5.4	1.4	0.2
65°	0.0	0.0	1.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P853612

CATALOG NUMBER: SQ2-BBN-075D-935-UNV-STD-W-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
4H	2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
8H	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
12H	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00