

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P855051

Luminaire Tested: SQ2-FA-025U-125D-830-UNV-STD-W-4

Issue Date: 7/12/2024

Test Information

Test Method: LM-79-2019
Report Number: P855051
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2104-222-9, G2-2308-131-11)
Test Lab: INNOVATION CENTER
Issue Date: 7/12/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ2-FA-025U-125D-830-UNV-STD-W-4
Description: CORELITE SQ2 SUSPENDED LED LUMINAIRE
DOWNLIGHT 1250 LUMENS PER FOOT
UPLIGHT 250 LUMENS PER FOOT
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6424.1 lumens
Efficiency: N/A
Efficacy: 113.5 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 0.95 / 0.95
Luminous Opening: Rectangular (W 0.17' x L: 4' x H: 0')
CIE Type: Semi-Direct

Input Watts (W): 56.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

Luminous Intensity Polar Plot





TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20				
RC	80					70					50					30				
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	115	115	115	115	110	110	110	110	101	101	101	93	93	93	86	86	86	82		
1	107	103	99	96	102	99	96	93	92	89	87	85	83	81	79	77	76	73		
2	99	92	87	82	95	89	84	80	83	79	76	77	74	71	72	69	67	64		
3	92	83	77	72	88	81	75	70	75	70	66	70	67	63	66	63	60	57		
4	86	76	69	63	82	73	67	62	69	64	59	65	60	57	61	57	54	52		
5	80	69	62	56	77	67	60	55	63	58	53	60	55	51	56	52	49	47		
6	75	64	56	51	72	62	55	50	58	53	48	55	50	47	52	48	45	43		
7	70	59	51	46	67	57	50	45	54	48	44	51	46	43	49	44	41	39		
8	66	54	47	42	63	53	46	42	50	45	40	48	43	39	46	41	38	36		
9	62	51	44	39	60	49	43	38	47	41	37	45	40	36	43	38	35	33		
10	59	47	40	36	57	46	40	35	44	38	34	42	37	34	40	36	33	31		

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	58461	58461	58461	58461
5°	58153	58240	57931	58196
10°	58063	57838	57838	57838
15°	57875	57282	57417	57282
20°	57426	54986	57003	55501
25°	56671	46408	56281	47381
30°	56151	26625	55539	26981
35°	55166	22874	54466	22551
40°	53639	12026	52140	11913
45°	48757	5174	47012	5174
50°	32169	6242	30521	5830
55°	17985	11530	17061	10452
60°	9700	16227	9523	14551
65°	8554	19713	8970	22426
70°	7992	23589	7605	24878
75°	7498	20268	7667	20954
80°	6351	14477	6351	15230
85°	5576	8077	5076	9615

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 48757 cd/sqm



TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	340.7	5.3
10°-20°	966.7	15.0
20°-30°	1318.0	20.5
30°-40°	1107.6	17.2
40°-50°	629.1	9.8
50°-60°	333.8	5.2
60°-70°	307.3	4.8
70°-80°	225.6	3.5
80°-90°	59.4	0.9
90°-100°	74.1	1.2
100°-110°	230.4	3.6
110°-120°	225.4	3.5
120°-130°	184.0	2.9
130°-140°	150.5	2.3
140°-150°	117.5	1.8
150°-160°	84.8	1.3
160°-170°	51.8	0.8
170°-180°	17.5	0.3
0°-30°	2625.4	40.9
0°-40°	3733.0	58.1
0°-60°	4695.8	73.1
0°-90°	5288.2	82.3
90°-120°	529.8	8.2
90°-150°	981.8	15.3
90°-180°	1136.0	17.7
0°-180°	6424.1	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	3621	3621	3621	3621	3621	
5°	3588	3593	3574	3591	3588	341
15°	3462	3427	3435	3427	3462	976
25°	3181	2605	3159	2660	3181	1467
35°	2799	1160	2763	1144	2799	1747
45°	2135	227	2059	227	2135	1561
55°	639	410	606	371	639	615
65°	224	516	235	587	224	225
75°	120	325	123	336	120	124
85°	30	44	27	52	30	33
90°	0	3	0	3	0	2
95°	10	33	10	33	10	12
105°	40	413	40	413	40	43
115°	72	445	72	445	72	71
125°	100	350	100	350	100	89
135°	120	290	120	290	120	93
145°	140	242	140	242	140	88
155°	161	207	161	207	161	74
165°	176	191	176	191	176	50
175°	183	183	183	183	183	17
180°	183	183	183	183	183	



TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
0°	3620.8	3620.8	3620.8	3620.8	3620.8	3620.8	3620.8	3620.8	3620.8	3620.8	3620.8
2.5°	3601.1	3654.5	3607.7	3601.6	3620.8	3616.5	3609.8	3635.0	3592.3	3635.0	3601.1
5°	3588.0	3649.4	3579.7	3561.4	3593.4	3572.0	3590.7	3627.7	3574.3	3622.4	3568.9
7.5°	3565.6	3620.0	3536.7	3524.8	3556.3	3537.6	3545.4	3596.8	3551.9	3583.5	3535.0
10°	3541.5	3589.6	3506.0	3498.5	3527.8	3509.2	3517.0	3570.6	3527.8	3557.2	3508.7
12.5°	3515.3	3552.7	3468.9	3465.6	3490.7	3478.4	3482.0	3527.2	3492.9	3522.3	3476.0
15°	3462.4	3497.1	3413.2	3400.2	3426.9	3416.1	3421.4	3461.8	3435.0	3453.8	3413.2
17.5°	3396.8	3424.6	3341.2	3301.8	3302.8	3316.3	3341.2	3389.7	3365.7	3390.2	3332.9
20°	3342.2	3374.3	3282.1	3205.6	3200.2	3213.5	3282.1	3331.0	3317.6	3344.3	3263.0
22.5°	3278.9	3300.2	3216.6	3087.3	3069.1	3082.5	3207.9	3265.6	3260.9	3279.0	3177.8
25°	3181.1	3202.4	3050.0	2863.9	2605.0	2847.9	3055.4	3159.2	3159.2	3175.3	3041.9
27.5°	3081.7	3082.2	2806.5	1839.3	1622.5	1773.1	2802.6	3027.6	3053.3	3045.3	2783.0
30°	3011.8	2993.2	2487.5	1486.8	1428.1	1465.4	2490.2	2936.3	2979.0	2949.6	2424.8
32.5°	2931.0	2878.2	1836.6	1366.9	1318.9	1352.0	1776.0	2827.9	2902.6	2839.0	1907.1
35°	2798.8	2660.0	1400.8	1208.5	1160.5	1203.2	1389.9	2613.8	2763.3	2592.5	1447.2
37.5°	2656.3	2114.3	1233.1	962.6	859.1	941.8	1227.1	2091.7	2598.4	2043.1	1232.1
40°	2544.9	1661.1	1108.6	704.2	570.6	664.1	1100.5	1584.8	2473.8	1705.0	1081.3
42.5°	2396.4	1459.2	890.2	447.3	350.0	409.3	853.5	1425.5	2321.0	1477.3	860.6
45°	2135.3	1254.2	527.0	245.3	226.6	237.3	486.1	1231.2	2058.9	1204.5	538.0
47.5°	1691.3	956.5	338.6	208.5	228.8	208.5	328.2	926.2	1597.4	924.5	338.1
50°	1280.7	746.7	262.1	211.1	248.5	211.1	253.9	721.1	1215.1	787.9	259.4
52.5°	948.6	623.9	214.0	231.4	298.7	235.7	208.0	607.4	900.6	635.6	202.6
55°	638.9	489.5	172.0	305.5	409.6	313.4	172.0	475.3	606.1	470.0	166.5
57.5°	405.2	364.1	174.2	392.7	467.5	400.2	176.9	351.0	388.8	352.5	152.9
60°	300.4	287.0	193.9	417.0	502.5	422.3	196.6	276.2	294.9	273.5	163.8
62.5°	248.0	226.0	233.1	451.6	522.1	439.8	238.1	215.6	257.8	206.5	181.4
65°	223.9	146.5	275.8	457.3	516.0	457.3	278.5	138.7	234.8	149.4	245.8
67.5°	202.0	108.7	266.5	454.2	519.3	455.3	259.9	103.7	193.9	101.0	251.2
70°	169.3	97.2	251.2	462.3	499.7	446.3	251.2	94.4	161.1	91.7	294.9
72.5°	140.9	92.3	233.7	426.9	442.9	410.9	236.0	91.8	141.4	82.7	277.5
75°	120.2	90.8	223.9	341.0	324.9	324.9	218.4	88.2	122.9	82.9	215.7
77.5°	90.1	80.5	185.7	222.5	210.3	210.3	182.4	77.7	85.7	72.9	175.2
80°	68.3	73.6	152.9	163.6	155.7	155.7	147.4	70.9	68.3	68.3	144.7
82.5°	53.0	62.6	117.9	120.0	114.1	112.0	114.6	62.1	53.0	57.2	111.9
85°	30.1	43.4	62.8	51.7	43.6	41.0	60.0	40.7	27.4	40.7	60.0
87.5°	11.0	19.7	9.4	9.4	9.4	9.4	9.4	19.7	11.0	17.5	11.6
90°	0.0	1.1	3.4	3.4	3.4	3.4	3.4	1.1	0.0	1.1	3.4
92.5°	3.6	12.6	42.9	14.1	11.4	14.1	42.9	12.6	3.6	12.6	42.9
95°	10.1	29.8	135.9	50.1	32.6	50.1	135.9	29.8	10.1	29.8	135.9
97.5°	18.4	38.8	225.0	140.1	88.3	140.1	225.0	38.8	18.4	38.8	225.0
100°	24.6	43.4	253.7	237.3	158.3	237.3	253.7	43.4	24.6	43.4	253.7
102.5°	31.0	48.7	248.4	339.0	266.2	339.0	248.4	48.7	31.0	48.7	248.4
105°	40.5	56.9	226.8	432.9	413.3	432.9	226.8	56.9	40.5	56.9	226.8
107.5°	49.9	65.2	206.1	440.2	462.0	440.2	206.1	65.2	49.9	65.2	206.1
110°	56.2	71.5	195.4	429.9	472.7	429.9	195.4	71.5	56.2	71.5	195.4



TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
112.5°	62.4	76.9	189.9	411.3	465.5	411.3	189.9	76.9	62.4	76.9	189.9
115°	71.9	85.0	184.2	379.9	444.7	379.9	184.2	85.0	71.9	85.0	184.2
117.5°	81.1	93.2	181.7	349.8	416.1	349.8	181.7	93.2	81.1	93.2	181.7
120°	86.5	98.6	180.8	332.6	396.4	332.6	180.8	98.6	86.5	98.6	180.8
122.5°	91.8	103.9	181.7	318.2	376.6	318.2	181.7	103.9	91.8	103.9	181.7
125°	99.9	110.9	181.9	298.7	350.3	298.7	181.9	110.9	99.9	110.9	181.9
127.5°	106.4	117.7	181.9	284.1	328.1	284.1	181.9	117.7	106.4	117.7	181.9
130°	110.0	122.1	181.9	276.0	315.6	276.0	181.9	122.1	110.0	122.1	181.9
132.5°	114.5	126.6	181.0	268.8	305.6	268.8	181.0	126.6	114.5	126.6	181.0
135°	120.2	133.3	180.8	257.9	289.7	257.9	180.8	133.3	120.2	133.3	180.8
137.5°	126.6	138.7	180.8	247.0	276.0	247.0	180.8	138.7	126.6	138.7	180.8
140°	130.3	142.3	180.8	239.8	266.2	239.8	180.8	142.3	130.3	142.3	180.8
142.5°	134.8	146.0	180.8	232.6	256.2	232.6	180.8	146.0	134.8	146.0	180.8
145°	140.3	151.3	180.8	222.7	242.5	222.7	180.8	151.3	140.3	151.3	180.8
147.5°	147.1	156.5	181.9	213.7	229.3	213.7	181.9	156.5	147.1	156.5	181.9
150°	151.6	159.3	181.9	209.2	221.2	209.2	181.9	159.3	151.6	159.3	181.9
152.5°	155.1	162.0	181.9	204.6	214.9	204.6	181.9	162.0	155.1	162.0	181.9
155°	160.6	166.1	181.9	200.0	206.6	200.0	181.9	166.1	160.6	166.1	181.9
157.5°	166.0	170.2	181.9	195.9	200.1	195.9	181.9	170.2	166.0	170.2	181.9
160°	169.6	172.9	181.9	193.2	196.5	193.2	181.9	172.9	169.6	172.9	181.9
162.5°	172.2	174.7	181.9	191.4	193.8	191.4	181.9	174.7	172.2	174.7	181.9
165°	176.3	177.4	183.1	188.7	190.9	188.7	183.1	177.4	176.3	177.4	183.1
167.5°	178.8	179.0	181.9	187.1	188.1	187.1	181.9	179.0	178.8	179.0	181.9
170°	179.7	180.8	181.9	185.3	186.4	185.3	181.9	180.8	179.7	180.8	181.9
172.5°	181.5	181.7	182.8	184.4	184.6	184.4	182.8	181.7	181.5	181.7	182.8
175°	183.1	183.1	183.1	184.1	183.1	184.1	183.1	183.1	183.1	183.1	183.1
177.5°	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1
180°	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1	183.1



TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
0°	3620.8	3620.8	3620.8	3620.8	3620.8	3620.8
2.5°	3592.6	3607.7	3607.7	3598.8	3641.7	3601.1
5°	3556.0	3590.7	3574.6	3574.3	3628.0	3588.0
7.5°	3530.3	3562.9	3547.8	3544.8	3597.6	3565.6
10°	3503.9	3527.8	3517.2	3525.1	3573.6	3541.5
12.5°	3466.8	3495.2	3484.4	3496.7	3540.9	3515.3
15°	3402.8	3426.9	3432.2	3437.8	3489.1	3462.4
17.5°	3297.2	3308.9	3335.6	3373.4	3426.8	3396.8
20°	3214.2	3230.2	3246.3	3312.2	3374.3	3342.2
22.5°	3119.8	3114.5	3151.9	3229.1	3306.7	3278.9
25°	2865.2	2659.6	2886.5	3085.5	3189.1	3181.1
27.5°	1994.9	1731.1	1964.5	2848.0	3065.7	3081.7
30°	1570.0	1447.2	1567.3	2542.1	2974.4	3011.8
32.5°	1394.0	1309.6	1382.8	1934.9	2859.4	2931.0
35°	1202.9	1144.1	1202.9	1447.2	2633.3	2798.8
37.5°	962.7	842.7	960.7	1250.6	2128.8	2656.3
40°	717.4	565.2	696.0	1119.6	1701.2	2544.9
42.5°	478.0	364.3	452.4	881.4	1471.5	2396.4
45°	258.7	226.6	248.0	532.4	1200.9	2135.3
47.5°	202.8	214.6	202.8	335.9	918.6	1691.3
50°	194.7	232.1	194.7	259.4	760.0	1280.7
52.5°	212.2	251.8	210.1	204.8	620.2	948.6
55°	240.5	371.3	243.2	166.5	454.7	638.9
57.5°	342.5	417.8	346.2	157.8	350.2	405.2
60°	351.7	450.6	349.1	166.5	271.0	300.4
62.5°	416.1	557.6	415.5	190.6	201.5	248.0
65°	533.7	587.0	539.0	243.0	143.8	223.9
67.5°	506.5	544.5	501.2	260.5	99.0	202.0
70°	497.6	527.0	492.3	297.6	91.9	169.3
72.5°	464.2	468.0	454.6	275.8	82.7	140.9
75°	359.9	335.9	346.5	237.5	82.8	120.2
77.5°	223.6	214.0	215.7	181.4	73.0	90.1
80°	169.1	163.8	161.1	152.9	68.3	68.3
82.5°	125.5	120.2	117.5	117.9	57.2	53.0
85°	57.2	51.9	49.2	68.3	40.7	30.1
87.5°	11.6	11.6	9.5	11.6	15.4	11.0
90°	3.4	3.4	3.4	3.4	1.1	0.0
92.5°	14.1	11.4	14.1	42.9	12.6	3.6
95°	50.1	32.6	50.1	135.9	29.8	10.1
97.5°	140.1	88.3	140.1	225.0	38.8	18.4
100°	237.3	158.3	237.3	253.7	43.4	24.6
102.5°	339.0	266.2	339.0	248.4	48.7	31.0
105°	432.9	413.3	432.9	226.8	56.9	40.5
107.5°	440.2	462.0	440.2	206.1	65.2	49.9
110°	429.9	472.7	429.9	195.4	71.5	56.2



TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
112.5°	411.3	465.5	411.3	189.9	76.9	62.4
115°	379.9	444.7	379.9	184.2	85.0	71.9
117.5°	349.8	416.1	349.8	181.7	93.2	81.1
120°	332.6	396.4	332.6	180.8	98.6	86.5
122.5°	318.2	376.6	318.2	181.7	103.9	91.8
125°	298.7	350.3	298.7	181.9	110.9	99.9
127.5°	284.1	328.1	284.1	181.9	117.7	106.4
130°	276.0	315.6	276.0	181.9	122.1	110.0
132.5°	268.8	305.6	268.8	181.0	126.6	114.5
135°	257.9	289.7	257.9	180.8	133.3	120.2
137.5°	247.0	276.0	247.0	180.8	138.7	126.6
140°	239.8	266.2	239.8	180.8	142.3	130.3
142.5°	232.6	256.2	232.6	180.8	146.0	134.8
145°	222.7	242.5	222.7	180.8	151.3	140.3
147.5°	213.7	229.3	213.7	181.9	156.5	147.1
150°	209.2	221.2	209.2	181.9	159.3	151.6
152.5°	204.6	214.9	204.6	181.9	162.0	155.1
155°	200.0	206.6	200.0	181.9	166.1	160.6
157.5°	195.9	200.1	195.9	181.9	170.2	166.0
160°	193.2	196.5	193.2	181.9	172.9	169.6
162.5°	191.4	193.8	191.4	181.9	174.7	172.2
165°	188.7	190.9	188.7	183.1	177.4	176.3
167.5°	187.1	188.1	187.1	181.9	179.0	178.8
170°	185.3	186.4	185.3	181.9	180.8	179.7
172.5°	184.4	184.6	184.4	182.8	181.7	181.5
175°	184.1	183.1	184.1	183.1	183.1	183.1
177.5°	183.1	183.1	183.1	183.1	183.1	183.1
180°	183.1	183.1	183.1	183.1	183.1	183.1



TEST NUMBER: P855051

CATALOG NUMBER: SQ2-FA-025U-125D-830-UNV-STD-W-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.77	17.81	17.41	18.45	19.17	15.63	16.67	16.27	17.30	18.03
	3H	17.48	18.41	18.14	19.06	19.83	21.79	22.72	22.44	23.37	24.13
	4H	17.90	18.78	18.57	19.43	20.21	23.07	23.95	23.75	24.61	25.39
	6H	18.26	19.07	18.95	19.74	20.53	23.69	24.49	24.37	25.17	25.96
	8H	18.39	19.15	19.08	19.84	20.64	23.82	24.58	24.51	25.27	26.07
	12H	18.46	19.19	19.16	19.88	20.69	23.86	24.59	24.56	25.28	26.09
4H	2H	17.18	18.06	17.86	18.72	19.50	16.18	17.05	16.86	17.71	18.49
	3H	18.19	18.92	18.88	19.62	20.42	22.52	23.24	23.20	23.94	24.74
	4H	18.76	19.42	19.46	20.12	20.95	23.97	24.63	24.67	25.33	26.16
	6H	19.25	19.82	19.97	20.54	21.38	24.72	25.29	25.44	26.01	26.85
	8H	19.42	19.95	20.15	20.67	21.52	24.89	25.42	25.61	26.14	26.99
	12H	19.54	20.02	20.29	20.77	21.62	24.96	25.43	25.70	26.18	27.03
8H	4H	19.87	20.40	20.60	21.13	21.97	24.11	24.64	24.83	25.36	26.21
	6H	20.49	20.92	21.24	21.69	22.54	24.99	25.43	25.75	26.19	27.04
	8H	20.72	21.11	21.49	21.88	22.74	25.24	25.63	26.01	26.40	27.26
	12H	20.90	21.24	21.67	22.00	22.93	25.37	25.71	26.14	26.47	27.40
12H	4H	20.03	20.50	20.77	21.25	22.10	24.08	24.55	24.82	25.30	26.15
	6H	20.76	21.15	21.53	21.92	22.78	25.00	25.39	25.77	26.16	27.02
	8H	21.07	21.41	21.84	22.16	23.09	25.29	25.63	26.06	26.39	27.31