

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P853822

Luminaire Tested: SQ2-FA-150U-125D-935-UNV-STD-W-4

Issue Date: 7/12/2024

Test Information

Test Method: LM-79-2019
Report Number: P853822
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2104-222-14, G2-2308-131-11)
Test Lab: INNOVATION CENTER
Issue Date: 7/12/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ2-FA-150U-125D-935-UNV-STD-W-4
Description: CORELITE SQ2 SUSPENDED LED LUMINAIRE
DOWNLIGHT 1250 LUMENS PER FOOT
UPLIGHT 1500 LUMENS PER FOOT
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 10572.5 lumens
Efficiency: N/A
Efficacy: 99.9 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 0.95 / 0.95
Luminous Opening: Rectangular (W 0.17' x L: 4' x H: 0')
CIE Type: General Diffuse

Input Watts (W): 105.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

Luminous Intensity Polar Plot





TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	106	106	106	106	97	97	97	97	80	80	80	65	65	65	51	51	51	44				
1	97	93	90	87	89	86	83	80	72	70	68	58	57	56	46	45	45	39				
2	90	83	77	73	82	76	72	68	64	61	58	53	50	48	42	41	39	35				
3	83	74	67	62	76	68	63	58	58	54	50	48	45	42	39	37	35	31				
4	76	66	59	54	70	62	55	51	52	48	44	44	40	38	35	33	31	28				
5	71	60	53	47	65	56	49	44	47	43	39	40	36	34	33	30	28	25				
6	66	54	47	42	60	51	44	39	43	38	35	37	33	30	30	28	26	23				
7	61	50	42	37	56	46	40	35	40	35	31	34	30	27	28	26	24	21				
8	57	46	38	33	52	43	36	32	37	32	28	31	28	25	26	24	22	19				
9	53	42	35	30	49	39	33	29	34	29	26	29	26	23	25	22	20	18				
10	50	39	32	28	46	36	30	26	32	27	24	27	24	21	23	20	19	17				

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	51705	51705	51705	51705
5°	51433	51511	51237	51472
10°	51354	51155	51155	51155
15°	51188	50663	50783	50663
20°	50790	48632	50417	49089
25°	50122	41046	49779	41906
30°	49663	23549	49122	23864
35°	48791	20231	48172	19945
40°	47440	10638	46116	10536
45°	43124	4576	41580	4576
50°	28452	5521	26995	5157
55°	15907	10199	15091	9244
60°	8580	14350	8422	12868
65°	7564	17436	7935	19836
70°	7067	20866	6727	22003
75°	6631	17929	6781	18534
80°	5616	12803	5616	13473
85°	4928	7151	4483	8503

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 43124 cd/sqm



TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	301.4	2.9
10°-20°	855.0	8.1
20°-30°	1165.7	11.0
30°-40°	979.6	9.3
40°-50°	556.4	5.3
50°-60°	295.2	2.8
60°-70°	271.8	2.6
70°-80°	199.6	1.9
80°-90°	53.2	0.5
90°-100°	363.9	3.4
100°-110°	1191.6	11.3
110°-120°	1178.0	11.1
120°-130°	963.0	9.1
130°-140°	785.9	7.4
140°-150°	611.6	5.8
150°-160°	440.4	4.2
160°-170°	269.4	2.5
170°-180°	91.0	0.9
0°-30°	2322.0	22.0
0°-40°	3301.7	31.2
0°-60°	4153.3	39.3
0°-90°	4677.8	44.2
90°-120°	2733.5	25.9
90°-150°	5093.9	48.2
90°-180°	5895.0	55.8
0°-180°	10572.5	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	3202	3202	3202	3202	3202	
5°	3173	3178	3161	3176	3173	302
15°	3062	3031	3038	3031	3062	863
25°	2814	2304	2794	2352	2814	1297
35°	2475	1026	2444	1012	2475	1545
45°	1889	200	1821	200	1889	1381
55°	565	362	536	328	565	544
65°	198	456	208	519	198	199
75°	106	287	109	297	106	110
85°	27	39	24	46	27	30
90°	1	8	1	8	1	4
95°	51	153	51	153	51	58
105°	207	2135	207	2135	207	218
115°	373	2331	373	2331	373	368
125°	519	1839	519	1839	519	462
135°	625	1522	625	1522	625	484
145°	731	1273	731	1273	731	458
155°	833	1080	833	1080	833	384
165°	910	994	910	994	910	256
175°	951	957	951	957	951	90
180°	955	955	955	955	955	

TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
0°	3202.4	3202.4	3202.4	3202.4	3202.4	3202.4	3202.4	3202.4	3202.4	3202.4	3202.4
2.5°	3185.0	3232.2	3190.8	3185.4	3202.4	3198.6	3192.7	3215.0	3177.2	3215.0	3185.0
5°	3173.4	3227.7	3166.1	3149.9	3178.2	3159.3	3175.8	3208.5	3161.3	3203.8	3156.5
7.5°	3153.6	3201.7	3128.0	3117.5	3145.4	3128.8	3135.7	3181.2	3141.5	3169.4	3126.5
10°	3132.3	3174.8	3100.9	3094.3	3120.2	3103.7	3110.6	3158.0	3120.2	3146.2	3103.3
12.5°	3109.1	3142.2	3068.1	3065.2	3087.4	3076.5	3079.7	3119.6	3089.3	3115.3	3074.4
15°	3062.3	3093.0	3018.8	3007.3	3030.9	3021.4	3026.1	3061.8	3038.1	3054.7	3018.8
17.5°	3004.3	3028.9	2955.1	2920.3	2921.2	2933.1	2955.1	2998.0	2976.8	2998.5	2947.8
20°	2956.0	2984.4	2902.9	2835.2	2830.4	2842.2	2902.9	2946.1	2934.3	2957.9	2886.0
22.5°	2900.0	2918.9	2844.9	2730.6	2714.5	2726.3	2837.2	2888.3	2884.1	2900.1	2810.6
25°	2813.5	2832.4	2697.6	2533.0	2304.0	2518.8	2702.4	2794.2	2794.2	2808.4	2690.4
27.5°	2725.6	2726.1	2482.2	1626.8	1435.0	1568.2	2478.8	2677.8	2700.5	2693.4	2461.4
30°	2663.8	2647.3	2200.1	1315.0	1263.1	1296.1	2202.5	2597.0	2634.8	2608.8	2144.6
32.5°	2592.3	2545.6	1624.4	1209.0	1166.5	1195.8	1570.8	2501.1	2567.2	2511.0	1686.7
35°	2475.4	2352.6	1238.9	1068.9	1026.4	1064.2	1229.3	2311.8	2444.0	2292.9	1280.0
37.5°	2349.4	1870.0	1090.6	851.4	759.8	833.0	1085.3	1850.0	2298.2	1807.0	1089.7
40°	2250.8	1469.2	980.5	622.8	504.7	587.4	973.3	1401.7	2188.0	1508.0	956.4
42.5°	2119.5	1290.6	787.3	395.6	309.6	362.0	754.9	1260.8	2052.8	1306.6	761.2
45°	1888.6	1109.3	466.1	217.0	200.4	209.9	429.9	1088.9	1821.0	1065.3	475.8
47.5°	1495.9	846.0	299.5	184.4	202.4	184.4	290.3	819.2	1412.8	817.7	299.0
50°	1132.7	660.4	231.8	186.7	219.8	186.7	224.6	637.8	1074.7	696.9	229.4
52.5°	839.0	551.8	189.3	204.7	264.2	208.5	184.0	537.2	796.5	562.2	179.2
55°	565.1	432.9	152.1	270.2	362.3	277.2	152.1	420.4	536.1	415.7	147.3
57.5°	358.4	322.0	154.1	347.3	413.5	354.0	156.5	310.4	343.9	311.8	135.2
60°	265.7	253.8	171.5	368.8	444.4	373.5	173.9	244.3	260.8	241.9	144.9
62.5°	219.3	199.9	206.2	399.4	461.8	389.0	210.6	190.7	228.0	182.6	160.4
65°	198.0	129.6	243.9	404.5	456.4	404.5	246.3	122.7	207.7	132.1	217.4
67.5°	178.7	96.1	235.7	401.7	459.3	402.7	229.9	91.7	171.5	89.3	222.2
70°	149.7	86.0	222.2	408.9	442.0	394.7	222.2	83.5	142.5	81.1	260.8
72.5°	124.6	81.6	206.7	377.6	391.7	363.4	208.7	81.2	125.1	73.1	245.4
75°	106.3	80.3	198.0	301.6	287.4	287.4	193.2	78.0	108.7	73.3	190.8
77.5°	79.7	71.2	164.2	196.8	186.0	186.0	161.3	68.7	75.8	64.5	155.0
80°	60.4	65.1	135.2	144.7	137.7	137.7	130.4	62.7	60.4	60.4	128.0
82.5°	46.9	55.4	104.3	106.1	100.9	99.1	101.4	54.9	46.9	50.6	99.0
85°	26.6	38.4	55.5	45.7	38.6	36.3	53.1	36.0	24.2	36.0	53.1
87.5°	9.9	17.8	9.3	9.1	9.3	9.1	9.3	17.8	9.9	15.9	11.2
90°	1.0	2.9	7.9	6.9	7.9	6.9	7.9	2.9	1.0	2.9	7.9
92.5°	16.7	60.8	186.9	60.8	48.7	60.8	186.9	60.8	16.7	60.8	186.9
95°	51.0	148.0	661.6	235.7	153.1	235.7	661.6	148.0	51.0	148.0	661.6
97.5°	92.7	195.2	1135.1	686.6	425.6	686.6	1135.1	195.2	92.7	195.2	1135.1
100°	121.7	219.6	1313.3	1172.8	777.4	1172.8	1313.3	219.6	121.7	219.6	1313.3
102.5°	154.7	250.3	1293.7	1728.1	1339.6	1728.1	1293.7	250.3	154.7	250.3	1293.7
105°	207.1	295.4	1182.8	2247.2	2134.9	2247.2	1182.8	295.4	207.1	295.4	1182.8
107.5°	258.7	339.7	1074.6	2295.7	2419.1	2295.7	1074.6	339.7	258.7	339.7	1074.6
110°	292.5	371.2	1022.8	2239.2	2468.6	2239.2	1022.8	371.2	292.5	371.2	1022.8



TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
112.5°	324.7	401.1	991.4	2141.0	2434.8	2141.0	991.4	401.1	324.7	401.1	991.4
115°	373.0	445.9	960.9	1985.7	2331.2	1985.7	960.9	445.9	373.0	445.9	960.9
117.5°	419.9	488.0	949.4	1833.1	2183.9	1833.1	949.4	488.0	419.9	488.0	949.4
120°	450.5	514.8	946.2	1744.1	2085.8	1744.1	946.2	514.8	450.5	514.8	946.2
122.5°	478.0	540.8	946.2	1667.4	1984.5	1667.4	946.2	540.8	478.0	540.8	946.2
125°	519.2	578.7	947.2	1565.9	1839.4	1565.9	947.2	578.7	519.2	578.7	947.2
127.5°	554.2	614.8	946.0	1491.1	1729.1	1491.1	946.0	614.8	554.2	614.8	946.0
130°	576.2	637.6	945.2	1445.8	1660.8	1445.8	945.2	637.6	576.2	637.6	945.2
132.5°	595.8	658.8	942.9	1406.9	1601.9	1406.9	942.9	658.8	595.8	658.8	942.9
135°	625.2	691.5	939.3	1350.6	1522.4	1350.6	939.3	691.5	625.2	691.5	939.3
137.5°	656.3	721.9	937.2	1291.9	1447.2	1291.9	937.2	721.9	656.3	721.9	937.2
140°	678.3	741.6	936.4	1254.8	1401.7	1254.8	936.4	741.6	678.3	741.6	936.4
142.5°	700.2	759.7	936.4	1215.2	1348.3	1215.2	936.4	759.7	700.2	759.7	936.4
145°	731.3	785.0	937.4	1161.7	1273.1	1161.7	937.4	785.0	731.3	785.0	937.4
147.5°	763.8	808.6	938.8	1115.2	1199.3	1115.2	938.8	808.6	763.8	808.6	938.8
150°	784.3	823.6	940.3	1088.2	1159.2	1088.2	940.3	823.6	784.3	823.6	940.3
152.5°	804.7	839.4	941.1	1065.9	1124.7	1065.9	941.1	839.4	804.7	839.4	941.1
155°	833.3	861.2	943.3	1039.4	1079.7	1039.4	943.3	861.2	833.3	861.2	943.3
157.5°	859.1	879.2	945.4	1018.5	1047.7	1018.5	945.4	879.2	859.1	879.2	945.4
160°	875.5	891.9	946.2	1006.6	1029.6	1006.6	946.2	891.9	875.5	891.9	946.2
162.5°	889.7	902.9	946.2	997.0	1013.9	997.0	946.2	902.9	889.7	902.9	946.2
165°	909.9	918.5	947.2	983.8	994.3	983.8	947.2	918.5	909.9	918.5	947.2
167.5°	927.0	931.2	948.4	973.4	979.2	973.4	948.4	931.2	927.0	931.2	948.4
170°	936.4	938.3	949.2	967.9	969.8	967.9	949.2	938.3	936.4	938.3	949.2
172.5°	943.5	944.6	951.5	963.9	964.3	963.9	951.5	944.6	943.5	944.6	951.5
175°	951.1	951.1	952.1	958.9	957.0	958.9	952.1	951.1	951.1	951.1	952.1
177.5°	955.0	954.3	953.5	958.1	955.0	958.1	953.5	954.3	955.0	954.3	953.5
180°	955.0	955.0	955.0	955.0	955.0	955.0	955.0	955.0	955.0	955.0	955.0



TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
0°	3202.4	3202.4	3202.4	3202.4	3202.4	3202.4
2.5°	3177.5	3190.8	3190.8	3183.0	3220.9	3185.0
5°	3145.1	3175.8	3161.6	3161.3	3208.8	3173.4
7.5°	3122.4	3151.2	3137.9	3135.2	3181.9	3153.6
10°	3099.0	3120.2	3110.8	3117.8	3160.7	3132.3
12.5°	3066.2	3091.3	3081.8	3092.7	3131.8	3109.1
15°	3009.6	3030.9	3035.6	3040.6	3085.9	3062.3
17.5°	2916.2	2926.6	2950.2	2983.6	3030.8	3004.3
20°	2842.8	2857.0	2871.2	2929.5	2984.4	2956.0
22.5°	2759.3	2754.6	2787.7	2856.0	2924.6	2900.0
25°	2534.1	2352.3	2553.0	2729.0	2820.6	2813.5
27.5°	1764.4	1531.1	1737.5	2518.9	2711.5	2725.6
30°	1388.6	1280.0	1386.2	2248.4	2630.7	2663.8
32.5°	1232.9	1158.3	1223.0	1711.3	2529.0	2592.3
35°	1063.9	1011.9	1063.9	1280.0	2329.0	2475.4
37.5°	851.5	745.3	849.7	1106.1	1882.8	2349.4
40°	634.5	499.9	615.6	990.2	1504.6	2250.8
42.5°	422.8	322.2	400.1	779.6	1301.5	2119.5
45°	228.8	200.4	219.3	470.9	1062.1	1888.6
47.5°	179.4	189.8	179.4	297.1	812.5	1495.9
50°	172.2	205.3	172.2	229.4	672.2	1132.7
52.5°	187.7	222.7	185.8	181.1	548.5	839.0
55°	212.7	328.4	215.1	147.3	402.2	565.1
57.5°	302.9	369.5	306.2	139.6	309.7	358.4
60°	311.1	398.5	308.8	147.3	239.7	265.7
62.5°	368.0	493.2	367.5	168.6	178.2	219.3
65°	472.0	519.2	476.7	214.9	127.2	198.0
67.5°	448.0	481.6	443.3	230.4	87.6	178.7
70°	440.1	466.1	435.4	263.2	81.3	149.7
72.5°	410.6	413.9	402.1	243.9	73.1	124.6
75°	318.3	297.1	306.5	210.1	73.2	106.3
77.5°	197.8	189.3	190.8	160.4	64.6	79.7
80°	149.6	144.9	142.5	135.2	60.4	60.4
82.5°	111.0	106.3	103.9	104.3	50.6	46.9
85°	50.6	45.9	43.5	60.4	36.0	26.6
87.5°	11.0	11.2	9.1	11.2	14.0	9.9
90°	6.9	7.9	6.9	7.9	2.9	1.0
92.5°	60.8	48.7	60.8	186.9	60.8	16.7
95°	235.7	153.1	235.7	661.6	148.0	51.0
97.5°	686.6	425.6	686.6	1135.1	195.2	92.7
100°	1172.8	777.4	1172.8	1313.3	219.6	121.7
102.5°	1728.1	1339.6	1728.1	1293.7	250.3	154.7
105°	2247.2	2134.9	2247.2	1182.8	295.4	207.1
107.5°	2295.7	2419.1	2295.7	1074.6	339.7	258.7
110°	2239.2	2468.6	2239.2	1022.8	371.2	292.5



TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
112.5°	2141.0	2434.8	2141.0	991.4	401.1	324.7
115°	1985.7	2331.2	1985.7	960.9	445.9	373.0
117.5°	1833.1	2183.9	1833.1	949.4	488.0	419.9
120°	1744.1	2085.8	1744.1	946.2	514.8	450.5
122.5°	1667.4	1984.5	1667.4	946.2	540.8	478.0
125°	1565.9	1839.4	1565.9	947.2	578.7	519.2
127.5°	1491.1	1729.1	1491.1	946.0	614.8	554.2
130°	1445.8	1660.8	1445.8	945.2	637.6	576.2
132.5°	1406.9	1601.9	1406.9	942.9	658.8	595.8
135°	1350.6	1522.4	1350.6	939.3	691.5	625.2
137.5°	1291.9	1447.2	1291.9	937.2	721.9	656.3
140°	1254.8	1401.7	1254.8	936.4	741.6	678.3
142.5°	1215.2	1348.3	1215.2	936.4	759.7	700.2
145°	1161.7	1273.1	1161.7	937.4	785.0	731.3
147.5°	1115.2	1199.3	1115.2	938.8	808.6	763.8
150°	1088.2	1159.2	1088.2	940.3	823.6	784.3
152.5°	1065.9	1124.7	1065.9	941.1	839.4	804.7
155°	1039.4	1079.7	1039.4	943.3	861.2	833.3
157.5°	1018.5	1047.7	1018.5	945.4	879.2	859.1
160°	1006.6	1029.6	1006.6	946.2	891.9	875.5
162.5°	997.0	1013.9	997.0	946.2	902.9	889.7
165°	983.8	994.3	983.8	947.2	918.5	909.9
167.5°	973.4	979.2	973.4	948.4	931.2	927.0
170°	967.9	969.8	967.9	949.2	938.3	936.4
172.5°	963.9	964.3	963.9	951.5	944.6	943.5
175°	958.9	957.0	958.9	952.1	951.1	951.1
177.5°	958.1	955.0	958.1	953.5	954.3	955.0
180°	955.0	955.0	955.0	955.0	955.0	955.0



TEST NUMBER: P853822

CATALOG NUMBER: SQ2-FA-150U-125D-935-UNV-STD-W-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	13.05	13.78	14.08	14.80	16.15	11.91	12.63	12.93	13.65	15.01
	3H	13.75	14.39	14.78	15.42	16.80	18.05	18.70	19.09	19.73	21.11
	4H	14.15	14.77	15.20	15.80	17.18	19.33	19.94	20.37	20.97	22.36
	6H	14.50	15.07	15.56	16.10	17.50	19.93	20.49	20.98	21.53	22.93
	8H	14.62	15.15	15.68	16.20	17.60	20.05	20.59	21.11	21.64	23.03
	12H	14.69	15.20	15.75	16.24	17.65	20.09	20.60	21.15	21.64	23.06
4H	2H	13.44	14.05	14.49	15.08	16.47	12.43	13.04	13.48	14.08	15.46
	3H	14.43	14.94	15.49	16.00	17.40	18.75	19.26	19.81	20.32	21.72
	4H	14.99	15.46	16.05	16.51	17.93	20.20	20.67	21.26	21.72	23.14
	6H	15.46	15.86	16.53	16.93	18.35	20.93	21.33	22.00	22.40	23.82
	8H	15.63	16.00	16.70	17.07	18.50	21.10	21.47	22.17	22.54	23.97
	12H	15.74	16.08	16.83	17.16	18.59	21.15	21.49	22.24	22.57	24.00
8H	4H	16.08	16.46	17.15	17.52	18.95	20.31	20.69	21.39	21.76	23.19
	6H	16.69	16.99	17.78	18.10	19.53	21.19	21.50	22.29	22.61	24.03
	8H	16.92	17.19	18.02	18.28	19.73	21.44	21.71	22.54	22.80	24.25
	12H	17.09	17.33	18.19	18.41	19.90	21.56	21.79	22.66	22.88	24.37
12H	4H	16.22	16.56	17.31	17.64	19.07	20.27	20.61	21.36	21.69	23.12
	6H	16.96	17.23	18.06	18.32	19.77	21.20	21.47	22.30	22.56	24.01
	8H	17.26	17.49	18.36	18.58	20.07	21.48	21.71	22.58	22.80	24.29