

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P853889

Luminaire Tested: SQ2-FB-125U-075D-940-UNV-STD-W-4

Issue Date: 7/12/2024

Test Information

Test Method: LM-79-2019
Report Number: P853889
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2104-222-13, G2-2308-131-12)
Test Lab: INNOVATION CENTER
Issue Date: 7/12/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ2-FB-125U-075D-940-UNV-STD-W-4
Description: CORELITE SQ2 SUSPENDED LED LUMINAIRE
DOWNLIGHT 750 LUMENS PER FOOT
UPLIGHT 1250 LUMENS PER FOOT
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8418.3 lumens
Efficiency: N/A
Efficacy: 119.2 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 2.98 / 2.56
Luminous Opening: Rectangular (W 0.17' x L: 4' x H: 0')
CIE Type: Semi-Indirect

Input Watts (W): 70.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P853889

CATALOG NUMBER: SQ2-FB-125U-075D-940-UNV-STD-W-4

Luminous Intensity Polar Plot





TEST NUMBER: P853889

CATALOG NUMBER: SQ2-FB-125U-075D-940-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	104	104	104	104	94	94	94	94	76	76	76	60	60	60	44	44	44	37
1	95	91	87	83	86	82	79	76	67	64	62	52	51	49	39	38	37	31
2	86	79	73	67	78	71	66	62	58	54	51	46	43	41	34	32	31	26
3	78	69	61	56	71	63	56	51	51	46	42	40	37	34	30	28	26	21
4	71	61	53	47	64	55	48	43	45	40	36	35	32	29	26	24	22	18
5	65	54	45	39	59	49	42	36	40	34	30	31	28	25	23	21	19	15
6	60	48	40	34	54	44	36	31	36	30	26	28	24	21	21	18	16	13
7	55	43	35	29	50	39	32	27	32	27	23	25	21	18	19	16	14	11
8	51	39	31	26	46	35	28	24	29	24	20	23	19	16	17	15	13	10
9	47	35	28	23	43	32	25	21	26	21	18	21	17	14	16	13	11	9
10	44	32	25	20	40	29	23	19	24	19	16	19	15	13	15	12	10	8

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	5125	5125	5125
5°	4995	6925	9076
10°	4677	13409	17662
15°	4234	17446	20329
20°	3749	19192	21289
25°	3317	20525	21638
30°	2931	21138	21906
35°	2618	21504	23550
40°	2380	21709	25022
45°	2194	21811	26202
50°	2070	22230	26676
55°	2018	22809	26888
60°	2070	23111	26757
65°	2159	22793	26002
70°	2233	22041	19667
75°	2477	19800	10855
80°	2557	10219	10070
85°	2538	7058	4242

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°
 Vertical Angle: 52.5°
 Luminance: 27132 cd/sqm



TEST NUMBER: P853889

CATALOG NUMBER: SQ2-FB-125U-075D-940-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	53.2	0.6
10°-20°	242.7	2.9
20°-30°	427.1	5.1
30°-40°	552.8	6.6
40°-50°	609.7	7.2
50°-60°	569.2	6.8
60°-70°	440.0	5.2
70°-80°	202.9	2.4
80°-90°	39.7	0.5
90°-100°	327.4	3.9
100°-110°	1066.0	12.7
110°-120°	1054.5	12.5
120°-130°	861.7	10.2
130°-140°	704.3	8.4
140°-150°	548.6	6.5
150°-160°	395.4	4.7
160°-170°	241.7	2.9
170°-180°	81.5	1.0
0°-30°	723.0	8.6
0°-40°	1275.7	15.2
0°-60°	2454.6	29.2
0°-90°	3137.2	37.3
90°-120°	2447.9	29.1
90°-150°	4562.4	54.2
90°-180°	5281.0	62.7
0°-180°	8418.3	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	317	317	317	317	317	
5°	308	353	427	521	560	29
15°	253	500	1044	1168	1216	71
25°	186	671	1152	1203	1215	86
35°	133	648	1091	1129	1195	84
45°	96	496	955	1097	1148	75
55°	72	296	810	931	955	65
65°	56	167	597	669	681	55
75°	40	102	317	171	174	41
85°	14	30	38	26	23	14
90°	0	3	7	6	6	3
95°	44	135	600	214	132	51
105°	181	261	1056	2017	1910	193
115°	335	400	860	1773	2086	331
125°	465	519	849	1400	1650	414
135°	562	621	844	1208	1362	434
145°	657	705	842	1040	1139	411
155°	750	774	848	932	966	345
165°	818	825	850	881	892	230
175°	853	853	853	859	857	81
180°	856	856	856	856	856	



TEST NUMBER: P853889

CATALOG NUMBER: SQ2-FB-125U-075D-940-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	317.4	317.4	317.4	317.4	317.4
2.5°	314.9	328.1	343.0	360.3	367.4
5°	308.2	353.0	427.3	521.2	560.0
7.5°	296.3	387.3	621.4	872.8	950.3
10°	285.3	412.2	817.9	1035.5	1077.3
12.5°	273.1	445.3	941.2	1094.1	1137.1
15°	253.3	499.5	1043.7	1168.4	1216.2
17.5°	232.9	560.5	1091.3	1214.3	1240.3
20°	218.2	603.1	1117.0	1222.6	1239.0
22.5°	204.8	635.1	1135.3	1215.3	1232.9
25°	186.2	671.1	1152.1	1202.7	1214.6
27.5°	168.2	680.5	1144.7	1178.0	1189.6
30°	157.2	677.9	1133.8	1158.5	1175.0
32.5°	147.4	670.5	1117.9	1141.9	1177.4
35°	132.8	647.5	1091.0	1129.1	1194.8
37.5°	120.2	610.5	1055.6	1133.7	1196.9
40°	112.9	582.9	1030.0	1133.4	1187.2
42.5°	105.6	550.5	1000.7	1121.2	1175.0
45°	96.1	496.0	955.2	1096.8	1147.5
47.5°	87.3	434.6	913.1	1062.9	1099.9
50°	82.4	392.7	885.0	1032.2	1062.0
52.5°	77.5	352.0	857.0	995.5	1023.0
55°	71.7	295.5	810.3	931.3	955.2
57.5°	66.5	247.1	757.2	860.4	879.8
60°	64.1	220.7	715.7	809.2	828.6
62.5°	60.4	196.8	669.3	755.4	773.6
65°	56.5	166.9	596.6	668.6	680.6
67.5°	51.0	144.7	519.4	563.5	541.1
70°	47.3	133.8	466.9	480.7	416.6
72.5°	44.9	121.8	409.6	373.2	251.8
75°	39.7	102.3	317.4	171.0	174.0
77.5°	32.3	79.2	208.7	131.3	134.0
80°	27.5	64.8	109.9	106.8	108.3
82.5°	22.6	50.3	75.7	78.7	76.6
85°	13.7	30.1	38.1	25.9	22.9
87.5°	4.9	11.5	7.6	7.4	7.4
90°	0.0	3.1	7.4	6.3	6.3
92.5°	15.2	54.5	174.1	57.4	44.2
95°	44.2	134.8	600.1	214.0	131.6
97.5°	83.2	175.4	1018.5	620.3	378.6
100°	108.4	199.0	1176.0	1048.7	680.1
102.5°	137.1	224.4	1156.6	1551.4	1179.6
105°	181.1	261.4	1056.0	2016.9	1909.8
107.5°	228.7	304.2	960.4	2057.3	2170.7
110°	263.2	332.2	914.9	2007.1	2212.0



TEST NUMBER: P853889

CATALOG NUMBER: SQ2-FB-125U-075D-940-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	291.8	360.0	886.3	1916.7	2180.8
115°	334.8	399.7	860.2	1772.7	2085.6
117.5°	379.0	437.5	850.1	1640.9	1952.4
120°	404.3	461.9	847.5	1559.8	1861.4
122.5°	428.7	485.5	848.4	1489.4	1770.4
125°	465.3	518.9	848.6	1399.6	1649.8
127.5°	496.7	551.5	848.4	1332.4	1540.9
130°	516.9	572.5	847.5	1293.9	1480.3
132.5°	534.6	592.7	846.7	1258.3	1433.1
135°	562.2	620.9	844.4	1207.9	1362.4
137.5°	589.2	648.3	842.0	1156.8	1293.9
140°	608.5	665.2	841.2	1122.1	1251.8
142.5°	627.1	681.2	841.2	1088.9	1204.6
145°	657.0	705.3	842.3	1040.3	1139.2
147.5°	686.0	728.0	843.7	999.0	1075.4
150°	705.4	742.5	845.4	974.3	1039.1
152.5°	724.8	755.2	846.3	955.5	1007.1
155°	749.6	774.3	847.5	931.5	966.5
157.5°	773.2	790.9	848.8	913.8	938.3
160°	787.5	801.9	849.6	902.7	922.3
162.5°	800.1	811.3	849.6	893.3	908.0
165°	818.0	825.3	849.6	881.4	891.7
167.5°	830.7	835.2	849.8	872.5	877.8
170°	839.1	841.2	850.7	866.5	868.6
172.5°	845.0	846.2	852.4	863.1	862.7
175°	852.8	852.8	852.8	859.1	857.0
177.5°	855.9	855.1	854.3	858.4	855.1
180°	855.9	855.9	855.9	855.9	855.9



TEST NUMBER: P853889

CATALOG NUMBER: SQ2-FB-125U-075D-940-UNV-STD-W-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	11.44	12.22	12.50	13.28	14.72	20.18	20.96	21.24	22.02	23.46
	3H	12.17	12.86	13.23	13.93	15.39	21.80	22.49	22.86	23.56	25.02
	4H	12.46	13.12	13.54	14.20	15.66	21.97	22.63	23.05	23.71	25.17
	6H	12.68	13.28	13.76	14.36	15.84	22.05	22.66	23.14	23.74	25.21
	8H	12.73	13.31	13.82	14.40	15.87	22.06	22.63	23.15	23.73	25.20
	12H	12.76	13.31	13.85	14.39	15.89	22.02	22.57	23.12	23.66	25.16
4H	2H	15.83	16.49	16.92	17.56	19.03	20.61	21.27	21.70	22.34	23.81
	3H	16.76	17.31	17.85	18.41	19.88	22.43	22.98	23.52	24.08	25.56
	4H	17.04	17.54	18.13	18.63	20.13	22.66	23.17	23.76	24.26	25.76
	6H	17.16	17.59	18.27	18.71	20.20	22.81	23.24	23.91	24.35	25.84
	8H	17.18	17.58	18.29	18.69	20.20	22.83	23.23	23.93	24.34	25.85
	12H	17.17	17.53	18.29	18.65	20.17	22.80	23.16	23.92	24.28	25.79
8H	4H	18.20	18.61	19.31	19.71	21.22	22.78	23.18	23.88	24.28	25.79
	6H	18.44	18.77	19.56	19.92	21.42	22.98	23.31	24.10	24.46	25.96
	8H	18.51	18.80	19.64	19.93	21.45	23.04	23.33	24.17	24.46	25.98
	12H	18.53	18.78	19.67	19.91	21.47	23.03	23.28	24.16	24.41	25.97
12H	4H	18.22	18.58	19.34	19.70	21.21	22.72	23.09	23.85	24.21	25.72
	6H	18.53	18.82	19.66	19.95	21.48	22.96	23.25	24.09	24.38	25.90
	8H	18.63	18.89	19.77	20.01	21.57	23.02	23.28	24.16	24.40	25.96