

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P937013

Luminaire Tested: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P937013
REPORT IS A COMBINATION OF REPORTS P933493 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Batwing Frosted Continuous Roll L
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 13829.0 lumens
Efficiency: N/A
Efficacy: 134.0 lumens/watt
Spacing Criteria (0/90/45): 0.71 / 2.69 / 2.33
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 12' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 103.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P937013
CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

Luminous Intensity Polar Plot





TEST NUMBER: P937013

CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	104	104	104	104	94	94	94	94	75	75	75	58	58	58	42	42	42	35				35
1	94	90	86	82	85	81	78	75	65	63	61	50	49	47	37	36	35	29				29
2	85	78	72	66	77	70	65	61	57	53	50	44	41	39	32	30	29	23				23
3	77	68	61	55	70	62	55	50	49	45	41	38	35	32	28	26	24	19				19
4	71	60	52	46	63	54	47	42	44	39	35	34	30	27	25	22	20	16				16
5	65	53	45	39	58	48	41	36	39	33	29	30	26	23	22	19	17	14				14
6	59	47	39	33	53	43	36	31	35	29	25	27	23	20	20	17	15	12				12
7	55	42	34	29	49	38	31	26	31	26	22	24	20	17	18	15	13	10				10
8	50	38	30	25	45	35	28	23	28	23	19	22	18	15	16	14	12	9				9
9	47	35	27	22	42	32	25	20	26	21	17	20	16	14	15	12	10	8				8
10	44	32	24	20	39	29	22	18	23	18	15	18	15	12	14	11	9	7				7

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1936	1936	1936
5°	1892	2238	2602
10°	1716	3263	4313
15°	1460	4264	5208
20°	1189	4942	5308
25°	992	5173	5200
30°	837	5207	5190
35°	740	5122	5325
40°	646	5011	5463
45°	585	4930	5485
50°	537	4858	5394
55°	515	4751	5155
60°	527	4545	4777
65°	550	4230	4258
70°	587	3691	3598
75°	653	3012	2807
80°	719	2091	1892
85°	651	1111	968

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°
 Vertical Angle: 45°
 Luminance: 5485 cd/sqm



TEST NUMBER: P937013

CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	80.9	0.6
10°-20°	358.8	2.6
20°-30°	627.5	4.5
30°-40°	807.8	5.8
40°-50°	902.3	6.5
50°-60°	864.2	6.2
60°-70°	684.9	5.0
70°-80°	402.7	2.9
80°-90°	117.2	0.8
90°-100°	675.4	4.9
100°-110°	1775.8	12.8
110°-120°	1841.3	13.3
120°-130°	1476.9	10.7
130°-140°	1158.9	8.4
140°-150°	889.5	6.4
150°-160°	640.6	4.6
160°-170°	391.9	2.8
170°-180°	132.4	1.0
0°-30°	1067.2	7.7
0°-40°	1875.0	13.6
0°-60°	3641.5	26.3
0°-90°	4846.3	35.0
90°-120°	4292.5	31.0
90°-150°	7817.8	56.5
90°-180°	8983.0	65.0
0°-180°	13829.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	626	626	626	626	626	
5°	610	654	736	833	863	56
15°	457	843	1421	1722	1777	127
25°	292	956	1692	1767	1769	134
35°	197	914	1594	1684	1751	123
45°	135	728	1408	1614	1686	104
55°	97	463	1195	1388	1427	88
65°	76	246	887	998	1012	76
75°	56	151	487	535	537	59
85°	20	46	121	133	135	21
90°	9	26	71	35	35	9
95°	89	350	1163	600	408	99
105°	320	484	1963	2981	2781	339
115°	568	690	1573	3137	3580	561
125°	790	886	1430	2417	2851	702
135°	942	1037	1386	1951	2212	729
145°	1093	1162	1368	1665	1795	685
155°	1235	1269	1368	1502	1546	567
165°	1333	1350	1368	1422	1440	376
175°	1386	1386	1377	1395	1395	132
180°	1386	1386	1386	1386	1386	



TEST NUMBER: P937013

CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	625.8	625.8	625.8	625.8	625.8	625.8	625.8	625.8	625.8	625.8	625.8
2.5°	625.8	625.8	629.8	631.8	635.8	637.8	641.9	645.9	658.0	660.0	664.0
5°	609.7	617.7	643.9	653.9	682.1	720.3	736.4	762.6	816.9	833.0	843.1
7.5°	585.5	603.6	668.0	684.1	754.6	855.2	897.4	953.8	1040.3	1082.5	1116.7
10°	547.3	585.5	700.2	738.5	853.1	1006.1	1084.5	1163.0	1293.8	1352.2	1374.3
12.5°	505.0	567.4	734.4	786.7	951.7	1175.1	1269.7	1356.2	1505.1	1583.6	1595.6
15°	456.8	541.3	766.6	843.1	1056.4	1315.9	1420.6	1527.2	1666.1	1722.4	1736.5
17.5°	414.5	521.1	796.8	877.3	1136.9	1442.7	1549.3	1637.9	1750.6	1788.8	1798.9
20°	362.2	489.0	816.9	921.6	1221.4	1535.3	1637.9	1706.3	1782.8	1806.9	1810.9
22.5°	324.0	454.7	829.0	937.7	1277.7	1591.6	1678.1	1732.5	1784.8	1792.8	1794.8
25°	291.8	416.5	827.0	955.8	1326.0	1625.8	1692.2	1732.5	1762.6	1766.7	1766.7
27.5°	261.6	374.3	818.9	959.8	1362.2	1633.9	1686.2	1714.3	1728.4	1736.5	1736.5
30°	235.4	334.0	798.8	951.7	1378.3	1625.8	1668.1	1682.2	1696.2	1708.3	1714.3
32.5°	215.3	295.8	768.6	935.6	1380.3	1605.7	1635.9	1643.9	1664.0	1692.2	1702.3
35°	197.2	257.6	734.4	913.5	1368.3	1573.5	1593.6	1601.7	1641.9	1684.2	1698.2
37.5°	179.1	229.4	690.2	875.3	1350.1	1535.3	1549.3	1563.4	1625.8	1676.1	1692.2
40°	161.0	205.2	637.8	833.0	1322.0	1489.0	1501.1	1523.2	1605.7	1664.0	1680.1
42.5°	146.9	185.1	581.5	788.8	1285.8	1436.7	1454.8	1487.0	1581.5	1643.9	1662.0
45°	134.8	165.0	521.1	728.4	1239.5	1382.3	1408.5	1452.8	1553.4	1613.7	1629.8
47.5°	122.7	150.9	458.8	666.0	1189.2	1328.0	1362.2	1412.5	1515.1	1573.5	1587.6
50°	112.7	136.8	396.4	599.6	1134.8	1269.7	1309.9	1362.2	1466.9	1521.2	1539.3
52.5°	104.6	124.8	338.0	533.2	1072.5	1209.3	1255.6	1309.9	1408.5	1460.8	1472.9
55°	96.6	114.7	287.7	462.8	1008.1	1144.9	1195.2	1247.5	1344.1	1388.4	1396.4
57.5°	92.6	106.6	245.5	396.4	939.7	1072.5	1128.8	1177.1	1267.6	1301.9	1309.9
60°	86.5	100.6	213.3	340.1	865.2	1004.1	1052.4	1100.6	1177.1	1205.3	1211.3
62.5°	80.5	96.6	189.1	285.7	788.8	923.6	971.9	1016.1	1080.5	1100.6	1108.7
65°	76.5	92.6	171.0	245.5	710.3	839.1	887.4	925.6	977.9	998.0	1002.0
67.5°	72.4	88.5	156.9	211.3	631.8	754.6	790.8	827.0	867.2	887.4	889.4
70°	66.4	84.5	144.9	187.1	551.3	658.0	688.2	726.4	758.6	768.6	774.7
72.5°	62.4	78.5	136.8	169.0	468.8	565.4	593.6	615.7	643.9	653.9	653.9
75°	56.3	70.4	128.8	150.9	384.3	462.8	486.9	509.1	531.2	535.2	529.2
77.5°	50.3	62.4	110.7	126.8	299.8	366.2	386.3	398.4	416.5	420.5	422.5
80°	42.3	54.3	86.5	98.6	217.3	269.6	283.7	293.8	309.9	309.9	313.9
82.5°	32.2	42.3	62.4	70.4	146.9	185.1	197.2	203.2	213.3	213.3	213.3
85°	20.1	26.2	40.2	46.3	88.5	112.7	120.7	122.7	130.8	132.8	132.8
87.5°	10.1	14.1	26.2	28.2	46.3	58.4	58.4	62.4	62.4	60.4	58.4
90°	9.3	16.7	24.1	26.0	40.9	60.8	70.7	62.8	47.1	35.3	35.3
92.5°	37.2	100.4	163.7	179.5	252.3	349.4	398.0	348.8	250.5	176.7	169.7
95°	89.3	205.0	320.8	349.7	620.9	982.6	1163.4	1038.2	787.7	599.8	578.5
97.5°	154.4	256.5	358.6	384.1	836.4	1439.4	1740.9	1661.7	1503.4	1384.7	1344.2
100°	204.6	297.2	389.8	412.9	914.8	1583.9	1918.5	1924.3	1935.9	1944.6	1896.3
102.5°	247.4	333.8	420.1	441.7	950.7	1629.4	1968.8	2069.6	2271.3	2422.6	2381.3
105°	319.9	393.1	466.2	484.5	977.4	1634.6	1963.2	2189.3	2641.5	2980.6	2958.4
107.5°	394.3	462.5	530.7	547.8	982.4	1561.9	1851.6	2167.0	2797.7	3270.7	3276.1
110°	444.5	506.1	567.7	583.1	974.9	1497.4	1758.6	2111.2	2816.3	3345.1	3368.2



TEST NUMBER: P937013

CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	493.8	552.5	611.2	625.9	975.3	1441.1	1674.0	2034.8	2756.5	3297.7	3333.2
115°	568.2	622.3	676.5	690.0	984.2	1376.5	1572.6	1920.2	2615.4	3136.8	3186.1
117.5°	641.7	690.9	740.0	752.3	1002.5	1336.0	1502.8	1816.5	2443.9	2914.5	2969.2
120°	684.5	730.8	777.0	788.6	1017.4	1322.4	1474.9	1761.5	2334.8	2764.8	2817.9
122.5°	726.3	773.0	819.7	831.4	1038.8	1315.3	1453.5	1711.6	2227.9	2615.1	2667.5
125°	790.5	833.1	875.7	886.3	1067.6	1309.4	1430.3	1649.6	2088.1	2417.0	2465.3
127.5°	842.6	885.6	928.6	939.3	1096.5	1306.0	1410.8	1599.1	1975.6	2258.0	2298.7
130°	870.5	916.8	963.0	974.6	1117.5	1308.0	1403.3	1570.9	1906.1	2157.5	2195.1
132.5°	899.3	945.6	991.8	1003.4	1134.5	1309.4	1396.8	1546.8	1846.9	2072.0	2105.7
135°	942.1	984.2	1026.4	1036.9	1153.2	1308.2	1385.7	1511.3	1762.6	1951.1	1980.1
137.5°	985.8	1027.5	1069.3	1079.7	1181.1	1316.2	1383.8	1490.0	1702.5	1861.8	1885.6
140°	1022.0	1060.4	1098.9	1108.5	1198.1	1317.6	1377.3	1469.1	1652.6	1790.2	1812.4
142.5°	1049.9	1085.5	1121.0	1129.9	1212.4	1322.3	1377.3	1457.9	1619.1	1740.0	1759.1
145°	1092.7	1123.7	1154.7	1162.5	1231.0	1322.3	1368.0	1433.9	1565.8	1664.7	1679.2
147.5°	1135.5	1165.7	1195.9	1203.4	1258.3	1331.4	1368.0	1419.9	1523.6	1601.4	1613.4
150°	1163.4	1190.7	1218.0	1224.8	1272.5	1336.2	1368.0	1411.8	1499.4	1565.1	1574.8
152.5°	1192.2	1212.9	1233.5	1238.7	1281.8	1339.3	1368.0	1405.4	1480.2	1536.3	1543.6
155°	1235.0	1250.3	1265.6	1269.4	1302.3	1346.1	1368.0	1397.8	1457.3	1501.9	1506.8
157.5°	1266.6	1281.5	1296.4	1300.1	1322.7	1352.9	1368.0	1391.1	1437.4	1472.1	1475.5
160°	1288.0	1299.6	1311.2	1314.1	1332.1	1356.0	1368.0	1387.8	1427.5	1457.3	1459.3
162.5°	1309.4	1318.1	1326.7	1328.9	1341.9	1359.3	1368.0	1384.7	1418.2	1443.3	1445.2
165°	1332.7	1340.5	1348.3	1350.3	1356.2	1364.1	1368.0	1380.0	1403.9	1421.9	1423.9
167.5°	1354.0	1357.7	1361.5	1362.4	1367.4	1374.0	1377.3	1385.1	1400.8	1412.6	1413.4
170°	1368.0	1371.7	1375.5	1376.4	1376.7	1377.1	1377.3	1385.1	1400.8	1412.6	1412.6
172.5°	1375.4	1376.2	1377.1	1377.3	1377.3	1377.3	1377.3	1383.5	1395.9	1405.2	1404.5
175°	1385.7	1385.7	1385.7	1385.7	1382.9	1379.2	1377.3	1381.2	1389.1	1395.0	1395.0
177.5°	1385.7	1385.7	1385.7	1385.7	1383.5	1380.6	1379.2	1382.3	1388.5	1393.1	1392.3
180°	1385.7	1385.7	1385.7	1385.7	1385.7	1385.7	1385.7	1385.7	1385.7	1385.7	1385.7



TEST NUMBER: P937013

CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

CANDELA DISTRIBUTION (continued):

	80°	90°
0°	625.8	625.8
2.5°	668.0	664.0
5°	859.2	863.2
7.5°	1157.0	1155.0
10°	1438.7	1456.8
12.5°	1643.9	1647.9
15°	1768.7	1776.7
17.5°	1817.0	1819.0
20°	1819.0	1815.0
22.5°	1796.8	1792.8
25°	1770.7	1768.7
27.5°	1746.5	1748.6
30°	1736.5	1742.5
32.5°	1736.5	1746.5
35°	1740.5	1750.6
37.5°	1738.5	1750.6
40°	1730.4	1744.5
42.5°	1708.3	1718.4
45°	1674.1	1686.2
47.5°	1629.8	1637.9
50°	1573.5	1581.5
52.5°	1503.1	1505.1
55°	1418.6	1426.6
57.5°	1328.0	1330.0
60°	1227.4	1233.4
62.5°	1120.8	1120.8
65°	1008.1	1012.1
67.5°	891.4	901.4
70°	772.7	774.7
72.5°	656.0	656.0
75°	535.2	537.2
77.5°	420.5	420.5
80°	311.9	313.9
82.5°	215.3	219.3
85°	134.8	134.8
87.5°	62.4	56.3
90°	35.3	35.3
92.5°	141.6	113.5
95°	493.4	408.3
97.5°	1182.2	1020.2
100°	1703.3	1510.3
102.5°	2215.9	2050.6
105°	2869.5	2780.6
107.5°	3297.6	3319.1
110°	3460.8	3553.4



TEST NUMBER: P937013

CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

CANDELA DISTRIBUTION (continued):

	80°	90°
112.5°	3475.4	3617.6
115°	3383.2	3580.4
117.5°	3187.8	3406.5
120°	3030.4	3242.8
122.5°	2877.0	3086.6
125°	2658.3	2851.3
127.5°	2461.6	2624.4
130°	2345.6	2496.1
132.5°	2240.4	2375.2
135°	2096.3	2212.4
137.5°	1980.6	2075.7
140°	1901.3	1990.1
142.5°	1835.6	1912.0
145°	1737.0	1794.8
147.5°	1661.3	1709.3
150°	1613.7	1652.6
152.5°	1573.0	1602.3
155°	1526.2	1545.6
157.5°	1489.2	1502.8
160°	1467.1	1474.9
162.5°	1452.6	1460.1
165°	1431.7	1439.6
167.5°	1416.8	1420.1
170°	1412.6	1412.6
172.5°	1401.6	1398.7
175°	1395.0	1395.0
177.5°	1389.0	1385.7
180°	1385.7	1385.7



TEST NUMBER: P937013
 CATALOG NUMBER: SQ4-FB-075U-050D-835-1D-UNV-STD-W-12

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	1.75	2.52	2.82	3.60	5.06	14.95	15.71	16.02	16.79	18.25
	3H	2.45	3.14	3.53	4.22	5.71	16.78	17.47	17.86	18.55	20.04
	4H	2.75	3.40	3.83	4.48	5.97	17.43	18.08	18.52	19.17	20.66
	6H	2.99	3.59	4.09	4.68	6.18	17.86	18.46	18.96	19.55	21.05
	8H	3.06	3.63	4.16	4.73	6.23	17.98	18.55	19.08	19.66	21.15
	12H	3.07	3.61	4.18	4.71	6.23	18.05	18.59	19.15	19.69	21.21
4H	2H	8.97	9.62	10.06	10.70	12.20	15.21	15.86	16.30	16.95	18.44
	3H	10.52	11.07	11.63	12.18	13.69	17.25	17.80	18.35	18.91	20.41
	4H	10.61	11.12	11.72	12.22	13.74	18.02	18.52	19.12	19.62	21.14
	6H	10.62	11.05	11.73	12.18	13.69	18.55	18.99	19.67	20.11	21.63
	8H	10.59	11.00	11.71	12.11	13.65	18.72	19.12	19.83	20.24	21.77
	12H	10.54	10.91	11.68	12.04	13.58	18.81	19.17	19.94	20.30	21.84
8H	4H	12.05	12.46	13.17	13.57	15.11	18.07	18.47	19.18	19.59	21.12
	6H	12.29	12.62	13.43	13.78	15.31	18.70	19.03	19.84	20.19	21.72
	8H	12.31	12.60	13.45	13.74	15.29	18.92	19.21	20.06	20.35	21.90
	12H	12.27	12.53	13.42	13.66	15.25	19.06	19.32	20.21	20.45	22.04
12H	4H	12.19	12.56	13.33	13.69	15.23	18.02	18.38	19.15	19.51	21.05
	6H	12.55	12.84	13.69	13.98	15.53	18.68	18.97	19.82	20.11	21.66
	8H	12.61	12.87	13.76	14.01	15.59	18.91	19.16	20.06	20.30	21.89