

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P938032

Luminaire Tested: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P938032
REPORT IS A COMBINATION OF REPORTS P933599 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Batwing Frosted Continuous Roll L
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7135.9 lumens
Efficiency: N/A
Efficacy: 110.8 lumens/watt
Spacing Criteria (0/90/45): 0.71 / 2.69 / 2.33
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 4' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P938032
CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

Luminous Intensity Polar Plot





TEST NUMBER: P938032

CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	104	104	104	104	95	95	95	95	77	77	77	61	61	61	46	46	46	39
1	95	90	86	83	86	82	79	76	67	65	62	53	51	50	40	39	38	32
2	86	78	72	67	78	71	66	61	58	54	51	46	43	41	35	33	31	26
3	78	68	61	55	71	62	56	51	51	46	42	40	37	34	30	28	26	21
4	71	60	52	46	64	55	48	42	45	40	35	35	32	29	27	24	22	18
5	65	53	45	39	59	49	41	36	40	34	30	31	27	24	24	21	19	15
6	60	47	39	33	54	43	36	31	35	30	26	28	24	21	21	18	16	13
7	55	43	35	29	50	39	32	27	32	26	23	25	21	18	19	16	14	11
8	51	38	31	25	46	35	28	23	29	24	20	23	19	16	18	15	13	10
9	47	35	27	22	43	32	25	21	26	21	17	21	17	14	16	13	11	9
10	44	32	25	20	40	29	23	18	24	19	16	19	15	13	15	12	10	8

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3325	3325	3325
5°	3246	3840	4470
10°	2940	5594	7410
15°	2495	7303	8947
20°	2030	8458	9118
25°	1691	8843	8934
30°	1424	8892	8917
35°	1257	8738	9148
40°	1094	8539	9385
45°	988	8390	9422
50°	904	8256	9267
55°	864	8063	8855
60°	881	7698	8206
65°	913	7148	7316
70°	965	6222	6180
75°	1059	5060	4824
80°	1133	3497	3249
85°	952	1847	1663

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°
 Vertical Angle: 45°
 Luminance: 9422 cd/sqm



TEST NUMBER: P938032

CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.4	0.6
10°-20°	205.4	2.9
20°-30°	359.3	5.0
30°-40°	462.6	6.5
40°-50°	516.7	7.2
50°-60°	494.9	6.9
60°-70°	392.2	5.5
70°-80°	230.6	3.2
80°-90°	66.6	0.9
90°-100°	327.9	4.6
100°-110°	862.1	12.1
110°-120°	893.9	12.5
120°-130°	717.0	10.0
130°-140°	562.6	7.9
140°-150°	431.8	6.1
150°-160°	311.0	4.4
160°-170°	190.3	2.7
170°-180°	64.3	0.9
0°-30°	611.1	8.6
0°-40°	1073.7	15.0
0°-60°	2085.3	29.2
0°-90°	2774.8	38.9
90°-120°	2084.0	29.2
90°-150°	3795.5	53.2
90°-180°	4361.0	61.1
0°-180°	7135.9	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	358	358	358	358	358	
5°	349	374	422	477	494	32
15°	262	483	814	986	1017	73
25°	167	547	969	1012	1013	77
35°	113	523	913	964	1002	71
45°	77	417	806	924	966	60
55°	55	265	684	795	817	50
65°	44	141	508	572	580	43
75°	32	86	279	306	308	34
85°	12	26	69	76	77	12
90°	4	13	34	17	17	5
95°	43	170	565	291	198	48
105°	155	235	953	1447	1350	165
115°	276	335	764	1523	1738	272
125°	384	430	694	1173	1384	341
135°	457	503	673	947	1074	354
145°	530	564	664	808	871	332
155°	600	616	664	729	750	276
165°	647	656	664	690	699	183
175°	673	673	669	677	677	64
180°	673	673	673	673	673	



TEST NUMBER: P938032

CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	358.3	358.3	358.3	358.3	358.3	358.3	358.3	358.3	358.3	358.3	358.3
2.5°	358.3	358.3	360.7	361.8	364.1	365.3	367.6	369.8	376.8	377.9	380.2
5°	349.2	353.8	368.7	374.5	390.6	412.5	421.7	436.7	467.8	477.0	482.8
7.5°	335.3	345.7	382.6	391.8	432.1	489.7	513.9	546.2	595.7	619.9	639.5
10°	313.4	335.3	401.0	422.8	488.5	576.2	621.1	666.0	740.9	774.3	787.0
12.5°	289.3	324.9	420.6	450.5	545.0	672.9	727.1	776.6	861.9	906.8	913.7
15°	261.5	309.9	439.0	482.8	604.9	753.6	813.5	874.6	954.1	986.4	994.4
17.5°	237.4	298.4	456.2	502.4	651.1	826.2	887.2	938.0	1002.5	1024.4	1030.1
20°	207.4	280.0	467.8	527.8	699.5	879.2	938.0	977.1	1020.9	1034.8	1037.0
22.5°	185.5	260.4	474.7	536.9	731.6	911.4	961.0	992.1	1022.0	1026.6	1027.8
25°	167.1	238.5	473.6	547.3	759.4	931.0	969.0	992.1	1009.4	1011.6	1011.6
27.5°	149.8	214.3	469.0	549.6	780.0	935.6	965.6	981.7	989.8	994.4	994.4
30°	134.8	191.2	457.5	545.0	789.3	931.0	955.2	963.2	971.4	978.2	981.7
32.5°	123.3	169.3	440.2	535.8	790.4	919.5	936.7	941.4	952.9	969.0	974.8
35°	112.9	147.5	420.6	523.1	783.5	901.1	912.6	917.2	940.2	964.5	972.5
37.5°	102.6	131.3	395.2	501.2	773.1	879.2	887.2	895.3	931.0	959.8	969.0
40°	92.2	117.6	365.3	477.0	757.0	852.7	859.6	872.3	919.5	952.9	962.1
42.5°	84.2	106.0	333.0	451.7	736.3	822.7	833.1	851.5	905.7	941.4	951.7
45°	77.2	94.4	298.4	417.1	709.7	791.6	806.5	831.9	889.6	924.1	933.3
47.5°	70.3	86.4	262.7	381.4	681.0	760.5	780.0	808.9	867.7	901.1	909.1
50°	64.5	78.4	227.0	343.4	649.8	727.1	750.1	780.0	840.0	871.1	881.5
52.5°	59.9	71.4	193.6	305.4	614.2	692.5	719.0	750.1	806.5	836.5	843.4
55°	55.3	65.7	164.8	265.0	577.3	655.6	684.5	714.4	769.7	795.0	799.7
57.5°	53.0	61.0	140.6	227.0	538.1	614.2	646.4	674.1	725.9	745.5	750.1
60°	49.5	57.6	122.2	194.7	495.5	574.9	602.7	630.3	674.1	690.2	693.6
62.5°	46.1	55.3	108.3	163.6	451.7	528.9	556.5	581.9	618.8	630.3	634.9
65°	43.8	53.0	97.9	140.6	406.7	480.5	508.1	530.0	560.0	571.5	573.8
67.5°	41.5	50.7	89.9	121.0	361.8	432.1	452.8	473.6	496.6	508.1	509.3
70°	38.0	48.4	82.9	107.2	315.7	376.8	394.1	416.0	434.4	440.2	443.6
72.5°	35.8	44.9	78.4	96.8	268.5	323.8	339.9	352.6	368.7	374.5	374.5
75°	32.3	40.3	73.8	86.4	220.1	265.0	278.9	291.5	304.2	306.5	303.0
77.5°	28.8	35.8	63.4	72.6	171.7	209.7	221.2	228.1	238.5	240.9	242.0
80°	24.2	31.1	49.5	56.4	124.4	154.4	162.5	168.2	177.5	177.5	179.7
82.5°	18.4	24.2	35.8	40.3	84.2	106.0	112.9	116.4	122.2	122.2	122.2
85°	11.5	15.0	23.0	26.5	50.7	64.5	69.2	70.3	74.9	76.0	76.0
87.5°	5.8	8.0	15.0	16.1	26.5	33.4	33.4	35.8	35.8	34.5	33.4
90°	4.5	8.1	11.8	12.6	19.9	29.5	34.3	30.4	22.8	17.2	17.2
92.5°	18.1	48.7	79.4	87.1	122.5	169.7	193.2	169.3	121.6	85.8	82.4
95°	43.3	99.5	155.7	169.8	301.5	477.0	564.8	504.0	382.5	291.3	280.9
97.5°	74.9	124.4	174.1	186.4	406.0	698.8	845.2	806.7	729.9	672.3	652.6
100°	99.3	144.3	189.2	200.5	444.1	769.0	931.4	934.2	939.9	944.1	920.6
102.5°	120.1	162.0	204.0	214.4	461.6	791.1	955.8	1004.8	1102.8	1176.2	1156.1
105°	155.3	190.9	226.4	235.3	474.6	793.6	953.1	1062.9	1282.4	1447.1	1436.2
107.5°	191.4	224.5	257.7	266.0	477.0	758.3	899.0	1052.1	1358.3	1587.9	1590.5
110°	215.8	245.7	275.6	283.1	473.3	727.0	853.8	1025.0	1367.3	1624.1	1635.3



TEST NUMBER: P938032

CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	239.7	268.2	296.7	303.8	473.4	699.6	812.7	987.9	1338.3	1601.1	1618.3
115°	275.8	302.2	328.5	335.0	477.9	668.2	763.5	932.2	1269.8	1522.9	1546.8
117.5°	311.6	335.5	359.4	365.3	486.8	648.7	729.6	881.9	1186.5	1415.0	1441.5
120°	332.3	354.8	377.3	382.9	494.0	642.1	716.1	855.3	1133.6	1342.3	1368.1
122.5°	352.7	375.3	398.0	403.7	504.4	638.6	705.7	831.0	1081.7	1269.6	1295.1
125°	383.8	404.4	425.1	430.3	518.3	635.7	694.4	800.9	1013.7	1173.4	1196.9
127.5°	409.1	429.9	450.8	456.0	532.3	634.1	684.9	776.3	959.2	1096.2	1116.0
130°	422.6	445.1	467.6	473.2	542.6	635.1	681.3	762.7	925.4	1047.5	1065.7
132.5°	436.6	459.1	481.6	487.2	550.9	635.7	678.2	751.0	896.7	1006.0	1022.3
135°	457.4	477.9	498.3	503.4	559.8	635.1	672.8	733.8	855.8	947.3	961.4
137.5°	478.6	498.8	519.1	524.2	573.4	639.0	671.8	723.4	826.5	903.9	915.4
140°	496.2	514.8	533.5	538.2	581.7	639.7	668.7	713.2	802.4	869.2	880.0
142.5°	509.7	527.0	544.2	548.6	588.6	642.0	668.7	707.8	786.1	844.7	854.0
145°	530.5	545.5	560.6	564.4	597.6	642.0	664.1	696.1	760.2	808.2	815.3
147.5°	551.3	566.0	580.6	584.3	610.9	646.4	664.1	689.3	739.7	777.5	783.3
150°	564.8	578.1	591.3	594.6	617.8	648.7	664.1	685.4	728.0	759.9	764.6
152.5°	578.9	588.9	598.9	601.4	622.4	650.2	664.1	682.3	718.6	745.9	749.4
155°	599.6	607.0	614.4	616.3	632.2	653.5	664.1	678.6	707.5	729.2	731.5
157.5°	615.0	622.2	629.3	631.2	642.2	656.8	664.1	675.4	697.9	714.7	716.4
160°	625.3	630.9	636.6	638.0	646.7	658.3	664.1	673.7	693.0	707.5	708.4
162.5°	635.7	639.9	644.2	645.2	651.5	660.0	664.1	672.3	688.6	700.8	701.6
165°	647.0	650.8	654.6	655.6	658.5	662.2	664.1	670.0	681.6	690.3	691.3
167.5°	657.4	659.2	661.0	661.4	663.9	667.1	668.7	672.5	680.1	685.9	686.3
170°	664.1	666.0	667.8	668.2	668.4	668.6	668.7	672.5	680.1	685.9	685.9
172.5°	667.8	668.2	668.6	668.7	668.7	668.7	668.7	671.6	677.7	682.2	681.8
175°	672.8	672.8	672.8	672.8	671.4	669.5	668.7	670.6	674.3	677.2	677.2
177.5°	672.8	672.8	672.8	672.8	671.7	670.2	669.5	671.0	674.1	676.3	675.9
180°	672.8	672.8	672.8	672.8	672.8	672.8	672.8	672.8	672.8	672.8	672.8



TEST NUMBER: P938032

CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

CANDELA DISTRIBUTION (continued):

	80°	90°
0°	358.3	358.3
2.5°	382.6	380.2
5°	492.0	494.4
7.5°	662.6	661.4
10°	823.9	834.2
12.5°	941.4	943.7
15°	1012.9	1017.4
17.5°	1040.5	1041.6
20°	1041.6	1039.3
22.5°	1029.0	1026.6
25°	1014.0	1012.9
27.5°	1000.1	1001.3
30°	994.4	997.9
32.5°	994.4	1000.1
35°	996.7	1002.5
37.5°	995.5	1002.5
40°	991.0	999.0
42.5°	978.2	984.0
45°	958.7	965.6
47.5°	933.3	938.0
50°	901.1	905.7
52.5°	860.7	861.9
55°	812.3	816.9
57.5°	760.5	761.6
60°	702.9	706.3
62.5°	641.8	641.8
65°	577.3	579.6
67.5°	510.5	516.2
70°	442.5	443.6
72.5°	375.7	375.7
75°	306.5	307.7
77.5°	240.9	240.9
80°	178.6	179.7
82.5°	123.3	125.6
85°	77.2	77.2
87.5°	35.8	32.3
90°	17.2	17.2
92.5°	68.7	55.1
95°	239.5	198.2
97.5°	574.0	495.3
100°	826.9	733.2
102.5°	1075.8	995.6
105°	1393.2	1350.0
107.5°	1601.0	1611.4
110°	1680.2	1725.1



TEST NUMBER: P938032

CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

CANDELA DISTRIBUTION (continued):

	80°	90°
112.5°	1687.3	1756.4
115°	1642.6	1738.3
117.5°	1547.7	1653.8
120°	1471.2	1574.4
122.5°	1396.7	1498.5
125°	1290.5	1384.3
127.5°	1195.0	1274.1
130°	1138.8	1211.9
132.5°	1087.7	1153.1
135°	1017.8	1074.1
137.5°	961.6	1007.7
140°	923.0	966.2
142.5°	891.1	928.3
145°	843.3	871.4
147.5°	806.5	829.8
150°	783.5	802.4
152.5°	763.6	777.9
155°	741.0	750.4
157.5°	723.0	729.6
160°	712.3	716.1
162.5°	705.3	708.9
165°	695.1	698.9
167.5°	687.9	689.4
170°	685.9	685.9
172.5°	680.4	679.1
175°	677.2	677.2
177.5°	674.3	672.8
180°	672.8	672.8



TEST NUMBER: P938032

CATALOG NUMBER: SQ4-FB-125U-100D-92765-1D-UNV-STD-W-4-3000K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	4.06	4.85	5.10	5.90	7.32	17.19	17.99	18.23	19.04	20.46
	3H	4.76	5.47	5.81	6.53	7.97	19.01	19.73	20.06	20.79	22.23
	4H	5.05	5.73	6.11	6.79	8.24	19.65	20.32	20.71	21.39	22.83
	6H	5.30	5.93	6.37	6.99	8.45	20.06	20.69	21.13	21.75	23.21
	8H	5.37	5.96	6.44	7.04	8.50	20.17	20.77	21.25	21.85	23.30
	12H	5.38	5.95	6.46	7.02	8.50	20.23	20.80	21.31	21.87	23.35
4H	2H	11.24	11.92	12.31	12.98	14.42	17.46	18.14	18.53	19.20	20.65
	3H	12.80	13.37	13.88	14.46	15.92	19.49	20.06	20.56	21.14	22.60
	4H	12.89	13.42	13.98	14.50	15.97	20.24	20.76	21.32	21.84	23.32
	6H	12.90	13.35	13.99	14.45	15.93	20.76	21.21	21.85	22.32	23.79
	8H	12.88	13.30	13.97	14.39	15.88	20.92	21.34	22.01	22.43	23.92
	12H	12.83	13.21	13.94	14.32	15.81	21.00	21.38	22.11	22.49	23.98
8H	4H	14.32	14.74	15.41	15.84	17.33	20.30	20.72	21.39	21.81	23.30
	6H	14.56	14.91	15.68	16.05	17.53	20.91	21.26	22.02	22.39	23.88
	8H	14.58	14.88	15.70	16.00	17.51	21.12	21.43	22.24	22.54	24.05
	12H	14.54	14.81	15.67	15.93	17.47	21.25	21.52	22.38	22.64	24.18
12H	4H	14.46	14.84	15.57	15.95	17.44	20.25	20.63	21.35	21.73	23.23
	6H	14.82	15.12	15.94	16.24	17.74	20.89	21.20	22.01	22.32	23.82
	8H	14.88	15.15	16.01	16.27	17.81	21.11	21.38	22.24	22.49	24.04