

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P938144

Luminaire Tested: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P938144
REPORT IS A COMBINATION OF REPORTS P933616 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Batwing Frosted Continuous Roll L
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 15828.3 lumens
Efficiency: N/A
Efficacy: 105.2 lumens/watt
Spacing Criteria (0/90/45): 0.71 / 2.69 / 2.33
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 8' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 150.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P938144
CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

Luminous Intensity Polar Plot





TEST NUMBER: P938144

CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	106	106	106	106	97	97	97	97	80	80	80	65	65	65	51	51	51	45
1	96	92	88	84	88	84	81	77	70	67	65	57	55	53	45	44	42	37
2	87	79	73	68	79	73	67	63	61	56	53	49	46	44	39	37	35	30
3	79	69	62	56	72	64	57	52	53	48	44	43	39	36	34	31	29	25
4	72	61	53	47	66	56	49	43	47	41	37	38	34	31	30	27	25	21
5	66	54	46	39	60	50	42	37	41	36	31	34	29	26	27	23	21	18
6	60	48	40	34	55	44	37	31	37	31	27	30	26	23	24	21	18	15
7	56	43	35	29	51	40	32	27	33	28	23	27	23	20	22	18	16	13
8	52	39	31	26	47	36	29	24	30	25	21	25	20	17	20	16	14	12
9	48	35	28	23	44	33	26	21	27	22	18	23	18	15	18	15	12	10
10	45	32	25	20	41	30	23	19	25	20	16	21	17	14	17	13	11	9

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	4259	4259	4259
5°	4161	4923	5724
10°	3774	7175	9490
15°	3207	9374	11460
20°	2611	10863	11679
25°	2178	11368	11442
30°	1837	11440	11420
35°	1624	11250	11715
40°	1415	11003	12021
45°	1282	10822	12068
50°	1176	10659	11868
55°	1126	10421	11342
60°	1153	9963	10511
65°	1199	9268	9370
70°	1277	8082	7915
75°	1416	6590	6178
80°	1547	4570	4162
85°	1374	2425	2131

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°
 Vertical Angle: 45°
 Luminance: 12068 cd/sqm



TEST NUMBER: P938144

CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	118.7	0.8
10°-20°	526.2	3.3
20°-30°	920.5	5.8
30°-40°	1184.9	7.5
40°-50°	1323.5	8.4
50°-60°	1267.6	8.0
60°-70°	1004.6	6.3
70°-80°	590.7	3.7
80°-90°	169.3	1.1
90°-100°	655.9	4.1
100°-110°	1724.3	10.9
110°-120°	1787.9	11.3
120°-130°	1434.1	9.1
130°-140°	1125.3	7.1
140°-150°	863.7	5.5
150°-160°	622.0	3.9
160°-170°	380.6	2.4
170°-180°	128.6	0.8
0°-30°	1565.5	9.9
0°-40°	2750.4	17.4
0°-60°	5341.5	33.7
0°-90°	7106.1	44.9
90°-120°	4168.0	26.3
90°-150°	7591.1	48.0
90°-180°	8722.0	55.1
0°-180°	15828.3	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	918	918	918	918	918	
5°	894	959	1080	1222	1266	83
15°	670	1237	2084	2526	2606	186
25°	428	1402	2482	2591	2594	197
35°	289	1340	2338	2470	2568	181
45°	198	1068	2066	2367	2473	153
55°	142	679	1753	2036	2093	129
65°	112	360	1302	1464	1485	111
75°	83	221	714	785	788	87
85°	30	68	177	195	198	31
90°	9	25	69	34	34	9
95°	87	340	1130	582	396	96
105°	311	470	1906	2894	2700	329
115°	552	670	1527	3046	3476	545
125°	768	860	1389	2347	2769	681
135°	915	1007	1346	1894	2148	708
145°	1061	1129	1328	1616	1743	665
155°	1199	1233	1328	1458	1501	551
165°	1294	1311	1328	1381	1398	365
175°	1346	1346	1337	1354	1354	128
180°	1346	1346	1346	1346	1346	



TEST NUMBER: P938144

CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	917.9	917.9	917.9	917.9	917.9	917.9	917.9	917.9	917.9	917.9	917.9
2.5°	917.9	917.9	923.8	926.8	932.6	935.6	941.5	947.5	965.2	968.1	974.0
5°	894.3	906.1	944.5	959.2	1000.6	1056.6	1080.3	1118.6	1198.3	1221.9	1236.6
7.5°	858.9	885.5	979.9	1003.5	1106.8	1254.4	1316.3	1399.0	1525.9	1587.9	1638.1
10°	802.8	858.9	1027.1	1083.2	1251.5	1475.7	1590.9	1706.0	1897.8	1983.4	2015.9
12.5°	740.8	832.4	1077.3	1154.0	1396.0	1723.7	1862.4	1989.3	2207.7	2322.8	2340.5
15°	670.0	794.0	1124.5	1236.6	1549.5	1930.2	2083.7	2240.2	2443.9	2526.5	2547.1
17.5°	608.0	764.4	1168.8	1286.9	1667.6	2116.3	2272.6	2402.5	2567.8	2623.9	2638.6
20°	531.2	717.2	1198.3	1351.7	1791.6	2252.0	2402.5	2502.8	2615.1	2650.5	2656.3
22.5°	475.2	667.0	1216.1	1375.4	1874.2	2334.6	2461.6	2541.2	2617.9	2629.8	2632.8
25°	428.0	610.9	1213.1	1402.0	1945.1	2384.8	2482.2	2541.2	2585.5	2591.4	2591.4
27.5°	383.7	548.9	1201.2	1407.9	1998.2	2396.6	2473.4	2514.7	2535.4	2547.1	2547.1
30°	345.3	489.9	1171.8	1396.0	2021.8	2384.8	2446.8	2467.4	2488.1	2505.8	2514.7
32.5°	315.9	433.8	1127.5	1372.4	2024.7	2355.3	2399.6	2411.3	2440.9	2482.2	2497.0
35°	289.3	377.8	1077.3	1340.0	2007.0	2308.1	2337.6	2349.3	2408.4	2470.4	2491.1
37.5°	262.7	336.4	1012.3	1283.9	1980.5	2252.0	2272.6	2293.3	2384.8	2458.6	2482.2
40°	236.1	301.0	935.6	1221.9	1939.1	2184.1	2201.8	2234.2	2355.3	2440.9	2464.5
42.5°	215.5	271.6	853.0	1157.0	1886.0	2107.4	2134.0	2181.1	2319.9	2411.3	2437.9
45°	197.8	242.0	764.4	1068.4	1818.1	2027.7	2066.0	2131.0	2278.5	2367.1	2390.7
47.5°	180.1	221.3	672.9	976.9	1744.3	1947.9	1998.2	2072.0	2222.5	2308.1	2328.8
50°	165.3	200.7	581.5	879.5	1664.6	1862.4	1921.4	1998.2	2151.7	2231.4	2257.9
52.5°	153.5	183.0	495.8	782.1	1573.1	1773.8	1841.7	1921.4	2066.0	2142.8	2160.5
55°	141.7	168.2	422.1	678.9	1478.7	1679.4	1753.2	1830.0	1971.6	2036.5	2048.3
57.5°	135.8	156.4	360.1	581.5	1378.3	1573.1	1655.8	1726.6	1859.4	1909.6	1921.4
60°	126.9	147.5	312.9	498.8	1269.2	1472.8	1543.6	1614.5	1726.6	1768.0	1776.8
62.5°	118.1	141.7	277.5	419.1	1157.0	1354.7	1425.6	1490.5	1584.9	1614.5	1626.3
65°	112.1	135.8	250.9	360.1	1041.9	1230.8	1301.6	1357.7	1434.4	1464.0	1469.8
67.5°	106.2	129.8	230.2	309.9	926.8	1106.8	1159.9	1213.1	1272.1	1301.6	1304.6
70°	97.4	124.0	212.5	274.5	808.7	965.2	1009.4	1065.5	1112.7	1127.5	1136.3
72.5°	91.5	115.1	200.7	247.9	687.7	829.4	870.7	903.2	944.5	959.2	959.2
75°	82.7	103.3	188.9	221.3	563.8	678.9	714.3	746.7	779.2	785.1	776.3
77.5°	73.8	91.5	162.4	185.9	439.8	537.2	566.6	584.4	610.9	616.9	619.8
80°	62.0	79.7	126.9	144.6	318.7	395.5	416.1	431.0	454.5	454.5	460.4
82.5°	47.3	62.0	91.5	103.3	215.5	271.6	289.3	298.1	312.9	312.9	312.9
85°	29.5	38.4	59.0	67.8	129.8	165.3	177.1	180.1	191.8	194.8	194.8
87.5°	14.7	20.7	38.4	41.3	67.8	85.6	85.6	91.5	91.5	88.5	85.6
90°	9.1	16.3	23.5	25.3	39.8	59.0	68.6	61.0	45.7	34.3	34.3
92.5°	36.1	97.5	159.0	174.3	245.0	339.3	386.5	338.7	243.2	171.5	164.7
95°	86.7	199.1	311.5	339.6	602.9	954.1	1129.6	1008.1	764.9	582.4	561.8
97.5°	149.9	249.1	348.2	373.0	812.1	1397.7	1690.4	1613.6	1459.9	1344.6	1305.3
100°	198.6	288.6	378.5	401.0	888.3	1538.0	1862.9	1868.5	1879.8	1888.2	1841.4
102.5°	240.2	324.0	407.9	429.0	923.2	1582.2	1911.7	2009.6	2205.5	2352.3	2312.2
105°	310.6	381.7	452.7	470.5	949.0	1587.2	1906.3	2125.8	2564.8	2894.1	2872.6
107.5°	382.9	449.1	515.3	531.9	953.8	1516.6	1797.9	2104.1	2716.6	3175.9	3181.1
110°	431.7	491.5	551.3	566.2	946.7	1453.9	1707.6	2050.0	2734.6	3248.1	3270.6



TEST NUMBER: P938144

CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	479.5	536.5	593.5	607.7	946.9	1399.3	1625.4	1975.8	2676.4	3202.0	3236.6
115°	551.7	604.3	656.8	670.0	955.7	1336.6	1527.0	1864.5	2539.5	3045.8	3093.7
117.5°	623.1	670.9	718.6	730.5	973.5	1297.3	1459.3	1763.9	2373.1	2830.0	2883.1
120°	664.6	709.6	754.5	765.7	987.8	1284.1	1432.1	1710.5	2267.1	2684.6	2736.2
122.5°	705.2	750.6	795.9	807.2	1008.6	1277.1	1411.4	1662.0	2163.3	2539.3	2590.1
125°	767.6	808.9	850.2	860.5	1036.6	1271.4	1388.8	1601.8	2027.6	2346.9	2393.7
127.5°	818.1	859.9	901.6	912.1	1064.7	1268.1	1369.9	1552.7	1918.3	2192.5	2232.0
130°	845.2	890.2	935.1	946.3	1085.1	1270.1	1362.6	1525.4	1850.9	2095.0	2131.5
132.5°	873.2	918.2	963.1	974.3	1101.6	1271.4	1356.3	1502.0	1793.3	2011.9	2044.6
135°	914.8	955.7	996.6	1006.9	1119.7	1270.2	1345.5	1467.5	1711.5	1894.5	1922.7
137.5°	957.1	997.7	1038.2	1048.4	1146.8	1278.1	1343.6	1446.8	1653.1	1807.8	1830.9
140°	992.4	1029.7	1067.0	1076.4	1163.4	1279.4	1337.4	1426.5	1604.6	1738.3	1759.9
142.5°	1019.5	1054.0	1088.5	1097.1	1177.2	1284.0	1337.4	1415.6	1572.1	1689.5	1708.1
145°	1061.0	1091.1	1121.3	1128.8	1195.3	1284.0	1328.3	1392.3	1520.4	1616.4	1630.4
147.5°	1102.6	1131.9	1161.2	1168.5	1221.8	1292.8	1328.3	1378.7	1479.4	1555.0	1566.6
150°	1129.6	1156.1	1182.7	1189.3	1235.6	1297.4	1328.3	1370.8	1455.9	1519.8	1529.2
152.5°	1157.6	1177.7	1197.7	1202.8	1244.7	1300.4	1328.3	1364.6	1437.3	1491.8	1498.9
155°	1199.2	1214.0	1228.9	1232.6	1264.5	1307.0	1328.3	1357.2	1415.0	1458.4	1463.1
157.5°	1229.9	1244.3	1258.8	1262.4	1284.3	1313.6	1328.3	1350.8	1395.7	1429.4	1432.8
160°	1250.7	1261.9	1273.2	1276.0	1293.4	1316.7	1328.3	1347.6	1386.1	1415.0	1416.9
162.5°	1271.4	1279.8	1288.3	1290.3	1303.0	1319.8	1328.3	1344.5	1377.0	1401.4	1403.3
165°	1294.0	1301.7	1309.3	1311.2	1316.9	1324.4	1328.3	1340.0	1363.3	1380.7	1382.6
167.5°	1314.8	1318.3	1322.0	1322.9	1327.7	1334.1	1337.4	1344.9	1360.2	1371.6	1372.4
170°	1328.3	1331.9	1335.6	1336.5	1336.7	1337.2	1337.4	1344.9	1360.2	1371.6	1371.6
172.5°	1335.5	1336.3	1337.2	1337.4	1337.4	1337.4	1337.4	1343.4	1355.4	1364.5	1363.8
175°	1345.5	1345.5	1345.5	1345.5	1342.8	1339.2	1337.4	1341.2	1348.8	1354.5	1354.5
177.5°	1345.5	1345.5	1345.5	1345.5	1343.4	1340.6	1339.2	1342.1	1348.2	1352.7	1351.9
180°	1345.5	1345.5	1345.5	1345.5	1345.5	1345.5	1345.5	1345.5	1345.5	1345.5	1345.5



TEST NUMBER: P938144

CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

CANDELA DISTRIBUTION (continued):

	80°	90°
0°	917.9	917.9
2.5°	979.9	974.0
5°	1260.3	1266.2
7.5°	1697.1	1694.2
10°	2110.3	2136.9
12.5°	2411.3	2417.3
15°	2594.4	2606.2
17.5°	2665.2	2668.2
20°	2668.2	2662.2
22.5°	2635.7	2629.8
25°	2597.4	2594.4
27.5°	2561.9	2564.8
30°	2547.1	2556.0
32.5°	2547.1	2561.9
35°	2553.1	2567.8
37.5°	2550.1	2567.8
40°	2538.3	2559.0
42.5°	2505.8	2520.6
45°	2455.6	2473.4
47.5°	2390.7	2402.5
50°	2308.1	2319.9
52.5°	2204.8	2207.7
55°	2080.8	2092.6
57.5°	1947.9	1950.9
60°	1800.4	1809.3
62.5°	1644.0	1644.0
65°	1478.7	1484.6
67.5°	1307.5	1322.3
70°	1133.4	1136.3
72.5°	962.2	962.2
75°	785.1	788.1
77.5°	616.9	616.9
80°	457.5	460.4
82.5°	315.9	321.7
85°	197.8	197.8
87.5°	91.5	82.7
90°	34.3	34.3
92.5°	137.4	110.1
95°	479.1	396.4
97.5°	1147.9	990.6
100°	1653.9	1466.5
102.5°	2151.7	1991.1
105°	2786.2	2700.0
107.5°	3201.9	3222.8
110°	3360.5	3450.4



TEST NUMBER: P938144

CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

CANDELA DISTRIBUTION (continued):

	80°	90°
112.5°	3374.6	3512.6
115°	3285.1	3476.5
117.5°	3095.4	3307.7
120°	2942.5	3148.7
122.5°	2793.6	2997.1
125°	2581.2	2768.6
127.5°	2390.2	2548.3
130°	2277.6	2423.6
132.5°	2175.5	2306.3
135°	2035.5	2148.3
137.5°	1923.2	2015.5
140°	1846.2	1932.4
142.5°	1782.3	1856.6
145°	1686.6	1742.8
147.5°	1613.2	1659.7
150°	1567.0	1604.6
152.5°	1527.4	1555.9
155°	1481.9	1500.8
157.5°	1446.0	1459.3
160°	1424.5	1432.1
162.5°	1410.5	1417.8
165°	1390.2	1397.9
167.5°	1375.6	1378.9
170°	1371.6	1371.6
172.5°	1360.9	1358.1
175°	1354.5	1354.5
177.5°	1348.7	1345.5
180°	1345.5	1345.5



TEST NUMBER: P938144
 CATALOG NUMBER: SQ4-FB-125U-125D-92765-1D-UNV-STD-W-8-3000K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	5.56	6.41	6.55	7.41	8.75	18.73	19.58	19.73	20.59	21.93
	3H	6.26	7.02	7.26	8.04	9.40	20.57	21.34	21.57	22.35	23.71
	4H	6.56	7.28	7.57	8.30	9.67	21.22	21.94	22.23	22.96	24.33
	6H	6.81	7.48	7.83	8.50	9.88	21.65	22.32	22.67	23.34	24.72
	8H	6.88	7.51	7.91	8.55	9.93	21.77	22.40	22.80	23.45	24.82
	12H	6.89	7.50	7.93	8.53	9.94	21.84	22.44	22.87	23.48	24.88
4H	2H	12.77	13.49	13.79	14.51	15.88	19.01	19.73	20.03	20.75	22.12
	3H	14.34	14.94	15.37	15.99	17.37	21.05	21.66	22.08	22.71	24.09
	4H	14.43	14.99	15.47	16.03	17.43	21.82	22.37	22.86	23.41	24.82
	6H	14.44	14.92	15.49	15.98	17.38	22.36	22.84	23.40	23.90	25.30
	8H	14.42	14.86	15.47	15.92	17.34	22.52	22.97	23.57	24.02	25.44
	12H	14.37	14.78	15.44	15.85	17.27	22.61	23.02	23.68	24.09	25.51
8H	4H	15.87	16.32	16.92	17.38	18.79	21.88	22.32	22.93	23.38	24.80
	6H	16.11	16.49	17.19	17.59	19.00	22.51	22.88	23.58	23.98	25.39
	8H	16.13	16.46	17.21	17.54	18.97	22.73	23.05	23.81	24.13	25.57
	12H	16.10	16.39	17.19	17.47	18.94	22.87	23.16	23.96	24.24	25.71
12H	4H	16.02	16.42	17.08	17.49	18.91	21.83	22.23	22.90	23.31	24.73
	6H	16.37	16.70	17.45	17.78	19.21	22.49	22.82	23.57	23.90	25.33
	8H	16.44	16.73	17.53	17.81	19.28	22.72	23.01	23.80	24.08	25.56