

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P521824

Luminaire Tested: **SQ4-WB-075U-075D-92765-1D-UNV-STD-W-4 (4000K)**

Issue Date: 5/5/2021

Test Information

Test Method: LM-79-08
Report Number: P521824
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2101-105-51,
Test Lab: INNOVATION CENTER
Issue Date: 5/5/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: CORELITE
Catalog Number: SQ4-WB-075U-075D-92765-1D-UNV-STD-W-4 (4000K)
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE
DOWNLIGHT 750 LUMENS PER FOOT
UPLIGHT 750 LUMENS PER FOOT
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 4000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5985.4 lumens
Efficiency: N/A
Efficacy: 107.7 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')
CIE Type: General Diffuse

Input Watts (W): 55.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P521824

CATALOG NUMBER: SQ4-WB-075U-075D-92765-1D-UNV-STD-W-4 (4000K)

Luminous Intensity Polar Plot





TEST NUMBER: P521824

CATALOG NUMBER: SQ4-WB-075U-075D-92765-1D-UNV-STD-W-4 (4000K)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	106	106	106	106	97	97	97	97	80	80	80	65	65	65	51	51	51	44				
1	98	94	90	87	89	86	83	80	72	70	68	59	57	56	47	46	45	39				
2	90	83	77	73	82	76	72	68	64	61	58	53	51	48	42	41	40	35				
3	82	74	67	62	76	68	62	58	58	53	50	48	45	42	38	37	35	31				
4	76	66	59	53	70	61	55	50	52	47	44	43	40	37	35	33	31	27				
5	70	59	52	46	64	55	49	44	47	42	38	39	36	33	32	30	28	25				
6	65	54	46	41	60	50	43	39	43	38	34	36	32	29	30	27	25	22				
7	60	49	42	36	55	46	39	34	39	34	30	33	29	27	27	25	23	20				
8	56	45	37	32	52	42	35	31	36	31	27	31	27	24	25	23	21	18				
9	53	41	34	29	48	38	32	28	33	28	25	28	25	22	24	21	19	17				
10	49	38	31	27	45	35	29	25	31	26	23	26	23	20	22	19	18	16				

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	16830	16830	16830
5°	16621	16561	16658
10°	15703	15845	16213
15°	14497	14833	15498
20°	13164	13659	14563
25°	11808	12451	13567
30°	10558	11248	12536
35°	9232	9899	11315
40°	7771	8387	9795
45°	6413	6966	8178
50°	5354	5836	6814
55°	4546	5009	5627
60°	3884	4342	4489
65°	3093	3652	2901
70°	2743	2851	1770
75°	2538	2310	1084
80°	2338	2125	935
85°	2117	1948	762



TEST NUMBER: P521824

CATALOG NUMBER: SQ4-WB-075U-075D-92765-1D-UNV-STD-W-4 (4000K)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	167.3	2.8
10°-20°	435.2	7.3
20°-30°	563.7	9.4
30°-40°	552.0	9.2
40°-50°	422.6	7.1
50°-60°	281.6	4.7
60°-70°	153.7	2.6
70°-80°	64.0	1.1
80°-90°	18.1	0.3
90°-100°	244.1	4.1
100°-110°	694.5	11.6
110°-120°	665.4	11.1
120°-130°	526.6	8.8
130°-140°	422.7	7.1
140°-150°	330.9	5.5
150°-160°	242.1	4.0
160°-170°	150.0	2.5
170°-180°	50.9	0.9
0°-30°	1166.3	19.5
0°-40°	1718.3	28.7
0°-60°	2422.4	40.5
0°-90°	2658.2	44.4
90°-120°	1603.9	26.8
90°-150°	2884.1	48.2
90°-180°	3327.0	55.6
0°-180°	5985.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1824	1824	1824	1824	1824	
5°	1795	1777	1788	1792	1799	167
15°	1518	1512	1553	1595	1622	424
25°	1160	1163	1223	1276	1333	533
35°	820	824	879	938	1005	510
45°	492	501	534	574	627	383
55°	283	294	311	323	350	256
65°	142	153	167	146	133	147
75°	71	71	65	44	30	76
85°	20	20	18	12	7	22
90°	0	0	0	0	0	2
95°	26	105	472	164	101	30
105°	108	164	708	1250	1188	114
115°	201	242	537	1137	1335	198
125°	283	314	512	850	1016	253
135°	346	375	506	718	812	267
145°	408	429	510	621	677	255
155°	466	477	522	562	584	216
165°	515	517	528	540	548	145
175°	540	537	535	532	528	51
180°	536	536	536	536	536	



TEST NUMBER: P521824

CATALOG NUMBER: SQ4-WB-075U-075D-92765-1D-UNV-STD-W-4 (4000K)

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1824.2	1824.2	1824.2	1824.2	1824.2
2.5°	1828.7	1812.4	1816.5	1816.4	1811.4
5°	1794.6	1776.6	1788.2	1792.3	1798.6
7.5°	1728.0	1714.4	1735.5	1751.2	1763.9
10°	1676.1	1664.4	1691.3	1714.1	1730.6
12.5°	1615.9	1606.1	1639.5	1670.1	1691.5
15°	1517.7	1512.2	1552.9	1595.1	1622.5
17.5°	1412.5	1409.8	1456.5	1505.8	1540.9
20°	1340.8	1340.0	1391.2	1442.5	1483.2
22.5°	1268.4	1270.1	1323.9	1377.3	1423.7
25°	1159.9	1163.0	1223.1	1276.4	1332.7
27.5°	1059.5	1060.9	1123.0	1179.3	1239.4
30°	991.0	994.9	1055.8	1114.0	1176.7
32.5°	922.4	927.0	986.6	1046.8	1110.7
35°	819.7	823.6	878.9	938.0	1004.6
37.5°	713.7	719.0	768.1	824.0	889.5
40°	645.2	653.0	696.4	749.1	813.3
42.5°	579.2	588.9	629.2	679.1	737.1
45°	491.5	500.9	533.9	574.3	626.8
47.5°	415.9	426.7	452.1	486.9	531.7
50°	373.0	383.2	406.6	432.4	474.7
52.5°	335.2	345.4	366.3	386.2	422.2
55°	282.6	294.3	311.4	323.2	349.8
57.5°	239.3	250.6	264.1	269.5	285.6
60°	210.5	223.0	235.3	234.7	243.3
62.5°	184.3	194.9	207.2	198.7	199.2
65°	141.7	153.4	167.3	146.2	132.9
67.5°	114.5	117.0	131.3	101.9	86.1
70°	101.7	101.7	105.7	78.9	65.6
72.5°	89.5	89.5	85.8	64.2	50.3
75°	71.2	71.2	64.8	44.5	30.4
77.5°	54.9	54.3	49.6	33.2	22.1
80°	44.0	44.0	40.0	26.2	17.6
82.5°	34.4	34.4	31.1	20.5	13.1
85°	20.0	20.0	18.4	11.9	7.2
87.5°	7.0	7.0	6.4	3.8	3.2
90°	0.0	0.0	0.0	0.0	0.0
92.5°	8.1	43.2	100.2	29.2	22.0
95°	26.5	105.1	472.5	163.5	100.8
97.5°	48.7	123.2	727.7	520.7	356.8
100°	64.2	133.8	783.1	793.2	611.0
102.5°	81.3	145.4	770.8	1015.3	856.2
105°	107.9	163.7	707.7	1250.1	1188.4
107.5°	135.0	185.0	634.0	1316.3	1371.2
110°	153.8	200.6	591.6	1290.9	1414.4

TEST NUMBER: P521824

CATALOG NUMBER: SQ4-WB-075U-075D-92765-1D-UNV-STD-W-4 (4000K)

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	171.7	216.1	563.1	1231.0	1407.1
115°	200.6	242.4	536.6	1136.8	1335.0
117.5°	226.1	265.3	521.0	1033.9	1243.7
120°	246.4	279.3	519.3	975.0	1176.1
122.5°	262.7	295.6	515.3	923.4	1110.1
125°	283.1	314.0	512.2	850.0	1016.3
127.5°	305.3	334.2	510.6	806.1	943.1
130°	316.7	345.6	508.1	775.6	895.1
132.5°	328.9	357.0	508.1	751.8	861.7
135°	346.2	375.1	506.1	718.0	811.6
137.5°	362.5	390.6	505.9	689.4	770.2
140°	374.7	403.6	505.1	665.7	743.4
142.5°	388.6	412.7	507.5	646.8	716.5
145°	408.3	429.2	510.2	621.4	677.2
147.5°	425.2	445.6	514.6	595.8	644.0
150°	439.9	453.8	516.3	587.3	621.2
152.5°	451.3	466.0	517.9	575.8	607.3
155°	466.4	477.3	522.4	561.6	584.5
157.5°	485.1	491.7	523.4	555.1	571.5
160°	494.9	499.9	527.5	550.2	564.1
162.5°	500.6	506.4	528.3	546.1	556.8
165°	515.3	517.2	528.5	539.9	547.8
167.5°	525.2	523.4	533.2	538.3	541.5
170°	528.5	527.5	531.5	532.7	536.6
172.5°	535.8	532.4	534.0	531.0	534.2
175°	539.7	536.7	534.6	531.5	527.5
177.5°	541.3	536.5	534.0	530.8	531.5
180°	535.6	535.6	535.6	535.6	535.6

(END OF REPORT)