

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P521875

Luminaire Tested: **SQ4-WB-0U-075D-92765-1D-UNV-STD-W-4 (3500K)**

Issue Date: 5/5/2021

Test Information

Test Method: LM-79-08
Report Number: P521875
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2009-966-13)
Test Lab: INNOVATION CENTER
Issue Date: 5/5/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: CORELITE
Catalog Number: SQ4-WB-0U-075D-92765-1D-UNV-STD-W-4 (3500K)
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE
DOWNLIGHT 750 LUMENS PER FOOT
DIRECT ONLY
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2610.5 lumens
Efficiency: N/A
Efficacy: 81.8 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 31.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P521875

CATALOG NUMBER: SQ4-WB-0U-075D-92765-1D-UNV-STD-W-4 (3500K)

Luminous Intensity Polar Plot





TEST NUMBER: P521875

CATALOG NUMBER: SQ4-WB-OU-075D-92765-1D-UNV-STD-W-4 (3500K)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89
2	103	97	91	87	101	95	90	86	92	87	84	88	85	82	85	83	80	78
3	96	87	81	75	94	86	80	75	83	78	73	80	76	72	78	74	71	69
4	89	79	72	66	87	78	71	66	76	70	65	74	68	64	71	67	64	62
5	83	72	65	59	81	71	64	59	69	63	58	67	62	58	66	61	57	55
6	78	66	59	53	76	65	58	53	64	57	53	62	56	52	61	56	52	50
7	73	61	53	48	71	60	53	48	59	52	48	58	52	47	56	51	47	45
8	68	57	49	44	67	56	49	44	55	48	44	53	48	43	52	47	43	41
9	64	53	45	40	63	52	45	40	51	45	40	50	44	40	49	44	40	38
10	61	49	42	37	60	48	42	37	48	41	37	47	41	37	46	41	37	35

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	16529	16529	16529
5°	16322	16264	16358
10°	15421	15561	15922
15°	14236	14566	15220
20°	12928	13414	14301
25°	11595	12227	13324
30°	10368	11046	12310
35°	9066	9721	11111
40°	7631	8237	9618
45°	6297	6841	8031
50°	5258	5731	6690
55°	4464	4919	5525
60°	3814	4264	4410
65°	3037	3587	2849
70°	2692	2800	1740
75°	2495	2271	1066
80°	2295	2088	919
85°	2085	1916	752



TEST NUMBER: P521875

CATALOG NUMBER: SQ4-WB-OU-075D-92765-1D-UNV-STD-W-4 (3500K)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	164.3	6.3
10°-20°	427.4	16.4
20°-30°	553.6	21.2
30°-40°	542.1	20.8
40°-50°	415.0	15.9
50°-60°	276.5	10.6
60°-70°	150.9	5.8
70°-80°	62.9	2.4
80°-90°	17.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1145.3	43.9
0°-40°	1687.4	64.6
0°-60°	2378.9	91.1
0°-90°	2610.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2610.5	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1792	1792	1792	1792	1792	
5°	1762	1745	1756	1760	1766	164
15°	1490	1485	1525	1566	1593	416
25°	1139	1142	1201	1254	1309	524
35°	805	809	863	921	986	500
45°	483	492	524	564	616	376
55°	278	289	306	317	344	252
65°	139	151	164	144	130	145
75°	70	70	64	44	30	75
85°	20	20	18	12	7	22
90°	0	0	0	0	0	



TEST NUMBER: P521875

CATALOG NUMBER: SQ4-WB-OU-075D-92765-1D-UNV-STD-W-4 (3500K)

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1791.5	1791.5	1791.5	1791.5	1791.5
2.5°	1795.9	1779.9	1783.9	1783.8	1778.9
5°	1762.4	1744.7	1756.1	1760.1	1766.3
7.5°	1697.0	1683.6	1704.4	1719.7	1732.2
10°	1646.0	1634.5	1661.0	1683.3	1699.5
12.5°	1586.9	1577.2	1610.0	1640.1	1661.1
15°	1490.4	1485.0	1525.0	1566.5	1593.4
17.5°	1387.1	1384.5	1430.3	1478.7	1513.2
20°	1316.7	1315.9	1366.2	1416.6	1456.6
22.5°	1245.6	1247.3	1300.2	1352.6	1398.1
25°	1139.0	1142.1	1201.1	1253.5	1308.8
27.5°	1040.4	1041.8	1102.9	1158.1	1217.1
30°	973.2	977.0	1036.8	1094.0	1155.5
32.5°	905.9	910.3	968.9	1028.0	1090.7
35°	804.9	808.8	863.1	921.2	986.5
37.5°	700.9	706.1	754.3	809.2	873.5
40°	633.6	641.3	683.9	735.6	798.6
42.5°	568.8	578.3	617.9	666.9	723.8
45°	482.6	491.9	524.3	564.0	615.5
47.5°	408.4	419.0	444.0	478.1	522.1
50°	366.3	376.3	399.3	424.6	466.1
52.5°	329.2	339.2	359.7	379.2	414.6
55°	277.5	289.0	305.8	317.4	343.5
57.5°	235.0	246.1	259.4	264.6	280.5
60°	206.7	219.0	231.1	230.5	239.0
62.5°	181.0	191.4	203.4	195.1	195.6
65°	139.1	150.7	164.3	143.6	130.5
67.5°	112.4	114.9	128.9	100.1	84.6
70°	99.8	99.8	103.8	77.5	64.5
72.5°	87.9	87.9	84.3	63.0	49.4
75°	70.0	70.0	63.7	43.7	29.9
77.5°	53.9	53.3	48.7	32.6	21.7
80°	43.2	43.2	39.3	25.7	17.3
82.5°	33.8	33.8	30.5	20.1	12.9
85°	19.7	19.7	18.1	11.7	7.1
87.5°	6.9	6.9	6.3	3.8	3.1
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)