

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P521966

Luminaire Tested: **SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (3500K)**

Issue Date: 5/5/2021

Test Information

Test Method: LM-79-08
Report Number: P521966
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2101-105-51,
Test Lab: INNOVATION CENTER
Issue Date: 5/5/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: CORELITE
Catalog Number: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (3500K)
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE
DOWNLIGHT 500 LUMENS PER FOOT
UPLIGHT 1250 LUMENS PER FOOT
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7234.9 lumens
Efficiency: N/A
Efficacy: 116.3 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')
CIE Type: Semi-Indirect

Input Watts (W): 62.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P521966
CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (3500K)

Luminous Intensity Polar Plot





TEST NUMBER: P521966

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (3500K)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	101	101	101	101	90	90	90	90	69	69	69	50	50	50	32	32	32	24
1	93	89	85	82	82	79	76	73	61	59	57	45	43	42	29	29	28	21
2	85	78	72	68	75	70	65	61	54	51	48	40	38	36	27	26	25	19
3	78	69	62	57	69	62	56	52	48	44	41	36	33	31	24	23	22	17
4	71	61	54	49	63	55	49	44	43	39	36	32	29	27	22	20	19	15
5	65	55	47	42	58	49	43	38	39	34	31	29	26	24	20	18	17	13
6	60	49	42	36	54	44	38	33	35	31	27	26	23	21	18	17	15	12
7	56	44	37	32	50	40	34	29	32	27	24	24	21	19	17	15	14	11
8	52	40	33	28	46	37	30	26	29	25	21	22	19	17	16	14	13	10
9	48	37	30	25	43	33	27	23	27	22	19	20	17	15	15	13	11	9
10	45	34	27	23	40	31	25	21	25	20	17	19	16	14	14	12	11	8

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11036	11036	11036
5°	10899	10860	10923
10°	10297	10391	10631
15°	9506	9726	10162
20°	8632	8956	9549
25°	7742	8164	8896
30°	6923	7375	8220
35°	6054	6491	7419
40°	5095	5499	6423
45°	4205	4568	5363
50°	3511	3827	4468
55°	2981	3285	3690
60°	2546	2847	2945
65°	2028	2395	1901
70°	1799	1869	1160
75°	1665	1515	709
80°	1536	1392	611
85°	1387	1281	498



TEST NUMBER: P521966

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (3500K)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	109.7	1.5
10°-20°	285.4	3.9
20°-30°	369.7	5.1
30°-40°	362.0	5.0
40°-50°	277.1	3.8
50°-60°	184.6	2.6
60°-70°	100.8	1.4
70°-80°	42.0	0.6
80°-90°	11.9	0.2
90°-100°	402.9	5.6
100°-110°	1146.3	15.8
110°-120°	1098.3	15.2
120°-130°	869.3	12.0
130°-140°	697.7	9.6
140°-150°	546.2	7.5
150°-160°	399.7	5.5
160°-170°	247.6	3.4
170°-180°	84.0	1.2
0°-30°	764.8	10.6
0°-40°	1126.7	15.6
0°-60°	1588.4	22.0
0°-90°	1743.1	24.1
90°-120°	2647.5	36.6
90°-150°	4760.6	65.8
90°-180°	5492.0	75.9
0°-180°	7234.9	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1196	1196	1196	1196	1196	
5°	1177	1165	1173	1175	1179	109
15°	995	992	1018	1046	1064	278
25°	760	763	802	837	874	350
35°	538	540	576	615	659	334
45°	322	328	350	377	411	251
55°	185	193	204	212	229	168
65°	93	101	110	96	87	97
75°	47	47	42	29	20	50
85°	13	13	12	8	5	14
90°	0	0	0	0	0	2
95°	44	174	780	270	166	50
105°	178	270	1168	2063	1962	188
115°	331	400	886	1876	2204	326
125°	467	518	846	1403	1678	418
135°	572	619	835	1185	1340	441
145°	674	708	842	1026	1118	421
155°	770	788	862	927	965	356
165°	850	854	872	891	904	239
175°	891	886	882	877	871	84
180°	884	884	884	884	884	



TEST NUMBER: P521966

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (3500K)

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1196.2	1196.2	1196.2	1196.2	1196.2
2.5°	1199.1	1188.5	1191.2	1191.1	1187.8
5°	1176.8	1165.0	1172.6	1175.3	1179.4
7.5°	1133.1	1124.2	1138.0	1148.3	1156.6
10°	1099.1	1091.4	1109.1	1124.0	1134.8
12.5°	1059.6	1053.2	1075.0	1095.1	1109.2
15°	995.2	991.6	1018.3	1046.0	1063.9
17.5°	926.2	924.4	955.1	987.4	1010.4
20°	879.2	878.7	912.2	945.9	972.6
22.5°	831.7	832.8	868.1	903.2	933.5
25°	760.5	762.6	802.0	837.0	873.9
27.5°	694.7	695.6	736.4	773.3	812.7
30°	649.8	652.4	692.3	730.5	771.6
32.5°	604.9	607.8	647.0	686.4	728.3
35°	537.5	540.0	576.3	615.1	658.7
37.5°	468.0	471.5	503.7	540.3	583.2
40°	423.0	428.2	456.6	491.2	533.3
42.5°	379.8	386.2	412.6	445.3	483.3
45°	322.3	328.4	350.1	376.6	411.0
47.5°	272.7	279.8	296.4	319.3	348.6
50°	244.6	251.3	266.6	283.5	311.3
52.5°	219.8	226.5	240.2	253.2	276.8
55°	185.3	193.0	204.2	211.9	229.4
57.5°	156.9	164.3	173.2	176.7	187.3
60°	138.0	146.3	154.3	153.9	159.6
62.5°	120.8	127.8	135.8	130.3	130.6
65°	92.9	100.6	109.7	95.9	87.1
67.5°	75.1	76.7	86.1	66.8	56.5
70°	66.7	66.7	69.3	51.8	43.0
72.5°	58.7	58.7	56.3	42.1	33.0
75°	46.7	46.7	42.5	29.2	19.9
77.5°	36.0	35.6	32.5	21.8	14.5
80°	28.9	28.9	26.2	17.2	11.5
82.5°	22.6	22.6	20.4	13.4	8.6
85°	13.1	13.1	12.1	7.8	4.7
87.5°	4.6	4.6	4.2	2.5	2.1
90°	0.0	0.0	0.0	0.0	0.0
92.5°	13.4	71.3	165.4	48.1	36.3
95°	43.7	173.5	779.9	269.9	166.4
97.5°	80.3	203.3	1201.1	859.5	589.0
100°	105.9	220.9	1292.6	1309.2	1008.5
102.5°	134.1	240.0	1272.4	1675.9	1413.2
105°	178.2	270.2	1168.2	2063.4	1961.5
107.5°	222.9	305.4	1046.5	2172.7	2263.4
110°	253.8	331.0	976.6	2130.9	2334.7



TEST NUMBER: P521966

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (3500K)

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	283.4	356.7	929.5	2032.0	2322.6
115°	331.1	400.1	885.8	1876.5	2203.6
117.5°	373.1	437.9	859.9	1706.5	2053.0
120°	406.8	461.0	857.2	1609.4	1941.3
122.5°	433.7	487.9	850.5	1524.1	1832.4
125°	467.3	518.2	845.5	1403.0	1677.5
127.5°	503.9	551.6	842.8	1330.6	1556.8
130°	522.7	570.4	838.7	1280.2	1477.4
132.5°	542.9	589.3	838.7	1240.9	1422.3
135°	571.5	619.1	835.4	1185.1	1339.6
137.5°	598.4	644.7	835.0	1137.9	1271.4
140°	618.5	666.2	833.7	1098.8	1227.0
142.5°	641.4	681.2	837.7	1067.6	1182.6
145°	674.0	708.5	842.1	1025.7	1117.7
147.5°	701.9	735.4	849.5	983.4	1063.0
150°	726.1	749.1	852.2	969.4	1025.3
152.5°	744.9	769.3	854.9	950.5	1002.4
155°	769.8	787.9	862.3	927.0	964.8
157.5°	800.7	811.6	863.9	916.3	943.3
160°	816.9	825.1	870.7	908.2	931.2
162.5°	826.3	835.8	872.0	901.3	919.1
165°	850.5	853.8	872.3	891.1	904.3
167.5°	867.0	864.0	880.1	888.6	893.9
170°	872.3	870.7	877.4	879.2	885.8
172.5°	884.4	878.9	881.4	876.5	881.8
175°	890.8	885.9	882.4	877.2	870.7
177.5°	893.5	885.6	881.4	876.1	877.4
180°	884.1	884.1	884.1	884.1	884.1

(END OF REPORT)