

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P521967

Luminaire Tested: **SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (4000K)**

Issue Date: 5/5/2021

Test Information

Test Method: LM-79-08
Report Number: P521967
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2101-105-51,
Test Lab: INNOVATION CENTER
Issue Date: 5/5/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: CORELITE
Catalog Number: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (4000K)
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE
DOWNLIGHT 500 LUMENS PER FOOT
UPLIGHT 1250 LUMENS PER FOOT
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 4000K CCT
Ballast/Driver: ELECTRONIC DRIVER


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7367.3 lumens
Efficiency: N/A
Efficacy: 118.4 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')
CIE Type: Semi-Indirect

Input Watts (W): 62.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P521967
CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (4000K)

Luminous Intensity Polar Plot





TEST NUMBER: P521967

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (4000K)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	101	101	101	101	90	90	90	90	69	69	69	50	50	50	32	32	32	24
1	93	89	85	82	82	79	76	73	61	59	57	45	43	42	29	29	28	21
2	85	78	72	68	75	70	65	61	54	51	48	40	38	36	27	26	25	19
3	78	69	62	57	69	62	56	52	48	44	41	36	33	31	24	23	22	17
4	71	61	54	49	63	55	49	44	43	39	36	32	29	27	22	20	19	15
5	65	55	47	42	58	49	43	38	39	34	31	29	26	24	20	18	17	13
6	60	49	42	36	54	44	38	33	35	31	27	26	23	21	18	17	15	12
7	56	44	37	32	50	40	34	29	32	27	24	24	21	19	17	15	14	11
8	52	40	33	28	46	37	30	26	29	25	21	22	19	17	16	14	13	10
9	48	37	30	25	43	33	27	23	27	22	19	20	17	15	15	13	11	9
10	45	34	27	23	40	31	25	21	25	20	17	19	16	14	14	12	11	8

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11238	11238	11238
5°	11098	11058	11123
10°	10485	10580	10825
15°	9680	9904	10348
20°	8789	9120	9724
25°	7884	8314	9059
30°	7049	7511	8370
35°	6164	6610	7555
40°	5189	5600	6540
45°	4282	4652	5461
50°	3575	3897	4549
55°	3035	3344	3758
60°	2594	2899	2999
65°	2065	2439	1936
70°	1832	1904	1182
75°	1697	1544	724
80°	1562	1419	627
85°	1419	1302	508



TEST NUMBER: P521967

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (4000K)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	111.7	1.5
10°-20°	290.6	3.9
20°-30°	376.4	5.1
30°-40°	368.6	5.0
40°-50°	282.1	3.8
50°-60°	188.0	2.6
60°-70°	102.6	1.4
70°-80°	42.8	0.6
80°-90°	12.1	0.2
90°-100°	410.2	5.6
100°-110°	1167.3	15.8
110°-120°	1118.4	15.2
120°-130°	885.2	12.0
130°-140°	710.5	9.6
140°-150°	556.2	7.5
150°-160°	407.0	5.5
160°-170°	252.1	3.4
170°-180°	85.5	1.2
0°-30°	778.7	10.6
0°-40°	1147.4	15.6
0°-60°	1617.5	22.0
0°-90°	1775.0	24.1
90°-120°	2695.9	36.6
90°-150°	4847.7	65.8
90°-180°	5592.0	75.9
0°-180°	7367.3	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1218	1218	1218	1218	1218	
5°	1198	1186	1194	1197	1201	111
15°	1013	1010	1037	1065	1083	283
25°	774	776	817	852	890	356
35°	547	550	587	626	671	340
45°	328	334	356	384	418	256
55°	189	196	208	216	234	171
65°	95	102	112	98	89	98
75°	48	48	43	30	20	51
85°	13	13	12	8	5	15
90°	0	0	0	0	0	3
95°	44	177	794	275	169	51
105°	181	275	1190	2101	1997	192
115°	337	408	902	1911	2244	332
125°	476	528	861	1429	1708	426
135°	582	630	851	1207	1364	449
145°	686	722	858	1044	1138	429
155°	784	802	878	944	982	362
165°	866	869	888	907	921	244
175°	907	902	899	893	887	86
180°	900	900	900	900	900	

TEST NUMBER: P521967

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (4000K)

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1218.1	1218.1	1218.1	1218.1	1218.1
2.5°	1221.1	1210.2	1212.9	1212.9	1209.5
5°	1198.3	1186.3	1194.0	1196.8	1201.0
7.5°	1153.8	1144.7	1158.9	1169.3	1177.8
10°	1119.2	1111.4	1129.3	1144.6	1155.5
12.5°	1079.0	1072.4	1094.7	1115.1	1129.5
15°	1013.4	1009.7	1036.9	1065.1	1083.4
17.5°	943.1	941.4	972.5	1005.5	1028.9
20°	895.2	894.7	928.9	963.2	990.4
22.5°	846.9	848.1	884.0	919.7	950.6
25°	774.5	776.5	816.7	852.3	889.9
27.5°	707.4	708.4	749.9	787.4	827.6
30°	661.7	664.3	705.0	743.9	785.7
32.5°	615.9	619.0	658.8	699.0	741.6
35°	547.3	549.9	586.9	626.3	670.8
37.5°	476.5	480.1	512.9	550.2	593.9
40°	430.8	436.0	465.0	500.2	543.0
42.5°	386.7	393.2	420.1	453.5	492.1
45°	328.2	334.4	356.5	383.5	418.5
47.5°	277.7	284.9	301.9	325.1	355.0
50°	249.1	255.9	271.5	288.7	316.9
52.5°	223.8	230.6	244.6	257.8	281.9
55°	188.7	196.5	207.9	215.8	233.6
57.5°	159.8	167.3	176.4	179.9	190.7
60°	140.6	148.9	157.1	156.7	162.5
62.5°	123.0	130.1	138.3	132.7	133.0
65°	94.6	102.4	111.7	97.6	88.7
67.5°	76.4	78.1	87.7	68.1	57.5
70°	67.9	67.9	70.6	52.7	43.8
72.5°	59.8	59.8	57.3	42.9	33.6
75°	47.6	47.6	43.3	29.7	20.3
77.5°	36.7	36.2	33.1	22.2	14.8
80°	29.4	29.4	26.7	17.5	11.8
82.5°	23.0	23.0	20.7	13.7	8.8
85°	13.4	13.4	12.3	7.9	4.8
87.5°	4.7	4.7	4.3	2.6	2.1
90°	0.0	0.0	0.0	0.0	0.0
92.5°	13.7	72.6	168.4	49.0	37.0
95°	44.5	176.7	794.2	274.9	169.4
97.5°	81.8	207.0	1223.1	875.2	599.7
100°	107.8	225.0	1316.2	1333.2	1026.9
102.5°	136.6	244.4	1295.7	1706.5	1439.1
105°	181.4	275.1	1189.5	2101.2	1997.4
107.5°	227.0	311.0	1065.6	2212.4	2304.8
110°	258.4	337.1	994.4	2169.9	2377.4



TEST NUMBER: P521967

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (4000K)

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	288.6	363.2	946.5	2069.2	2365.0
115°	337.2	407.5	902.0	1910.8	2243.9
117.5°	380.0	445.9	875.6	1737.7	2090.5
120°	414.2	469.4	872.9	1638.8	1976.9
122.5°	441.6	496.8	866.1	1552.0	1866.0
125°	475.8	527.7	860.9	1428.7	1708.1
127.5°	513.1	561.7	858.2	1355.0	1585.3
130°	532.3	580.8	854.1	1303.6	1504.5
132.5°	552.8	600.0	854.1	1263.6	1448.3
135°	581.9	630.5	850.7	1206.8	1364.1
137.5°	609.3	656.5	850.3	1158.7	1294.6
140°	629.9	678.4	848.9	1118.9	1249.4
142.5°	653.1	693.6	853.0	1087.1	1204.3
145°	686.3	721.5	857.5	1044.5	1138.2
147.5°	714.8	748.9	865.0	1001.4	1082.4
150°	739.4	762.8	867.8	987.2	1044.1
152.5°	758.6	783.3	870.5	967.9	1020.8
155°	783.9	802.3	878.0	943.9	982.4
157.5°	815.4	826.4	879.7	933.1	960.5
160°	831.8	840.2	886.6	924.8	948.2
162.5°	841.4	851.1	888.0	917.8	935.9
165°	866.1	869.4	888.3	907.4	920.8
167.5°	882.8	879.8	896.2	904.9	910.2
170°	888.3	886.6	893.4	895.3	902.0
172.5°	900.6	894.9	897.5	892.5	897.9
175°	907.1	902.1	898.6	893.3	886.6
177.5°	909.9	901.8	897.5	892.1	893.4
180°	900.3	900.3	900.3	900.3	900.3

(END OF REPORT)