

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P521970

Luminaire Tested: **SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (5700K)**

Issue Date: 5/5/2021

Test Information

Test Method: LM-79-08
Report Number: P521970
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2101-105-51,
Test Lab: INNOVATION CENTER
Issue Date: 5/5/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: CORELITE
Catalog Number: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (5700K)
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE
DOWNLIGHT 500 LUMENS PER FOOT
UPLIGHT 1250 LUMENS PER FOOT
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 5700K CCT
Ballast/Driver: ELECTRONIC DRIVER


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7676.8 lumens
Efficiency: N/A
Efficacy: 123.8 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')
CIE Type: Semi-Indirect

Input Watts (W): 62
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P521970
CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (5700K)

Luminous Intensity Polar Plot





TEST NUMBER: P521970

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (5700K)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	101	101	101	101	90	90	90	90	69	69	69	50	50	50	32	32	32	24
1	93	89	85	82	82	79	76	73	61	59	57	45	43	42	29	29	28	21
2	85	78	72	68	75	70	65	61	54	51	48	40	38	36	27	26	25	19
3	78	69	62	57	69	62	56	52	48	44	41	36	33	31	24	23	22	17
4	71	61	54	49	63	55	49	44	43	39	36	32	29	27	22	20	19	15
5	65	55	47	42	58	49	43	38	39	34	31	29	26	24	20	18	17	13
6	60	49	42	36	54	44	38	33	35	31	27	26	23	21	18	17	15	12
7	56	44	37	32	50	40	34	29	32	27	24	24	21	19	17	15	14	11
8	52	40	33	28	46	37	30	26	29	25	21	22	19	17	16	14	13	10
9	48	37	30	25	43	33	27	23	27	22	19	20	17	15	15	13	11	9
10	45	34	27	23	40	31	25	21	25	20	17	19	16	14	14	12	11	8

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11710	11710	11710
5°	11564	11523	11590
10°	10926	11025	11281
15°	10086	10320	10783
20°	9160	9503	10133
25°	8215	8663	9440
30°	7346	7826	8722
35°	6423	6887	7872
40°	5407	5835	6814
45°	4462	4847	5690
50°	3725	4061	4741
55°	3162	3484	3915
60°	2703	3021	3124
65°	2153	2541	2019
70°	1907	1983	1233
75°	1768	1608	756
80°	1626	1477	654
85°	1471	1355	529



TEST NUMBER: P521970

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (5700K)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	116.4	1.5
10°-20°	302.8	3.9
20°-30°	392.2	5.1
30°-40°	384.1	5.0
40°-50°	294.0	3.8
50°-60°	195.9	2.6
60°-70°	106.9	1.4
70°-80°	44.6	0.6
80°-90°	12.6	0.2
90°-100°	427.5	5.6
100°-110°	1216.3	15.8
110°-120°	1165.4	15.2
120°-130°	922.3	12.0
130°-140°	740.3	9.6
140°-150°	579.6	7.5
150°-160°	424.1	5.5
160°-170°	262.7	3.4
170°-180°	89.1	1.2
0°-30°	811.5	10.6
0°-40°	1195.6	15.6
0°-60°	1685.5	22.0
0°-90°	1849.5	24.1
90°-120°	2809.1	36.6
90°-150°	5051.4	65.8
90°-180°	5827.0	75.9
0°-180°	7676.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1269	1269	1269	1269	1269	
5°	1249	1236	1244	1247	1251	116
15°	1056	1052	1080	1110	1129	295
25°	807	809	851	888	927	371
35°	570	573	612	653	699	355
45°	342	348	372	400	436	267
55°	197	205	217	225	243	178
65°	99	107	116	102	92	102
75°	50	50	45	31	21	53
85°	14	14	13	8	5	15
90°	0	0	0	0	0	3
95°	46	184	828	286	177	53
105°	189	287	1240	2189	2081	200
115°	351	425	940	1991	2338	346
125°	496	550	897	1489	1780	444
135°	606	657	886	1258	1421	468
145°	715	752	894	1088	1186	447
155°	817	836	915	984	1024	378
165°	902	906	926	946	960	254
175°	945	940	936	931	924	90
180°	938	938	938	938	938	

TEST NUMBER: P521970

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (5700K)

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1269.2	1269.2	1269.2	1269.2	1269.2
2.5°	1272.4	1261.0	1263.9	1263.8	1260.3
5°	1248.6	1236.1	1244.2	1247.1	1251.4
7.5°	1202.3	1192.8	1207.5	1218.4	1227.2
10°	1166.2	1158.0	1176.8	1192.6	1204.1
12.5°	1124.3	1117.5	1140.7	1162.0	1176.9
15°	1055.9	1052.1	1080.4	1109.8	1128.9
17.5°	982.8	980.9	1013.4	1047.7	1072.1
20°	932.9	932.3	967.9	1003.7	1032.0
22.5°	882.5	883.7	921.2	958.3	990.6
25°	807.0	809.2	851.0	888.1	927.3
27.5°	737.2	738.1	781.4	820.5	862.3
30°	689.5	692.2	734.6	775.1	818.7
32.5°	641.8	645.0	686.5	728.4	772.8
35°	570.3	573.0	611.5	652.7	698.9
37.5°	496.6	500.3	534.4	573.3	618.9
40°	448.9	454.3	484.5	521.2	565.8
42.5°	403.0	409.7	437.7	472.5	512.8
45°	342.0	348.5	371.5	399.6	436.1
47.5°	289.4	296.9	314.6	338.8	369.9
50°	259.5	266.6	282.9	300.9	330.3
52.5°	233.2	240.3	254.9	268.7	293.7
55°	196.6	204.8	216.6	224.9	243.4
57.5°	166.5	174.4	183.8	187.5	198.7
60°	146.5	155.2	163.7	163.3	169.3
62.5°	128.2	135.6	144.1	138.2	138.6
65°	98.6	106.7	116.4	101.7	92.5
67.5°	79.6	81.4	91.3	70.9	59.9
70°	70.7	70.7	73.5	54.9	45.7
72.5°	62.3	62.3	59.7	44.7	35.0
75°	49.6	49.6	45.1	31.0	21.2
77.5°	38.2	37.8	34.5	23.1	15.4
80°	30.6	30.6	27.8	18.2	12.3
82.5°	23.9	23.9	21.6	14.3	9.1
85°	13.9	13.9	12.8	8.3	5.0
87.5°	4.9	4.9	4.5	2.7	2.2
90°	0.0	0.0	0.0	0.0	0.0
92.5°	14.3	75.7	175.5	51.1	38.5
95°	46.4	184.1	827.5	286.4	176.6
97.5°	85.2	215.7	1274.5	912.0	624.9
100°	112.4	234.4	1371.5	1389.2	1070.1
102.5°	142.3	254.6	1350.1	1778.2	1499.5
105°	189.0	286.7	1239.5	2189.4	2081.3
107.5°	236.5	324.0	1110.4	2305.4	2401.6
110°	269.3	351.3	1036.2	2261.0	2477.2

TEST NUMBER: P521970

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (5700K)

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	300.7	378.5	986.3	2156.1	2464.4
115°	351.3	424.6	939.9	1991.1	2338.1
117.5°	395.9	464.6	912.4	1810.7	2178.3
120°	431.6	489.1	909.6	1707.7	2059.9
122.5°	460.1	517.7	902.4	1617.2	1944.3
125°	495.8	549.9	897.1	1488.7	1779.9
127.5°	534.7	585.3	894.2	1411.9	1651.8
130°	554.7	605.2	890.0	1358.4	1567.7
132.5°	576.1	625.2	890.0	1316.7	1509.2
135°	606.4	657.0	886.4	1257.5	1421.4
137.5°	634.9	684.1	886.0	1207.4	1349.0
140°	656.3	706.9	884.6	1165.9	1301.9
142.5°	680.6	722.8	888.9	1132.8	1254.8
145°	715.2	751.8	893.5	1088.4	1186.0
147.5°	744.8	780.4	901.4	1043.5	1127.9
150°	770.5	794.9	904.2	1028.6	1087.9
152.5°	790.4	816.2	907.1	1008.6	1063.7
155°	816.8	836.0	914.9	983.6	1023.7
157.5°	849.6	861.2	916.7	972.3	1000.9
160°	866.8	875.5	923.8	963.6	988.0
162.5°	876.8	886.9	925.3	956.4	975.2
165°	902.4	905.9	925.6	945.6	959.5
167.5°	919.9	916.8	933.8	942.9	948.4
170°	925.6	923.9	931.0	932.9	939.9
172.5°	938.5	932.5	935.3	930.0	935.6
175°	945.2	940.0	936.3	930.8	923.8
177.5°	948.1	939.7	935.3	929.6	931.0
180°	938.1	938.1	938.1	938.1	938.1

(END OF REPORT)