

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P521971

Luminaire Tested: **SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (6500K)**

Issue Date: 5/5/2021

Test Information

Test Method: LM-79-08
Report Number: P521971
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2101-105-51,
Test Lab: INNOVATION CENTER
Issue Date: 5/5/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: CORELITE
Catalog Number: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (6500K)
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE
DOWNLIGHT 500 LUMENS PER FOOT
UPLIGHT 1250 LUMENS PER FOOT
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 6500K CCT
Ballast/Driver: ELECTRONIC DRIVER


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7749.5 lumens
Efficiency: N/A
Efficacy: 125.6 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')
CIE Type: Semi-Indirect

Input Watts (W): 61.7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P521971
CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (6500K)

Luminous Intensity Polar Plot





TEST NUMBER: P521971

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (6500K)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	101	101	101	101	90	90	90	90	69	69	69	50	50	50	32	32	32	24
1	93	89	85	82	82	79	76	73	61	59	57	45	43	42	29	29	28	21
2	85	78	72	68	75	70	65	61	54	51	48	40	38	36	27	26	25	19
3	78	69	62	57	69	62	56	52	48	44	41	36	33	31	24	23	22	17
4	71	61	54	49	63	55	49	44	43	39	36	32	29	27	22	20	19	15
5	65	55	47	42	58	49	43	38	39	34	31	29	26	24	20	18	17	13
6	60	49	42	36	54	44	38	33	35	31	27	26	23	21	18	17	15	12
7	56	44	37	32	50	40	34	29	32	27	24	24	21	19	17	15	14	11
8	52	40	33	28	46	37	30	26	29	25	21	22	19	17	16	14	13	10
9	48	37	30	25	43	33	27	23	27	22	19	20	17	15	15	13	11	9
10	45	34	27	23	40	31	25	21	25	20	17	19	16	14	14	12	11	8

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11822	11822	11822
5°	11674	11632	11700
10°	11030	11130	11387
15°	10182	10418	10885
20°	9246	9593	10229
25°	8293	8746	9529
30°	7415	7901	8804
35°	6484	6953	7947
40°	5457	5891	6880
45°	4504	4893	5744
50°	3761	4099	4785
55°	3193	3518	3952
60°	2729	3050	3154
65°	2172	2565	2037
70°	1926	2002	1244
75°	1782	1622	763
80°	1642	1493	659
85°	1493	1366	540



TEST NUMBER: P521971

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (6500K)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	117.5	1.5
10°-20°	305.7	3.9
20°-30°	395.9	5.1
30°-40°	387.7	5.0
40°-50°	296.8	3.8
50°-60°	197.8	2.6
60°-70°	107.9	1.4
70°-80°	45.0	0.6
80°-90°	12.7	0.2
90°-100°	431.5	5.6
100°-110°	1227.8	15.8
110°-120°	1176.4	15.2
120°-130°	931.1	12.0
130°-140°	747.3	9.6
140°-150°	585.1	7.5
150°-160°	428.1	5.5
160°-170°	265.2	3.4
170°-180°	90.0	1.2
0°-30°	819.2	10.6
0°-40°	1206.9	15.6
0°-60°	1701.4	22.0
0°-90°	1867.1	24.1
90°-120°	2835.8	36.6
90°-150°	5099.2	65.8
90°-180°	5882.0	75.9
0°-180°	7749.5	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1281	1281	1281	1281	1281	
5°	1260	1248	1256	1259	1263	117
15°	1066	1062	1091	1120	1140	298
25°	815	817	859	896	936	375
35°	576	578	617	659	706	358
45°	345	352	375	403	440	269
55°	198	207	219	227	246	180
65°	100	108	118	103	93	103
75°	50	50	46	31	21	53
85°	14	14	13	8	5	15
90°	0	0	0	0	0	3
95°	47	186	835	289	178	54
105°	191	289	1251	2210	2101	202
115°	355	429	949	2010	2360	349
125°	500	555	906	1503	1797	448
135°	612	663	895	1269	1435	472
145°	722	759	902	1099	1197	451
155°	825	844	924	993	1033	381
165°	911	914	934	954	969	256
175°	954	949	945	940	933	90
180°	947	947	947	947	947	



TEST NUMBER: P521971

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (6500K)

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1281.3	1281.3	1281.3	1281.3	1281.3
2.5°	1284.4	1273.0	1275.9	1275.8	1272.3
5°	1260.5	1247.8	1256.0	1258.9	1263.3
7.5°	1213.7	1204.1	1219.0	1230.0	1238.9
10°	1177.3	1169.0	1188.0	1204.0	1215.5
12.5°	1135.0	1128.1	1151.5	1173.0	1188.1
15°	1066.0	1062.1	1090.7	1120.4	1139.6
17.5°	992.1	990.2	1023.0	1057.6	1082.3
20°	941.7	941.2	977.1	1013.2	1041.8
22.5°	890.9	892.1	929.9	967.4	999.9
25°	814.6	816.8	859.1	896.5	936.1
27.5°	744.1	745.1	788.8	828.3	870.5
30°	696.0	698.8	741.6	782.5	826.4
32.5°	647.9	651.1	693.0	735.3	780.1
35°	575.7	578.5	617.3	658.8	705.6
37.5°	501.3	505.0	539.5	578.8	624.7
40°	453.1	458.6	489.1	526.1	571.2
42.5°	406.8	413.6	441.9	477.0	517.7
45°	345.2	351.8	375.0	403.4	440.2
47.5°	292.1	299.7	317.5	342.0	373.4
50°	262.0	269.1	285.6	303.7	333.4
52.5°	235.5	242.6	257.3	271.2	296.5
55°	198.5	206.7	218.7	227.0	245.7
57.5°	168.1	176.0	185.5	189.3	200.6
60°	147.9	156.7	165.3	164.9	170.9
62.5°	129.4	136.9	145.5	139.5	139.9
65°	99.5	107.8	117.5	102.7	93.3
67.5°	80.4	82.2	92.2	71.6	60.5
70°	71.4	71.4	74.2	55.4	46.1
72.5°	62.9	62.9	60.3	45.1	35.3
75°	50.0	50.0	45.5	31.3	21.4
77.5°	38.6	38.1	34.9	23.3	15.5
80°	30.9	30.9	28.1	18.4	12.4
82.5°	24.2	24.2	21.8	14.4	9.2
85°	14.1	14.1	12.9	8.4	5.1
87.5°	4.9	4.9	4.5	2.7	2.2
90°	0.0	0.0	0.0	0.0	0.0
92.5°	14.4	76.4	177.2	51.6	38.9
95°	46.8	185.9	835.4	289.1	178.2
97.5°	86.1	217.7	1286.6	920.6	630.9
100°	113.4	236.6	1384.5	1402.4	1080.2
102.5°	143.7	257.0	1362.9	1795.1	1513.8
105°	190.8	289.4	1251.3	2210.2	2101.0
107.5°	238.7	327.1	1120.9	2327.2	2424.4
110°	271.9	354.6	1046.0	2282.4	2500.7

TEST NUMBER: P521971

CATALOG NUMBER: SQ4-WB-125U-050D-92765-1D-UNV-STD-W-4 (6500K)

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	303.5	382.1	995.6	2176.5	2487.8
115°	354.7	428.6	948.8	2010.0	2360.3
117.5°	399.7	469.0	921.1	1827.9	2199.0
120°	435.7	493.8	918.2	1723.8	2079.4
122.5°	464.5	522.6	911.0	1632.5	1962.8
125°	500.5	555.1	905.6	1502.8	1796.8
127.5°	539.8	590.8	902.7	1425.3	1667.5
130°	559.9	611.0	898.4	1371.3	1582.5
132.5°	581.5	631.2	898.4	1329.1	1523.5
135°	612.1	663.2	894.8	1269.4	1434.9
137.5°	640.9	690.6	894.4	1218.9	1361.8
140°	662.5	713.6	893.0	1177.0	1314.3
142.5°	687.0	729.6	897.3	1143.5	1266.7
145°	722.0	758.9	902.0	1098.7	1197.3
147.5°	751.8	787.8	909.9	1053.4	1138.6
150°	777.8	802.4	912.8	1038.4	1098.2
152.5°	797.9	824.0	915.7	1018.1	1073.7
155°	824.6	843.9	923.6	992.9	1033.4
157.5°	857.7	869.3	925.4	981.5	1010.4
160°	875.0	883.8	932.6	972.8	997.4
162.5°	885.1	895.3	934.0	965.4	984.4
165°	911.0	914.5	934.4	954.5	968.6
167.5°	928.6	925.5	942.7	951.8	957.4
170°	934.4	932.6	939.8	941.8	948.8
172.5°	947.4	941.4	944.1	938.8	944.5
175°	954.2	948.9	945.2	939.6	932.6
177.5°	957.1	948.6	944.1	938.4	939.8
180°	947.0	947.0	947.0	947.0	947.0

(END OF REPORT)