

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P522058

Luminaire Tested: **SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4000K)**

Issue Date: 5/5/2021

**Test Information**

Test Method: LM-79-08  
Report Number: P522058  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2101-105-51,  
Test Lab: INNOVATION CENTER  
Issue Date: 5/5/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: CORELITE  
Catalog Number: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4000K)  
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE  
DOWNLIGHT 1250 LUMENS PER FOOT  
UPLIGHT 1500 LUMENS PER FOOT  
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 4000K CCT  
Ballast/Driver: ELECTRONIC DRIVER


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 11163.8 lumens  
Efficiency: N/A  
Efficacy: 104.3 lumens/watt  
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02  
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')  
CIE Type: Semi-Indirect

Input Watts (W): 107  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P522058  
CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4000K)

### Luminous Intensity Polar Plot





TEST NUMBER: P522058

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4000K)

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	105	105	105	105	95	95	95	95	78	78	78	61	61	61	47	47	47	40
1	96	92	89	86	88	84	81	79	69	67	65	55	54	53	43	42	41	35
2	88	82	76	72	80	75	70	66	62	58	56	50	48	46	39	37	36	31
3	81	73	66	61	74	67	61	56	55	51	48	45	42	40	35	33	32	27
4	75	65	58	52	68	60	53	49	50	45	42	41	37	35	32	30	28	24
5	69	58	51	45	63	54	47	42	45	40	37	37	34	31	29	27	25	22
6	64	53	45	40	58	49	42	37	41	36	32	34	30	28	27	25	23	20
7	59	48	40	35	54	44	38	33	37	32	29	31	27	25	25	23	21	18
8	55	44	36	32	50	40	34	30	34	29	26	29	25	22	23	21	19	16
9	52	40	33	28	47	37	31	27	32	27	24	26	23	20	22	19	17	15
10	48	37	30	26	44	34	28	24	29	25	21	25	21	19	20	18	16	14

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	28012	28012	28012
5°	27662	27564	27724
10°	26135	26372	26984
15°	24127	24686	25793
20°	21910	22733	24238
25°	19651	20722	22580
30°	17571	18720	20864
35°	15365	16476	18831
40°	12933	13959	16301
45°	10673	11594	13610
50°	8911	9714	11339
55°	7565	8335	9365
60°	6466	7228	7473
65°	5148	6078	4827
70°	4564	4745	2946
75°	4228	3846	1804
80°	3895	3539	1557
85°	3525	3239	1270



TEST NUMBER: P522058

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4000K)

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	278.5	2.5
10°-20°	724.4	6.5
20°-30°	938.2	8.4
30°-40°	918.8	8.2
40°-50°	703.3	6.3
50°-60°	468.6	4.2
60°-70°	255.7	2.3
70°-80°	106.6	1.0
80°-90°	30.2	0.3
90°-100°	494.4	4.4
100°-110°	1406.7	12.6
110°-120°	1347.8	12.1
120°-130°	1066.7	9.6
130°-140°	856.2	7.7
140°-150°	670.3	6.0
150°-160°	490.5	4.4
160°-170°	303.8	2.7
170°-180°	103.1	0.9
0°-30°	1941.1	17.4
0°-40°	2859.9	25.6
0°-60°	4031.7	36.1
0°-90°	4424.2	39.6
90°-120°	3249.0	29.1
90°-150°	5842.2	52.3
90°-180°	6740.0	60.4
0°-180°	11163.8	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	3036	3036	3036	3036	3036	
5°	2987	2957	2976	2983	2994	278
15°	2526	2517	2584	2655	2700	705
25°	1930	1936	2036	2124	2218	888
35°	1364	1371	1463	1561	1672	848
45°	818	834	889	956	1043	638
55°	470	490	518	538	582	426
65°	236	255	278	243	221	245
75°	119	119	108	74	51	127
85°	33	33	31	20	12	36
90°	0	0	0	0	0	4
95°	54	213	957	331	204	61
105°	219	332	1434	2532	2407	231
115°	406	491	1087	2303	2704	400
125°	573	636	1038	1722	2059	513
135°	701	760	1025	1454	1644	541
145°	827	870	1033	1259	1372	517
155°	945	967	1058	1138	1184	437
165°	1044	1048	1070	1094	1110	294
175°	1093	1087	1083	1076	1068	104
180°	1085	1085	1085	1085	1085	

TEST NUMBER: P522058

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4000K)

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°
0°	3036.1	3036.1	3036.1	3036.1	3036.1
2.5°	3043.6	3016.5	3023.3	3023.2	3014.8
5°	2986.8	2956.9	2976.2	2983.1	2993.5
7.5°	2876.0	2853.3	2888.5	2914.6	2935.7
10°	2789.7	2770.1	2815.0	2852.9	2880.3
12.5°	2689.5	2673.1	2728.7	2779.6	2815.2
15°	2525.9	2516.8	2584.5	2654.8	2700.4
17.5°	2350.8	2346.4	2424.1	2506.2	2564.5
20°	2231.5	2230.2	2315.4	2400.9	2468.6
22.5°	2111.0	2113.9	2203.5	2292.4	2369.5
25°	1930.4	1935.6	2035.6	2124.4	2218.1
27.5°	1763.3	1765.7	1869.1	1962.8	2062.8
30°	1649.3	1655.8	1757.2	1854.2	1958.4
32.5°	1535.3	1542.8	1642.1	1742.3	1848.6
35°	1364.2	1370.7	1462.8	1561.2	1671.9
37.5°	1187.8	1196.7	1278.4	1371.5	1480.4
40°	1073.8	1086.8	1159.0	1246.7	1353.5
42.5°	964.0	980.1	1047.1	1130.3	1226.7
45°	818.0	833.6	888.6	955.9	1043.1
47.5°	692.2	710.2	752.4	810.4	884.9
50°	620.8	637.7	676.8	719.7	790.0
52.5°	557.9	574.9	609.6	642.7	702.6
55°	470.3	489.8	518.2	537.9	582.2
57.5°	398.3	417.1	439.6	448.5	475.3
60°	350.4	371.2	391.7	390.7	405.0
62.5°	306.7	324.4	344.8	330.7	331.5
65°	235.8	255.3	278.4	243.3	221.1
67.5°	190.5	194.7	218.5	169.7	143.3
70°	169.2	169.2	175.9	131.4	109.2
72.5°	148.9	148.9	142.8	106.8	83.7
75°	118.6	118.6	107.9	74.1	50.6
77.5°	91.4	90.3	82.6	55.3	36.8
80°	73.3	73.3	66.6	43.6	29.3
82.5°	57.3	57.3	51.7	34.1	21.8
85°	33.3	33.3	30.6	19.8	12.0
87.5°	11.7	11.7	10.7	6.4	5.3
90°	0.0	0.0	0.0	0.0	0.0
92.5°	16.5	87.5	203.0	59.1	44.6
95°	53.6	213.0	957.1	331.3	204.2
97.5°	98.6	249.5	1474.0	1054.7	722.8
100°	129.9	271.1	1586.2	1606.7	1237.6
102.5°	164.6	294.5	1561.5	2056.6	1734.3
105°	218.6	331.6	1433.6	2532.2	2407.2
107.5°	273.5	374.8	1284.2	2666.3	2777.6
110°	311.5	406.3	1198.4	2615.0	2865.1

TEST NUMBER: P522058

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4000K)

**CANDELA DISTRIBUTION (continued):**

	0°	22.5°	45°	67.5°	90°
112.5°	347.8	437.7	1140.7	2493.7	2850.2
115°	406.4	491.1	1087.0	2302.8	2704.2
117.5°	457.9	537.4	1055.3	2094.2	2519.4
120°	499.2	565.7	1052.0	1975.0	2382.4
122.5°	532.2	598.7	1043.7	1870.4	2248.8
125°	573.4	636.0	1037.5	1721.8	2058.6
127.5°	618.4	676.9	1034.2	1632.9	1910.5
130°	641.5	700.0	1029.3	1571.1	1813.1
132.5°	666.3	723.1	1029.3	1522.8	1745.5
135°	701.3	759.8	1025.2	1454.4	1644.0
137.5°	734.3	791.2	1024.7	1396.5	1560.2
140°	759.1	817.6	1023.1	1348.5	1505.8
142.5°	787.1	835.9	1028.0	1310.1	1451.3
145°	827.1	869.5	1033.4	1258.7	1371.7
147.5°	861.4	902.5	1042.5	1206.8	1304.4
150°	891.1	919.3	1045.8	1189.7	1258.2
152.5°	914.2	944.0	1049.1	1166.5	1230.2
155°	944.7	966.9	1058.2	1137.6	1184.0
157.5°	982.7	996.0	1060.2	1124.5	1157.6
160°	1002.5	1012.6	1068.5	1114.5	1142.7
162.5°	1014.0	1025.7	1070.1	1106.1	1127.9
165°	1043.7	1047.8	1070.5	1093.6	1109.7
167.5°	1063.9	1060.3	1080.0	1090.5	1096.9
170°	1070.5	1068.5	1076.7	1079.0	1087.0
172.5°	1085.4	1078.5	1081.7	1075.6	1082.1
175°	1093.2	1087.2	1082.9	1076.5	1068.5
177.5°	1096.5	1086.8	1081.7	1075.1	1076.7
180°	1085.0	1085.0	1085.0	1085.0	1085.0

(END OF REPORT)