

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: CORELITE

Report Number: P522059

Luminaire Tested: **SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4500K)**

Issue Date: 5/5/2021

**Test Information**

Test Method: LM-79-08  
Report Number: P522059  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2101-105-51,  
Test Lab: INNOVATION CENTER  
Issue Date: 5/5/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: CORELITE  
Catalog Number: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4500K)  
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH WHITE BAFFLE  
DOWNLIGHT 1250 LUMENS PER FOOT  
UPLIGHT 1500 LUMENS PER FOOT  
Light Source: 2700K/65000K CCT, 90 CRI LEDS, TUNED TO 4500K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 11343.8 lumens  
Efficiency: N/A  
Efficacy: 106.2 lumens/watt  
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02  
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')  
CIE Type: Semi-Indirect

Input Watts (W): 106.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P522059

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4500K)

### Luminous Intensity Polar Plot





TEST NUMBER: P522059

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4500K)

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	105	105	105	105	95	95	95	95	78	78	78	61	61	61	47	47	47	40
1	96	92	89	86	88	84	81	79	69	67	65	55	54	53	43	42	41	35
2	88	82	76	72	80	75	70	66	62	58	56	50	48	46	39	37	36	31
3	81	73	66	61	74	67	61	56	55	51	48	45	42	40	35	33	32	27
4	75	65	58	52	68	60	53	49	50	45	42	41	37	35	32	30	28	24
5	69	58	51	45	63	54	47	42	45	40	37	37	34	31	29	27	25	22
6	64	53	45	40	58	49	42	37	41	36	32	34	30	28	27	25	23	20
7	59	48	40	35	54	44	38	33	37	32	29	31	27	25	25	23	21	18
8	55	44	36	32	50	40	34	30	34	29	26	29	25	22	23	21	19	16
9	52	40	33	28	47	37	31	27	32	27	24	26	23	20	22	19	17	15
10	48	37	30	26	44	34	28	24	29	25	21	25	21	19	20	18	16	14

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	28464	28464	28464
5°	28108	28008	28171
10°	26557	26798	27419
15°	24515	25085	26210
20°	22263	23100	24628
25°	19968	21057	22945
30°	17854	19022	21200
35°	15613	16741	19135
40°	13141	14184	16565
45°	10845	11781	13831
50°	9054	9871	11523
55°	7687	8471	9516
60°	6569	7344	7593
65°	5231	6176	4905
70°	4637	4821	2994
75°	4296	3911	1832
80°	3958	3597	1583
85°	3578	3292	1291



TEST NUMBER: P522059

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4500K)

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	283.0	2.5
10°-20°	736.0	6.5
20°-30°	953.4	8.4
30°-40°	933.6	8.2
40°-50°	714.6	6.3
50°-60°	476.2	4.2
60°-70°	259.8	2.3
70°-80°	108.3	1.0
80°-90°	30.6	0.3
90°-100°	502.4	4.4
100°-110°	1429.4	12.6
110°-120°	1369.6	12.1
120°-130°	1083.9	9.6
130°-140°	870.0	7.7
140°-150°	681.1	6.0
150°-160°	498.4	4.4
160°-170°	308.7	2.7
170°-180°	104.8	0.9
0°-30°	1972.4	17.4
0°-40°	2906.0	25.6
0°-60°	4096.8	36.1
0°-90°	4495.6	39.6
90°-120°	3301.4	29.1
90°-150°	5936.5	52.3
90°-180°	6848.0	60.4
0°-180°	11343.8	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	3085	3085	3085	3085	3085	
5°	3035	3005	3024	3031	3042	282
15°	2567	2557	2626	2698	2744	717
25°	1962	1967	2068	2159	2254	902
35°	1386	1393	1486	1586	1699	862
45°	831	847	903	971	1060	648
55°	478	498	527	547	592	433
65°	240	260	283	247	225	249
75°	120	120	110	75	51	129
85°	34	34	31	20	12	37
90°	0	0	0	0	0	4
95°	54	216	972	337	208	62
105°	222	337	1457	2573	2446	235
115°	413	499	1105	2340	2748	407
125°	583	646	1054	1750	2092	522
135°	713	772	1042	1478	1670	550
145°	840	884	1050	1279	1394	525
155°	960	982	1075	1156	1203	444
165°	1061	1065	1088	1111	1128	298
175°	1111	1105	1100	1094	1086	105
180°	1102	1102	1102	1102	1102	

TEST NUMBER: P522059

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4500K)

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°
0°	3085.1	3085.1	3085.1	3085.1	3085.1
2.5°	3092.7	3065.2	3072.1	3071.9	3063.4
5°	3035.0	3004.6	3024.2	3031.2	3041.8
7.5°	2922.4	2899.4	2935.1	2961.6	2983.0
10°	2834.7	2814.8	2860.4	2898.9	2926.7
12.5°	2732.9	2716.2	2772.7	2824.4	2860.7
15°	2566.6	2557.4	2626.2	2697.6	2744.0
17.5°	2388.8	2384.3	2463.2	2546.6	2605.9
20°	2267.5	2266.1	2352.7	2439.6	2508.4
22.5°	2145.1	2148.0	2239.0	2329.4	2407.7
25°	1961.5	1966.8	2068.5	2158.6	2253.9
27.5°	1791.8	1794.2	1899.3	1994.4	2096.1
30°	1675.9	1682.5	1785.5	1884.1	1990.0
32.5°	1560.0	1567.7	1668.6	1770.4	1878.4
35°	1386.2	1392.8	1486.4	1586.4	1698.9
37.5°	1207.0	1216.0	1299.0	1393.6	1504.2
40°	1091.1	1104.3	1177.7	1266.8	1375.4
42.5°	979.5	996.0	1064.0	1148.5	1246.5
45°	831.2	847.1	902.9	971.3	1060.0
47.5°	703.4	721.7	764.6	823.4	899.1
50°	630.8	648.0	687.7	731.3	802.8
52.5°	566.9	584.1	619.5	653.1	713.9
55°	477.9	497.7	526.6	546.6	591.6
57.5°	404.8	423.8	446.7	455.7	483.0
60°	356.0	377.2	398.0	397.0	411.5
62.5°	311.6	329.6	350.3	336.0	336.8
65°	239.6	259.5	282.9	247.2	224.7
67.5°	193.6	197.8	222.0	172.4	145.7
70°	171.9	171.9	178.7	133.5	111.0
72.5°	151.3	151.3	145.1	108.6	85.0
75°	120.5	120.5	109.7	75.3	51.4
77.5°	92.9	91.8	83.9	56.2	37.4
80°	74.5	74.5	67.7	44.3	29.8
82.5°	58.2	58.2	52.5	34.6	22.2
85°	33.8	33.8	31.1	20.1	12.2
87.5°	11.9	11.9	10.8	6.5	5.4
90°	0.0	0.0	0.0	0.0	0.0
92.5°	16.8	88.9	206.2	60.0	45.3
95°	54.5	216.4	972.5	336.6	207.5
97.5°	100.2	253.5	1497.8	1071.8	734.4
100°	132.0	275.5	1611.8	1632.6	1257.6
102.5°	167.3	299.2	1586.6	2089.8	1762.3
105°	222.2	336.9	1456.7	2573.1	2446.0
107.5°	277.9	380.8	1305.0	2709.3	2822.4
110°	316.5	412.8	1217.8	2657.2	2911.3

TEST NUMBER: P522059

CATALOG NUMBER: SQ4-WB-150U-125D-92765-1D-UNV-STD-W-4 (4500K)

**CANDELA DISTRIBUTION (continued):**

	0°	22.5°	45°	67.5°	90°
112.5°	353.4	444.8	1159.1	2533.9	2896.2
115°	412.9	499.0	1104.6	2340.0	2747.8
117.5°	465.3	546.1	1072.3	2128.0	2560.0
120°	507.2	574.9	1068.9	2006.9	2420.8
122.5°	540.8	608.4	1060.6	1900.6	2285.0
125°	582.7	646.2	1054.3	1749.5	2091.8
127.5°	628.4	687.8	1050.9	1659.3	1941.3
130°	651.8	711.3	1045.9	1596.4	1842.4
132.5°	677.0	734.8	1045.9	1547.4	1773.6
135°	712.6	772.1	1041.7	1477.8	1670.5
137.5°	746.2	804.0	1041.3	1419.0	1585.4
140°	771.3	830.7	1039.6	1370.2	1530.1
142.5°	799.8	849.4	1044.6	1331.3	1474.7
145°	840.5	883.5	1050.1	1279.1	1393.8
147.5°	875.3	917.1	1059.3	1226.3	1325.5
150°	905.5	934.2	1062.7	1208.9	1278.5
152.5°	928.9	959.3	1066.0	1185.3	1250.0
155°	960.0	982.5	1075.2	1156.0	1203.1
157.5°	998.5	1012.0	1077.3	1142.6	1176.3
160°	1018.6	1028.9	1085.7	1132.5	1161.2
162.5°	1030.4	1042.3	1087.4	1123.9	1146.1
165°	1060.6	1064.7	1087.8	1111.2	1127.6
167.5°	1081.1	1077.4	1097.4	1108.1	1114.6
170°	1087.8	1085.8	1094.1	1096.4	1104.6
172.5°	1102.9	1095.9	1099.1	1093.0	1099.5
175°	1110.9	1104.7	1100.4	1093.9	1085.7
177.5°	1114.2	1104.4	1099.1	1092.5	1094.1
180°	1102.5	1102.5	1102.5	1102.5	1102.5

(END OF REPORT)