

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P937336

Luminaire Tested: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P937336
REPORT IS A COMBINATION OF REPORTS P933504 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Batwing Frosted Continuous Roll L
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6757.4 lumens
Efficiency: N/A
Efficacy: 109.0 lumens/watt
Spacing Criteria (0/90/45): 0.71 / 2.69 / 2.33
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 62
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

Luminous Intensity Polar Plot



TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	109	109	109	109	101	101	101	101	88	88	88	75	75	75	63	63	63
1	99	94	90	86	92	88	84	81	76	73	71	65	63	61	55	53	52
2	89	82	75	69	83	76	70	65	66	61	57	56	53	50	47	45	43
3	81	71	63	57	75	66	59	54	57	52	47	49	45	41	41	38	36
4	74	62	54	48	68	58	51	45	50	45	40	43	39	35	36	33	30
5	68	55	47	40	63	52	44	38	45	39	34	38	34	30	33	29	26
6	62	49	41	35	57	46	38	33	40	34	29	34	29	26	29	25	22
7	57	44	36	30	53	41	34	28	36	30	25	31	26	22	26	22	19
8	53	40	32	26	49	37	30	25	33	27	22	28	23	20	24	20	17
9	49	36	28	23	46	34	27	22	30	24	20	26	21	17	22	18	15
10	46	33	26	21	43	31	24	20	27	22	18	24	19	16	20	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	4668	4668	4668
5°	4556	5393	6276
10°	4128	7854	10405
15°	3505	10255	12563
20°	2851	11876	12804
25°	2374	12418	12544
30°	1999	12486	12521
35°	1765	12269	12844
40°	1536	11990	13178
45°	1388	11782	13231
50°	1270	11593	13011
55°	1212	11321	12434
60°	1238	10809	11525
65°	1282	10037	10272
70°	1356	8735	8679
75°	1486	7105	6773
80°	1587	4909	4563
85°	1341	2592	2336

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 45°

Luminance: 13231 cd/sqm

TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	65.1	1.0
10°-20°	288.5	4.3
20°-30°	504.6	7.5
30°-40°	649.6	9.6
40°-50°	725.5	10.7
50°-60°	694.9	10.3
60°-70°	550.7	8.1
70°-80°	323.8	4.8
80°-90°	91.7	1.4
90°-100°	215.3	3.2
100°-110°	566.0	8.4
110°-120°	586.9	8.7
120°-130°	470.8	7.0
130°-140°	369.4	5.5
140°-150°	283.5	4.2
150°-160°	204.2	3.0
160°-170°	124.9	1.8
170°-180°	42.2	0.6
0°-30°	858.2	12.7
0°-40°	1507.7	22.3
0°-60°	2928.2	43.3
0°-90°	3894.4	57.6
90°-120°	1368.2	20.2
90°-150°	2491.8	36.9
90°-180°	2863.0	42.4
0°-180°	6757.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	503	503	503	503	503	
5°	490	526	592	670	694	45
15°	367	678	1142	1385	1429	102
25°	235	768	1361	1421	1422	108
35°	158	734	1281	1354	1408	99
45°	108	586	1133	1298	1356	84
55°	78	372	961	1116	1147	71
65°	62	197	714	802	814	61
75°	45	121	392	430	432	47
85°	16	37	97	107	108	17
90°	3	8	23	11	11	4
95°	28	112	371	191	130	32
105°	102	154	626	950	886	108
115°	181	220	501	1000	1141	179
125°	252	282	456	770	909	224
135°	300	330	442	622	705	232
145°	348	370	436	531	572	218
155°	394	405	436	479	493	181
165°	425	430	436	453	459	120
175°	442	442	439	445	445	42
180°	442	442	442	442	442	

TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	503.1	503.1	503.1	503.1	503.1	503.1	503.1	503.1	503.1	503.1	503.1
2.5°	503.1	503.1	506.4	508.0	511.3	512.9	516.2	519.4	529.1	530.7	533.9
5°	490.2	496.7	517.8	525.8	548.5	579.3	592.2	613.2	656.9	669.8	677.9
7.5°	470.8	485.4	537.2	550.1	606.7	687.6	721.6	767.0	836.5	870.4	898.0
10°	440.0	470.8	563.0	593.8	686.0	808.9	872.0	935.2	1040.3	1087.3	1105.1
12.5°	406.1	456.3	590.5	632.6	765.3	944.9	1020.9	1090.5	1210.3	1273.4	1283.0
15°	367.3	435.3	616.5	677.9	849.4	1058.1	1142.3	1228.0	1339.7	1384.9	1396.3
17.5°	333.3	419.1	640.7	705.5	914.1	1160.1	1245.8	1317.1	1407.6	1438.4	1446.4
20°	291.3	393.2	656.9	741.0	982.1	1234.5	1317.1	1372.0	1433.5	1452.9	1456.2
22.5°	260.5	365.6	666.6	754.0	1027.4	1279.8	1349.4	1393.1	1435.2	1441.7	1443.2
25°	234.6	335.0	665.0	768.5	1066.3	1307.3	1360.8	1393.1	1417.4	1420.6	1420.6
27.5°	210.4	300.9	658.5	771.7	1095.3	1313.8	1355.9	1378.5	1389.8	1396.3	1396.3
30°	189.3	268.6	642.4	765.3	1108.3	1307.3	1341.3	1352.6	1363.9	1373.7	1378.5
32.5°	173.2	237.8	618.1	752.3	1109.9	1291.1	1315.4	1321.8	1338.1	1360.8	1368.8
35°	158.5	207.1	590.5	734.5	1100.2	1265.2	1281.4	1287.9	1320.2	1354.3	1365.5
37.5°	144.0	184.4	555.0	703.9	1085.7	1234.5	1245.8	1257.2	1307.3	1347.8	1360.8
40°	129.5	165.0	512.9	669.8	1063.0	1197.2	1207.0	1224.8	1291.1	1338.1	1351.0
42.5°	118.1	148.9	467.6	634.2	1033.8	1155.3	1169.8	1195.7	1271.7	1321.8	1336.5
45°	108.4	132.7	419.1	585.7	996.6	1111.6	1132.6	1168.2	1249.1	1297.6	1310.6
47.5°	98.7	121.3	368.9	535.6	956.2	1067.9	1095.3	1135.9	1218.3	1265.2	1276.6
50°	90.6	110.1	318.7	482.1	912.5	1020.9	1053.3	1095.3	1179.5	1223.2	1237.8
52.5°	84.1	100.3	271.8	428.8	862.4	972.4	1009.6	1053.3	1132.6	1174.7	1184.3
55°	77.6	92.2	231.4	372.2	810.6	920.6	961.1	1003.1	1080.8	1116.4	1122.9
57.5°	74.4	85.8	197.4	318.7	755.6	862.4	907.7	946.5	1019.3	1046.8	1053.3
60°	69.6	80.9	171.5	273.5	695.7	807.4	846.2	885.1	946.5	969.2	974.0
62.5°	64.7	77.6	152.1	229.8	634.2	742.7	781.5	817.1	868.9	885.1	891.5
65°	61.5	74.4	137.5	197.4	571.1	674.7	713.5	744.3	786.4	802.5	805.8
67.5°	58.2	71.2	126.2	169.9	508.0	606.7	635.9	665.0	697.4	713.5	715.1
70°	53.4	68.0	116.5	150.5	443.3	529.1	553.3	584.0	610.0	618.1	623.0
72.5°	50.2	63.1	110.1	135.9	377.0	454.7	477.3	495.1	517.8	525.8	525.8
75°	45.3	56.6	103.6	121.3	309.0	372.2	391.6	409.3	427.1	430.4	425.5
77.5°	40.4	50.2	89.0	101.9	241.1	294.5	310.7	320.3	335.0	338.1	339.7
80°	33.9	43.7	69.6	79.3	174.7	216.8	228.1	236.2	249.2	249.2	252.4
82.5°	25.9	33.9	50.2	56.6	118.1	148.9	158.5	163.4	171.5	171.5	171.5
85°	16.2	21.0	32.3	37.2	71.2	90.6	97.1	98.7	105.2	106.8	106.8
87.5°	8.1	11.3	21.0	22.7	37.2	46.9	46.9	50.2	50.2	48.6	46.9
90°	3.0	5.4	7.7	8.3	13.1	19.4	22.6	20.1	15.0	11.3	11.3
92.5°	11.9	32.0	52.1	57.2	80.4	111.4	126.9	111.2	79.8	56.3	54.1
95°	28.5	65.4	102.3	111.5	197.9	313.2	370.8	330.8	251.0	191.1	184.4
97.5°	49.2	81.8	114.3	122.4	266.6	458.8	554.9	529.6	479.2	441.4	428.5
100°	65.2	94.7	124.2	131.6	291.5	504.9	611.5	613.3	617.0	619.8	604.4
102.5°	78.9	106.4	133.9	140.8	303.0	519.4	627.5	659.7	723.9	772.1	758.9
105°	101.9	125.3	148.6	154.4	311.5	521.0	625.7	697.8	841.9	950.0	942.9
107.5°	125.6	147.4	169.2	174.6	313.2	497.8	590.2	690.7	891.6	1042.4	1044.2
110°	141.7	161.3	181.0	185.9	310.8	477.2	560.5	672.9	897.6	1066.2	1073.5

TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	157.4	176.1	194.8	199.5	310.9	459.4	533.6	648.6	878.6	1051.0	1062.4
115°	181.1	198.3	215.6	219.9	313.7	438.7	501.2	612.1	833.6	999.8	1015.5
117.5°	204.5	220.2	235.9	239.8	319.6	425.8	479.0	579.0	778.9	928.9	946.3
120°	218.2	232.9	247.7	251.4	324.2	421.5	470.1	561.5	744.2	881.2	898.2
122.5°	231.5	246.4	261.2	265.0	331.0	419.2	463.3	545.5	710.1	833.5	850.2
125°	252.0	265.5	279.1	282.5	340.3	417.4	455.9	525.8	665.6	770.4	785.8
127.5°	268.6	282.3	295.9	299.4	349.5	416.3	449.7	509.7	629.7	719.7	732.7
130°	277.5	292.2	306.9	310.7	356.2	416.9	447.3	500.8	607.6	687.7	699.6
132.5°	286.7	301.4	316.1	319.8	361.6	417.4	445.2	493.0	588.7	660.4	671.2
135°	300.2	313.6	327.1	330.5	367.6	417.0	441.7	481.7	561.9	621.9	631.2
137.5°	314.2	327.5	340.8	344.1	376.5	419.6	441.1	474.9	542.6	593.4	601.0
140°	325.8	338.0	350.3	353.3	381.9	420.0	439.0	468.2	526.7	570.6	577.6
142.5°	334.7	346.0	357.2	360.1	386.4	421.5	439.0	464.7	516.1	554.6	560.7
145°	348.2	358.2	368.0	370.5	392.3	421.5	436.0	457.1	499.0	530.6	535.2
147.5°	361.9	371.5	381.1	383.5	401.0	424.4	436.0	452.6	485.7	510.4	514.2
150°	370.8	379.5	388.2	390.4	405.6	425.9	436.0	450.0	477.9	498.8	501.9
152.5°	380.0	386.6	393.2	394.8	408.6	426.8	436.0	448.0	471.8	489.7	492.0
155°	393.7	398.5	403.3	404.6	415.1	429.0	436.0	445.5	464.4	478.7	480.2
157.5°	403.7	408.5	413.3	414.4	421.6	431.2	436.0	443.4	458.1	469.2	470.3
160°	410.5	414.2	417.9	418.8	424.5	432.2	436.0	442.3	455.1	464.5	465.1
162.5°	417.4	420.2	422.9	423.6	427.7	433.3	436.0	441.4	452.0	460.0	460.6
165°	424.7	427.2	429.7	430.4	432.3	434.8	436.0	439.8	447.5	453.2	453.9
167.5°	431.5	432.7	433.9	434.2	435.8	437.9	439.0	441.5	446.5	450.3	450.6
170°	436.0	437.2	438.4	438.7	438.8	438.9	439.0	441.5	446.5	450.3	450.3
172.5°	438.4	438.7	438.9	439.0	439.0	439.0	439.0	441.0	444.9	447.9	447.7
175°	441.7	441.7	441.7	441.7	440.8	439.6	439.0	440.2	442.7	444.6	444.6
177.5°	441.7	441.7	441.7	441.7	441.0	440.0	439.6	440.5	442.5	444.1	443.8
180°	441.7	441.7	441.7	441.7	441.7	441.7	441.7	441.7	441.7	441.7	441.7

TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

CANDELA DISTRIBUTION (continued):

	80°	90°
0°	503.1	503.1
2.5°	537.2	533.9
5°	690.8	694.1
7.5°	930.4	928.8
10°	1156.8	1171.4
12.5°	1321.8	1325.1
15°	1422.2	1428.6
17.5°	1461.1	1462.7
20°	1462.7	1459.4
22.5°	1444.8	1441.7
25°	1423.8	1422.2
27.5°	1404.4	1406.0
30°	1396.3	1401.2
32.5°	1396.3	1404.4
35°	1399.6	1407.6
37.5°	1398.0	1407.6
40°	1391.5	1402.7
42.5°	1373.7	1381.7
45°	1346.1	1355.9
47.5°	1310.6	1317.1
50°	1265.2	1271.7
52.5°	1208.6	1210.3
55°	1140.6	1147.1
57.5°	1067.9	1069.5
60°	987.0	991.9
62.5°	901.2	901.2
65°	810.6	813.8
67.5°	716.8	724.9
70°	621.3	623.0
72.5°	527.4	527.4
75°	430.4	432.0
77.5°	338.1	338.1
80°	250.8	252.4
82.5°	173.2	176.3
85°	108.4	108.4
87.5°	50.2	45.3
90°	11.3	11.3
92.5°	45.1	36.1
95°	157.3	130.1
97.5°	376.8	325.2
100°	542.9	481.3
102.5°	706.2	653.6
105°	914.6	886.3
107.5°	1051.0	1057.9
110°	1103.1	1132.6



TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

CANDELA DISTRIBUTION (continued):

	80°	90°
112.5°	1107.7	1153.1
115°	1078.4	1141.2
117.5°	1016.1	1085.8
120°	965.9	1033.5
122.5°	917.0	983.8
125°	847.3	908.8
127.5°	784.6	836.5
130°	747.6	795.6
132.5°	714.1	757.0
135°	668.2	705.2
137.5°	631.3	661.6
140°	606.0	634.3
142.5°	585.0	609.4
145°	553.6	572.1
147.5°	529.5	544.8
150°	514.3	526.8
152.5°	501.3	510.7
155°	486.4	492.6
157.5°	474.7	479.0
160°	467.6	470.1
162.5°	463.0	465.4
165°	456.4	458.9
167.5°	451.6	452.7
170°	450.3	450.3
172.5°	446.7	445.8
175°	444.6	444.6
177.5°	442.7	441.7
180°	441.7	441.7

TEST NUMBER: P937336

CATALOG NUMBER: SQ4-FB-075U-125D-92765-1D-UNV-STD-W-4-6500K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	7.01	7.99	7.89	8.90	10.05	20.15	21.13	21.03	22.04	23.19
	3H	7.73	8.61	8.62	9.53	10.71	21.98	22.87	22.88	23.78	24.96
	4H	8.03	8.87	8.94	9.79	10.98	22.62	23.46	23.53	24.38	25.57
	6H	8.29	9.06	9.21	9.99	11.19	23.05	23.82	23.97	24.75	25.95
	8H	8.36	9.10	9.29	10.04	11.24	23.17	23.90	24.09	24.85	26.05
	12H	8.38	9.08	9.32	10.02	11.25	23.23	23.93	24.16	24.87	26.10
4H	2H	14.22	15.05	15.13	15.97	17.16	20.44	21.28	21.35	22.20	23.39
	3H	15.80	16.50	16.72	17.45	18.65	22.48	23.18	23.41	24.14	25.34
	4H	15.90	16.54	16.83	17.49	18.71	23.24	23.88	24.18	24.83	26.06
	6H	15.92	16.47	16.86	17.44	18.67	23.78	24.33	24.73	25.30	26.53
	8H	15.90	16.41	16.85	17.38	18.62	23.94	24.45	24.89	25.42	26.66
	12H	15.86	16.33	16.83	17.31	18.56	24.03	24.50	25.00	25.48	26.73
8H	4H	17.34	17.86	18.29	18.83	20.07	23.32	23.83	24.27	24.80	26.04
	6H	17.59	18.02	18.57	19.03	20.27	23.94	24.37	24.92	25.37	26.62
	8H	17.61	17.99	18.60	18.99	20.25	24.15	24.53	25.14	25.53	26.79
	12H	17.59	17.92	18.58	18.91	20.22	24.29	24.63	25.28	25.62	26.92
12H	4H	17.49	17.96	18.46	18.94	20.19	23.27	23.74	24.25	24.73	25.97
	6H	17.85	18.23	18.83	19.22	20.48	23.92	24.30	24.91	25.30	26.56
	8H	17.92	18.26	18.91	19.25	20.55	24.15	24.49	25.14	25.48	26.78

END OF REPORT