

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P937082

Luminaire Tested: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

Issue Date: 12/17/2024

**Test Information**


Test Method: LM-79-2019  
Report Number: P937082  
REPORT IS A COMBINATION OF REPORTS P933501 AND P933786  
Test Lab: INNOVATION CENTER  
Issue Date: 12/17/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: CORELITE  
Catalog Number: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K  
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Batwing Frosted Continuous Roll L  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4591.6 lumens  
Efficiency: N/A  
Efficacy: 133.5 lumens/watt  
Spacing Criteria (0/90/45): 0.71 / 2.69 / 2.33  
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 4' x H: 0.1')  
CIE Type: Semi-Indirect  
  
Input Watts (W): 34.4  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P937082  
CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

### Luminous Intensity Polar Plot





TEST NUMBER: P937082

CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	104	104	104	104	94	94	94	94	75	75	75	58	58	58	42	42	42	35		
1	94	90	86	82	85	81	78	75	65	63	61	50	49	47	37	36	35	29		
2	85	78	72	66	77	70	65	61	57	53	50	44	41	39	32	30	29	23		
3	77	68	61	55	70	62	55	50	49	45	41	38	35	32	28	26	24	19		
4	71	60	52	46	63	54	47	42	44	39	35	34	30	27	25	22	20	16		
5	65	53	45	39	58	48	41	36	39	33	29	30	26	23	22	19	17	14		
6	59	47	39	33	53	43	36	31	35	29	25	27	23	20	20	17	15	12		
7	55	42	34	29	49	38	31	26	31	26	22	24	20	17	18	15	13	10		
8	50	38	30	25	45	35	28	23	28	23	19	22	18	15	16	14	12	9		
9	47	35	27	22	42	32	25	20	26	21	17	20	16	14	15	12	10	8		
10	44	32	24	20	39	29	22	18	23	18	15	18	15	12	14	11	9	7		

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	1928	1928	1928
5°	1882	2226	2591
10°	1705	3244	4297
15°	1448	4235	5188
20°	1177	4904	5288
25°	981	5128	5180
30°	826	5156	5171
35°	728	5067	5304
40°	635	4952	5442
45°	572	4865	5464
50°	524	4788	5374
55°	501	4675	5135
60°	511	4464	4759
65°	529	4144	4242
70°	559	3607	3585
75°	613	2934	2797
80°	655	2027	1886
85°	555	1070	963

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 90°  
 Vertical Angle: 45°  
 Luminance: 5464 cd/sqm



TEST NUMBER: P937082

CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	26.9	0.6
10°-20°	119.1	2.6
20°-30°	208.4	4.5
30°-40°	268.2	5.8
40°-50°	299.6	6.5
50°-60°	287.0	6.2
60°-70°	227.4	5.0
70°-80°	133.7	2.9
80°-90°	38.9	0.8
90°-100°	224.3	4.9
100°-110°	589.6	12.8
110°-120°	611.3	13.3
120°-130°	490.4	10.7
130°-140°	384.8	8.4
140°-150°	295.3	6.4
150°-160°	212.7	4.6
160°-170°	130.1	2.8
170°-180°	44.0	1.0
0°-30°	354.4	7.7
0°-40°	622.6	13.6
0°-60°	1209.2	26.3
0°-90°	1609.3	35.0
90°-120°	1425.1	31.0
90°-150°	2595.5	56.5
90°-180°	2982.0	64.9
0°-180°	4591.6	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	208	208	208	208	208	
5°	202	217	244	277	287	19
15°	152	280	472	572	590	42
25°	97	317	562	587	587	45
35°	65	303	529	559	581	41
45°	45	242	468	536	560	35
55°	32	154	397	461	474	29
65°	25	82	295	331	336	25
75°	19	50	162	178	178	20
85°	7	15	40	44	45	7
90°	3	9	24	12	12	3
95°	30	116	386	199	136	33
105°	106	161	652	990	923	113
115°	189	229	522	1041	1189	186
125°	262	294	475	802	947	233
135°	313	344	460	648	735	242
145°	363	386	454	553	596	227
155°	410	421	454	499	513	188
165°	442	448	454	472	478	125
175°	460	460	457	463	463	44
180°	460	460	460	460	460	



TEST NUMBER: P937082

CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

**CANDELA DISTRIBUTION (FULL):**

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8
2.5°	207.8	207.8	209.2	209.8	211.2	211.8	213.1	214.4	218.5	219.1	220.5
5°	202.5	205.2	213.8	217.1	226.5	239.2	244.5	253.3	271.3	276.6	280.0
7.5°	194.4	200.5	221.8	227.2	250.6	284.0	298.0	316.7	345.4	359.5	370.8
10°	181.8	194.4	232.6	245.2	283.3	334.1	360.2	386.2	429.7	449.0	456.4
12.5°	167.7	188.4	243.9	261.3	316.0	390.2	421.6	450.4	499.8	525.9	529.9
15°	151.7	179.8	254.6	280.0	350.8	436.9	471.7	507.2	553.3	571.9	576.6
17.5°	137.6	173.1	264.6	291.3	377.5	479.1	514.5	543.9	581.3	594.0	597.3
20°	120.3	162.3	271.3	306.1	405.6	509.9	543.9	566.6	592.0	600.0	601.4
22.5°	107.6	151.0	275.3	311.3	424.3	528.5	557.3	575.3	592.6	595.3	596.0
25°	96.9	138.3	274.6	317.4	440.3	539.8	561.9	575.3	585.3	586.6	586.6
27.5°	86.9	124.3	271.9	318.7	452.4	542.5	560.0	569.3	574.0	576.6	576.6
30°	78.2	111.0	265.2	316.0	457.7	539.8	553.9	558.6	563.2	567.3	569.3
32.5°	71.5	98.2	255.3	310.7	458.4	533.2	543.2	545.9	552.6	561.9	565.2
35°	65.4	85.6	243.9	303.4	454.4	522.5	529.2	531.9	545.2	559.3	563.9
37.5°	59.5	76.2	229.2	290.6	448.3	509.9	514.5	519.2	539.8	556.6	561.9
40°	53.5	68.1	211.8	276.6	439.0	494.4	498.5	505.8	533.2	552.6	558.0
42.5°	48.8	61.5	193.1	261.9	427.0	477.1	483.1	493.8	525.2	545.9	551.9
45°	44.7	54.8	173.1	241.8	411.5	459.1	467.7	482.5	515.8	535.8	541.2
47.5°	40.7	50.1	152.4	221.2	394.9	441.0	452.4	469.0	503.2	522.5	527.2
50°	37.4	45.4	131.7	199.1	376.9	421.6	435.0	452.4	487.1	505.2	511.1
52.5°	34.8	41.4	112.2	177.1	356.2	401.6	416.9	435.0	467.7	485.1	489.1
55°	32.1	38.0	95.5	153.7	334.8	380.2	396.9	414.2	446.3	461.0	463.7
57.5°	30.8	35.5	81.5	131.7	312.0	356.2	374.8	390.8	420.9	432.3	435.0
60°	28.7	33.4	70.8	112.9	287.3	333.5	349.5	365.5	390.8	400.2	402.3
62.5°	26.7	32.1	62.8	94.9	261.9	306.7	322.7	337.4	358.8	365.5	368.1
65°	25.4	30.8	56.8	81.5	235.9	278.6	294.6	307.4	324.7	331.4	332.8
67.5°	24.1	29.4	52.1	70.1	209.8	250.6	262.5	274.6	287.9	294.6	295.3
70°	22.0	28.1	48.1	62.2	183.1	218.5	228.5	241.2	251.9	255.3	257.3
72.5°	20.7	26.1	45.4	56.2	155.7	187.7	197.1	204.5	213.8	217.1	217.1
75°	18.7	23.4	42.7	50.1	127.6	153.7	161.7	169.0	176.4	177.7	175.7
77.5°	16.7	20.7	36.8	42.1	99.6	121.6	128.3	132.3	138.3	139.6	140.3
80°	14.0	18.0	28.7	32.8	72.2	89.5	94.2	97.5	102.9	102.9	104.3
82.5°	10.7	14.0	20.7	23.4	48.8	61.5	65.4	67.5	70.8	70.8	70.8
85°	6.7	8.7	13.3	15.3	29.4	37.4	40.1	40.7	43.4	44.1	44.1
87.5°	3.4	4.7	8.7	9.4	15.3	19.4	19.4	20.7	20.7	20.0	19.4
90°	3.1	5.6	8.1	8.7	13.6	20.2	23.5	20.9	15.6	11.8	11.8
92.5°	12.4	33.4	54.3	59.6	83.8	116.0	132.2	115.8	83.2	58.7	56.4
95°	29.7	68.1	106.6	116.1	206.2	326.2	386.2	344.6	261.4	199.1	192.0
97.5°	51.3	85.2	119.0	127.5	277.7	477.9	578.0	551.7	499.2	459.8	446.3
100°	67.9	98.6	129.4	137.0	303.7	525.9	636.9	638.8	642.7	645.6	629.6
102.5°	82.2	110.9	139.4	146.6	315.6	541.0	653.7	687.1	754.1	804.3	790.5
105°	106.2	130.5	154.8	160.9	324.5	542.7	651.8	726.9	877.0	989.5	982.2
107.5°	130.9	153.6	176.2	181.9	326.2	518.5	614.7	719.4	928.8	1085.8	1087.6
110°	147.6	168.0	188.5	193.6	323.7	497.1	583.9	700.9	934.9	1110.5	1118.2



TEST NUMBER: P937082

CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

**CANDELA DISTRIBUTION (continued):**

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	163.9	183.5	202.9	207.8	323.8	478.5	555.8	675.6	915.1	1094.8	1106.7
115°	188.6	206.6	224.6	229.1	326.8	457.0	522.1	637.5	868.3	1041.4	1057.8
117.5°	213.0	229.4	245.7	249.8	332.9	443.5	498.9	603.1	811.3	967.6	985.7
120°	227.3	242.6	258.0	261.8	337.7	439.0	489.6	584.9	775.2	917.9	935.5
122.5°	241.1	256.7	272.1	276.0	344.8	436.6	482.6	568.2	739.6	868.2	885.6
125°	262.4	276.6	290.7	294.2	354.5	434.8	474.9	547.7	693.3	802.5	818.5
127.5°	279.8	294.0	308.3	311.8	364.0	433.7	468.4	531.0	656.0	749.7	763.2
130°	289.0	304.4	319.7	323.6	371.0	434.3	465.9	521.6	632.9	716.3	728.8
132.5°	298.6	313.9	329.3	333.2	376.7	434.8	463.7	513.5	613.2	687.9	699.1
135°	312.7	326.7	340.7	344.2	382.9	434.4	460.1	501.8	585.2	647.8	657.5
137.5°	327.3	341.1	355.0	358.5	392.1	437.0	459.5	494.7	565.2	618.1	626.0
140°	339.3	352.1	364.8	368.0	397.8	437.4	457.3	487.7	548.6	594.3	601.7
142.5°	348.6	360.4	372.1	375.1	402.5	439.0	457.3	484.1	537.5	577.7	584.1
145°	362.7	373.1	383.4	386.0	408.7	439.0	454.2	476.1	519.8	552.7	557.5
147.5°	377.0	386.9	397.0	399.5	417.7	442.0	454.2	471.4	505.9	531.7	535.6
150°	386.2	395.3	404.4	406.7	422.5	443.6	454.2	468.7	497.8	519.6	522.8
152.5°	395.8	402.7	409.6	411.2	425.6	444.6	454.2	466.6	491.4	510.1	512.4
155°	410.1	415.1	420.1	421.4	432.4	446.9	454.2	464.0	483.8	498.6	500.2
157.5°	420.5	425.5	430.5	431.7	439.1	449.2	454.2	461.8	477.2	488.7	489.8
160°	427.6	431.5	435.3	436.2	442.2	450.2	454.2	460.7	474.0	483.9	484.5
162.5°	434.8	437.6	440.5	441.2	445.5	451.3	454.2	459.8	470.8	479.2	479.8
165°	442.4	445.0	447.6	448.3	450.3	452.9	454.2	458.2	466.1	472.1	472.8
167.5°	449.5	450.7	452.0	452.3	454.0	456.2	457.3	459.9	465.1	469.0	469.3
170°	454.2	455.4	456.7	457.0	457.1	457.2	457.3	459.9	465.1	469.0	469.0
172.5°	456.7	457.0	457.2	457.3	457.3	457.3	457.3	459.4	463.4	466.5	466.3
175°	460.1	460.1	460.1	460.1	459.2	457.9	457.3	458.6	461.1	463.1	463.1
177.5°	460.1	460.1	460.1	460.1	459.4	458.4	457.9	458.9	460.9	462.5	462.2
180°	460.1	460.1	460.1	460.1	460.1	460.1	460.1	460.1	460.1	460.1	460.1



TEST NUMBER: P937082  
 CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

**CANDELA DISTRIBUTION (continued):**

	80°	90°
0°	207.8	207.8
2.5°	221.8	220.5
5°	285.4	286.6
7.5°	384.2	383.6
10°	477.8	483.8
12.5°	545.9	547.2
15°	587.3	590.0
17.5°	603.4	604.1
20°	604.1	602.7
22.5°	596.7	595.3
25°	588.0	587.3
27.5°	580.0	580.7
30°	576.6	578.7
32.5°	576.6	580.0
35°	578.0	581.3
37.5°	577.3	581.3
40°	574.6	579.3
42.5°	567.3	570.6
45°	555.9	560.0
47.5°	541.2	543.9
50°	522.5	525.2
52.5°	499.1	499.8
55°	471.1	473.7
57.5°	441.0	441.6
60°	407.6	409.6
62.5°	372.2	372.2
65°	334.8	336.1
67.5°	296.0	299.3
70°	256.6	257.3
72.5°	217.8	217.8
75°	177.7	178.4
77.5°	139.6	139.6
80°	103.6	104.3
82.5°	71.5	72.8
85°	44.7	44.7
87.5°	20.7	18.7
90°	11.8	11.8
92.5°	47.0	37.6
95°	163.8	135.6
97.5°	392.5	338.7
100°	565.5	501.4
102.5°	735.6	680.8
105°	952.7	923.2
107.5°	1094.8	1102.0
110°	1149.0	1179.8





TEST NUMBER: P937082

CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

**CANDELA DISTRIBUTION (continued):**

	80°	90°
112.5°	1153.9	1201.1
115°	1123.3	1188.7
117.5°	1058.3	1131.0
120°	1006.1	1076.6
122.5°	955.2	1024.8
125°	882.6	946.6
127.5°	817.2	871.3
130°	778.8	828.7
132.5°	743.8	788.5
135°	696.0	734.6
137.5°	657.6	689.1
140°	631.3	660.7
142.5°	609.4	634.8
145°	576.7	595.9
147.5°	551.6	567.5
150°	535.7	548.7
152.5°	522.2	532.0
155°	506.7	513.1
157.5°	494.4	498.9
160°	487.0	489.6
162.5°	482.3	484.8
165°	475.4	478.0
167.5°	470.4	471.5
170°	469.0	469.0
172.5°	465.3	464.3
175°	463.1	463.1
177.5°	461.1	460.1
180°	460.1	460.1



TEST NUMBER: P937082

CATALOG NUMBER: SQ4-FB-075U-050D-B2750-1D-UNV-STD-W-4-2700K

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	1.72	2.49	2.79	3.56	5.03	14.86	15.63	15.93	16.70	18.17
	3H	2.42	3.11	3.50	4.19	5.68	16.68	17.37	17.76	18.45	19.93
	4H	2.72	3.37	3.81	4.45	5.95	17.31	17.96	18.40	19.05	20.54
	6H	2.96	3.56	4.06	4.65	6.15	17.72	18.32	18.82	19.41	20.91
	8H	3.03	3.60	4.13	4.70	6.20	17.83	18.41	18.94	19.51	21.01
	12H	3.04	3.58	4.15	4.68	6.20	17.89	18.43	19.00	19.53	21.05
4H	2H	8.90	9.55	10.00	10.64	12.13	15.13	15.78	16.22	16.86	18.35
	3H	10.46	11.01	11.57	12.12	13.62	17.15	17.69	18.25	18.80	20.31
	4H	10.55	11.05	11.66	12.16	13.68	17.90	18.40	19.01	19.50	21.03
	6H	10.56	10.99	11.67	12.11	13.63	18.42	18.85	19.54	19.98	21.49
	8H	10.53	10.94	11.65	12.05	13.59	18.57	18.98	19.69	20.09	21.63
	12H	10.48	10.85	11.62	11.98	13.52	18.65	19.02	19.79	20.15	21.69
8H	4H	11.98	12.38	13.10	13.50	15.03	17.95	18.35	19.07	19.47	21.01
	6H	12.22	12.55	13.36	13.71	15.24	18.56	18.90	19.70	20.06	21.59
	8H	12.23	12.53	13.38	13.66	15.22	18.78	19.07	19.92	20.21	21.76
	12H	12.20	12.45	13.35	13.59	15.18	18.91	19.16	20.05	20.30	21.88
12H	4H	12.11	12.48	13.25	13.61	15.15	17.90	18.27	19.03	19.39	20.93
	6H	12.47	12.76	13.61	13.90	15.45	18.55	18.84	19.69	19.98	21.53
	8H	12.54	12.79	13.68	13.93	15.51	18.76	19.02	19.91	20.16	21.74