

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P934587

Luminaire Tested: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P934587
REPORT IS A COMBINATION OF REPORTS P933703 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Asymmetric Frosted Continuous I
Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9904.2 lumens
Efficiency: N/A
Efficacy: 117.9 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.26 / 1.36
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 6' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 84
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

Luminous Intensity Polar Plot



TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	112	112	112	112	106	106	106	106	94	94	94	84	84	84	74	74	74	74	74	74
1	102	98	94	90	97	93	89	86	83	80	78	74	72	70	66	65	63	63	63	59
2	93	86	79	74	88	81	76	71	73	68	65	65	62	59	58	56	53	53	53	50
3	85	75	68	62	80	71	65	59	64	59	54	58	53	50	52	48	45	45	45	42
4	78	67	58	52	73	63	56	50	57	51	46	51	47	43	46	42	39	39	39	36
5	72	60	51	45	67	57	49	43	51	45	40	46	41	37	41	37	34	34	34	31
6	66	53	45	39	62	51	43	38	46	40	35	42	36	32	38	33	30	30	30	27
7	61	48	40	34	58	46	39	33	42	36	31	38	33	29	34	30	27	27	27	24
8	57	44	36	30	54	42	35	29	38	32	28	35	29	26	31	27	24	24	24	22
9	53	40	32	27	50	38	31	26	35	29	25	32	27	23	29	25	21	21	21	19
10	49	37	30	25	47	35	28	24	32	26	22	30	25	21	27	23	19	19	19	18

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	16530	16530	16530	16530
5°	16647	16686	16647	13120
10°	16530	16437	16530	11751
15°	16344	16081	16344	13427
20°	15996	15659	15996	13456
25°	15289	15043	15289	13170
30°	14379	14533	14379	12545
35°	12813	13886	12813	11857
40°	10670	13126	10670	11336
45°	9528	12235	9528	10739
50°	10115	11173	10115	10139
55°	9507	10029	9507	9792
60°	9788	8518	9788	8968
65°	8861	7041	8861	7871
70°	6121	5612	6121	6597
75°	5346	4148	5346	4968
80°	4280	2742	4280	2986
85°	2409	1452	2409	1235

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 20°

Vertical Angle: 45°

Luminance: 14612 cd/sqm

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	241.2	2.4
10°-20°	684.8	6.9
20°-30°	1058.6	10.7
30°-40°	1263.8	12.8
40°-50°	1271.2	12.8
50°-60°	1106.1	11.2
60°-70°	784.2	7.9
70°-80°	414.9	4.2
80°-90°	105.1	1.1
90°-100°	223.7	2.3
100°-110°	588.0	5.9
110°-120°	609.7	6.2
120°-130°	489.0	4.9
130°-140°	383.7	3.9
140°-150°	294.5	3.0
150°-160°	212.1	2.1
160°-170°	129.8	1.3
170°-180°	43.8	0.4
0°-30°	1984.7	20.0
0°-40°	3248.4	32.8
0°-60°	5625.7	56.8
0°-90°	6929.9	70.0
90°-120°	1421.3	14.4
90°-150°	2588.6	26.1
90°-180°	2974.0	30.0
0°-180°	9904.2	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	2672	2672	2672	2672	2672	
5°	2685	2768	2685	2177	2685	255
15°	2563	2743	2563	2290	2563	721
25°	2257	2558	2257	2240	2257	1037
35°	1716	2283	1716	1949	1716	1062
45°	1107	1881	1107	1651	1107	887
55°	902	1388	902	1355	902	829
65°	627	837	627	935	627	599
75°	238	397	238	475	238	250
85°	40	101	40	86	40	55
90°	3	12	3	12	3	4
95°	30	135	30	135	30	33
105°	106	921	106	921	106	112
115°	188	1186	188	1186	188	186
125°	262	944	262	944	262	232
135°	312	733	312	733	312	241
145°	362	594	362	594	362	227
155°	409	512	409	512	409	188
165°	441	477	441	477	441	125
175°	459	462	459	462	459	44
180°	459	459	459	459	459	

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1
2.5°	2694.8	2694.8	2710.0	2715.0	2715.0	2707.4	2699.9	2707.4	2730.2	2737.8	2735.2
5°	2684.7	2704.9	2732.7	2737.8	2742.9	2740.3	2735.2	2740.3	2765.6	2770.7	2773.2
7.5°	2664.5	2702.3	2737.8	2745.4	2752.9	2745.4	2742.9	2747.9	2773.2	2778.2	2778.2
10°	2639.2	2692.3	2732.7	2737.8	2745.4	2737.8	2737.8	2747.9	2773.2	2778.2	2780.7
12.5°	2603.8	2677.1	2715.0	2720.1	2730.2	2727.6	2725.2	2735.2	2760.5	2765.6	2765.6
15°	2563.4	2649.3	2684.7	2689.8	2707.4	2702.3	2702.3	2712.5	2740.3	2747.9	2745.4
17.5°	2507.7	2613.9	2654.3	2661.9	2674.6	2672.1	2674.6	2684.7	2710.0	2715.0	2717.6
20°	2444.6	2565.9	2613.9	2621.5	2634.1	2634.1	2634.1	2646.8	2672.1	2682.1	2682.1
22.5°	2358.6	2515.3	2565.9	2571.0	2586.1	2586.1	2591.2	2608.8	2631.6	2634.1	2634.1
25°	2257.4	2459.7	2502.6	2517.9	2533.0	2540.6	2548.2	2558.3	2565.9	2563.4	2565.9
27.5°	2151.3	2388.9	2444.6	2454.6	2474.9	2482.4	2492.6	2495.1	2497.7	2505.2	2500.2
30°	2032.4	2290.3	2373.8	2383.8	2416.7	2421.8	2411.7	2416.7	2429.3	2434.4	2439.5
32.5°	1898.5	2143.7	2300.5	2323.2	2353.5	2338.4	2335.8	2343.4	2363.6	2363.6	2368.7
35°	1716.5	2029.9	2232.2	2252.5	2275.2	2257.4	2267.6	2270.1	2282.7	2290.3	2287.8
37.5°	1516.8	1931.3	2161.4	2176.6	2194.3	2171.5	2186.7	2194.3	2204.3	2199.4	2199.4
40°	1339.8	1777.2	2078.0	2088.1	2103.3	2085.5	2100.8	2105.8	2110.8	2105.8	2103.3
42.5°	1208.3	1607.7	1989.5	2002.2	1992.0	2004.6	2009.7	2019.9	2012.2	2002.2	2002.2
45°	1107.3	1562.3	1893.4	1908.6	1893.4	1913.7	1921.3	1921.3	1898.5	1893.4	1890.9
47.5°	1074.4	1471.3	1797.4	1797.4	1789.8	1815.1	1827.8	1810.0	1787.2	1779.7	1779.7
50°	1071.9	1370.2	1665.9	1655.8	1691.2	1721.6	1708.9	1691.2	1673.5	1645.7	1645.7
52.5°	973.3	1246.3	1496.6	1534.4	1590.1	1607.7	1587.5	1569.9	1539.5	1526.9	1516.8
55°	902.5	1117.3	1342.3	1418.2	1476.4	1499.1	1461.1	1443.5	1398.0	1390.4	1385.3
57.5°	887.3	930.3	1200.8	1296.9	1367.6	1365.1	1342.3	1309.4	1271.6	1264.0	1261.4
60°	814.0	672.4	1049.1	1162.8	1236.1	1228.6	1208.3	1178.1	1142.6	1137.6	1132.6
62.5°	738.1	487.9	877.2	1006.2	1109.7	1107.3	1089.5	1044.0	1018.8	1006.2	996.0
65°	627.0	409.6	624.4	836.7	985.9	990.9	953.1	920.2	892.4	877.2	874.7
67.5°	477.8	333.7	422.2	697.7	867.1	862.0	814.0	798.8	763.4	755.9	740.7
70°	353.9	222.5	293.2	566.2	750.8	738.1	700.3	682.6	649.7	632.0	621.9
72.5°	293.2	179.5	214.8	439.8	632.0	616.8	584.0	563.7	535.9	520.8	510.6
75°	237.6	189.6	164.3	326.1	513.1	503.1	472.7	452.5	429.8	409.6	412.0
77.5°	174.4	177.0	131.5	240.1	407.0	391.8	374.1	348.9	338.7	318.5	318.5
80°	131.5	139.0	98.6	164.3	293.2	293.2	278.1	260.4	242.7	232.6	232.6
82.5°	88.4	88.4	73.3	103.7	199.7	192.1	182.0	177.0	166.8	161.8	161.8
85°	40.4	50.6	45.5	63.2	108.7	113.7	113.7	108.7	106.2	101.1	103.7
87.5°	12.6	22.7	27.8	35.4	55.6	58.2	60.7	60.7	60.7	63.2	63.2
90°	3.1	5.6	8.1	8.7	13.5	20.1	23.4	20.8	15.5	11.7	11.7
92.5°	12.4	33.3	54.2	59.5	83.6	115.7	131.8	115.4	82.9	58.5	56.2
95°	29.6	67.8	106.2	115.7	205.6	325.4	385.3	343.8	260.9	198.6	191.5
97.5°	51.1	85.0	118.7	127.2	277.0	476.7	576.5	550.3	497.8	458.5	445.0
100°	67.7	98.4	129.1	136.8	302.9	524.5	635.2	637.1	641.0	643.9	628.0
102.5°	81.9	110.6	139.1	146.3	314.8	539.5	651.9	685.2	752.1	802.2	788.5
105°	106.0	130.2	154.4	160.5	323.6	541.2	650.0	724.9	874.6	986.9	979.6
107.5°	130.6	153.2	175.7	181.4	325.3	517.1	613.0	717.4	926.3	1083.0	1084.7
110°	147.2	167.5	187.9	193.0	322.8	495.8	582.3	699.0	932.6	1107.7	1115.3

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	163.5	183.0	202.4	207.3	322.9	477.2	554.3	673.8	912.7	1091.9	1103.7
115°	188.1	206.1	224.0	228.5	325.9	455.8	520.7	635.8	866.0	1038.6	1055.0
117.5°	212.4	228.8	245.0	249.1	332.0	442.4	497.6	601.5	809.2	965.0	983.2
120°	226.6	241.9	257.3	261.2	336.8	437.8	488.3	583.3	773.1	915.4	933.1
122.5°	240.5	256.0	271.4	275.3	343.9	435.5	481.3	566.7	737.7	865.9	883.3
125°	261.7	275.8	289.9	293.4	353.5	433.6	473.6	546.2	691.4	800.3	816.2
127.5°	279.0	293.2	307.5	311.1	363.0	432.5	467.1	529.5	654.1	747.6	761.0
130°	288.2	303.6	318.9	322.7	370.0	433.1	464.6	520.1	631.2	714.4	726.9
132.5°	297.8	313.1	328.5	332.3	375.7	433.6	462.5	512.2	611.5	686.0	697.2
135°	311.9	325.9	339.8	343.3	381.9	433.2	458.9	500.5	583.7	646.0	655.7
137.5°	326.4	340.2	354.0	357.5	391.0	435.8	458.2	493.3	563.6	616.4	624.3
140°	338.4	351.2	363.8	367.0	396.7	436.2	456.1	486.4	547.2	592.7	600.1
142.5°	347.6	359.4	371.1	374.1	401.4	437.8	456.1	482.8	536.0	576.1	582.5
145°	361.8	372.1	382.4	385.0	407.7	437.8	453.0	474.8	518.4	551.2	556.0
147.5°	376.0	386.0	396.0	398.5	416.6	440.8	453.0	470.1	504.5	530.3	534.3
150°	385.3	394.3	403.3	405.6	421.4	442.4	453.0	467.5	496.5	518.2	521.4
152.5°	394.7	401.6	408.5	410.2	424.4	443.4	453.0	465.3	490.1	508.7	511.0
155°	409.0	414.0	419.0	420.3	431.2	445.7	453.0	462.8	482.6	497.3	498.9
157.5°	419.4	424.3	429.3	430.5	437.9	448.0	453.0	460.6	476.0	487.4	488.5
160°	426.5	430.3	434.1	435.1	441.0	449.0	453.0	459.6	472.7	482.6	483.2
162.5°	433.6	436.4	439.3	440.0	444.3	450.1	453.0	458.6	469.6	477.9	478.5
165°	441.2	443.8	446.4	447.1	449.1	451.7	453.0	457.0	464.8	470.8	471.5
167.5°	448.3	449.5	450.8	451.1	452.8	455.0	456.1	458.7	463.8	467.7	468.0
170°	453.0	454.2	455.5	455.8	455.9	456.0	456.1	458.7	463.8	467.7	467.7
172.5°	455.5	455.8	456.0	456.1	456.1	456.1	456.1	458.1	462.1	465.2	465.0
175°	458.9	458.9	458.9	458.9	458.0	456.7	456.1	457.4	460.0	461.8	461.8
177.5°	458.9	458.9	458.9	458.9	458.2	457.2	456.7	457.7	459.8	461.2	460.9
180°	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
0°	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1
2.5°	2740.3	2732.7	2740.3	2735.2	2737.8	2730.2	2707.4	2699.9	2707.4	2715.0	2715.0
5°	2773.2	2768.1	2773.2	2773.2	2770.7	2765.6	2740.3	2735.2	2740.3	2742.9	2737.8
7.5°	2783.3	2775.8	2783.3	2778.2	2778.2	2773.2	2747.9	2742.9	2745.4	2752.9	2745.4
10°	2783.3	2775.8	2783.3	2780.7	2778.2	2773.2	2747.9	2737.8	2737.8	2745.4	2737.8
12.5°	2770.7	2765.6	2770.7	2765.6	2765.6	2760.5	2735.2	2725.2	2727.6	2730.2	2720.1
15°	2750.5	2742.9	2750.5	2745.4	2747.9	2740.3	2712.5	2702.3	2702.3	2707.4	2689.8
17.5°	2720.1	2710.0	2720.1	2717.6	2715.0	2710.0	2684.7	2674.6	2672.1	2674.6	2661.9
20°	2684.7	2677.1	2684.7	2682.1	2682.1	2672.1	2646.8	2634.1	2634.1	2634.1	2621.5
22.5°	2629.0	2621.5	2629.0	2634.1	2634.1	2631.6	2608.8	2591.2	2586.1	2586.1	2571.0
25°	2565.9	2558.3	2565.9	2565.9	2563.4	2565.9	2558.3	2548.2	2540.6	2533.0	2517.9
27.5°	2505.2	2500.2	2505.2	2500.2	2505.2	2497.7	2495.1	2492.6	2482.4	2474.9	2454.6
30°	2444.6	2439.5	2444.6	2439.5	2434.4	2429.3	2416.7	2411.7	2421.8	2416.7	2383.8
32.5°	2368.7	2363.6	2368.7	2368.7	2363.6	2363.6	2343.4	2335.8	2338.4	2353.5	2323.2
35°	2290.3	2282.7	2290.3	2287.8	2290.3	2282.7	2270.1	2267.6	2257.4	2275.2	2252.5
37.5°	2199.4	2191.7	2199.4	2199.4	2199.4	2204.3	2194.3	2186.7	2171.5	2194.3	2176.6
40°	2105.8	2095.7	2105.8	2103.3	2105.8	2110.8	2105.8	2100.8	2085.5	2103.3	2088.1
42.5°	1999.7	1997.1	1999.7	2002.2	2002.2	2012.2	2019.9	2009.7	2004.6	1992.0	2002.2
45°	1885.8	1880.8	1885.8	1890.9	1893.4	1898.5	1921.3	1921.3	1913.7	1893.4	1908.6
47.5°	1764.5	1751.9	1764.5	1779.7	1779.7	1787.2	1810.0	1827.8	1815.1	1789.8	1797.4
50°	1635.6	1638.1	1635.6	1645.7	1645.7	1673.5	1691.2	1708.9	1721.6	1691.2	1655.8
52.5°	1509.2	1506.6	1509.2	1516.8	1526.9	1539.5	1569.9	1587.5	1607.7	1590.1	1534.4
55°	1382.7	1387.8	1382.7	1385.3	1390.4	1398.0	1443.5	1461.1	1499.1	1476.4	1418.2
57.5°	1256.4	1248.8	1256.4	1261.4	1264.0	1271.6	1309.4	1342.3	1365.1	1367.6	1296.9
60°	1109.7	1099.7	1109.7	1132.6	1137.6	1142.6	1178.1	1208.3	1228.6	1236.1	1162.8
62.5°	980.9	963.1	980.9	996.0	1006.2	1018.8	1044.0	1089.5	1107.3	1109.7	1006.2
65°	844.3	836.7	844.3	874.7	877.2	892.4	920.2	953.1	990.9	985.9	836.7
67.5°	720.5	720.5	720.5	740.7	755.9	763.4	798.8	814.0	862.0	867.1	697.7
70°	606.7	604.2	606.7	621.9	632.0	649.7	682.6	700.3	738.1	750.8	566.2
72.5°	498.0	495.5	498.0	510.6	520.8	535.9	563.7	584.0	616.8	632.0	439.8
75°	402.0	396.9	402.0	412.0	409.6	429.8	452.5	472.7	503.1	513.1	326.1
77.5°	308.5	308.5	308.5	318.5	318.5	338.7	348.9	374.1	391.8	407.0	240.1
80°	230.1	227.5	230.1	232.6	232.6	242.7	260.4	278.1	293.2	293.2	164.3
82.5°	161.8	156.8	161.8	161.8	161.8	166.8	177.0	182.0	192.1	199.7	103.7
85°	101.1	101.1	101.1	103.7	101.1	106.2	108.7	113.7	113.7	108.7	63.2
87.5°	65.7	63.2	65.7	63.2	63.2	60.7	60.7	60.7	58.2	55.6	35.4
90°	11.7	11.7	11.7	11.7	11.7	15.5	20.8	23.4	20.1	13.5	8.7
92.5°	46.8	37.5	46.8	56.2	58.5	82.9	115.4	131.8	115.7	83.6	59.5
95°	163.3	135.2	163.3	191.5	198.6	260.9	343.8	385.3	325.4	205.6	115.7
97.5°	391.4	337.8	391.4	445.0	458.5	497.8	550.3	576.5	476.7	277.0	127.2
100°	564.0	500.1	564.0	628.0	643.9	641.0	637.1	635.2	524.5	302.9	136.8
102.5°	733.8	679.0	733.8	788.5	802.2	752.1	685.2	651.9	539.5	314.8	146.3
105°	950.2	920.7	950.2	979.6	986.9	874.6	724.9	650.0	541.2	323.6	160.5
107.5°	1091.8	1099.0	1091.8	1084.7	1083.0	926.3	717.4	613.0	517.1	325.3	181.4
110°	1145.9	1176.6	1145.9	1115.3	1107.7	932.6	699.0	582.3	495.8	322.8	193.0



TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
112.5°	1150.8	1197.8	1150.8	1103.7	1091.9	912.7	673.8	554.3	477.2	322.9	207.3
115°	1120.2	1185.5	1120.2	1055.0	1038.6	866.0	635.8	520.7	455.8	325.9	228.5
117.5°	1055.6	1128.0	1055.6	983.2	965.0	809.2	601.5	497.6	442.4	332.0	249.1
120°	1003.4	1073.8	1003.4	933.1	915.4	773.1	583.3	488.3	437.8	336.8	261.2
122.5°	952.7	1022.0	952.7	883.3	865.9	737.7	566.7	481.3	435.5	343.9	275.3
125°	880.2	944.1	880.2	816.2	800.3	691.4	546.2	473.6	433.6	353.5	293.4
127.5°	815.0	869.0	815.0	761.0	747.6	654.1	529.5	467.1	432.5	363.0	311.1
130°	776.7	826.5	776.7	726.9	714.4	631.2	520.1	464.6	433.1	370.0	322.7
132.5°	741.8	786.4	741.8	697.2	686.0	611.5	512.2	462.5	433.6	375.7	332.3
135°	694.1	732.6	694.1	655.7	646.0	583.7	500.5	458.9	433.2	381.9	343.3
137.5°	655.9	687.3	655.9	624.3	616.4	563.6	493.3	458.2	435.8	391.0	357.5
140°	629.5	659.0	629.5	600.1	592.7	547.2	486.4	456.1	436.2	396.7	367.0
142.5°	607.8	633.1	607.8	582.5	576.1	536.0	482.8	456.1	437.8	401.4	374.1
145°	575.2	594.3	575.2	556.0	551.2	518.4	474.8	453.0	437.8	407.7	385.0
147.5°	550.1	565.9	550.1	534.3	530.3	504.5	470.1	453.0	440.8	416.6	398.5
150°	534.4	547.2	534.4	521.4	518.2	496.5	467.5	453.0	442.4	421.4	405.6
152.5°	520.8	530.6	520.8	511.0	508.7	490.1	465.3	453.0	443.4	424.4	410.2
155°	505.4	511.7	505.4	498.9	497.3	482.6	462.8	453.0	445.7	431.2	420.3
157.5°	493.1	497.6	493.1	488.5	487.4	476.0	460.6	453.0	448.0	437.9	430.5
160°	485.7	488.3	485.7	483.2	482.6	472.7	459.6	453.0	449.0	441.0	435.1
162.5°	481.0	483.5	481.0	478.5	477.9	469.6	458.6	453.0	450.1	444.3	440.0
165°	474.1	476.7	474.1	471.5	470.8	464.8	457.0	453.0	451.7	449.1	447.1
167.5°	469.1	470.2	469.1	468.0	467.7	463.8	458.7	456.1	455.0	452.8	451.1
170°	467.7	467.7	467.7	467.7	467.7	463.8	458.7	456.1	456.0	455.9	455.8
172.5°	464.0	463.1	464.0	465.0	465.2	462.1	458.1	456.1	456.1	456.1	456.1
175°	461.8	461.8	461.8	461.8	461.8	460.0	457.4	456.1	456.7	458.0	458.9
177.5°	460.0	458.9	460.0	460.9	461.2	459.8	457.7	456.7	457.2	458.2	458.9
180°	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
0°	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1
2.5°	2710.0	2694.8	2694.8	2669.6	2659.4	2651.8	2639.2	2601.3	2591.2	2581.0	2596.2
5°	2732.7	2704.9	2684.7	2639.2	2601.3	2586.1	2538.1	2447.1	2386.4	2340.9	2315.6
7.5°	2737.8	2702.3	2664.5	2593.7	2502.6	2462.2	2315.6	2148.8	2103.3	2062.8	2037.5
10°	2732.7	2692.3	2639.2	2533.0	2318.2	2247.4	2100.8	1992.0	1964.2	1956.6	1964.2
12.5°	2715.0	2677.1	2603.8	2426.9	2126.1	2078.0	1992.0	1928.9	1923.8	1936.4	2004.6
15°	2684.7	2649.3	2563.4	2285.3	2019.9	1984.4	1923.8	1901.1	1928.9	2017.3	2222.1
17.5°	2654.3	2613.9	2507.7	2146.3	1938.9	1913.7	1870.7	1916.2	2073.0	2191.7	2260.0
20°	2613.9	2565.9	2444.6	2045.1	1880.8	1858.0	1837.8	2042.6	2161.4	2204.3	2242.3
22.5°	2565.9	2515.3	2358.6	1974.4	1820.1	1802.5	1815.1	2113.4	2161.4	2191.7	2224.6
25°	2502.6	2459.7	2257.4	1918.7	1772.1	1751.9	1799.9	2105.8	2133.6	2141.2	2206.9
27.5°	2444.6	2388.9	2151.3	1868.2	1713.9	1706.3	1812.5	2073.0	2093.2	2100.8	2171.5
30°	2373.8	2290.3	2032.4	1815.1	1653.3	1650.8	1815.1	2032.4	2027.5	2047.7	2118.4
32.5°	2300.5	2143.7	1898.5	1749.4	1595.2	1592.6	1797.4	1971.8	1966.8	1994.6	2047.7
35°	2232.2	2029.9	1716.5	1673.5	1521.8	1524.4	1754.5	1901.1	1903.6	1928.9	1961.7
37.5°	2161.4	1931.3	1516.8	1590.1	1451.1	1451.1	1696.3	1835.3	1830.2	1837.8	1883.3
40°	2078.0	1777.2	1339.8	1481.4	1385.3	1377.8	1625.5	1764.5	1746.8	1744.3	1807.5
42.5°	1989.5	1607.7	1208.3	1337.3	1309.4	1299.4	1539.5	1678.6	1645.7	1653.3	1734.1
45°	1893.4	1562.3	1107.3	1130.0	1231.2	1223.5	1446.0	1580.0	1557.2	1577.5	1660.8
47.5°	1797.4	1471.3	1074.4	937.8	1147.7	1145.2	1342.3	1483.9	1471.3	1491.5	1580.0
50°	1665.9	1370.2	1071.9	803.9	1054.2	1064.2	1218.5	1390.4	1390.4	1408.0	1501.6
52.5°	1496.6	1246.3	973.3	728.1	945.5	975.8	1109.7	1309.4	1314.5	1332.2	1415.6
55°	1342.3	1117.3	902.5	669.9	816.5	882.3	1003.6	1226.1	1236.1	1253.9	1329.7
57.5°	1200.8	930.3	887.3	601.7	697.7	760.9	910.0	1145.2	1150.2	1165.4	1238.7
60°	1049.1	672.4	814.0	528.4	594.1	642.1	824.1	1049.1	1066.8	1076.9	1140.1
62.5°	877.2	487.9	738.1	477.8	543.5	553.6	753.4	958.1	980.9	988.4	1026.4
65°	624.4	409.6	627.0	434.9	490.4	492.9	677.5	864.5	884.7	897.4	925.3
67.5°	422.2	333.7	477.8	394.3	450.0	452.5	604.2	755.9	783.7	793.8	811.4
70°	293.2	222.5	353.9	351.4	404.5	409.6	525.8	657.3	682.6	690.1	700.3
72.5°	214.8	179.5	293.2	316.0	356.5	361.5	444.9	546.0	571.3	578.9	584.0
75°	164.3	189.6	237.6	275.6	303.4	305.9	364.0	444.9	462.6	467.7	470.2
77.5°	131.5	177.0	174.4	222.5	247.7	242.7	285.7	343.8	359.0	359.0	359.0
80°	98.6	139.0	131.5	159.3	182.0	177.0	204.8	245.2	250.3	255.3	252.8
82.5°	73.3	88.4	88.4	101.1	121.3	116.3	136.6	159.3	159.3	159.3	164.3
85°	45.5	50.6	40.4	53.1	68.2	65.7	75.8	86.0	88.4	88.4	83.5
87.5°	27.8	22.7	12.6	20.2	30.4	30.4	35.4	37.9	35.4	35.4	35.4
90°	8.1	5.6	3.1	5.6	8.1	8.7	13.5	20.1	23.4	20.8	15.5
92.5°	54.2	33.3	12.4	33.3	54.2	59.5	83.6	115.7	131.8	115.4	82.9
95°	106.2	67.8	29.6	67.8	106.2	115.7	205.6	325.4	385.3	343.8	260.9
97.5°	118.7	85.0	51.1	85.0	118.7	127.2	277.0	476.7	576.5	550.3	497.8
100°	129.1	98.4	67.7	98.4	129.1	136.8	302.9	524.5	635.2	637.1	641.0
102.5°	139.1	110.6	81.9	110.6	139.1	146.3	314.8	539.5	651.9	685.2	752.1
105°	154.4	130.2	106.0	130.2	154.4	160.5	323.6	541.2	650.0	724.9	874.6
107.5°	175.7	153.2	130.6	153.2	175.7	181.4	325.3	517.1	613.0	717.4	926.3
110°	187.9	167.5	147.2	167.5	187.9	193.0	322.8	495.8	582.3	699.0	932.6

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
112.5°	202.4	183.0	163.5	183.0	202.4	207.3	322.9	477.2	554.3	673.8	912.7
115°	224.0	206.1	188.1	206.1	224.0	228.5	325.9	455.8	520.7	635.8	866.0
117.5°	245.0	228.8	212.4	228.8	245.0	249.1	332.0	442.4	497.6	601.5	809.2
120°	257.3	241.9	226.6	241.9	257.3	261.2	336.8	437.8	488.3	583.3	773.1
122.5°	271.4	256.0	240.5	256.0	271.4	275.3	343.9	435.5	481.3	566.7	737.7
125°	289.9	275.8	261.7	275.8	289.9	293.4	353.5	433.6	473.6	546.2	691.4
127.5°	307.5	293.2	279.0	293.2	307.5	311.1	363.0	432.5	467.1	529.5	654.1
130°	318.9	303.6	288.2	303.6	318.9	322.7	370.0	433.1	464.6	520.1	631.2
132.5°	328.5	313.1	297.8	313.1	328.5	332.3	375.7	433.6	462.5	512.2	611.5
135°	339.8	325.9	311.9	325.9	339.8	343.3	381.9	433.2	458.9	500.5	583.7
137.5°	354.0	340.2	326.4	340.2	354.0	357.5	391.0	435.8	458.2	493.3	563.6
140°	363.8	351.2	338.4	351.2	363.8	367.0	396.7	436.2	456.1	486.4	547.2
142.5°	371.1	359.4	347.6	359.4	371.1	374.1	401.4	437.8	456.1	482.8	536.0
145°	382.4	372.1	361.8	372.1	382.4	385.0	407.7	437.8	453.0	474.8	518.4
147.5°	396.0	386.0	376.0	386.0	396.0	398.5	416.6	440.8	453.0	470.1	504.5
150°	403.3	394.3	385.3	394.3	403.3	405.6	421.4	442.4	453.0	467.5	496.5
152.5°	408.5	401.6	394.7	401.6	408.5	410.2	424.4	443.4	453.0	465.3	490.1
155°	419.0	414.0	409.0	414.0	419.0	420.3	431.2	445.7	453.0	462.8	482.6
157.5°	429.3	424.3	419.4	424.3	429.3	430.5	437.9	448.0	453.0	460.6	476.0
160°	434.1	430.3	426.5	430.3	434.1	435.1	441.0	449.0	453.0	459.6	472.7
162.5°	439.3	436.4	433.6	436.4	439.3	440.0	444.3	450.1	453.0	458.6	469.6
165°	446.4	443.8	441.2	443.8	446.4	447.1	449.1	451.7	453.0	457.0	464.8
167.5°	450.8	449.5	448.3	449.5	450.8	451.1	452.8	455.0	456.1	458.7	463.8
170°	455.5	454.2	453.0	454.2	455.5	455.8	455.9	456.0	456.1	458.7	463.8
172.5°	456.0	455.8	455.5	455.8	456.0	456.1	456.1	456.1	456.1	458.1	462.1
175°	458.9	458.9	458.9	458.9	458.9	458.9	458.0	456.7	456.1	457.4	460.0
177.5°	458.9	458.9	458.9	458.9	458.9	458.9	458.2	457.2	456.7	457.7	459.8
180°	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
0°	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1	2672.1
2.5°	2578.5	2571.0	2581.0	2553.2	2581.0	2571.0	2578.5	2596.2	2581.0	2591.2	2601.3
5°	2262.5	2249.9	2209.4	2176.6	2209.4	2249.9	2262.5	2315.6	2340.9	2386.4	2447.1
7.5°	2022.4	2012.2	2002.2	1981.9	2002.2	2012.2	2022.4	2037.5	2062.8	2103.3	2148.8
10°	1969.3	1971.8	1987.0	1984.4	1987.0	1971.8	1969.3	1964.2	1956.6	1964.2	1992.0
12.5°	2105.8	2128.6	2212.0	2206.9	2212.0	2128.6	2105.8	2004.6	1936.4	1923.8	1928.9
15°	2262.5	2270.1	2287.8	2290.3	2287.8	2270.1	2262.5	2222.1	2017.3	1928.9	1901.1
17.5°	2277.7	2280.2	2292.9	2292.9	2292.9	2280.2	2277.7	2260.0	2191.7	2073.0	1916.2
20°	2265.1	2270.1	2295.4	2300.5	2295.4	2270.1	2265.1	2242.3	2204.3	2161.4	2042.6
22.5°	2260.0	2270.1	2290.3	2287.8	2290.3	2270.1	2260.0	2224.6	2191.7	2161.4	2113.4
25°	2234.7	2234.7	2237.2	2239.8	2237.2	2234.7	2234.7	2206.9	2141.2	2133.6	2105.8
27.5°	2181.6	2186.7	2201.9	2199.4	2201.9	2186.7	2181.6	2171.5	2100.8	2093.2	2073.0
30°	2133.6	2128.6	2115.9	2105.8	2115.9	2128.6	2133.6	2118.4	2047.7	2027.5	2032.4
32.5°	2052.8	2040.1	2027.5	2019.9	2027.5	2040.1	2052.8	2047.7	1994.6	1966.8	1971.8
35°	1956.6	1959.1	1956.6	1949.1	1956.6	1959.1	1956.6	1961.7	1928.9	1903.6	1901.1
37.5°	1888.4	1893.4	1890.9	1880.8	1890.9	1893.4	1888.4	1883.3	1837.8	1830.2	1835.3
40°	1817.6	1820.1	1817.6	1810.0	1817.6	1820.1	1817.6	1807.5	1744.3	1746.8	1764.5
42.5°	1749.4	1746.8	1739.2	1734.1	1739.2	1746.8	1749.4	1734.1	1653.3	1645.7	1678.6
45°	1671.0	1673.5	1658.3	1650.8	1658.3	1673.5	1671.0	1660.8	1577.5	1557.2	1580.0
47.5°	1592.6	1592.6	1580.0	1572.4	1580.0	1592.6	1592.6	1580.0	1491.5	1471.3	1483.9
50°	1509.2	1506.6	1489.0	1486.4	1489.0	1506.6	1509.2	1501.6	1408.0	1390.4	1390.4
52.5°	1413.1	1413.1	1415.6	1420.7	1415.6	1413.1	1413.1	1415.6	1332.2	1314.5	1309.4
55°	1329.7	1332.2	1350.0	1355.0	1350.0	1332.2	1329.7	1329.7	1253.9	1236.1	1226.1
57.5°	1243.8	1243.8	1256.4	1256.4	1256.4	1243.8	1243.8	1238.7	1165.4	1150.2	1145.2
60°	1145.2	1150.2	1160.3	1157.8	1160.3	1150.2	1145.2	1140.1	1076.9	1066.8	1049.1
62.5°	1041.5	1046.6	1049.1	1044.0	1049.1	1046.6	1041.5	1026.4	988.4	980.9	958.1
65°	932.9	937.8	940.4	935.3	940.4	937.8	932.9	925.3	897.4	884.7	864.5
67.5°	821.6	819.0	816.5	826.7	816.5	819.0	821.6	811.4	793.8	783.7	755.9
70°	707.9	707.9	705.3	710.3	705.3	707.9	707.9	700.3	690.1	682.6	657.3
72.5°	586.4	584.0	594.1	586.4	594.1	584.0	586.4	584.0	578.9	571.3	546.0
75°	467.7	472.7	467.7	475.3	467.7	472.7	467.7	470.2	467.7	462.6	444.9
77.5°	356.5	361.5	356.5	356.5	356.5	361.5	356.5	359.0	359.0	359.0	343.8
80°	252.8	250.3	250.3	247.7	250.3	250.3	252.8	252.8	255.3	250.3	245.2
82.5°	161.8	159.3	159.3	164.3	159.3	159.3	161.8	164.3	159.3	159.3	159.3
85°	88.4	91.0	86.0	86.0	86.0	91.0	88.4	83.5	88.4	88.4	86.0
87.5°	32.9	30.4	30.4	30.4	30.4	30.4	32.9	35.4	35.4	35.4	37.9
90°	11.7	11.7	11.7	11.7	11.7	11.7	11.7	15.5	20.8	23.4	20.1
92.5°	58.5	56.2	46.8	37.5	46.8	56.2	58.5	82.9	115.4	131.8	115.7
95°	198.6	191.5	163.3	135.2	163.3	191.5	198.6	260.9	343.8	385.3	325.4
97.5°	458.5	445.0	391.4	337.8	391.4	445.0	458.5	497.8	550.3	576.5	476.7
100°	643.9	628.0	564.0	500.1	564.0	628.0	643.9	641.0	637.1	635.2	524.5
102.5°	802.2	788.5	733.8	679.0	733.8	788.5	802.2	752.1	685.2	651.9	539.5
105°	986.9	979.6	950.2	920.7	950.2	979.6	986.9	874.6	724.9	650.0	541.2
107.5°	1083.0	1084.7	1091.8	1099.0	1091.8	1084.7	1083.0	926.3	717.4	613.0	517.1
110°	1107.7	1115.3	1145.9	1176.6	1145.9	1115.3	1107.7	932.6	699.0	582.3	495.8

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
112.5°	1091.9	1103.7	1150.8	1197.8	1150.8	1103.7	1091.9	912.7	673.8	554.3	477.2
115°	1038.6	1055.0	1120.2	1185.5	1120.2	1055.0	1038.6	866.0	635.8	520.7	455.8
117.5°	965.0	983.2	1055.6	1128.0	1055.6	983.2	965.0	809.2	601.5	497.6	442.4
120°	915.4	933.1	1003.4	1073.8	1003.4	933.1	915.4	773.1	583.3	488.3	437.8
122.5°	865.9	883.3	952.7	1022.0	952.7	883.3	865.9	737.7	566.7	481.3	435.5
125°	800.3	816.2	880.2	944.1	880.2	816.2	800.3	691.4	546.2	473.6	433.6
127.5°	747.6	761.0	815.0	869.0	815.0	761.0	747.6	654.1	529.5	467.1	432.5
130°	714.4	726.9	776.7	826.5	776.7	726.9	714.4	631.2	520.1	464.6	433.1
132.5°	686.0	697.2	741.8	786.4	741.8	697.2	686.0	611.5	512.2	462.5	433.6
135°	646.0	655.7	694.1	732.6	694.1	655.7	646.0	583.7	500.5	458.9	433.2
137.5°	616.4	624.3	655.9	687.3	655.9	624.3	616.4	563.6	493.3	458.2	435.8
140°	592.7	600.1	629.5	659.0	629.5	600.1	592.7	547.2	486.4	456.1	436.2
142.5°	576.1	582.5	607.8	633.1	607.8	582.5	576.1	536.0	482.8	456.1	437.8
145°	551.2	556.0	575.2	594.3	575.2	556.0	551.2	518.4	474.8	453.0	437.8
147.5°	530.3	534.3	550.1	565.9	550.1	534.3	530.3	504.5	470.1	453.0	440.8
150°	518.2	521.4	534.4	547.2	534.4	521.4	518.2	496.5	467.5	453.0	442.4
152.5°	508.7	511.0	520.8	530.6	520.8	511.0	508.7	490.1	465.3	453.0	443.4
155°	497.3	498.9	505.4	511.7	505.4	498.9	497.3	482.6	462.8	453.0	445.7
157.5°	487.4	488.5	493.1	497.6	493.1	488.5	487.4	476.0	460.6	453.0	448.0
160°	482.6	483.2	485.7	488.3	485.7	483.2	482.6	472.7	459.6	453.0	449.0
162.5°	477.9	478.5	481.0	483.5	481.0	478.5	477.9	469.6	458.6	453.0	450.1
165°	470.8	471.5	474.1	476.7	474.1	471.5	470.8	464.8	457.0	453.0	451.7
167.5°	467.7	468.0	469.1	470.2	469.1	468.0	467.7	463.8	458.7	456.1	455.0
170°	467.7	467.7	467.7	467.7	467.7	467.7	467.7	463.8	458.7	456.1	456.0
172.5°	465.2	465.0	464.0	463.1	464.0	465.0	465.2	462.1	458.1	456.1	456.1
175°	461.8	461.8	461.8	461.8	461.8	461.8	461.8	460.0	457.4	456.1	456.7
177.5°	461.2	460.9	460.0	458.9	460.0	460.9	461.2	459.8	457.7	456.7	457.2
180°	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9	458.9

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
0°	2672.1	2672.1	2672.1	2672.1	2672.1
2.5°	2639.2	2651.8	2659.4	2669.6	2694.8
5°	2538.1	2586.1	2601.3	2639.2	2684.7
7.5°	2315.6	2462.2	2502.6	2593.7	2664.5
10°	2100.8	2247.4	2318.2	2533.0	2639.2
12.5°	1992.0	2078.0	2126.1	2426.9	2603.8
15°	1923.8	1984.4	2019.9	2285.3	2563.4
17.5°	1870.7	1913.7	1938.9	2146.3	2507.7
20°	1837.8	1858.0	1880.8	2045.1	2444.6
22.5°	1815.1	1802.5	1820.1	1974.4	2358.6
25°	1799.9	1751.9	1772.1	1918.7	2257.4
27.5°	1812.5	1706.3	1713.9	1868.2	2151.3
30°	1815.1	1650.8	1653.3	1815.1	2032.4
32.5°	1797.4	1592.6	1595.2	1749.4	1898.5
35°	1754.5	1524.4	1521.8	1673.5	1716.5
37.5°	1696.3	1451.1	1451.1	1590.1	1516.8
40°	1625.5	1377.8	1385.3	1481.4	1339.8
42.5°	1539.5	1299.4	1309.4	1337.3	1208.3
45°	1446.0	1223.5	1231.2	1130.0	1107.3
47.5°	1342.3	1145.2	1147.7	937.8	1074.4
50°	1218.5	1064.2	1054.2	803.9	1071.9
52.5°	1109.7	975.8	945.5	728.1	973.3
55°	1003.6	882.3	816.5	669.9	902.5
57.5°	910.0	760.9	697.7	601.7	887.3
60°	824.1	642.1	594.1	528.4	814.0
62.5°	753.4	553.6	543.5	477.8	738.1
65°	677.5	492.9	490.4	434.9	627.0
67.5°	604.2	452.5	450.0	394.3	477.8
70°	525.8	409.6	404.5	351.4	353.9
72.5°	444.9	361.5	356.5	316.0	293.2
75°	364.0	305.9	303.4	275.6	237.6
77.5°	285.7	242.7	247.7	222.5	174.4
80°	204.8	177.0	182.0	159.3	131.5
82.5°	136.6	116.3	121.3	101.1	88.4
85°	75.8	65.7	68.2	53.1	40.4
87.5°	35.4	30.4	30.4	20.2	12.6
90°	13.5	8.7	8.1	5.6	3.1
92.5°	83.6	59.5	54.2	33.3	12.4
95°	205.6	115.7	106.2	67.8	29.6
97.5°	277.0	127.2	118.7	85.0	51.1
100°	302.9	136.8	129.1	98.4	67.7
102.5°	314.8	146.3	139.1	110.6	81.9
105°	323.6	160.5	154.4	130.2	106.0
107.5°	325.3	181.4	175.7	153.2	130.6
110°	322.8	193.0	187.9	167.5	147.2

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
112.5°	322.9	207.3	202.4	183.0	163.5
115°	325.9	228.5	224.0	206.1	188.1
117.5°	332.0	249.1	245.0	228.8	212.4
120°	336.8	261.2	257.3	241.9	226.6
122.5°	343.9	275.3	271.4	256.0	240.5
125°	353.5	293.4	289.9	275.8	261.7
127.5°	363.0	311.1	307.5	293.2	279.0
130°	370.0	322.7	318.9	303.6	288.2
132.5°	375.7	332.3	328.5	313.1	297.8
135°	381.9	343.3	339.8	325.9	311.9
137.5°	391.0	357.5	354.0	340.2	326.4
140°	396.7	367.0	363.8	351.2	338.4
142.5°	401.4	374.1	371.1	359.4	347.6
145°	407.7	385.0	382.4	372.1	361.8
147.5°	416.6	398.5	396.0	386.0	376.0
150°	421.4	405.6	403.3	394.3	385.3
152.5°	424.4	410.2	408.5	401.6	394.7
155°	431.2	420.3	419.0	414.0	409.0
157.5°	437.9	430.5	429.3	424.3	419.4
160°	441.0	435.1	434.1	430.3	426.5
162.5°	444.3	440.0	439.3	436.4	433.6
165°	449.1	447.1	446.4	443.8	441.2
167.5°	452.8	451.1	450.8	449.5	448.3
170°	455.9	455.8	455.5	454.2	453.0
172.5°	456.1	456.1	456.0	455.8	455.5
175°	458.0	458.9	458.9	458.9	458.9
177.5°	458.2	458.9	458.9	458.9	458.9
180°	458.9	458.9	458.9	458.9	458.9

TEST NUMBER: P934587

CATALOG NUMBER: SQ4-FA-050U-125D-B2750-1D-UNV-STD-W-6-2700K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.22	17.29	16.98	18.08	19.03	19.04	20.11	19.80	20.90	21.86
	3H	16.71	17.67	17.49	18.47	19.45	20.40	21.36	21.18	22.16	23.15
	4H	16.91	17.82	17.71	18.63	19.62	20.85	21.76	21.65	22.57	23.56
	6H	17.04	17.88	17.85	18.69	19.70	21.15	21.99	21.96	22.80	23.81
	8H	17.05	17.85	17.87	18.68	19.69	21.23	22.03	22.05	22.86	23.87
	12H	17.03	17.79	17.85	18.61	19.65	21.27	22.03	22.10	22.86	23.90
4H	2H	17.27	18.18	18.07	18.99	19.98	19.48	20.39	20.27	21.19	22.19
	3H	18.32	19.08	19.13	19.92	20.93	21.00	21.76	21.81	22.60	23.61
	4H	18.60	19.29	19.43	20.13	21.17	21.53	22.22	22.36	23.06	24.10
	6H	18.74	19.34	19.58	20.20	21.25	21.91	22.51	22.75	23.37	24.41
	8H	18.75	19.31	19.60	20.17	21.23	22.02	22.58	22.87	23.44	24.49
	12H	18.73	19.23	19.60	20.11	21.17	22.09	22.59	22.95	23.47	24.53
8H	4H	19.07	19.63	19.92	20.49	21.55	21.68	22.23	22.52	23.09	24.15
	6H	19.34	19.81	20.22	20.71	21.76	22.12	22.58	22.99	23.48	24.54
	8H	19.39	19.80	20.27	20.69	21.77	22.27	22.68	23.16	23.58	24.65
	12H	19.38	19.74	20.27	20.63	21.76	22.38	22.74	23.27	23.63	24.76
12H	4H	19.09	19.59	19.96	20.47	21.53	21.65	22.15	22.52	23.03	24.09
	6H	19.41	19.82	20.29	20.71	21.79	22.12	22.53	23.00	23.42	24.50
	8H	19.48	19.84	20.37	20.73	21.86	22.29	22.65	23.18	23.54	24.67

END OF REPORT