

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P621550

Luminaire Tested: VLT-F-125U-125D-930-UNV-STD-W-4

Issue Date: 9/2/2020

Test Information

Test Method: LM-79-2019
Report Number: P621550
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2203-563-26, G2-2203-563-1)
Test Lab: INNOVATION CENTER
Issue Date: 9/2/2020
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: VLT-F-125U-125D-930-UNV-STD-W-4
Description: CORELITE VAULT SUSPENDED LED LUMINAIRE
FROSTED LENS
DOWNLIGHT 1250 LUMENS PER FOOT
UPLIGHT 1250 LUMENS PER FOOT
Light Source: 3000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8451.7 lumens
Efficiency: N/A
Efficacy: 109.9 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.12 / 1.23
Luminous Opening: Rectangular (W 0.38' x L: 4' x H: 0')
CIE Type: General Diffuse

Input Watts (W): 76.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P621550
CATALOG NUMBER: VLT-F-125U-125D-930-UNV-STD-W-4

Luminous Intensity Polar Plot





TEST NUMBER: P621550

CATALOG NUMBER: VLT-F-125U-125D-930-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	107	107	107	107	99	99	99	99	83	83	83	69	69	69	56	56	56	50
1	99	94	91	88	91	87	84	81	74	72	70	62	60	59	51	50	49	44
2	90	83	78	73	83	77	72	68	66	62	59	55	53	50	46	44	42	38
3	83	74	67	61	76	69	63	58	59	54	50	50	46	44	41	39	37	33
4	76	66	58	53	70	61	55	50	53	48	44	45	41	38	37	34	32	29
5	70	59	51	46	65	55	48	43	47	42	38	40	36	33	34	31	29	25
6	65	53	45	40	60	50	43	38	43	38	34	37	33	30	31	28	26	23
7	60	48	41	35	55	45	38	33	39	34	30	34	29	26	28	25	23	20
8	56	44	36	31	52	41	34	30	36	31	27	31	27	24	26	23	21	18
9	52	40	33	28	48	38	31	27	33	28	24	29	24	21	24	21	19	17
10	49	37	30	25	45	35	28	24	30	25	22	26	22	20	23	19	17	15

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	14896	14896	14896
5°	14737	14845	14969
10°	14657	14720	14798
15°	14498	14513	14513
20°	14263	14198	14067
25°	13991	13753	13516
30°	13665	13273	12741
35°	13301	12699	11177
40°	12917	11892	8999
45°	12514	10533	6528
50°	12089	8810	4525
55°	11670	6707	3380
60°	11233	4647	2555
65°	10741	3313	2622
70°	10033	2790	2700
75°	9274	2853	2734
80°	8062	3013	2835
85°	6529	3351	2824

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 12514 cd/sqm



TEST NUMBER: P621550

CATALOG NUMBER: VLT-F-125U-125D-930-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	195.6	2.3
10°-20°	550.1	6.5
20°-30°	800.1	9.5
30°-40°	885.2	10.5
40°-50°	760.0	9.0
50°-60°	526.2	6.2
60°-70°	313.6	3.7
70°-80°	154.5	1.8
80°-90°	49.5	0.6
90°-100°	96.5	1.1
100°-110°	687.8	8.1
110°-120°	933.8	11.0
120°-130°	760.0	9.0
130°-140°	611.2	7.2
140°-150°	481.9	5.7
150°-160°	352.4	4.2
160°-170°	218.9	2.6
170°-180°	74.6	0.9
0°-30°	1545.8	18.3
0°-40°	2431.0	28.8
0°-60°	3717.1	44.0
0°-90°	4234.6	50.1
90°-120°	1718.1	20.3
90°-150°	3571.3	42.3
90°-180°	4217.0	49.9
0°-180°	8451.7	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2076	2076	2076	2076	2076	
5°	2046	2077	2061	2059	2078	194
15°	1952	1977	1954	1943	1954	549
25°	1767	1780	1737	1707	1707	813
35°	1518	1514	1450	1333	1276	949
45°	1233	1212	1038	750	643	951
55°	933	893	536	308	270	834
65°	633	509	195	156	154	626
75°	334	146	103	101	99	353
85°	79	40	41	36	34	92
90°	0	5	10	15	15	5
95°	40	73	40	45	54	44
105°	153	235	894	1142	755	161
115°	272	330	770	1601	1871	270
125°	390	443	726	1269	1501	347
135°	484	537	731	1045	1200	372
145°	573	621	736	911	1007	360
155°	672	696	750	825	864	308
165°	746	755	770	790	805	209
175°	785	790	785	780	775	74
180°	785	785	785	785	785	



TEST NUMBER: P621550

CATALOG NUMBER: VLT-F-125U-125D-930-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2075.8	2075.8	2075.8	2075.8	2075.8
2.5°	2058.7	2082.2	2070.7	2070.9	2079.3
5°	2045.8	2077.3	2060.8	2059.1	2078.0
7.5°	2026.9	2055.9	2038.9	2036.7	2053.1
10°	2011.5	2038.8	2020.1	2016.1	2030.8
12.5°	1989.2	2016.5	1996.1	1988.7	2003.3
15°	1951.5	1976.6	1953.6	1943.1	1953.6
17.5°	1903.8	1924.8	1898.7	1882.1	1888.4
20°	1867.8	1888.8	1859.2	1835.8	1842.1
22.5°	1828.4	1846.0	1812.9	1786.0	1790.6
25°	1767.0	1779.6	1737.0	1707.0	1707.0
27.5°	1698.8	1706.4	1656.8	1625.3	1616.5
30°	1649.1	1653.3	1601.9	1564.8	1537.6
32.5°	1597.6	1600.1	1541.9	1482.1	1439.8
35°	1518.3	1514.1	1449.6	1332.6	1275.9
37.5°	1433.8	1424.6	1348.4	1170.2	1085.9
40°	1378.9	1366.3	1269.5	1055.1	960.7
42.5°	1322.3	1304.7	1182.0	936.5	832.0
45°	1233.1	1212.1	1037.9	750.3	643.3
47.5°	1144.7	1117.0	890.4	581.2	489.4
50°	1082.9	1053.6	789.2	478.7	405.3
52.5°	1021.2	991.8	686.2	401.8	343.5
55°	932.8	893.0	536.1	307.9	270.2
57.5°	842.8	785.7	399.3	239.9	210.6
60°	782.7	707.2	323.8	199.0	178.0
62.5°	724.4	628.8	265.5	173.6	169.4
65°	632.6	508.9	195.1	156.5	154.4
67.5°	545.1	388.3	145.0	141.1	139.0
70°	478.2	306.3	133.0	130.8	128.7
72.5°	418.2	234.5	120.9	118.8	116.7
75°	334.5	145.8	102.9	100.7	98.6
77.5°	250.0	91.9	84.9	82.7	80.6
80°	195.1	75.6	72.9	70.7	68.6
82.5°	147.1	61.1	59.2	57.0	54.9
85°	79.3	39.5	40.7	36.4	34.3
87.5°	27.4	20.0	20.8	18.4	16.7
90°	0.0	4.8	9.9	14.8	14.8
92.5°	11.8	16.7	21.7	30.7	34.6
95°	39.5	73.3	39.5	44.7	54.3
97.5°	70.1	140.6	290.3	85.6	74.1
100°	93.8	175.9	582.6	171.5	113.6
102.5°	117.5	203.4	788.0	452.6	247.9
105°	153.1	235.1	893.7	1141.7	755.4
107.5°	188.6	250.4	853.2	1661.5	1556.3
110°	212.3	270.2	829.5	1745.9	1876.2



TEST NUMBER: P621550

CATALOG NUMBER: VLT-F-125U-125D-930-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	236.0	293.9	805.8	1696.6	1915.7
115°	271.6	329.5	770.2	1600.9	1871.3
117.5°	308.1	365.1	761.4	1497.4	1775.5
120°	335.7	388.9	745.6	1418.7	1708.4
122.5°	355.5	412.5	725.8	1351.0	1617.5
125°	390.1	443.2	725.8	1269.3	1501.0
127.5°	418.7	472.8	726.8	1174.4	1403.2
130°	434.5	492.4	730.7	1110.9	1328.2
132.5°	454.2	512.2	730.7	1082.4	1261.0
135°	483.9	537.0	730.7	1045.3	1199.8
137.5°	508.6	565.5	730.7	1004.3	1136.6
140°	528.3	581.4	730.7	980.4	1101.1
142.5°	548.1	597.3	734.7	952.5	1065.5
145°	572.7	621.0	735.7	910.7	1007.2
147.5°	602.4	644.9	741.6	880.6	954.9
150°	622.1	660.7	745.6	860.5	923.3
152.5°	641.9	676.6	745.6	844.5	895.7
155°	671.5	695.6	750.5	825.4	864.1
157.5°	695.2	718.4	756.4	813.3	841.3
160°	711.0	730.3	760.4	805.4	829.5
162.5°	722.8	742.2	764.3	801.2	817.6
165°	745.6	755.2	770.2	790.3	804.8
167.5°	758.4	767.1	775.2	785.3	793.9
170°	770.2	775.1	775.2	785.2	790.0
172.5°	774.2	782.9	779.1	781.2	786.0
175°	785.1	789.9	785.1	780.0	775.2
177.5°	785.1	788.9	785.1	785.0	781.1
180°	785.1	785.1	785.1	785.1	785.1



TEST NUMBER: P621550

CATALOG NUMBER: VLT-F-125U-125D-930-UNV-STD-W-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	17.01	17.83	17.98	18.80	20.08	9.25	10.06	10.22	11.04	12.31
	3H	18.51	19.23	19.48	20.21	21.51	10.60	11.33	11.58	12.31	13.61
	4H	19.02	19.70	20.01	20.69	22.00	11.25	11.94	12.24	12.92	14.23
	6H	19.41	20.04	20.41	21.03	22.35	11.84	12.47	12.84	13.46	14.78
	8H	19.54	20.14	20.55	21.15	22.46	12.06	12.66	13.07	13.67	14.98
	12H	19.62	20.19	20.63	21.19	22.53	12.23	12.80	13.24	13.80	15.13
4H	2H	16.84	17.53	17.84	18.51	19.82	9.86	10.55	10.86	11.53	12.84
	3H	18.47	19.04	19.48	20.06	21.38	11.41	11.98	12.41	12.99	14.31
	4H	19.06	19.58	20.07	20.59	21.93	12.20	12.72	13.22	13.73	15.07
	6H	19.55	20.00	20.58	21.03	22.37	12.94	13.38	13.96	14.42	15.76
	8H	19.74	20.15	20.76	21.18	22.53	13.23	13.65	14.26	14.67	16.02
	12H	19.86	20.24	20.91	21.28	22.64	13.44	13.82	14.49	14.86	16.22
8H	4H	18.97	19.39	20.00	20.42	21.77	12.65	13.07	13.68	14.09	15.45
	6H	19.51	19.85	20.56	20.92	22.27	13.53	13.88	14.58	14.94	16.29
	8H	19.74	20.04	20.80	21.10	22.47	13.93	14.23	14.98	15.28	16.65
	12H	19.93	20.20	20.99	21.24	22.66	14.25	14.51	15.31	15.56	16.97
12H	4H	18.92	19.30	19.97	20.34	21.70	12.70	13.08	13.74	14.12	15.47
	6H	19.48	19.78	20.54	20.84	22.21	13.65	13.95	14.70	15.00	16.37
	8H	19.72	19.99	20.78	21.03	22.45	14.09	14.35	15.15	15.40	16.81