

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P621653

Luminaire Tested: VLT-FA-0U-050D-935-UNV-STD-W-4

Issue Date: 9/2/2020

Test Information

Test Method: LM-79-2019
Report Number: P621653
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2203-563-21)
Test Lab: INNOVATION CENTER
Issue Date: 9/2/2020
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: VLT-FA-0U-050D-935-UNV-STD-W-4
Description: CORELITE VAULT SUSPENDED LED LUMINAIRE
LIGHT SHAPING LENS - ASYMMETRIC
DOWNLIGHT 500 LUMENS PER FOOT
DIRECT ONLY
Light Source: 3500K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1412.8 lumens
Efficiency: N/A
Efficacy: 98.1 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.19 / 1.3
Luminous Opening: Rectangular (W 0.38' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 14.4
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P621653
CATALOG NUMBER: VLT-FA-OU-050D-935-UNV-STD-W-4

Luminous Intensity Polar Plot





TEST NUMBER: P621653

CATALOG NUMBER: VLT-FA-OU-050D-935-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	90					88				
2	102	95	89	85	100	93	88	84	90	86	82	87	83	80	84	81	78					76				
3	94	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	68					66				
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60					58				
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	54					52				
6	75	63	55	49	73	62	55	49	61	54	49	59	53	48	57	52	48					46				
7	70	58	50	44	68	57	49	44	56	49	44	54	48	43	53	47	43					41				
8	66	53	45	40	64	52	45	40	51	44	40	50	44	39	49	43	39					37				
9	61	49	41	36	60	48	41	36	47	41	36	46	40	36	45	40	36					34				
10	58	45	38	33	57	45	38	33	44	37	33	43	37	33	42	37	33					31				

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	4917	4917	4917	4917
5°	4926	6186	4850	4218
10°	4860	5785	4790	3662
15°	4728	5696	4743	3361
20°	4583	5520	4636	3939
25°	4443	5580	4493	4227
30°	4286	5106	4343	3991
35°	3926	4732	3828	3578
40°	3199	4212	3088	2912
45°	2907	1563	2936	2653
50°	2957	1190	2903	2521
55°	2790	925	2695	1509
60°	2570	710	2550	840
65°	2367	734	2319	888
70°	2106	774	2048	921
75°	1797	812	1719	948
80°	1355	835	1269	979
85°	922	749	807	922

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°
 Vertical Angle: 45°
 Luminance: 5384 cd/sqm



TEST NUMBER: P621653
 CATALOG NUMBER: VLT-FA-OU-050D-935-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	66.1	4.7
10°-20°	181.1	12.8
20°-30°	270.9	19.2
30°-40°	308.1	21.8
40°-50°	263.5	18.7
50°-60°	177.7	12.6
60°-70°	91.7	6.5
70°-80°	41.4	2.9
80°-90°	12.3	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	518.1	36.7
0°-40°	826.2	58.5
0°-60°	1267.4	89.7
0°-90°	1412.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1412.8	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	685	685	685	685	685	
5°	684	859	673	586	684	65
15°	636	767	638	452	636	179
25°	561	705	567	534	561	258
35°	448	540	437	408	448	274
45°	286	154	289	261	286	227
55°	223	74	215	121	223	199
65°	139	43	137	52	139	138
75°	65	29	62	34	65	69
85°	11	9	10	11	11	15
90°	0	0	0	0	0	



TEST NUMBER: P621653

CATALOG NUMBER: VLT-FA-OU-050D-935-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
0°	685.2	685.2	685.2	685.2	685.2	685.2	685.2	685.2	685.2	685.2	685.2
2.5°	687.4	710.8	740.4	760.6	769.4	760.6	735.3	710.7	679.6	670.3	648.4
5°	683.8	756.0	843.4	853.9	858.7	853.9	835.7	751.7	673.3	639.9	603.6
7.5°	675.4	801.8	842.4	818.8	819.0	823.3	843.7	797.8	664.5	612.0	567.5
10°	667.0	827.2	821.8	787.8	793.9	791.2	828.0	822.2	657.3	596.6	545.8
12.5°	655.9	835.1	794.4	783.3	790.0	786.2	798.5	830.8	651.1	585.6	520.7
15°	636.4	823.8	771.6	766.7	766.7	770.1	775.1	827.2	638.5	565.5	490.0
17.5°	616.3	801.1	755.7	731.5	728.9	733.4	761.4	806.9	620.5	543.3	460.3
20°	600.1	785.5	739.5	711.2	722.8	712.6	745.8	789.7	607.1	529.4	441.9
22.5°	585.6	766.1	718.9	706.8	722.2	707.1	724.6	770.3	591.5	513.8	428.0
25°	561.1	733.5	687.9	699.2	704.7	699.2	690.7	736.4	567.4	493.8	413.3
27.5°	536.7	699.2	664.8	672.4	655.7	668.6	668.6	699.3	542.5	470.4	408.9
30°	517.2	675.3	653.1	642.1	616.2	636.6	658.0	675.4	524.1	455.3	407.7
32.5°	491.5	653.5	641.4	603.2	586.6	600.5	646.8	653.0	495.7	441.6	406.6
35°	448.2	622.6	620.3	557.2	540.2	553.1	625.2	621.0	437.0	420.0	398.0
37.5°	390.0	595.2	580.0	510.7	483.6	507.3	584.6	592.2	367.6	400.2	377.8
40°	341.5	576.7	549.9	476.1	449.6	472.7	553.4	575.0	329.7	386.2	355.5
42.5°	314.2	560.2	518.2	439.6	275.0	434.0	521.6	558.2	306.3	368.3	336.0
45°	286.5	530.5	471.9	243.3	154.0	231.7	472.6	523.0	289.3	341.1	306.0
47.5°	274.3	493.8	423.5	146.6	130.1	142.3	423.1	485.8	274.5	313.7	277.4
50°	264.9	470.7	388.9	129.1	106.6	124.4	389.6	463.1	260.0	295.4	257.9
52.5°	249.2	443.1	339.3	107.0	92.1	104.4	331.1	434.4	244.9	275.5	233.4
55°	223.0	390.0	141.5	84.1	73.9	80.7	134.5	376.9	215.4	244.0	204.9
57.5°	195.3	332.0	99.3	65.5	57.3	64.8	98.6	318.7	191.7	206.7	178.7
60°	179.1	292.9	80.9	54.9	49.5	54.3	80.2	281.3	177.7	181.8	154.7
62.5°	163.0	253.3	66.9	48.3	46.7	47.7	66.8	240.6	160.5	160.7	109.0
65°	139.4	191.9	49.5	43.9	43.2	43.2	48.1	185.0	136.6	132.5	62.7
67.5°	115.4	137.8	39.7	40.4	39.7	39.7	39.0	133.9	112.6	105.7	47.4
70°	100.4	105.8	36.9	37.6	36.9	36.9	36.2	103.0	97.6	81.9	44.6
72.5°	85.9	72.2	34.2	34.3	34.2	34.2	33.5	67.8	83.1	57.6	40.7
75°	64.8	36.2	29.3	29.3	29.3	29.3	28.6	34.8	62.0	37.5	34.9
77.5°	45.0	23.9	24.3	24.1	24.1	23.6	23.6	23.7	42.4	25.9	28.2
80°	32.8	19.8	20.9	20.2	20.2	20.2	20.2	19.1	30.7	21.8	23.7
82.5°	23.3	15.8	17.0	16.3	16.3	16.3	16.3	15.6	21.2	17.8	19.2
85°	11.2	10.5	11.2	9.7	9.1	9.7	10.5	10.4	9.8	11.8	12.5
87.5°	3.3	5.0	4.5	3.3	3.3	3.3	3.9	4.4	2.8	5.5	5.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P621653

CATALOG NUMBER: VLT-FA-OU-050D-935-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
0°	685.2	685.2	685.2	685.2	685.2	685.2
2.5°	640.5	640.0	641.1	650.6	669.9	687.4
5°	583.4	585.5	587.5	603.6	637.4	683.8
7.5°	539.6	536.6	541.2	567.4	608.9	675.4
10°	509.4	502.5	509.4	545.1	593.4	667.0
12.5°	480.9	472.4	483.1	522.2	580.6	655.9
15°	444.2	452.4	447.6	491.4	561.4	636.4
17.5°	452.9	494.0	461.6	464.6	542.3	616.3
20°	473.5	515.8	487.2	446.8	529.9	600.1
22.5°	492.3	524.1	498.3	431.7	517.6	585.6
25°	506.6	533.9	505.3	418.2	499.8	561.1
27.5°	507.4	511.2	507.6	417.1	477.7	536.7
30°	498.0	481.6	496.6	418.2	462.0	517.2
32.5°	471.2	452.6	465.4	416.0	446.1	491.5
35°	433.0	408.4	426.2	404.3	421.6	448.2
37.5°	392.7	361.6	386.1	381.1	400.7	390.0
40°	365.4	310.9	359.9	358.3	389.2	341.5
42.5°	330.4	284.1	325.5	339.9	376.6	314.2
45°	266.8	261.4	264.1	308.8	349.9	286.5
47.5°	244.0	240.3	242.6	280.5	319.6	274.3
50°	230.6	225.8	229.2	262.1	300.3	264.9
52.5°	212.0	199.1	210.7	237.0	280.3	249.2
55°	159.4	120.6	158.7	208.4	250.3	223.0
57.5°	93.6	69.7	91.5	181.4	212.1	195.3
60°	63.3	58.5	64.0	159.6	186.6	179.1
62.5°	57.8	56.3	58.0	111.1	163.9	163.0
65°	53.0	52.3	53.0	64.1	135.3	139.4
67.5°	47.9	47.3	48.5	49.2	106.8	115.4
70°	44.6	43.9	44.6	45.3	82.0	100.4
72.5°	40.7	40.0	40.7	41.4	57.7	85.9
75°	34.8	34.2	34.8	35.5	38.2	64.8
77.5°	28.2	28.2	28.8	28.9	26.8	45.0
80°	23.7	23.7	24.4	24.4	23.2	32.8
82.5°	19.2	18.7	19.9	20.5	19.2	23.3
85°	11.8	11.2	12.5	13.2	12.5	11.2
87.5°	4.4	3.9	5.0	6.1	6.1	3.3
90°	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)