

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P621996

Luminaire Tested: VLT-BB-M-150U-125D-940-UNV-STD-W-4

Issue Date: 9/2/2020

Test Information

Test Method: LM-79-2019
Report Number: P621996
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2203-563-26, G2-2203-563-26)
Test Lab: INNOVATION CENTER
Issue Date: 10/28/2022
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: VLT-BB-M-150U-125D-940-UNV-STD-W-4
Description: CORELITE VAULT SUSPENDED LED LUMINAIRE
BLACK BAFFLE WITH MEDIUM OPTIC
DOWNLIGHT 1250 LUMENS PER FOOT
UPLIGHT 1500 LUMENS PER FOOT
Light Source: 4000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9825.9 lumens
Efficiency: N/A
Efficacy: 92.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.18 / 1.14
Luminous Opening: Rectangular (W 0.38' x L: 4' x H: 0')
CIE Type: General Diffuse

Input Watts (W): 105.8
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P621996
CATALOG NUMBER: VLT-BB-M-150U-125D-940-UNV-STD-W-4

Luminous Intensity Polar Plot





TEST NUMBER: P621996

CATALOG NUMBER: VLT-BB-M-150U-125D-940-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20										
RC	80									70									50									30									10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0														
RCR																																						
0	107	107	107	107	98	98	98	98	82	82	82	67	67	67	54	54	54	48																				
1	99	96	93	90	91	88	86	83	75	73	71	62	61	60	51	50	49	44																				
2	92	86	81	77	85	80	76	72	68	65	63	57	55	54	47	46	45	40																				
3	86	78	72	67	79	72	67	63	62	58	55	53	50	48	44	42	41	37																				
4	79	70	64	59	73	66	60	55	57	53	49	49	46	43	41	39	37	34																				
5	74	64	57	52	68	60	54	49	52	48	44	45	42	39	38	36	34	31																				
6	69	58	51	46	64	55	49	44	48	43	40	41	38	35	35	33	31	29																				
7	64	53	46	42	60	50	44	40	44	39	36	38	35	32	33	31	29	26																				
8	60	49	42	38	56	46	40	36	41	36	33	36	32	30	31	28	26	24																				
9	56	45	39	34	52	43	37	33	38	33	30	33	30	27	29	26	24	22																				
10	53	42	35	31	49	40	34	30	35	31	27	31	28	25	27	25	23	21																				

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	24410	24410	24410
5°	24119	24484	24960
10°	24453	24804	25174
15°	24950	25007	25157
20°	24852	24814	24581
25°	24141	24041	23760
30°	22700	22657	22237
35°	20399	20421	19844
40°	16562	16562	7580
45°	9524	11584	154
50°	3002	2775	142
55°	1047	223	126
60°	73	145	145
65°	42	129	129
70°	52	159	159
75°	0	141	141
80°	0	211	211
85°	0	206	206

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 45°
 Vertical Angle: 45°
 Luminance: 11584 cd/sqm



TEST NUMBER: P621996

CATALOG NUMBER: VLT-BB-M-150U-125D-940-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	325.0	3.3
10°-20°	948.5	9.7
20°-30°	1385.6	14.1
30°-40°	1372.2	14.0
40°-50°	574.5	5.8
50°-60°	61.5	0.6
60°-70°	8.6	0.1
70°-80°	5.2	0.1
80°-90°	4.6	0.0
90°-100°	117.7	1.2
100°-110°	838.3	8.5
110°-120°	1138.2	11.6
120°-130°	926.4	9.4
130°-140°	745.1	7.6
140°-150°	587.4	6.0
150°-160°	429.5	4.4
160°-170°	266.8	2.7
170°-180°	91.0	0.9
0°-30°	2659.1	27.1
0°-40°	4031.3	41.0
0°-60°	4667.3	47.5
0°-90°	4685.7	47.7
90°-120°	2094.2	21.3
90°-150°	4353.0	44.3
90°-180°	5140.0	52.3
0°-180°	9825.9	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3402	3402	3402	3402	3402	
5°	3348	3408	3399	3408	3465	320
15°	3358	3428	3366	3342	3386	943
25°	3049	3101	3036	2964	3001	1392
35°	2329	2334	2331	2285	2265	1428
45°	938	1115	1142	23	15	736
55°	84	111	18	13	10	94
65°	2	10	8	8	8	3
75°	0	5	5	5	5	0
85°	0	2	2	2	2	0
90°	0	6	12	18	18	2
95°	48	89	48	54	66	54
105°	187	287	1089	1392	921	197
115°	331	402	939	1951	2281	329
125°	475	540	885	1547	1830	422
135°	590	654	891	1274	1462	454
145°	698	757	897	1110	1228	438
155°	818	848	915	1006	1053	376
165°	909	920	939	963	981	255
175°	957	963	957	951	945	90
180°	957	957	957	957	957	



TEST NUMBER: P621996

CATALOG NUMBER: VLT-BB-M-150U-125D-940-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	3401.6	3401.6	3401.6	3401.6	3401.6
2.5°	3365.0	3412.7	3397.5	3394.1	3423.9
5°	3348.3	3407.8	3399.0	3407.9	3465.0
7.5°	3349.8	3404.9	3408.2	3407.9	3465.0
10°	3355.9	3413.0	3404.1	3397.8	3454.8
12.5°	3364.0	3423.1	3389.9	3379.5	3434.5
15°	3358.4	3427.9	3366.1	3341.7	3386.3
17.5°	3307.2	3387.6	3306.2	3259.2	3292.0
20°	3254.4	3338.8	3249.4	3184.2	3218.9
22.5°	3179.4	3257.7	3172.3	3097.1	3137.8
25°	3049.0	3101.1	3036.3	2963.6	3000.8
27.5°	2871.4	2901.2	2864.3	2798.9	2821.7
30°	2739.5	2759.4	2734.4	2668.8	2683.7
32.5°	2593.4	2603.3	2588.3	2528.6	2535.6
35°	2328.6	2333.5	2331.1	2285.0	2265.2
37.5°	2001.4	2011.3	2005.4	1805.0	1245.5
40°	1768.0	1777.9	1768.0	1057.2	809.2
42.5°	1475.8	1539.3	1522.5	720.9	230.8
45°	938.5	1114.6	1141.5	22.7	15.2
47.5°	463.7	653.7	536.7	14.7	14.7
50°	268.9	385.4	248.6	12.7	12.7
52.5°	179.6	234.7	72.0	12.7	12.7
55°	83.7	111.0	17.8	12.6	10.1
57.5°	29.4	55.7	12.2	10.1	10.1
60°	5.1	27.4	10.1	10.1	10.1
62.5°	3.0	15.4	10.1	8.2	10.1
65°	2.5	10.0	7.6	7.6	7.6
67.5°	2.5	7.5	7.6	7.6	7.6
70°	2.5	7.5	7.6	7.6	7.6
72.5°	0.5	5.5	5.6	5.6	7.6
75°	0.0	5.0	5.1	5.1	5.1
77.5°	0.0	5.0	5.1	5.1	5.1
80°	0.0	5.0	5.1	5.1	5.1
82.5°	0.0	3.0	3.0	3.1	5.1
85°	0.0	2.5	2.5	2.5	2.5
87.5°	0.0	3.2	4.4	5.6	5.6
90°	0.0	5.9	12.0	18.1	18.1
92.5°	14.4	20.3	26.5	37.4	42.1
95°	48.1	89.3	48.1	54.4	66.2
97.5°	85.5	171.4	353.9	104.4	90.3
100°	114.3	214.4	710.2	209.0	138.4
102.5°	143.2	248.0	960.5	551.6	302.1
105°	186.6	286.6	1089.3	1391.5	920.8
107.5°	229.9	305.2	1039.9	2025.2	1896.9
110°	258.8	329.4	1011.1	2128.0	2286.9

TEST NUMBER: P621996

CATALOG NUMBER: VLT-BB-M-150U-125D-940-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	287.7	358.3	982.2	2067.9	2335.1
115°	331.0	401.6	938.8	1951.4	2280.9
117.5°	375.5	445.0	928.0	1825.2	2164.2
120°	409.2	474.0	908.8	1729.2	2082.3
122.5°	433.3	502.7	884.7	1646.7	1971.6
125°	475.4	540.2	884.7	1547.1	1829.5
127.5°	510.3	576.3	885.9	1431.5	1710.4
130°	529.6	600.2	890.7	1354.1	1618.9
132.5°	553.7	624.3	890.7	1319.3	1537.1
135°	589.8	654.5	890.7	1274.1	1462.4
137.5°	619.9	689.3	890.7	1224.2	1385.4
140°	643.9	708.7	890.7	1195.0	1342.1
142.5°	668.0	728.0	895.5	1161.0	1298.7
145°	698.1	757.0	896.7	1110.0	1227.7
147.5°	734.2	786.0	903.9	1073.3	1163.9
150°	758.3	805.4	908.8	1048.9	1125.4
152.5°	782.4	824.7	908.8	1029.3	1091.7
155°	818.5	847.9	914.8	1006.1	1053.2
157.5°	847.4	875.6	922.0	991.4	1025.5
160°	866.6	890.2	926.8	981.6	1011.1
162.5°	881.1	904.6	931.6	976.6	996.6
165°	908.8	920.5	938.8	963.3	981.0
167.5°	924.4	935.0	944.9	957.1	967.7
170°	938.8	944.7	944.9	957.0	962.9
172.5°	943.7	954.2	949.7	952.2	958.1
175°	956.9	962.8	956.9	950.7	944.9
177.5°	956.9	961.6	956.9	956.8	952.1
180°	956.9	956.9	956.9	956.9	956.9



TEST NUMBER: P621996

CATALOG NUMBER: VLT-BB-M-150U-125D-940-UNV-STD-W-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.00	0.00	0.00	0.00	1.23	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	1.05	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.93	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.79	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.72	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.64	0.00	0.00	0.00	0.00	0.00
4H	2H	0.00	0.00	0.00	0.00	0.89	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.74	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.65	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.55	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.48	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.40	0.00	0.00	0.00	0.00	0.00
8H	4H	0.00	0.00	0.00	0.00	0.49	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.50	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.48	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.46	0.00	0.00	0.00	0.00	0.00
12H	4H	0.00	0.00	0.00	0.00	0.42	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.46	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.50	0.00	0.00	0.00	0.00	0.00