

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P365169

Luminaire Tested: **FLD6BX10D010-FEU6B12-8027-F6LBXVM1-MW-BTR84**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P365169
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-15)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6BX10D010-FEU6B12-8027-F6LBXVM1-MW-BTR84
Description: VANDAL RESISTANT ENCLOSED BOTTOM TRIM RING, MATTE WHITE REFLECTOR,
BOTTOM TRIM POLYCARBONATE, CLEAR 0.125", 1000LM
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 611.0 lumens
Efficiency: N/A
Efficacy: 61.1 lumens/watt
Spacing Criteria (0/90/45): 0.87 / 0.87 / 0.84
Luminous Opening: Circular (Dia: 0.44' x H: 0')
CIE Type: Direct


Input Watts (W): 10
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P365169

CATALOG NUMBER: FLD6BX10D010-FEU6B12-8027-F6LBXVM1-MW-BTR84

Luminous Intensity Polar Plot





TEST NUMBER: P365169

CATALOG NUMBER: FLD6BX10D010-FEU6B12-8027-F6LBXVM1-MW-BTR84

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95	94	93	91
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	83	82
3	99	91	85	80	96	89	84	80	87	82	78		84	80	77		82	79	76	74
4	93	84	77	72	91	82	76	72	80	75	71		78	74	70		76	72	69	67
5	87	77	71	65	85	76	70	65	74	69	65		73	68	64		71	67	63	62
6	82	72	65	60	81	71	64	60	69	64	59		68	63	59		67	62	58	57
7	78	67	60	55	76	66	60	55	65	59	55		64	58	54		62	58	54	53
8	73	63	56	51	72	62	56	51	61	55	51		60	55	51		59	54	50	49
9	70	59	52	48	68	58	52	48	57	52	47		56	51	47		55	51	47	46
10	66	55	49	45	65	55	49	45	54	48	44		53	48	44		52	48	44	43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	42911
5°	42141
10°	39850
15°	37264
20°	33877
25°	28196
30°	20355
35°	14064
40°	10282
45°	8354
50°	7274
55°	6392
60°	5571
65°	4727
70°	3810
75°	2656
80°	1691
85°	1972



TEST NUMBER: P365169

CATALOG NUMBER: FLD6BX10D010-FEU6B12-8027-F6LBXVM1-MW-BTR84

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	54.7	9.0
10°-20°	140.5	23.0
20°-30°	160.4	26.3
30°-40°	103.5	16.9
40°-50°	65.0	10.6
50°-60°	46.1	7.5
60°-70°	27.8	4.5
70°-80°	10.7	1.8
80°-90°	2.4	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	355.6	58.2
0°-40°	459.1	75.1
0°-60°	570.1	93.3
0°-90°	611.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	611.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	599	
5°	586	55
15°	503	140
25°	357	160
35°	161	103
45°	82	65
55°	51	46
65°	28	28
75°	10	11
85°	2	2
90°	0	



TEST NUMBER: P365169

CATALOG NUMBER: FLD6BX10D010-FEU6B12-8027-F6LBXVM1-MW-BTR84

CANDELA DISTRIBUTION (FULL):

	0°
0°	599.3
2.5°	595.9
5°	586.3
7.5°	569.8
10°	548.1
12.5°	526.8
15°	502.7
17.5°	476.9
20°	444.6
22.5°	405.4
25°	356.9
27.5°	302.3
30°	246.2
32.5°	199.1
35°	160.9
37.5°	131.4
40°	110.0
42.5°	94.6
45°	82.5
47.5°	73.2
50°	65.3
52.5°	58.1
55°	51.2
57.5°	45.0
60°	38.9
62.5°	33.4
65°	27.9
67.5°	22.7
70°	18.2
72.5°	13.4
75°	9.6
77.5°	6.5
80°	4.1
82.5°	2.8
85°	2.4
87.5°	1.4
90°	0.0

(END OF REPORT)