

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P365267

Luminaire Tested: **FLD6BX15D010-FEU6B12-8030-F6LBXVM1-MW-BL84**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P365267
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-36)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6BX15D010-FEU6B12-8030-F6LBXVM1-MW-BL84
Description: VANDAL RESISTANT ENCLOSED BOTTOM LENS, MATTE WHITE REFLECTOR, BOTTOM LENS POLYCARBONATE, CLEAR 0.125", 1500LM
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1125.0 lumens
Efficiency: N/A
Efficacy: 79.2 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.95
Luminous Opening: Circular (Dia: 0.71' x H: 0')
CIE Type: Direct


Input Watts (W): 14.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P365267

CATALOG NUMBER: FLD6BX15D010-FEU6B12-8030-F6LBXVM1-MW-BL84

Luminous Intensity Polar Plot





TEST NUMBER: P365267

CATALOG NUMBER: FLD6BX15D010-FEU6B12-8030-F6LBXVM1-MW-BL84

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	108	105	102	109	106	103	101	102	100	97		98	96	95		95	93	92	90
2	104	98	93	89	102	96	92	88	93	89	86		90	87	84		87	84	82	80
3	97	89	83	78	95	88	82	77	85	80	76		82	78	75		80	77	74	72
4	91	82	75	70	89	80	74	69	78	73	68		76	71	67		74	70	67	65
5	85	75	68	63	84	74	67	62	72	66	62		70	65	61		69	64	61	59
6	80	69	62	57	78	68	62	57	67	61	56		65	60	56		64	59	55	54
7	75	64	57	52	74	64	57	52	62	56	51		61	55	51		60	55	51	49
8	71	60	53	48	70	59	52	48	58	52	47		57	51	47		56	51	47	45
9	67	56	49	44	66	55	49	44	54	48	44		53	48	44		52	47	44	42
10	64	52	46	41	62	52	45	41	51	45	41		50	45	41		49	44	41	39

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	24925
5°	24417
10°	23193
15°	21698
20°	20243
25°	18575
30°	15862
35°	12091
40°	8904
45°	6760
50°	5503
55°	4843
60°	4327
65°	3820
70°	3242
75°	2522
80°	1699
85°	752



TEST NUMBER: P365267

CATALOG NUMBER: FLD6BX15D010-FEU6B12-8030-F6LBXVM1-MW-BL84

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	83.3	7.4
10°-20°	215.3	19.1
20°-30°	279.8	24.9
30°-40°	228.0	20.3
40°-50°	138.4	12.3
50°-60°	91.6	8.1
60°-70°	58.8	5.2
70°-80°	25.9	2.3
80°-90°	3.9	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	578.4	51.4
0°-40°	806.4	71.7
0°-60°	1036.5	92.1
0°-90°	1125.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1125.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	912	
5°	890	83
15°	767	215
25°	616	280
35°	363	228
45°	175	138
55°	102	92
65°	59	59
75°	24	26
85°	2	4
90°	0	



TEST NUMBER: P365267

CATALOG NUMBER: FLD6BX15D010-FEU6B12-8030-F6LBXVM1-MW-BL84

CANDELA DISTRIBUTION (FULL):

	0°
0°	912.5
2.5°	906.6
5°	890.5
7.5°	866.0
10°	836.2
12.5°	803.0
15°	767.3
17.5°	730.7
20°	696.4
22.5°	659.3
25°	616.3
27.5°	565.5
30°	502.9
32.5°	432.5
35°	362.6
37.5°	300.6
40°	249.7
42.5°	207.2
45°	175.0
47.5°	149.6
50°	129.5
52.5°	114.4
55°	101.7
57.5°	89.9
60°	79.2
62.5°	68.9
65°	59.1
67.5°	49.9
70°	40.6
72.5°	31.8
75°	23.9
77.5°	17.1
80°	10.8
82.5°	5.9
85°	2.4
87.5°	0.5
90°	0.0

(END OF REPORT)