

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P365469

Luminaire Tested: **FLD6BX30D010-FEU6B35-8035-F6LBXVM1-MW-BL89AM**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P365469
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-40)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6BX30D010-FEU6B35-8035-F6LBXVM1-MW-BL89AM
Description: VANDAL RESISTANT ENCLOSED BOTTOM LENS, MATTE WHITE REFLECTOR, BOTTOM LENS POLYCARBONATE, OPAL SMOOTH 0.125", 3000LM
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1015.0 lumens
Efficiency: N/A
Efficacy: 37.6 lumens/watt
Spacing Criteria (0/90/45): 1.25 / 1.25 / 1.37
Luminous Opening: Circular (Dia: 0.71' x H: 0')
CIE Type: Direct


Input Watts (W): 27
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P365469

CATALOG NUMBER: FLD6BX30D010-FEU6B35-8035-F6LBXVM1-MW-BL89AM

Luminous Intensity Polar Plot





TEST NUMBER: P365469

CATALOG NUMBER: FLD6BX30D010-FEU6B35-8035-F6LBXVM1-MW-BL89AM

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	95	98	94	92	94	91	89	90	88	86	84
2	99	91	84	78	96	89	83	77	85	80	75	82	78	74	79	75	72	70
3	90	80	71	65	88	78	70	64	75	69	63	72	67	62	70	65	61	59
4	82	70	62	55	80	69	61	55	67	59	54	64	58	53	62	57	52	50
5	76	63	54	47	74	62	53	47	60	52	46	58	51	46	56	50	45	43
6	70	57	48	41	68	56	47	41	54	46	41	52	45	40	51	45	40	38
7	65	51	42	36	63	50	42	36	49	41	36	47	41	36	46	40	35	33
8	60	47	38	32	59	46	38	32	45	37	32	43	37	32	42	36	32	30
9	56	43	35	29	55	42	34	29	41	34	29	40	33	29	39	33	29	27
10	53	40	32	26	52	39	31	26	38	31	26	37	31	26	36	30	26	24

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	9754
5°	9792
10°	9738
15°	9702
20°	9654
25°	9557
30°	9497
35°	9440
40°	9310
45°	9198
50°	9098
55°	8958
60°	8637
65°	8273
70°	7747
75°	6860
80°	5506
85°	3134



TEST NUMBER: P365469

CATALOG NUMBER: FLD6BX30D010-FEUG6B35-8035-F6LBXVM1-MW-BL89AM

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	33.9	3.3
10°-20°	96.7	9.5
20°-30°	146.4	14.4
30°-40°	176.7	17.4
40°-50°	184.0	18.1
50°-60°	167.4	16.5
60°-70°	126.6	12.5
70°-80°	69.1	6.8
80°-90°	14.3	1.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	277.0	27.3
0°-40°	453.7	44.7
0°-60°	805.1	79.3
0°-90°	1015.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1015.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	357	
5°	357	34
15°	343	97
25°	317	146
35°	283	177
45°	238	184
55°	188	167
65°	128	127
75°	65	69
85°	10	14
90°	0	



TEST NUMBER: P365469

CATALOG NUMBER: FLD6BX30D010-FEU6B35-8035-F6LBXVM1-MW-BL89AM

CANDELA DISTRIBUTION (FULL):

	0°
0°	357.1
2.5°	358.1
5°	357.1
7.5°	354.1
10°	351.1
12.5°	347.1
15°	343.1
17.5°	337.1
20°	332.1
22.5°	325.1
25°	317.1
27.5°	310.1
30°	301.1
32.5°	292.1
35°	283.1
37.5°	272.1
40°	261.1
42.5°	250.1
45°	238.1
47.5°	227.1
50°	214.1
52.5°	201.1
55°	188.1
57.5°	173.1
60°	158.1
62.5°	143.0
65°	128.0
67.5°	113.0
70°	97.0
72.5°	81.0
75°	65.0
77.5°	50.0
80°	35.0
82.5°	22.0
85°	10.0
87.5°	3.0
90°	0.0

(END OF REPORT)