

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P365493

Luminaire Tested: **FLD6BX30D010-FEU6B35-8040-F6LBXVM1-MW-BTR84**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P365493
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-15)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6BX30D010-FEU6B35-8040-F6LBXVM1-MW-BTR84
Description: VANDAL RESISTANT ENCLOSED BOTTOM TRIM RING, MATTE WHITE REFLECTOR,
BOTTOM TRIM POLYCARBONATE, CLEAR 0.125", 3000LM
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1796.0 lumens
Efficiency: N/A
Efficacy: 66.5 lumens/watt
Spacing Criteria (0/90/45): 0.87 / 0.87 / 0.84
Luminous Opening: Circular (Dia: 0.44' x H: 0')
CIE Type: Direct


Input Watts (W): 27
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P365493

CATALOG NUMBER: FLD6BX30D010-FEU6B35-8040-F6LBXVM1-MW-BTR84

Luminous Intensity Polar Plot





TEST NUMBER: P365493

CATALOG NUMBER: FLD6BX30D010-FEU6B35-8040-F6LBXVM1-MW-BTR84

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95	94	93	91
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	84	82
3	99	91	85	80	96	89	84	80	87	82	78		84	80	77		82	79	76	74
4	93	84	77	72	91	82	76	72	80	75	71		78	74	70		76	72	69	67
5	87	77	71	65	85	76	70	65	74	69	65		73	68	64		71	67	63	62
6	82	72	65	60	81	71	64	60	69	64	59		68	63	59		67	62	58	57
7	78	67	60	55	76	66	60	55	65	59	55		64	58	54		62	58	54	53
8	73	63	56	51	72	62	56	51	61	55	51		60	55	51		59	54	50	49
9	70	59	52	48	68	58	52	48	57	52	47		56	51	47		55	51	47	46
10	66	55	49	45	65	55	49	45	54	48	44		53	48	44		52	48	44	43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	126141
5°	123863
10°	117137
15°	109538
20°	99582
25°	82891
30°	59835
35°	41345
40°	30228
45°	24566
50°	21387
55°	18800
60°	16354
65°	13876
70°	11221
75°	7829
80°	4989
85°	5833



TEST NUMBER: P365493

CATALOG NUMBER: FLD6BX30D010-FEU6B35-8040-F6LBXVM1-MW-BTR84

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	160.9	9.0
10°-20°	412.9	23.0
20°-30°	471.6	26.3
30°-40°	304.2	16.9
40°-50°	191.0	10.6
50°-60°	135.5	7.5
60°-70°	81.6	4.5
70°-80°	31.5	1.8
80°-90°	6.9	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1045.3	58.2
0°-40°	1349.5	75.1
0°-60°	1676.0	93.3
0°-90°	1796.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1796.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1762	
5°	1723	161
15°	1478	413
25°	1049	472
35°	473	304
45°	243	191
55°	151	135
65°	82	82
75°	28	32
85°	7	7
90°	0	



TEST NUMBER: P365493

CATALOG NUMBER: FLD6BX30D010-FEU6B35-8040-F6LBXVM1-MW-BTR84

CANDELA DISTRIBUTION (FULL):

	0°
0°	1761.7
2.5°	1751.6
5°	1723.3
7.5°	1674.8
10°	1611.1
12.5°	1548.5
15°	1477.7
17.5°	1401.9
20°	1306.9
22.5°	1191.7
25°	1049.2
27.5°	888.5
30°	723.7
32.5°	585.2
35°	473.0
37.5°	386.1
40°	323.4
42.5°	278.0
45°	242.6
47.5°	215.3
50°	192.0
52.5°	170.8
55°	150.6
57.5°	132.4
60°	114.2
62.5°	98.0
65°	81.9
67.5°	66.7
70°	53.6
72.5°	39.4
75°	28.3
77.5°	19.2
80°	12.1
82.5°	8.1
85°	7.1
87.5°	4.0
90°	0.0

(END OF REPORT)