

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P364914

Luminaire Tested: **FLD6BX50D010TE-FEU6B35-8030-F6LBXVM1-LI-BTR80**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P364914  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-23)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: FAIL-SAFE  
Catalog Number: FLD6BX50D010TE-FEU6B35-8030-F6LBXVM1-LI-BTR80  
Description: VANDAL RESISTANT ENCLOSED BOTTOM TRIM RING, SPECULAR CLEAR REFLECTOR, BOTTOM TRIM ACRYLIC, PATTERN 12 0.125", 5000LM  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3960.0 lumens  
Efficiency: N/A  
Efficacy: 71.9 lumens/watt  
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87  
Luminous Opening: Circular (Dia: 0.44' x H: 0')  
CIE Type: Direct


Input Watts (W): 55.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P364914

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8030-F6LBXVM1-LI-BTR80

### Luminous Intensity Polar Plot





TEST NUMBER: P364914

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8030-F6LBXVM1-LI-BTR80

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96	95	93	91
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89	87	85	83
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83	80	78	76
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78	74	71	69
5	88	79	72	67	87	78	72	67	76	71	67		74	70	66		73	69	65	64
6	83	73	67	62	82	73	66	62	71	65	61		69	65	61		68	64	60	59
7	79	68	62	57	77	68	61	57	66	61	57		65	60	56		64	59	56	54
8	75	64	57	53	73	63	57	53	62	57	52		61	56	52		60	55	52	50
9	71	60	54	49	69	60	53	49	59	53	49		58	52	49		57	52	49	47
10	67	57	50	46	66	56	50	46	55	50	46		54	49	46		54	49	45	44

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	287338
5°	281184
10°	265786
15°	242716
20°	211714
25°	178715
30°	146457
35°	114481
40°	84384
45°	59389
50°	41906
55°	29673
60°	21051
65°	15638
70°	12163
75°	9932
80°	9154
85°	9858



TEST NUMBER: P364914

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8030-F6LBXVM1-LI-BTR80

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	365.3	9.2
10°-20°	909.5	23.0
20°-30°	1036.2	26.2
30°-40°	817.8	20.7
40°-50°	464.8	11.7
50°-60°	219.3	5.5
60°-70°	94.9	2.4
70°-80°	39.4	1.0
80°-90°	12.8	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2310.9	58.4
0°-40°	3128.7	79.0
0°-60°	3812.9	96.3
0°-90°	3960.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3960.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4013	
5°	3912	365
15°	3274	909
25°	2262	1036
35°	1310	818
45°	586	465
55°	238	219
65°	92	95
75°	36	39
85°	12	13
90°	0	



TEST NUMBER: P364914

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8030-F6LBXVM1-LI-BTR80

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4013.0
2.5°	3983.9
5°	3912.1
7.5°	3800.9
10°	3655.6
12.5°	3481.2
15°	3274.3
17.5°	3040.1
20°	2778.5
22.5°	2525.4
25°	2262.1
27.5°	2010.8
30°	1771.4
32.5°	1528.6
35°	1309.7
37.5°	1099.4
40°	902.8
42.5°	735.2
45°	586.5
47.5°	468.5
50°	376.2
52.5°	299.2
55°	237.7
57.5°	188.1
60°	147.0
62.5°	116.3
65°	92.3
67.5°	73.5
70°	58.1
72.5°	46.2
75°	35.9
77.5°	27.4
80°	22.2
82.5°	17.1
85°	12.0
87.5°	6.8
90°	0.0

(END OF REPORT)