

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P364946

Luminaire Tested: **FLD6BX50D010TE-FEU6B35-8040-F6LBXVM1-LI-BL87**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P364946
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-43)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6BX50D010TE-FEU6B35-8040-F6LBXVM1-LI-BL87
Description: VANDAL RESISTANT ENCLOSED BOTTOM LENS, SPECULAR CLEAR REFLECTOR,
BOTTOM LENS POLYCARBONATE, CLEAR 0.375", 5000LM
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4415.0 lumens
Efficiency: N/A
Efficacy: 80.1 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.82
Luminous Opening: Circular (Dia: 0.71' x H: 0')
CIE Type: Direct


Input Watts (W): 55.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P364946

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8040-F6LBXVM1-LI-BL87

Luminous Intensity Polar Plot





TEST NUMBER: P364946

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8040-F6LBXVM1-LI-BL87

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98	97	96	94
2	109	104	100	97	106	102	99	96	99	96	94		96	94	92		93	91	90	88
3	103	97	93	89	101	96	92	88	93	90	87		91	88	85		89	86	84	83
4	99	91	86	82	97	90	85	82	88	84	81		86	83	80		84	81	79	77
5	94	86	80	76	92	85	80	76	83	79	75		82	78	75		80	77	74	73
6	90	81	75	71	88	80	75	71	79	74	71		77	73	70		76	73	70	68
7	85	77	71	67	84	76	71	67	75	70	66		74	69	66		72	69	66	64
8	82	72	67	63	80	72	67	63	71	66	63		70	65	62		69	65	62	61
9	78	69	63	59	77	68	63	59	67	62	59		66	62	59		66	62	59	57
10	74	65	60	56	74	65	60	56	64	59	56		63	59	56		63	58	56	54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	169863
5°	166634
10°	153883
15°	137127
20°	117107
25°	98350
30°	77206
35°	40008
40°	19105
45°	7521
50°	1980
55°	552
60°	366
65°	323
70°	264
75°	348
80°	267
85°	533



TEST NUMBER: P364946

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8040-F6LBXVM1-LI-BL87

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	563.5	12.8
10°-20°	1347.7	30.5
20°-30°	1487.9	33.7
30°-40°	818.7	18.5
40°-50°	173.1	3.9
50°-60°	14.6	0.3
60°-70°	4.5	0.1
70°-80°	3.3	0.1
80°-90°	1.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3399.1	77.0
0°-40°	4217.9	95.5
0°-60°	4405.6	99.8
0°-90°	4415.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4415.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6219	
5°	6077	564
15°	4849	1348
25°	3263	1488
35°	1200	819
45°	195	173
55°	12	15
65°	5	5
75°	3	3
85°	2	2
90°	0	



TEST NUMBER: P364946

CATALOG NUMBER: FLD6BX50D010TE-FEU6B35-8040-F6LBXVM1-LI-BL87

CANDELA DISTRIBUTION (FULL):

	0°
0°	6218.6
2.5°	6215.3
5°	6077.2
7.5°	5864.2
10°	5548.0
12.5°	5233.5
15°	4849.1
17.5°	4458.0
20°	4028.7
22.5°	3652.6
25°	3263.2
27.5°	2887.2
30°	2447.8
32.5°	1868.7
35°	1199.8
37.5°	808.7
40°	535.8
42.5°	334.5
45°	194.7
47.5°	99.8
50°	46.6
52.5°	20.0
55°	11.6
57.5°	8.3
60°	6.7
62.5°	5.0
65°	5.0
67.5°	3.3
70°	3.3
72.5°	5.0
75°	3.3
77.5°	1.7
80°	1.7
82.5°	1.7
85°	1.7
87.5°	1.7
90°	0.0

(END OF REPORT)