

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P365739

Luminaire Tested: **FLD6BX60D010TE-FEU6B67-8035-F6LBXVM1-MW-BL89AM**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P365739
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-40)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6BX60D010TE-FEU6B67-8035-F6LBXVM1-MW-BL89AM
Description: VANDAL RESISTANT ENCLOSED BOTTOM LENS, MATTE WHITE REFLECTOR, BOTTOM LENS POLYCARBONATE, OPAL SMOOTH 0.125", 6000LM
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2068.0 lumens
Efficiency: N/A
Efficacy: 35.6 lumens/watt
Spacing Criteria (0/90/45): 1.25 / 1.25 / 1.37
Luminous Opening: Circular (Dia: 0.71' x H: 0')
CIE Type: Direct


Input Watts (W): 58.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P365739

CATALOG NUMBER: FLD6BX60D010TE-FEU6B67-8035-F6LBXVM1-MW-BL89AM

Luminous Intensity Polar Plot





TEST NUMBER: P365739

CATALOG NUMBER: FLD6BX60D010TE-FEU6B67-8035-F6LBXVM1-MW-BL89AM

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	95	98	94	92	94	91	89	90	88	86	84
2	99	91	84	78	96	89	83	77	85	80	75	82	78	74	79	75	72	70
3	90	80	71	65	88	78	70	64	75	69	63	72	67	62	70	65	61	59
4	82	70	62	55	80	69	61	55	67	59	54	64	58	53	62	57	52	50
5	76	63	54	47	74	62	53	47	60	52	46	58	51	46	56	50	45	43
6	70	57	48	41	68	56	47	41	54	46	41	52	45	40	51	45	40	38
7	65	51	42	36	63	50	42	36	49	41	36	47	41	36	46	40	35	33
8	60	47	38	32	59	46	38	32	45	37	32	43	37	32	42	36	32	30
9	56	43	35	29	55	42	34	29	41	34	29	40	33	29	39	33	29	27
10	53	40	32	26	52	39	31	26	38	31	26	37	31	26	36	30	26	24

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	19875
5°	19951
10°	19843
15°	19770
20°	19668
25°	19473
30°	19350
35°	19234
40°	18966
45°	18739
50°	18536
55°	18249
60°	17591
65°	16863
70°	15789
75°	13984
80°	11216
85°	6394



TEST NUMBER: P365739

CATALOG NUMBER: FLD6BX60D010TE-FEU6B67-8035-F6LBXVM1-MW-BL89AM

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	69.0	3.3
10°-20°	197.1	9.5
20°-30°	298.3	14.4
30°-40°	360.1	17.4
40°-50°	374.8	18.1
50°-60°	341.0	16.5
60°-70°	257.9	12.5
70°-80°	140.7	6.8
80°-90°	29.1	1.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	564.4	27.3
0°-40°	924.5	44.7
0°-60°	1640.3	79.3
0°-90°	2068.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2068.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	728	
5°	728	69
15°	699	197
25°	646	298
35°	577	360
45°	485	375
55°	383	341
65°	261	258
75°	132	141
85°	20	29
90°	0	



TEST NUMBER: P365739

CATALOG NUMBER: FLD6BX60D010TE-FEU6B67-8035-F6LBXVM1-MW-BL89AM

CANDELA DISTRIBUTION (FULL):

	0°
0°	727.6
2.5°	729.6
5°	727.6
7.5°	721.5
10°	715.4
12.5°	707.2
15°	699.1
17.5°	686.8
20°	676.6
22.5°	662.4
25°	646.1
27.5°	631.8
30°	613.5
32.5°	595.1
35°	576.8
37.5°	554.4
40°	531.9
42.5°	509.5
45°	485.1
47.5°	462.6
50°	436.2
52.5°	409.7
55°	383.2
57.5°	352.6
60°	322.0
62.5°	291.4
65°	260.9
67.5°	230.3
70°	197.7
72.5°	165.1
75°	132.5
77.5°	101.9
80°	71.3
82.5°	44.8
85°	20.4
87.5°	6.1
90°	0.0

(END OF REPORT)