

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P365069

Luminaire Tested: **FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-LI-BL84**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P365069  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-43)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: FAIL-SAFE  
Catalog Number: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-LI-BL84  
Description: VANDAL RESISTANT ENCLOSED BOTTOM LENS, SPECULAR CLEAR REFLECTOR,  
BOTTOM LENS POLYCARBONATE, CLEAR 0.125", 7000LM  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5954.9 lumens  
Efficiency: N/A  
Efficacy: 81.1 lumens/watt  
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.82  
Luminous Opening: Circular (Dia: 0.71' x H: 0')  
CIE Type: Direct


Input Watts (W): 73.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P365069

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-LI-BL84

### Luminous Intensity Polar Plot





TEST NUMBER: P365069

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-LI-BL84

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98	97	96	94
2	109	104	100	97	106	102	99	96	99	96	94		96	94	92		93	91	90	88
3	103	97	93	89	101	96	92	88	93	90	87		91	88	85		89	86	84	83
4	99	91	86	82	97	90	85	82	88	84	81		86	83	80		84	81	79	77
5	94	86	80	76	92	85	80	76	83	79	75		82	78	75		80	77	74	73
6	90	81	75	71	88	80	75	71	79	74	71		77	73	70		76	73	70	68
7	85	77	71	67	84	76	71	67	75	70	66		74	69	66		72	69	66	64
8	82	72	67	63	80	72	67	63	71	66	63		70	65	62		69	65	62	61
9	78	69	63	59	77	68	63	59	67	62	59		66	62	59		66	62	59	57
10	74	65	60	56	74	65	60	56	64	59	56		63	59	56		63	58	56	54

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	229112
5°	224759
10°	207559
15°	184958
20°	157957
25°	132657
30°	104139
35°	53963
40°	25770
45°	10144
50°	2669
55°	748
60°	492
65°	433
70°	359
75°	475
80°	346
85°	689



TEST NUMBER: P365069

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-LI-BL84

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	760.1	12.8
10°-20°	1817.8	30.5
20°-30°	2007.0	33.7
30°-40°	1104.3	18.5
40°-50°	233.4	3.9
50°-60°	19.7	0.3
60°-70°	6.1	0.1
70°-80°	4.4	0.1
80°-90°	2.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4584.8	77.0
0°-40°	5689.1	95.5
0°-60°	5942.3	99.8
0°-90°	5954.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5954.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	8388	
5°	8197	760
15°	6540	1818
25°	4402	2007
35°	1618	1104
45°	263	233
55°	16	20
65°	7	6
75°	4	4
85°	2	2
90°	0	



TEST NUMBER: P365069

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-LI-BL84

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	8387.7
2.5°	8383.2
5°	8197.0
7.5°	7909.7
10°	7483.2
12.5°	7059.0
15°	6540.5
17.5°	6013.0
20°	5434.0
22.5°	4926.7
25°	4401.5
27.5°	3894.2
30°	3301.7
32.5°	2520.6
35°	1618.3
37.5°	1090.8
40°	722.7
42.5°	451.1
45°	262.6
47.5°	134.7
50°	62.8
52.5°	26.9
55°	15.7
57.5°	11.2
60°	9.0
62.5°	6.7
65°	6.7
67.5°	4.5
70°	4.5
72.5°	6.7
75°	4.5
77.5°	2.2
80°	2.2
82.5°	2.2
85°	2.2
87.5°	2.2
90°	0.0

(END OF REPORT)