

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P366511

Luminaire Tested: **FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-WMH-BL86**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P366511
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1910-544-47)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-WMH-BL86
Description: VANDAL RESISTANT ENCLOSED BOTTOM LENS, WARM HAZE REFLECTOR, BOTTOM LENS POLYCARBONATE, CLEAR 0.250", 7000LM
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5789.0 lumens
Efficiency: N/A
Efficacy: 78.9 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.85
Luminous Opening: Circular (Dia: 0.71' x H: 0')
CIE Type: Direct


Input Watts (W): 73.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P366511

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-WMH-BL86

Luminous Intensity Polar Plot





TEST NUMBER: P366511

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-WMH-BL86

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98	97	96	94
2	108	104	100	97	106	102	98	95	99	96	93		96	93	91		93	91	89	88
3	103	97	92	88	101	96	91	88	93	89	86		91	88	85		88	86	84	82
4	98	91	86	82	96	90	85	81	88	83	80		86	82	79		84	81	78	77
5	93	85	80	76	92	85	79	75	83	78	75		81	77	74		80	76	73	72
6	89	80	75	71	88	80	74	70	78	73	70		77	73	69		76	72	69	68
7	85	76	70	66	83	75	70	66	74	69	65		73	68	65		72	68	65	63
8	81	72	66	62	80	71	66	62	70	65	62		69	65	61		68	64	61	60
9	77	68	62	58	76	67	62	58	66	62	58		66	61	58		65	61	58	56
10	74	64	59	55	73	64	59	55	63	58	55		62	58	55		62	58	55	53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	203652
5°	202795
10°	192645
15°	174989
20°	152271
25°	129459
30°	101836
35°	58102
40°	26144
45°	11006
50°	3472
55°	1052
60°	727
65°	569
70°	527
75°	697
80°	346
85°	689



TEST NUMBER: P366511

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-WMH-BL86

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	691.8	12.0
10°-20°	1721.3	29.7
20°-30°	1950.6	33.7
30°-40°	1130.8	19.5
40°-50°	250.8	4.3
50°-60°	27.5	0.5
60°-70°	9.0	0.2
70°-80°	5.8	0.1
80°-90°	1.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4363.7	75.4
0°-40°	5494.4	94.9
0°-60°	5772.7	99.7
0°-90°	5789.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5789.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7456	
5°	7396	692
15°	6188	1721
25°	4295	1951
35°	1742	1131
45°	285	251
55°	22	27
65°	9	9
75°	7	6
85°	2	1
90°	0	



TEST NUMBER: P366511

CATALOG NUMBER: FLD6BX70D010TE-FEU6B67-8027-F6LBXVM1-WMH-BL86

CANDELA DISTRIBUTION (FULL):

0°	
0°	7455.6
2.5°	7462.3
5°	7396.0
7.5°	7234.8
10°	6945.5
12.5°	6594.4
15°	6188.0
17.5°	5759.6
20°	5238.4
22.5°	4768.0
25°	4295.4
27.5°	3791.9
30°	3228.7
32.5°	2564.0
35°	1742.4
37.5°	1119.7
40°	733.2
42.5°	479.2
45°	284.9
47.5°	159.0
50°	81.7
52.5°	37.5
55°	22.1
57.5°	17.7
60°	13.3
62.5°	11.0
65°	8.8
67.5°	6.6
70°	6.6
72.5°	6.6
75°	6.6
77.5°	4.4
80°	2.2
82.5°	2.2
85°	2.2
87.5°	0.0
90°	0.0

(END OF REPORT)