

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P574048

Luminaire Tested: **FLD6C-02-D010 FEU6C-X-90-50 F6X-M-X-H**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P574048
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P203254)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD6C-02-D010 FEU6C-X-90-50 F6X-M-X-H
Description: 6 INCH FAIL-SAFE LED DOWNLIGHT WITH 5000K, 90 CRI LEDS, 6LBMH TRIM

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 255.0 lumens
Efficiency: N/A
Efficacy: 72.9 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.93
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 3.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P574048

CATALOG NUMBER: FLD6C-02-D010 FEU6C-X-90-50 F6X-M-X-H

Luminous Intensity Polar Plot





TEST NUMBER: P574048

CATALOG NUMBER: FLD6C-02-D010 FEU6C-X-90-50 F6X-M-X-H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	92																			
2	107	102	97	93	105	100	96	92	97	93	90	94	91	88	91	89	87	85																			
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78																			
4	95	87	81	76	93	86	80	76	84	79	75	82	78	74	80	76	73	72																			
5	90	81	75	70	88	80	74	70	78	73	69	76	72	68	75	71	68	66																			
6	85	75	69	64	83	75	69	64	73	68	64	72	67	63	70	66	63	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	76	66	60	55	75	65	59	55	64	59	55	63	58	55	62	58	54	53																			
9	72	62	56	51	71	61	55	51	60	55	51	60	55	51	59	54	51	49																			
10	69	58	52	48	68	58	52	48	57	52	48	56	51	48	55	51	48	46																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	13837
5°	13587
10°	12892
15°	12089
20°	11259
25°	10374
30°	8647
35°	6090
40°	3886
45°	2318
50°	1365
55°	870
60°	603
65°	428
70°	289
75°	233
80°	126
85°	0



TEST NUMBER: P574048

CATALOG NUMBER: FLD6C-02-D010 FEU6C-X-90-50 F6X-M-X-H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	23.1	9.0
10°-20°	59.7	23.4
20°-30°	77.4	30.3
30°-40°	57.4	22.5
40°-50°	24.2	9.5
50°-60°	8.6	3.4
60°-70°	3.3	1.3
70°-80°	1.2	0.5
80°-90°	0.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	160.1	62.8
0°-40°	217.5	85.3
0°-60°	250.4	98.2
0°-90°	255.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	255.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	252	
5°	247	23
15°	213	60
25°	172	77
35°	91	57
45°	30	24
55°	9	9
65°	3	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P574048

CATALOG NUMBER: FLD6C-02-D010 FEU6C-X-90-50 F6X-M-X-H

CANDELA DISTRIBUTION (FULL):

	0°
0°	252.4
2.5°	251.6
5°	246.9
7.5°	240.0
10°	231.6
12.5°	222.5
15°	213.0
17.5°	202.5
20°	193.0
22.5°	183.2
25°	171.5
27.5°	155.5
30°	136.6
32.5°	114.3
35°	91.0
37.5°	71.4
40°	54.3
42.5°	40.4
45°	29.9
47.5°	21.8
50°	16.0
52.5°	12.0
55°	9.1
57.5°	6.9
60°	5.5
62.5°	4.0
65°	3.3
67.5°	2.5
70°	1.8
72.5°	1.5
75°	1.1
77.5°	0.7
80°	0.4
82.5°	0.4
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)