

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P578898

Luminaire Tested: **FLD6C-65-D010 FEU6C-X-90-50 F6X-W-X-LI**

Issue Date: 3/1/2023



**Test Information**

Test Method: LM-79-08  
Report Number: P578898  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205209)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/1/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: FAIL-SAFE  
Catalog Number: FLD6C-65-D010 FEU6C-X-90-50 F6X-W-X-LI  
Description: 6 INCH FAIL-SAFE LED DOWNLIGHT WITH 5000K, 90 CRI LEDS, 6LBWLI TRIM

Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 7141.1 lumens  
Efficiency: N/A  
Efficacy: 98.6 lumens/watt  
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.18  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct

Input Watts (W): 72.4  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P578898

CATALOG NUMBER: FLD6C-65-D010 FEU6C-X-90-50 F6X-W-X-LI

### Luminous Intensity Polar Plot





TEST NUMBER: P578898

CATALOG NUMBER: FLD6C-65-D010 FEU6C-X-90-50 F6X-W-X-LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	113	110	107	104	110	107	105	103	103	101	99	100	98	97	96	95	94	92				92
2	106	101	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83				83
3	100	92	87	82	97	91	86	81	88	84	80	86	82	79	83	80	77	76				76
4	93	85	78	73	92	84	78	73	81	76	72	79	75	71	77	74	70	69				69
5	88	78	71	66	86	77	71	66	75	70	65	73	69	65	72	68	64	63				63
6	82	72	65	60	81	71	65	60	70	64	59	68	63	59	67	62	59	57				57
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52				52
8	73	62	55	50	71	61	55	50	60	54	50	59	54	50	58	53	49	48				48
9	69	57	51	46	67	57	50	46	56	50	46	55	50	46	54	49	46	44				44
10	65	54	47	43	64	53	47	42	52	46	42	51	46	42	51	46	42	41				41

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	244564
5°	246824
10°	253731
15°	260081
20°	264028
25°	258571
30°	242423
35°	216744
40°	175557
45°	116128
50°	58702
55°	24764
60°	7982
65°	3139
70°	2613
75°	1737
80°	0
85°	0



TEST NUMBER: P578898

CATALOG NUMBER: FLD6C-65-D010 FEU6C-X-90-50 F6X-W-X-LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	430.4	6.0
10°-20°	1293.5	18.1
20°-30°	1949.9	27.3
30°-40°	1995.9	27.9
40°-50°	1162.7	16.3
50°-60°	267.2	3.7
60°-70°	32.8	0.5
70°-80°	8.6	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3673.8	51.4
0°-40°	5669.7	79.4
0°-60°	7099.6	99.4
0°-90°	7141.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7141.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4461	
5°	4485	430
15°	4583	1294
25°	4275	1950
35°	3239	1996
45°	1498	1163
55°	259	267
65°	24	33
75°	8	9
85°	0	0
90°	0	



TEST NUMBER: P578898

CATALOG NUMBER: FLD6C-65-D010 FEU6C-X-90-50 F6X-W-X-LI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4461.2
2.5°	4453.0
5°	4485.3
7.5°	4517.6
10°	4558.1
12.5°	4566.3
15°	4582.6
17.5°	4566.3
20°	4525.8
22.5°	4396.2
25°	4274.8
27.5°	4080.6
30°	3829.7
32.5°	3570.6
35°	3238.7
37.5°	2866.0
40°	2453.2
42.5°	1991.7
45°	1497.9
47.5°	1044.3
50°	688.3
52.5°	437.3
55°	259.1
57.5°	137.7
60°	72.8
62.5°	40.5
65°	24.2
67.5°	24.2
70°	16.3
72.5°	8.2
75°	8.2
77.5°	8.2
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC







— 0°-180°







(END OF REPORT)