

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C100D010 FEU4C1009040 F4LC-DFSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C100D010 FEU4C1009040 F4LC-DFSSQ-MW
 Description: 4 INCH 10000 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 4000K, 90CRI LEDS AND F4LC-DFSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 10098.0 lumens
 Efficiency: N/A
 Efficacy: 88.3 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 114.4
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C100D010 FEU4C1009040 F4LC-DFSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C100D010 FEU4C1009040 F4LC-DFSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89				89
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77				77
3	95	86	79	74	93	85	78	73	82	76	72	79	74	71	77	73	69	67				67
4	88	77	70	64	86	76	69	63	74	67	63	71	66	62	69	65	61	59				59
5	81	70	62	56	79	69	61	56	67	60	55	65	59	54	63	58	54	52				52
6	75	63	55	49	73	62	55	49	61	54	49	59	53	48	57	52	48	46				46
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41				41
8	65	53	45	40	64	52	45	39	51	44	39	50	44	39	49	43	39	37				37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	35	45	39	35	33				33
10	57	45	38	33	56	44	37	33	44	37	32	43	37	32	42	36	32	31				31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	456122	456122	456122
5°	448760	454601	455898
10°	452636	451323	453283
15°	444712	445361	446710
20°	434363	441253	439199
25°	432488	432488	435341
30°	420427	423425	424182
35°	407310	411280	404153
40°	388213	395796	392420
45°	367408	375663	363737
50°	323562	351783	321551
55°	262041	321912	263202
60°	191762	266927	187902
65°	116531	190093	113471
70°	45449	102323	43587
75°	4996	27588	4996
80°	3778	3778	3778
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C100D010 FEU4C1009040 F4LC-DFSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	446.2	4.4
10°-20°	1262.6	12.5
20°-30°	1873.5	18.6
30°-40°	2170.8	21.5
40°-50°	2081.3	20.6
50°-60°	1530.3	15.2
60°-70°	661.0	6.5
70°-80°	71.3	0.7
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3582.3	35.5
0°-40°	5753.1	57.0
0°-60°	9364.7	92.7
0°-90°	10098.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	10098.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	4727	4727	4727	4727	4727	
5°	4633	4680	4694	4700	4707	442
15°	4452	4479	4458	4465	4472	1255
25°	4062	4056	4062	4069	4089	1860
35°	3458	3478	3492	3485	3431	2162
45°	2692	2699	2753	2713	2666	2047
55°	1558	1719	1914	1712	1565	1402
65°	510	638	833	631	497	525
75°	13	20	74	13	13	41
85°	0	0	0	0	0	1
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C100D010 FEU4C1009040 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2
2.5°	4693.5	4747.2	4754.0	4720.3	4706.9	4686.9	4733.8	4700.3	4713.8	4700.3	4693.5
5°	4633.2	4693.5	4700.3	4700.3	4686.9	4680.1	4700.3	4693.5	4686.9	4673.5	4693.5
7.5°	4606.4	4639.8	4673.5	4633.2	4653.2	4646.6	4693.5	4673.5	4666.6	4666.6	4653.2
10°	4619.8	4612.9	4639.8	4599.5	4612.9	4599.5	4639.8	4639.8	4626.4	4612.9	4606.4
12.5°	4512.1	4565.8	4565.8	4559.3	4545.8	4525.6	4565.8	4592.9	4552.4	4552.4	4545.8
15°	4451.9	4465.3	4471.9	4471.9	4465.3	4478.7	4498.7	4471.9	4478.7	4445.0	4458.4
17.5°	4384.7	4357.9	4377.9	4364.5	4371.3	4384.7	4411.6	4411.6	4371.3	4364.5	4377.9
20°	4230.2	4310.8	4317.6	4277.3	4283.9	4283.9	4331.0	4290.8	4317.6	4283.9	4297.3
22.5°	4156.3	4210.0	4216.8	4163.1	4196.5	4156.3	4203.4	4142.8	4210.0	4163.1	4183.1
25°	4062.3	4055.7	4075.7	4048.9	4055.7	4055.7	4089.1	4062.3	4082.6	4055.7	4062.3
27.5°	3908.0	3961.7	3954.9	3928.0	3941.5	3934.9	4002.0	3928.0	3968.3	3934.9	3948.3
30°	3773.5	3820.7	3807.2	3780.4	3780.4	3760.1	3834.1	3813.8	3807.2	3807.2	3800.4
32.5°	3639.3	3646.1	3632.7	3639.3	3646.1	3619.3	3679.6	3652.7	3646.1	3652.7	3659.6
35°	3457.9	3457.9	3471.4	3451.4	3478.2	3478.2	3531.9	3498.2	3491.6	3471.4	3491.6
37.5°	3296.8	3276.8	3283.4	3283.4	3296.8	3310.3	3337.1	3323.7	3323.7	3303.7	3317.1
40°	3082.1	3068.6	3088.6	3088.6	3108.9	3108.9	3135.8	3122.3	3142.3	3142.3	3142.3
42.5°	2894.1	2894.1	2880.7	2900.7	2907.5	2900.7	2947.8	2941.0	2947.8	2934.4	2941.0
45°	2692.5	2692.5	2679.1	2672.5	2705.9	2699.3	2753.0	2732.8	2759.6	2746.2	2753.0
47.5°	2417.2	2450.9	2430.6	2450.9	2491.1	2498.0	2531.4	2518.0	2544.8	2524.8	2551.7
50°	2155.5	2155.5	2175.5	2202.4	2242.6	2249.5	2289.8	2316.6	2330.0	2336.6	2343.5
52.5°	1880.2	1873.3	1893.6	1927.0	1960.7	1987.6	2027.9	2068.1	2095.0	2135.2	2115.0
55°	1557.7	1571.2	1591.4	1631.7	1685.4	1718.8	1752.5	1806.2	1853.3	1873.3	1913.6
57.5°	1282.4	1269.0	1282.4	1336.1	1396.7	1423.5	1470.6	1524.3	1591.4	1631.7	1645.1
60°	993.7	1000.5	1013.9	1061.0	1107.9	1148.2	1168.4	1255.6	1316.1	1356.4	1383.2
62.5°	732.0	745.4	758.9	799.1	846.0	879.7	913.1	987.1	1040.8	1081.0	1107.9
65°	510.4	517.0	537.2	557.2	604.4	637.8	664.6	725.2	778.9	812.6	832.6
67.5°	315.6	322.2	335.6	362.7	396.1	423.0	449.8	490.1	537.2	570.7	577.5
70°	161.1	167.9	174.5	194.8	221.6	235.1	255.1	288.8	322.2	349.0	362.7
72.5°	53.7	53.7	60.5	74.0	87.4	100.8	107.4	141.1	167.9	181.4	187.9
75°	13.4	13.4	13.4	13.4	13.4	20.3	20.3	40.3	53.7	67.1	74.0
77.5°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	13.4	13.4
80°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C100D010 FEU4C1009040 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2	4727.2
2.5°	4727.2	4713.8	4706.9	4713.8	4713.8	4706.9	4727.2	4754.0	4787.5	4700.3
5°	4720.3	4706.9	4720.3	4680.1	4700.3	4686.9	4713.8	4706.9	4733.8	4706.9
7.5°	4700.3	4673.5	4680.1	4660.1	4686.9	4653.2	4673.5	4713.8	4686.9	4646.6
10°	4633.2	4619.8	4666.6	4599.5	4586.1	4612.9	4666.6	4626.4	4612.9	4626.4
12.5°	4565.8	4565.8	4586.1	4532.4	4539.0	4552.4	4579.3	4552.4	4565.8	4599.5
15°	4492.1	4478.7	4512.1	4471.9	4465.3	4451.9	4478.7	4478.7	4492.1	4471.9
17.5°	4404.7	4384.7	4384.7	4371.3	4364.5	4398.2	4411.6	4418.2	4425.0	4398.2
20°	4297.3	4290.8	4310.8	4290.8	4297.3	4304.2	4304.2	4290.8	4351.0	4277.3
22.5°	4183.1	4203.4	4176.5	4163.1	4176.5	4190.0	4190.0	4196.5	4183.1	4169.7
25°	4069.1	4082.6	4089.1	4048.9	4069.1	4048.9	4096.0	4102.6	4075.7	4089.1
27.5°	3968.3	3948.3	3941.5	3914.6	3928.0	3921.5	3928.0	3928.0	3968.3	3914.6
30°	3813.8	3793.8	3800.4	3780.4	3787.0	3780.4	3787.0	3787.0	3813.8	3807.2
32.5°	3666.1	3646.1	3652.7	3632.7	3632.7	3639.3	3625.9	3625.9	3646.1	3632.7
35°	3525.1	3478.2	3484.8	3478.2	3484.8	3457.9	3457.9	3451.4	3464.8	3431.1
37.5°	3323.7	3303.7	3296.8	3290.3	3296.8	3283.4	3296.8	3276.8	3296.8	3270.0
40°	3142.3	3128.9	3135.8	3095.5	3095.5	3102.1	3088.6	3082.1	3088.6	3115.5
42.5°	2961.2	2934.4	2921.0	2907.5	2914.1	2894.1	2887.3	2873.8	2887.3	2860.4
45°	2746.2	2746.2	2739.6	2705.9	2712.8	2712.8	2685.9	2659.1	2665.6	2665.6
47.5°	2551.7	2538.2	2531.4	2498.0	2491.1	2484.5	2457.4	2437.4	2437.4	2417.2
50°	2336.6	2323.2	2303.2	2269.5	2256.1	2215.8	2195.8	2168.9	2142.1	2142.1
52.5°	2135.2	2088.1	2061.3	2007.6	1987.6	1967.3	1913.6	1893.6	1873.3	1853.3
55°	1893.6	1853.3	1799.6	1739.1	1712.3	1678.6	1624.9	1584.6	1557.7	1564.6
57.5°	1658.6	1591.4	1537.7	1457.2	1423.5	1403.2	1349.5	1295.8	1269.0	1269.0
60°	1369.8	1316.1	1249.0	1175.0	1148.2	1114.7	1047.4	1013.9	993.7	973.7
62.5°	1094.5	1054.2	993.7	899.7	879.7	846.0	799.1	758.9	738.6	738.6
65°	819.1	778.9	725.2	658.1	631.2	604.4	564.1	523.8	503.5	497.0
67.5°	577.5	530.4	483.5	429.8	409.6	396.1	355.9	329.0	315.6	308.8
70°	349.0	322.2	288.8	248.5	228.2	214.8	187.9	167.9	161.1	154.5
72.5°	181.4	161.1	134.2	107.4	94.0	80.5	67.1	53.7	47.1	47.1
75°	67.1	53.7	33.7	20.3	13.4	13.4	13.4	13.4	13.4	13.4
77.5°	13.4	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
80°	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)