

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C30D010 FEU4C309050 F4LC-CSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C30D010 FEU4C309050 F4LC-CSSQ-MW
 Description: 4 INCH 3000 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 5000K, 90CRI LEDS AND F4LC-CSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 2988.0 lumens
 Efficiency: N/A
 Efficacy: 94.6 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 31.6
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C30D010 FEU4C309050 F4LC-CSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#

CATALOG NUMBER: FLDSQ4C30D010 FEU4C309050 F4LC-CSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89				89
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77				77
3	95	86	79	74	93	85	78	73	82	76	72	79	74	71	77	73	69	67				67
4	88	77	70	64	86	76	69	63	74	67	63	71	66	62	69	65	61	59				59
5	81	70	62	56	79	69	61	56	67	60	55	65	59	54	63	58	54	52				52
6	75	63	55	49	73	62	55	49	61	54	49	59	53	48	57	52	48	46				46
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41				41
8	65	53	45	40	64	52	45	39	51	44	39	50	44	39	49	43	39	37				37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	35	45	39	35	33				33
10	57	45	38	33	56	44	37	33	44	37	32	43	37	32	42	36	32	31				31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	134969	134969	134969
5°	132792	134516	134903
10°	133935	133543	134121
15°	131589	131788	132178
20°	128526	130570	129964
25°	127969	127969	128821
30°	124407	125287	125521
35°	120524	121702	119593
40°	114873	117115	116120
45°	108714	111157	107636
50°	95740	104086	95140
55°	77534	95248	77887
60°	56735	78986	55597
65°	34475	56256	33585
70°	13457	30271	12893
75°	1491	8164	1491
80°	1111	1111	1111
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C30D010 FEU4C309050 F4LC-CSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	132.0	4.4
10°-20°	373.6	12.5
20°-30°	554.4	18.6
30°-40°	642.3	21.5
40°-50°	615.9	20.6
50°-60°	452.8	15.2
60°-70°	195.6	6.5
70°-80°	21.1	0.7
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1060.0	35.5
0°-40°	1702.4	57.0
0°-60°	2771.0	92.7
0°-90°	2988.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2988.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1399	1399	1399	1399	1399	
5°	1371	1385	1389	1391	1393	131
15°	1317	1325	1319	1321	1323	371
25°	1202	1200	1202	1204	1210	550
35°	1023	1029	1033	1031	1015	640
45°	797	799	815	803	789	606
55°	461	509	566	507	463	415
65°	151	189	246	187	147	155
75°	4	6	22	4	4	12
85°	0	0	0	0	0	0
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C30D010 FEU4C309050 F4LC-CSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8
2.5°	1388.8	1404.7	1406.7	1396.8	1392.8	1386.9	1400.7	1390.8	1394.8	1390.8	1388.8
5°	1371.0	1388.8	1390.8	1390.8	1386.9	1384.8	1390.8	1388.8	1386.9	1382.9	1388.8
7.5°	1363.0	1372.9	1382.9	1371.0	1376.9	1374.9	1388.8	1382.9	1380.9	1380.9	1376.9
10°	1367.0	1365.0	1372.9	1361.0	1365.0	1361.0	1372.9	1372.9	1368.9	1365.0	1363.0
12.5°	1335.1	1351.0	1351.0	1349.1	1345.1	1339.1	1351.0	1359.1	1347.1	1347.1	1345.1
15°	1317.3	1321.3	1323.2	1323.2	1321.3	1325.2	1331.2	1323.2	1325.2	1315.3	1319.3
17.5°	1297.4	1289.5	1295.4	1291.4	1293.5	1297.4	1305.4	1305.4	1293.5	1291.4	1295.4
20°	1251.7	1275.6	1277.6	1265.7	1267.6	1267.6	1281.6	1269.6	1277.6	1267.6	1271.6
22.5°	1229.8	1245.7	1247.8	1231.9	1241.8	1229.8	1243.8	1225.9	1245.7	1231.9	1237.8
25°	1202.0	1200.1	1206.0	1198.1	1200.1	1200.1	1210.0	1202.0	1208.0	1200.1	1202.0
27.5°	1156.4	1172.3	1170.3	1162.3	1166.3	1164.3	1184.2	1162.3	1174.2	1164.3	1168.3
30°	1116.6	1130.5	1126.6	1118.6	1118.6	1112.6	1134.5	1128.5	1126.6	1126.6	1124.5
32.5°	1076.9	1078.9	1074.9	1076.9	1078.9	1070.9	1088.8	1080.8	1078.9	1080.8	1082.9
35°	1023.2	1023.2	1027.2	1021.3	1029.2	1029.2	1045.1	1035.1	1033.2	1027.2	1033.2
37.5°	975.5	969.6	971.6	971.6	975.5	979.5	987.5	983.5	983.5	977.6	981.5
40°	912.0	908.0	913.9	913.9	919.9	919.9	927.9	923.9	929.8	929.8	929.8
42.5°	856.4	856.4	852.4	858.3	860.3	858.3	872.3	870.2	872.3	868.3	870.2
45°	796.7	796.7	792.7	790.8	800.7	798.7	814.6	808.6	816.6	812.6	814.6
47.5°	715.2	725.2	719.2	725.2	737.1	739.1	749.0	745.1	753.0	747.1	755.0
50°	637.8	637.8	643.7	651.7	663.6	665.6	677.5	685.5	689.5	691.4	693.4
52.5°	556.3	554.3	560.3	570.2	580.2	588.1	600.0	612.0	619.9	631.8	625.8
55°	460.9	464.9	470.9	482.8	498.7	508.6	518.6	534.5	548.4	554.3	566.2
57.5°	379.5	375.5	379.5	395.4	413.3	421.2	435.2	451.0	470.9	482.8	486.8
60°	294.0	296.0	300.0	314.0	327.8	339.7	345.7	371.5	389.4	401.4	409.3
62.5°	216.6	220.6	224.5	236.5	250.3	260.3	270.2	292.1	308.0	319.9	327.8
65°	151.0	153.0	159.0	164.9	178.8	188.7	196.7	214.6	230.5	240.4	246.4
67.5°	93.4	95.3	99.3	107.3	117.2	125.2	133.1	145.0	159.0	168.9	170.9
70°	47.7	49.7	51.6	57.6	65.6	69.6	75.5	85.4	95.3	103.3	107.3
72.5°	15.9	15.9	17.9	21.9	25.9	29.8	31.8	41.7	49.7	53.7	55.6
75°	4.0	4.0	4.0	4.0	4.0	6.0	6.0	11.9	15.9	19.9	21.9
77.5°	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	4.0	4.0
80°	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C30D010 FEU4C309050 F4LC-CSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8	1398.8
2.5°	1398.8	1394.8	1392.8	1394.8	1394.8	1392.8	1398.8	1406.7	1416.6	1390.8
5°	1396.8	1392.8	1396.8	1384.8	1390.8	1386.9	1394.8	1392.8	1400.7	1392.8
7.5°	1390.8	1382.9	1384.8	1378.9	1386.9	1376.9	1382.9	1394.8	1386.9	1374.9
10°	1371.0	1367.0	1380.9	1361.0	1357.0	1365.0	1380.9	1368.9	1365.0	1368.9
12.5°	1351.0	1351.0	1357.0	1341.1	1343.1	1347.1	1355.0	1347.1	1351.0	1361.0
15°	1329.2	1325.2	1335.1	1323.2	1321.3	1317.3	1325.2	1325.2	1329.2	1323.2
17.5°	1303.4	1297.4	1297.4	1293.5	1291.4	1301.4	1305.4	1307.3	1309.4	1301.4
20°	1271.6	1269.6	1275.6	1269.6	1271.6	1273.6	1273.6	1269.6	1287.5	1265.7
22.5°	1237.8	1243.8	1235.8	1231.9	1235.8	1239.8	1239.8	1241.8	1237.8	1233.8
25°	1204.1	1208.0	1210.0	1198.1	1204.1	1198.1	1212.0	1213.9	1206.0	1210.0
27.5°	1174.2	1168.3	1166.3	1158.3	1162.3	1160.4	1162.3	1162.3	1174.2	1158.3
30°	1128.5	1122.6	1124.5	1118.6	1120.6	1118.6	1120.6	1120.6	1128.5	1126.6
32.5°	1084.8	1078.9	1080.8	1074.9	1074.9	1076.9	1072.9	1072.9	1078.9	1074.9
35°	1043.1	1029.2	1031.1	1029.2	1031.1	1023.2	1023.2	1021.3	1025.2	1015.3
37.5°	983.5	977.6	975.5	973.6	975.5	971.6	975.5	969.6	975.5	967.6
40°	929.8	925.8	927.9	916.0	916.0	917.9	913.9	912.0	913.9	921.9
42.5°	876.2	868.3	864.3	860.3	862.3	856.4	854.3	850.4	854.3	846.4
45°	812.6	812.6	810.6	800.7	802.7	802.7	794.8	786.8	788.8	788.8
47.5°	755.0	751.1	749.0	739.1	737.1	735.2	727.2	721.2	721.2	715.2
50°	691.4	687.4	681.5	671.5	667.6	655.7	649.7	641.8	633.8	633.8
52.5°	631.8	617.9	609.9	594.0	588.1	582.1	566.2	560.3	554.3	548.4
55°	560.3	548.4	532.5	514.6	506.7	496.7	480.8	468.9	460.9	463.0
57.5°	490.8	470.9	455.0	431.2	421.2	415.2	399.3	383.4	375.5	375.5
60°	405.3	389.4	369.6	347.7	339.7	329.9	309.9	300.0	294.0	288.1
62.5°	323.9	311.9	294.0	266.2	260.3	250.3	236.5	224.5	218.6	218.6
65°	242.4	230.5	214.6	194.7	186.8	178.8	166.9	155.0	149.0	147.1
67.5°	170.9	156.9	143.1	127.2	121.2	117.2	105.3	97.4	93.4	91.4
70°	103.3	95.3	85.4	73.5	67.5	63.6	55.6	49.7	47.7	45.7
72.5°	53.7	47.7	39.7	31.8	27.8	23.8	19.9	15.9	13.9	13.9
75°	19.9	15.9	10.0	6.0	4.0	4.0	4.0	4.0	4.0	4.0
77.5°	4.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
80°	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)