

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C45D010 FEU4C459040 F4LC-DFSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.



Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C45D010 FEU4C459040 F4LC-DFSSQ-MW
 Description: 4 INCH 4500 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 4000K, 90CRI LEDS AND F4LC-DFSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 4643.0 lumens
 Efficiency: N/A
 Efficacy: 93.6 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 49.6
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C45D010 FEU4C459040 F4LC-DFSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#

CATALOG NUMBER: FLDSQ4C45D010 FEU4C459040 F4LC-DFSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	111	108	104	101	109	105	102	100	101	99	96		97	95	94		94	92	91	89
2	103	96	91	86	100	94	89	85	91	87	83		88	84	81		85	82	79	77
3	95	86	79	74	93	85	78	73	82	76	72		79	74	71		77	73	69	67
4	88	77	70	64	86	76	69	63	74	67	63		71	66	62		69	65	61	59
5	81	70	62	56	79	69	61	56	67	60	55		65	59	54		63	58	54	52
6	75	63	55	49	73	62	55	49	61	54	49		59	53	48		57	52	48	46
7	70	58	50	44	68	57	49	44	55	49	44		54	48	43		53	47	43	41
8	65	53	45	40	64	52	45	39	51	44	39		50	44	39		49	43	39	37
9	61	49	41	36	60	48	41	36	47	40	36		46	40	35		45	39	35	33
10	57	45	38	33	56	44	37	33	44	37	32		43	37	32		42	36	32	31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	209719	209719	209719
5°	206335	209018	209619
10°	208124	207516	208418
15°	204470	204780	205389
20°	199715	202888	201943
25°	198853	198853	200173
30°	193306	194688	195033
35°	187276	189102	185827
40°	178494	181983	180434
45°	168932	172726	167240
50°	148774	161744	147843
55°	120481	148020	121020
60°	88172	122734	86396
65°	53585	87398	52169
70°	20905	47057	20030
75°	2311	12675	2311
80°	1723	1723	1723
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C45D010 FEU4C459040 F4LC-DFSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	205.2	4.4
10°-20°	580.6	12.5
20°-30°	861.4	18.6
30°-40°	998.1	21.5
40°-50°	957.0	20.6
50°-60°	703.6	15.2
60°-70°	303.9	6.5
70°-80°	32.8	0.7
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1647.1	35.5
0°-40°	2645.3	57.0
0°-60°	4305.9	92.7
0°-90°	4643.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4643.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2174	2174	2174	2174	2174	
5°	2130	2152	2158	2161	2164	203
15°	2047	2059	2050	2053	2056	577
25°	1868	1865	1868	1871	1880	855
35°	1590	1599	1605	1602	1578	994
45°	1238	1241	1266	1247	1226	941
55°	716	790	880	787	719	645
65°	235	293	383	290	228	241
75°	6	9	34	6	6	19
85°	0	0	0	0	0	0
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C45D010 FEU4C459040 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5
2.5°	2158.0	2182.7	2185.9	2170.4	2164.2	2155.0	2176.6	2161.2	2167.4	2161.2	2158.0
5°	2130.3	2158.0	2161.2	2161.2	2155.0	2151.9	2161.2	2158.0	2155.0	2148.8	2158.0
7.5°	2118.0	2133.4	2148.8	2130.3	2139.5	2136.5	2158.0	2148.8	2145.7	2145.7	2139.5
10°	2124.2	2121.0	2133.4	2114.8	2121.0	2114.8	2133.4	2133.4	2127.2	2121.0	2118.0
12.5°	2074.7	2099.3	2099.3	2096.3	2090.1	2080.8	2099.3	2111.8	2093.2	2093.2	2090.1
15°	2046.9	2053.1	2056.1	2056.1	2053.1	2059.3	2068.5	2056.1	2059.3	2043.8	2050.0
17.5°	2016.1	2003.7	2012.9	2006.8	2009.9	2016.1	2028.4	2028.4	2009.9	2006.8	2012.9
20°	1945.0	1982.1	1985.2	1966.7	1969.7	1969.7	1991.4	1972.9	1985.2	1969.7	1975.9
22.5°	1911.0	1935.7	1938.9	1914.2	1929.5	1911.0	1932.7	1904.9	1935.7	1914.2	1923.4
25°	1867.8	1864.8	1874.0	1861.6	1864.8	1864.8	1880.2	1867.8	1877.1	1864.8	1867.8
27.5°	1796.9	1821.6	1818.4	1806.1	1812.3	1809.2	1840.1	1806.1	1824.6	1809.2	1815.4
30°	1735.0	1756.7	1750.5	1738.2	1738.2	1728.9	1762.9	1753.6	1750.5	1750.5	1747.4
32.5°	1673.3	1676.5	1670.3	1673.3	1676.5	1664.1	1691.8	1679.5	1676.5	1679.5	1682.6
35°	1589.9	1589.9	1596.1	1586.9	1599.3	1599.3	1623.9	1608.5	1605.4	1596.1	1605.4
37.5°	1515.9	1506.7	1509.7	1509.7	1515.9	1522.0	1534.4	1528.2	1528.2	1519.0	1525.2
40°	1417.1	1410.9	1420.1	1420.1	1429.5	1429.5	1441.8	1435.6	1444.8	1444.8	1444.8
42.5°	1330.7	1330.7	1324.5	1333.7	1336.9	1333.7	1355.4	1352.2	1355.4	1349.2	1352.2
45°	1238.0	1238.0	1231.8	1228.8	1244.2	1241.1	1265.8	1256.5	1268.9	1262.7	1265.8
47.5°	1111.4	1126.9	1117.6	1126.9	1145.4	1148.6	1163.9	1157.7	1170.1	1160.9	1173.2
50°	991.1	991.1	1000.3	1012.6	1031.2	1034.3	1052.8	1065.2	1071.3	1074.4	1077.5
52.5°	864.5	861.4	870.7	886.0	901.5	913.9	932.4	950.9	963.3	981.8	972.5
55°	716.2	722.4	731.7	750.2	774.9	790.3	805.8	830.5	852.2	861.4	879.9
57.5°	589.6	583.5	589.6	614.3	642.2	654.5	676.2	700.9	731.7	750.2	756.4
60°	456.9	460.0	466.2	487.9	509.4	527.9	537.2	577.3	605.1	623.7	636.0
62.5°	336.6	342.7	348.9	367.4	389.0	404.5	419.8	453.9	478.5	497.1	509.4
65°	234.7	237.7	247.0	256.2	277.9	293.2	305.6	333.4	358.1	373.6	382.8
67.5°	145.1	148.1	154.3	166.8	182.1	194.5	206.8	225.4	247.0	262.4	265.5
70°	74.1	77.2	80.2	89.6	101.9	108.1	117.3	132.8	148.1	160.5	166.8
72.5°	24.7	24.7	27.8	34.0	40.2	46.4	49.4	64.9	77.2	83.4	86.4
75°	6.2	6.2	6.2	6.2	6.2	9.3	9.3	18.5	24.7	30.9	34.0
77.5°	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	6.2	6.2
80°	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C45D010 FEU4C459040 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5	2173.5
2.5°	2173.5	2167.4	2164.2	2167.4	2167.4	2164.2	2173.5	2185.9	2201.2	2161.2
5°	2170.4	2164.2	2170.4	2151.9	2161.2	2155.0	2167.4	2164.2	2176.6	2164.2
7.5°	2161.2	2148.8	2151.9	2142.7	2155.0	2139.5	2148.8	2167.4	2155.0	2136.5
10°	2130.3	2124.2	2145.7	2114.8	2108.7	2121.0	2145.7	2127.2	2121.0	2127.2
12.5°	2099.3	2099.3	2108.7	2084.0	2087.0	2093.2	2105.5	2093.2	2099.3	2114.8
15°	2065.5	2059.3	2074.7	2056.1	2053.1	2046.9	2059.3	2059.3	2065.5	2056.1
17.5°	2025.3	2016.1	2016.1	2009.9	2006.8	2022.2	2028.4	2031.4	2034.6	2022.2
20°	1975.9	1972.9	1982.1	1972.9	1975.9	1979.0	1979.0	1972.9	2000.6	1966.7
22.5°	1923.4	1932.7	1920.3	1914.2	1920.3	1926.5	1926.5	1929.5	1923.4	1917.2
25°	1871.0	1877.1	1880.2	1861.6	1871.0	1861.6	1883.3	1886.3	1874.0	1880.2
27.5°	1824.6	1815.4	1812.3	1799.9	1806.1	1803.1	1806.1	1806.1	1824.6	1799.9
30°	1753.6	1744.4	1747.4	1738.2	1741.2	1738.2	1741.2	1741.2	1753.6	1750.5
32.5°	1685.7	1676.5	1679.5	1670.3	1670.3	1673.3	1667.2	1667.2	1676.5	1670.3
35°	1620.8	1599.3	1602.3	1599.3	1602.3	1589.9	1589.9	1586.9	1593.1	1577.6
37.5°	1528.2	1519.0	1515.9	1512.8	1515.9	1509.7	1515.9	1506.7	1515.9	1503.5
40°	1444.8	1438.7	1441.8	1423.3	1423.3	1426.3	1420.1	1417.1	1420.1	1432.5
42.5°	1361.6	1349.2	1343.0	1336.9	1339.9	1330.7	1327.6	1321.4	1327.6	1315.2
45°	1262.7	1262.7	1259.7	1244.2	1247.3	1247.3	1235.0	1222.6	1225.6	1225.6
47.5°	1173.2	1167.1	1163.9	1148.6	1145.4	1142.4	1129.9	1120.7	1120.7	1111.4
50°	1074.4	1068.2	1059.0	1043.5	1037.3	1018.8	1009.6	997.3	984.9	984.9
52.5°	981.8	960.1	947.8	923.1	913.9	904.6	879.9	870.7	861.4	852.2
55°	870.7	852.2	827.5	799.6	787.3	771.8	747.1	728.6	716.2	719.4
57.5°	762.6	731.7	707.0	670.0	654.5	645.2	620.5	595.8	583.5	583.5
60°	629.8	605.1	574.3	540.3	527.9	512.6	481.6	466.2	456.9	447.7
62.5°	503.2	484.7	456.9	413.7	404.5	389.0	367.4	348.9	339.6	339.6
65°	376.6	358.1	333.4	302.6	290.2	277.9	259.4	240.8	231.5	228.5
67.5°	265.5	243.9	222.3	197.6	188.3	182.1	163.6	151.3	145.1	142.0
70°	160.5	148.1	132.8	114.2	104.9	98.8	86.4	77.2	74.1	71.0
72.5°	83.4	74.1	61.7	49.4	43.2	37.0	30.9	24.7	21.7	21.7
75°	30.9	24.7	15.5	9.3	6.2	6.2	6.2	6.2	6.2	6.2
77.5°	6.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
80°	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)