

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C65D010 FEU4C659050 F4LC-DFSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.



Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C65D010 FEU4C659050 F4LC-DFSSQ-MW
 Description: 4 INCH 6500 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 5000K, 90CRI LEDS AND F4LC-DFSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 6784.0 lumens
 Efficiency: N/A
 Efficacy: 93.7 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 72.4
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C65D010 FEU4C659050 F4LC-DFSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C65D010 FEU4C659050 F4LC-DFSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89				89
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77				77
3	95	86	79	74	93	85	78	73	82	76	72	79	74	71	77	73	69	67				67
4	88	77	70	64	86	76	69	63	74	67	63	71	66	62	69	65	61	59				59
5	81	70	62	56	79	69	61	56	67	60	55	65	59	54	63	58	54	52				52
6	75	63	55	49	73	62	55	49	61	54	49	59	53	48	57	52	48	46				46
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41				41
8	65	53	45	40	64	52	45	39	51	44	39	50	44	39	49	43	39	37				37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	35	45	39	35	33				33
10	57	45	38	33	56	44	37	33	44	37	32	43	37	32	42	36	32	31				31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	306429	306429	306429
5°	301488	305411	306283
10°	304092	303201	304524
15°	298759	299208	300107
20°	291810	296441	295065
25°	290550	290550	292466
30°	282450	284467	284979
35°	273641	276303	271520
40°	260807	265908	263629
45°	246835	252375	244365
50°	217374	236333	216023
55°	176046	216268	176819
60°	128832	179334	126227
65°	78288	127695	76233
70°	30525	68751	29284
75°	3355	18528	3355
80°	2556	2556	2556
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C65D010 FEU4C659050 F4LC-DFSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	299.8	4.4
10°-20°	848.3	12.5
20°-30°	1258.6	18.6
30°-40°	1458.4	21.5
40°-50°	1398.3	20.6
50°-60°	1028.1	15.2
60°-70°	444.0	6.5
70°-80°	47.9	0.7
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2406.7	35.5
0°-40°	3865.0	57.0
0°-60°	6291.4	92.7
0°-90°	6784.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6784.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3176	3176	3176	3176	3176	
5°	3113	3144	3153	3158	3162	297
15°	2991	3009	2995	3000	3004	843
25°	2729	2725	2729	2734	2747	1250
35°	2323	2337	2346	2341	2305	1453
45°	1809	1814	1850	1822	1791	1375
55°	1046	1155	1286	1150	1051	942
65°	343	428	559	424	334	352
75°	9	14	50	9	9	28
85°	0	0	0	0	0	1
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C65D010 FEU4C659050 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8
2.5°	3153.2	3189.2	3193.8	3171.2	3162.2	3148.7	3180.2	3157.8	3166.8	3157.8	3153.2
5°	3112.7	3153.2	3157.8	3157.8	3148.7	3144.1	3157.8	3153.2	3148.7	3139.7	3153.2
7.5°	3094.6	3117.1	3139.7	3112.7	3126.1	3121.7	3153.2	3139.7	3135.1	3135.1	3126.1
10°	3103.7	3099.1	3117.1	3090.0	3099.1	3090.0	3117.1	3117.1	3108.1	3099.1	3094.6
12.5°	3031.3	3067.4	3067.4	3063.0	3054.0	3040.3	3067.4	3085.6	3058.4	3058.4	3054.0
15°	2990.8	2999.8	3004.3	3004.3	2999.8	3008.9	3022.3	3004.3	3008.9	2986.2	2995.3
17.5°	2945.7	2927.7	2941.1	2932.1	2936.7	2945.7	2963.8	2963.8	2936.7	2932.1	2941.1
20°	2841.9	2896.0	2900.6	2873.6	2878.0	2878.0	2909.7	2882.6	2900.6	2878.0	2887.0
22.5°	2792.2	2828.3	2832.9	2796.8	2819.3	2792.2	2823.9	2783.2	2828.3	2796.8	2810.3
25°	2729.1	2724.7	2738.1	2720.1	2724.7	2724.7	2747.1	2729.1	2742.7	2724.7	2729.1
27.5°	2625.5	2661.6	2657.0	2638.9	2647.9	2643.5	2688.6	2638.9	2666.0	2643.5	2652.5
30°	2535.1	2566.8	2557.8	2539.7	2539.7	2526.1	2575.8	2562.2	2557.8	2557.8	2553.2
32.5°	2444.9	2449.5	2440.5	2444.9	2449.5	2431.5	2472.0	2454.0	2449.5	2454.0	2458.6
35°	2323.1	2323.1	2332.1	2318.7	2336.7	2336.7	2372.8	2350.2	2345.7	2332.1	2345.7
37.5°	2214.9	2201.4	2205.9	2205.9	2214.9	2223.9	2241.9	2232.9	2232.9	2219.5	2228.5
40°	2070.6	2061.6	2075.0	2075.0	2088.6	2088.6	2106.6	2097.6	2111.1	2111.1	2111.1
42.5°	1944.3	1944.3	1935.3	1948.7	1953.3	1948.7	1980.4	1975.8	1980.4	1971.4	1975.8
45°	1808.9	1808.9	1799.8	1795.4	1817.9	1813.5	1849.5	1835.9	1854.0	1844.9	1849.5
47.5°	1623.9	1646.5	1632.9	1646.5	1673.6	1678.2	1700.6	1691.6	1709.7	1696.2	1714.2
50°	1448.1	1448.1	1461.6	1479.6	1506.6	1511.2	1538.3	1556.3	1565.4	1569.8	1574.4
52.5°	1263.1	1258.5	1272.2	1294.6	1317.3	1335.3	1362.3	1389.4	1407.4	1434.5	1420.9
55°	1046.5	1055.5	1069.2	1096.2	1132.3	1154.7	1177.4	1213.4	1245.1	1258.5	1285.6
57.5°	861.5	852.5	861.5	897.6	938.3	956.3	988.0	1024.1	1069.2	1096.2	1105.2
60°	667.6	672.2	681.2	712.8	744.3	771.4	785.0	843.5	884.2	911.2	929.3
62.5°	491.8	500.8	509.8	536.9	568.4	591.0	613.4	663.1	699.2	726.3	744.3
65°	342.9	347.3	360.9	374.4	406.0	428.5	446.5	487.2	523.3	545.9	559.3
67.5°	212.0	216.4	225.5	243.7	266.1	284.2	302.2	329.3	360.9	383.4	388.0
70°	108.2	112.8	117.2	130.9	148.9	157.9	171.4	194.0	216.4	234.5	243.7
72.5°	36.1	36.1	40.7	49.7	58.7	67.7	72.1	94.8	112.8	121.8	126.3
75°	9.0	9.0	9.0	9.0	9.0	13.6	13.6	27.1	36.1	45.1	49.7
77.5°	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	9.0	9.0
80°	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C65D010 FEU4C659050 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8	3175.8
2.5°	3175.8	3166.8	3162.2	3166.8	3166.8	3162.2	3175.8	3193.8	3216.3	3157.8
5°	3171.2	3162.2	3171.2	3144.1	3157.8	3148.7	3166.8	3162.2	3180.2	3162.2
7.5°	3157.8	3139.7	3144.1	3130.7	3148.7	3126.1	3139.7	3166.8	3148.7	3121.7
10°	3112.7	3103.7	3135.1	3090.0	3081.0	3099.1	3135.1	3108.1	3099.1	3108.1
12.5°	3067.4	3067.4	3081.0	3044.9	3049.4	3058.4	3076.4	3058.4	3067.4	3090.0
15°	3017.9	3008.9	3031.3	3004.3	2999.8	2990.8	3008.9	3008.9	3017.9	3004.3
17.5°	2959.2	2945.7	2945.7	2936.7	2932.1	2954.8	2963.8	2968.2	2972.8	2954.8
20°	2887.0	2882.6	2896.0	2882.6	2887.0	2891.6	2891.6	2882.6	2923.1	2873.6
22.5°	2810.3	2823.9	2805.9	2796.8	2805.9	2814.9	2814.9	2819.3	2810.3	2801.3
25°	2733.7	2742.7	2747.1	2720.1	2733.7	2720.1	2751.7	2756.2	2738.1	2747.1
27.5°	2666.0	2652.5	2647.9	2629.9	2638.9	2634.5	2638.9	2638.9	2666.0	2629.9
30°	2562.2	2548.7	2553.2	2539.7	2544.1	2539.7	2544.1	2544.1	2562.2	2557.8
32.5°	2463.0	2449.5	2454.0	2440.5	2440.5	2444.9	2435.9	2435.9	2449.5	2440.5
35°	2368.2	2336.7	2341.1	2336.7	2341.1	2323.1	2323.1	2318.7	2327.7	2305.1
37.5°	2232.9	2219.5	2214.9	2210.5	2214.9	2205.9	2214.9	2201.4	2214.9	2196.8
40°	2111.1	2102.1	2106.6	2079.6	2079.6	2084.0	2075.0	2070.6	2075.0	2093.0
42.5°	1989.4	1971.4	1962.4	1953.3	1957.8	1944.3	1939.7	1930.7	1939.7	1921.7
45°	1844.9	1844.9	1840.5	1817.9	1822.5	1822.5	1804.4	1786.4	1790.8	1790.8
47.5°	1714.2	1705.2	1700.6	1678.2	1673.6	1669.2	1650.9	1637.5	1637.5	1623.9
50°	1569.8	1560.8	1547.3	1524.7	1515.7	1488.6	1475.2	1457.1	1439.1	1439.1
52.5°	1434.5	1402.8	1384.8	1348.7	1335.3	1321.7	1285.6	1272.2	1258.5	1245.1
55°	1272.2	1245.1	1209.0	1168.4	1150.3	1127.7	1091.6	1064.6	1046.5	1051.1
57.5°	1114.2	1069.2	1033.1	979.0	956.3	942.7	906.6	870.6	852.5	852.5
60°	920.3	884.2	839.1	789.4	771.4	748.9	703.6	681.2	667.6	654.1
62.5°	735.3	708.2	667.6	604.4	591.0	568.4	536.9	509.8	496.2	496.2
65°	550.3	523.3	487.2	442.1	424.1	406.0	379.0	351.9	338.3	333.9
67.5°	388.0	356.3	324.8	288.8	275.2	266.1	239.1	221.0	212.0	207.4
70°	234.5	216.4	194.0	166.9	153.3	144.3	126.3	112.8	108.2	103.8
72.5°	121.8	108.2	90.2	72.1	63.1	54.1	45.1	36.1	31.7	31.7
75°	45.1	36.1	22.6	13.6	9.0	9.0	9.0	9.0	9.0	9.0
77.5°	9.0	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
80°	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)