

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C70D010 FEU4C709035 F4LC-CSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C70D010 FEU4C709035 F4LC-CSSQ-MW
 Description: 4 INCH 7000 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 3500K, 90CRI LEDS AND F4LC-CSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 6971.0 lumens
 Efficiency: N/A
 Efficacy: 89.4 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 78
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C70D010 FEU4C709035 F4LC-CSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#

CATALOG NUMBER: FLDSQ4C70D010 FEU4C709035 F4LC-CSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	111	108	104	101	109	105	102	100	101	99	96		97	95	94		94	92	91	89
2	103	96	91	86	100	94	89	85	91	87	83		88	84	81		85	82	79	77
3	95	86	79	74	93	85	78	73	82	76	72		79	74	71		77	73	69	67
4	88	77	70	64	86	76	69	63	74	67	63		71	66	62		69	65	61	59
5	81	70	62	56	79	69	61	56	67	60	55		65	59	54		63	58	54	52
6	75	63	55	49	73	62	55	49	61	54	49		59	53	48		57	52	48	46
7	70	58	50	44	68	57	49	44	55	49	44		54	48	43		53	47	43	41
8	65	53	45	40	64	52	45	39	51	44	39		50	44	39		49	43	39	37
9	61	49	41	36	60	48	41	36	47	40	36		46	40	35		45	39	35	33
10	57	45	38	33	56	44	37	33	44	37	32		43	37	32		42	36	32	31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	314872	314872	314872
5°	309799	313828	314719
10°	312469	311558	312910
15°	307000	307450	308379
20°	299860	304614	303197
25°	298556	298556	300536
30°	290238	292299	292834
35°	281179	283924	279000
40°	267987	273239	270896
45°	253631	259334	251106
50°	223364	242848	221983
55°	180907	222223	181698
60°	132383	184274	129700
65°	80434	131234	78334
70°	31371	70642	30102
75°	3467	19050	3467
80°	2612	2612	2612
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C70D010 FEU4C709035 F4LC-CSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	308.0	4.4
10°-20°	871.6	12.5
20°-30°	1293.3	18.6
30°-40°	1498.6	21.5
40°-50°	1436.8	20.6
50°-60°	1056.4	15.2
60°-70°	456.3	6.5
70°-80°	49.3	0.7
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2473.0	35.5
0°-40°	3971.6	57.0
0°-60°	6464.8	92.7
0°-90°	6971.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6971.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3263	3263	3263	3263	3263	
5°	3198	3231	3240	3245	3249	305
15°	3073	3092	3078	3082	3087	866
25°	2804	2800	2804	2809	2823	1284
35°	2387	2401	2410	2406	2369	1493
45°	1859	1863	1900	1873	1840	1413
55°	1075	1187	1321	1182	1080	968
65°	352	440	575	436	343	362
75°	9	14	51	9	9	28
85°	0	0	0	0	0	1
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C70D010 FEU4C709035 F4LC-CSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3
2.5°	3240.1	3277.2	3281.9	3258.6	3249.3	3235.5	3267.9	3244.8	3254.1	3244.8	3240.1
5°	3198.5	3240.1	3244.8	3244.8	3235.5	3230.8	3244.8	3240.1	3235.5	3226.3	3240.1
7.5°	3179.9	3203.0	3226.3	3198.5	3212.3	3207.7	3240.1	3226.3	3221.5	3221.5	3212.3
10°	3189.2	3184.5	3203.0	3175.2	3184.5	3175.2	3203.0	3203.0	3193.7	3184.5	3179.9
12.5°	3114.9	3152.0	3152.0	3147.4	3138.1	3124.2	3152.0	3170.7	3142.7	3142.7	3138.1
15°	3073.3	3082.5	3087.1	3087.1	3082.5	3091.8	3105.6	3087.1	3091.8	3068.5	3077.8
17.5°	3026.9	3008.4	3022.2	3012.9	3017.7	3026.9	3045.5	3045.5	3017.7	3012.9	3022.2
20°	2920.3	2975.9	2980.6	2952.8	2957.3	2957.3	2989.9	2962.1	2980.6	2957.3	2966.6
22.5°	2869.2	2906.3	2911.0	2873.9	2897.0	2869.2	2901.7	2859.9	2906.3	2873.9	2887.7
25°	2804.3	2799.8	2813.6	2795.1	2799.8	2799.8	2822.9	2804.3	2818.3	2799.8	2804.3
27.5°	2697.9	2734.9	2730.2	2711.7	2720.9	2716.4	2762.7	2711.7	2739.5	2716.4	2725.7
30°	2605.0	2637.5	2628.3	2609.7	2609.7	2595.7	2646.8	2632.8	2628.3	2628.3	2623.5
32.5°	2512.3	2517.1	2507.8	2512.3	2517.1	2498.5	2540.1	2521.6	2517.1	2521.6	2526.3
35°	2387.1	2387.1	2396.4	2382.6	2401.1	2401.1	2438.2	2414.9	2410.4	2396.4	2410.4
37.5°	2275.9	2262.1	2266.7	2266.7	2275.9	2285.2	2303.7	2294.5	2294.5	2280.6	2289.9
40°	2127.6	2118.4	2132.2	2132.2	2146.2	2146.2	2164.7	2155.5	2169.3	2169.3	2169.3
42.5°	1997.9	1997.9	1988.6	2002.5	2007.2	2002.5	2035.0	2030.3	2035.0	2025.7	2030.3
45°	1858.7	1858.7	1849.5	1844.9	1868.0	1863.4	1900.5	1886.5	1905.1	1895.8	1900.5
47.5°	1668.6	1691.9	1677.9	1691.9	1719.7	1724.4	1747.5	1738.2	1756.8	1743.0	1761.5
50°	1488.0	1488.0	1501.8	1520.4	1548.2	1552.9	1580.7	1599.2	1608.5	1613.0	1617.8
52.5°	1298.0	1293.2	1307.2	1330.3	1353.6	1372.1	1399.9	1427.7	1446.2	1474.0	1460.0
55°	1075.4	1084.6	1098.6	1126.4	1163.5	1186.6	1209.8	1246.9	1279.4	1293.2	1321.0
57.5°	885.3	876.0	885.3	922.4	964.2	982.7	1015.2	1052.3	1098.6	1126.4	1135.7
60°	686.0	690.7	699.9	732.5	764.8	792.6	806.6	866.8	908.6	936.4	954.9
62.5°	505.3	514.6	523.9	551.7	584.0	607.3	630.4	681.4	718.5	746.3	764.8
65°	352.3	356.9	370.9	384.7	417.2	440.3	458.8	500.6	537.7	560.9	574.8
67.5°	217.9	222.4	231.7	250.4	273.5	292.0	310.5	338.3	370.9	393.9	398.7
70°	111.2	115.9	120.5	134.5	153.0	162.3	176.1	199.3	222.4	240.9	250.4
72.5°	37.1	37.1	41.8	51.1	60.3	69.6	74.1	97.4	115.9	125.2	129.7
75°	9.3	9.3	9.3	9.3	9.3	14.0	14.0	27.8	37.1	46.3	51.1
77.5°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	9.3	9.3
80°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C70D010 FEU4C709035 F4LC-CSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3	3263.3
2.5°	3263.3	3254.1	3249.3	3254.1	3254.1	3249.3	3263.3	3281.9	3305.0	3244.8
5°	3258.6	3249.3	3258.6	3230.8	3244.8	3235.5	3254.1	3249.3	3267.9	3249.3
7.5°	3244.8	3226.3	3230.8	3217.0	3235.5	3212.3	3226.3	3254.1	3235.5	3207.7
10°	3198.5	3189.2	3221.5	3175.2	3165.9	3184.5	3221.5	3193.7	3184.5	3193.7
12.5°	3152.0	3152.0	3165.9	3128.9	3133.4	3142.7	3161.2	3142.7	3152.0	3175.2
15°	3101.1	3091.8	3114.9	3087.1	3082.5	3073.3	3091.8	3091.8	3101.1	3087.1
17.5°	3040.7	3026.9	3026.9	3017.7	3012.9	3036.2	3045.5	3050.0	3054.7	3036.2
20°	2966.6	2962.1	2975.9	2962.1	2966.6	2971.3	2971.3	2962.1	3003.7	2952.8
22.5°	2887.7	2901.7	2883.2	2873.9	2883.2	2892.5	2892.5	2897.0	2887.7	2878.5
25°	2809.1	2818.3	2822.9	2795.1	2809.1	2795.1	2827.6	2832.1	2813.6	2822.9
27.5°	2739.5	2725.7	2720.9	2702.4	2711.7	2707.1	2711.7	2711.7	2739.5	2702.4
30°	2632.8	2619.0	2623.5	2609.7	2614.3	2609.7	2614.3	2614.3	2632.8	2628.3
32.5°	2530.9	2517.1	2521.6	2507.8	2507.8	2512.3	2503.1	2503.1	2517.1	2507.8
35°	2433.5	2401.1	2405.7	2401.1	2405.7	2387.1	2387.1	2382.6	2391.9	2368.6
37.5°	2294.5	2280.6	2275.9	2271.4	2275.9	2266.7	2275.9	2262.1	2275.9	2257.4
40°	2169.3	2160.0	2164.7	2136.9	2136.9	2141.5	2132.2	2127.6	2132.2	2150.7
42.5°	2044.2	2025.7	2016.4	2007.2	2011.7	1997.9	1993.2	1983.9	1993.2	1974.6
45°	1895.8	1895.8	1891.2	1868.0	1872.7	1872.7	1854.2	1835.6	1840.2	1840.2
47.5°	1761.5	1752.2	1747.5	1724.4	1719.7	1715.2	1696.5	1682.6	1682.6	1668.6
50°	1613.0	1603.8	1590.0	1566.7	1557.4	1529.6	1515.8	1497.3	1478.8	1478.8
52.5°	1474.0	1441.5	1423.0	1385.9	1372.1	1358.1	1321.0	1307.2	1293.2	1279.4
55°	1307.2	1279.4	1242.4	1200.6	1182.0	1158.8	1121.7	1093.9	1075.4	1080.1
57.5°	1145.0	1098.6	1061.6	1005.9	982.7	968.7	931.6	894.6	876.0	876.0
60°	945.6	908.6	862.2	811.2	792.6	769.5	723.0	699.9	686.0	672.1
62.5°	755.6	727.8	686.0	621.1	607.3	584.0	551.7	523.9	509.9	509.9
65°	565.5	537.7	500.6	454.3	435.7	417.2	389.4	361.6	347.6	343.1
67.5°	398.7	366.1	333.8	296.7	282.7	273.5	245.7	227.1	217.9	213.1
70°	240.9	222.4	199.3	171.5	157.5	148.3	129.7	115.9	111.2	106.7
72.5°	125.2	111.2	92.7	74.1	64.9	55.6	46.3	37.1	32.5	32.5
75°	46.3	37.1	23.3	14.0	9.3	9.3	9.3	9.3	9.3	9.3
77.5°	9.3	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
80°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)