

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C70D010 FEU4C709040 F4LC-CSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C70D010 FEU4C709040 F4LC-CSSQ-MW
 Description: 4 INCH 7000 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 4000K, 90CRI LEDS AND F4LC-CSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 6982.0 lumens
 Efficiency: N/A
 Efficacy: 89.5 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 78
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C70D010 FEU4C709040 F4LC-CSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#

CATALOG NUMBER: FLDSQ4C70D010 FEU4C709040 F4LC-CSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89				89
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77				77
3	95	86	79	74	93	85	78	73	82	76	72	79	74	71	77	73	69	67				67
4	88	77	70	64	86	76	69	63	74	67	63	71	66	62	69	65	61	59				59
5	81	70	62	56	79	69	61	56	67	60	55	65	59	54	63	58	54	52				52
6	75	63	55	49	73	62	55	49	61	54	49	59	53	48	57	52	48	46				46
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41				41
8	65	53	45	40	64	52	45	39	51	44	39	50	44	39	49	43	39	37				37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	35	45	39	35	33				33
10	57	45	38	33	56	44	37	33	44	37	32	43	37	32	42	36	32	31				31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	315374	315374	315374
5°	310283	314322	315223
10°	312959	312058	313410
15°	307480	307939	308868
20°	300333	305097	303680
25°	299035	299035	301005
30°	290695	292767	293291
35°	281627	284371	279436
40°	268415	273667	271325
45°	254040	259744	251502
50°	223724	243223	222328
55°	181193	222576	181984
60°	132576	184564	129913
65°	80571	131439	78448
70°	31428	70754	30130
75°	3467	19050	3467
80°	2612	2612	2612
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C70D010 FEU4C709040 F4LC-CSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	308.5	4.4
10°-20°	873.0	12.5
20°-30°	1295.4	18.6
30°-40°	1500.9	21.5
40°-50°	1439.1	20.6
50°-60°	1058.1	15.2
60°-70°	457.0	6.5
70°-80°	49.3	0.7
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2476.9	35.5
0°-40°	3977.8	57.0
0°-60°	6475.0	92.7
0°-90°	6982.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6982.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3268	3268	3268	3268	3268	
5°	3204	3236	3245	3250	3254	306
15°	3078	3097	3083	3087	3092	868
25°	2809	2804	2809	2814	2827	1286
35°	2391	2405	2414	2410	2372	1495
45°	1862	1866	1904	1876	1843	1415
55°	1077	1188	1323	1184	1082	969
65°	353	441	576	436	344	363
75°	9	14	51	9	9	29
85°	0	0	0	0	0	1
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C70D010 FEU4C709040 F4LC-CSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5
2.5°	3245.2	3282.3	3287.1	3263.8	3254.5	3240.6	3273.0	3249.9	3259.2	3249.9	3245.2
5°	3203.5	3245.2	3249.9	3249.9	3240.6	3235.9	3249.9	3245.2	3240.6	3231.4	3245.2
7.5°	3185.0	3208.1	3231.4	3203.5	3217.3	3212.8	3245.2	3231.4	3226.6	3226.6	3217.3
10°	3194.2	3189.5	3208.1	3180.2	3189.5	3180.2	3208.1	3208.1	3198.8	3189.5	3185.0
12.5°	3119.8	3156.9	3156.9	3152.4	3143.1	3129.1	3156.9	3175.7	3147.6	3147.6	3143.1
15°	3078.1	3087.4	3092.0	3092.0	3087.4	3096.7	3110.5	3092.0	3096.7	3073.4	3082.7
17.5°	3031.7	3013.1	3027.0	3017.7	3022.4	3031.7	3050.3	3050.3	3022.4	3017.7	3027.0
20°	2924.9	2980.6	2985.3	2957.5	2962.0	2962.0	2994.6	2966.7	2985.3	2962.0	2971.3
22.5°	2873.7	2910.9	2915.6	2878.5	2901.6	2873.7	2906.3	2864.5	2910.9	2878.5	2892.3
25°	2808.8	2804.2	2818.0	2799.5	2804.2	2804.2	2827.3	2808.8	2822.8	2804.2	2808.8
27.5°	2702.1	2739.2	2734.5	2715.9	2725.2	2720.7	2767.1	2715.9	2743.8	2720.7	2730.0
30°	2609.1	2641.7	2632.4	2613.8	2613.8	2599.8	2651.0	2637.0	2632.4	2632.4	2627.7
32.5°	2516.3	2521.0	2511.7	2516.3	2521.0	2502.5	2544.1	2525.6	2521.0	2525.6	2530.3
35°	2390.9	2390.9	2400.2	2386.3	2404.9	2404.9	2442.0	2418.7	2414.2	2400.2	2414.2
37.5°	2279.5	2265.7	2270.2	2270.2	2279.5	2288.8	2307.4	2298.1	2298.1	2284.2	2293.5
40°	2131.0	2121.7	2135.6	2135.6	2149.6	2149.6	2168.1	2158.9	2172.7	2172.7	2172.7
42.5°	2001.1	2001.1	1991.8	2005.6	2010.3	2005.6	2038.2	2033.5	2038.2	2028.9	2033.5
45°	1861.7	1861.7	1852.4	1847.8	1870.9	1866.4	1903.5	1889.5	1908.1	1898.8	1903.5
47.5°	1671.3	1694.6	1680.6	1694.6	1722.4	1727.2	1750.3	1741.0	1759.6	1745.7	1764.3
50°	1490.4	1490.4	1504.2	1522.8	1550.6	1555.3	1583.2	1601.8	1611.0	1615.6	1620.3
52.5°	1300.0	1295.3	1309.3	1332.4	1355.7	1374.3	1402.1	1430.0	1448.5	1476.4	1462.3
55°	1077.1	1086.3	1100.4	1128.2	1165.3	1188.4	1211.7	1248.9	1281.4	1295.3	1323.1
57.5°	886.7	877.4	886.7	923.8	965.7	984.2	1016.8	1053.9	1100.4	1128.2	1137.5
60°	687.0	691.8	701.1	733.6	766.0	793.9	807.9	868.1	910.0	937.8	956.4
62.5°	506.1	515.4	524.7	552.5	584.9	608.2	631.3	682.5	719.6	747.5	766.0
65°	352.9	357.4	371.5	385.3	417.9	441.0	459.5	501.4	538.5	561.8	575.7
67.5°	218.2	222.8	232.0	250.8	273.9	292.5	311.0	338.9	371.5	394.6	399.3
70°	111.4	116.1	120.7	134.7	153.2	162.5	176.4	199.7	222.8	241.3	250.8
72.5°	37.1	37.1	41.9	51.1	60.4	69.7	74.3	97.6	116.1	125.4	129.9
75°	9.3	9.3	9.3	9.3	9.3	14.0	14.0	27.8	37.1	46.4	51.1
77.5°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	9.3	9.3
80°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C70D010 FEU4C709040 F4LC-CSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5	3268.5
2.5°	3268.5	3259.2	3254.5	3259.2	3259.2	3254.5	3268.5	3287.1	3310.2	3249.9
5°	3263.8	3254.5	3263.8	3235.9	3249.9	3240.6	3259.2	3254.5	3273.0	3254.5
7.5°	3249.9	3231.4	3235.9	3222.1	3240.6	3217.3	3231.4	3259.2	3240.6	3212.8
10°	3203.5	3194.2	3226.6	3180.2	3170.9	3189.5	3226.6	3198.8	3189.5	3198.8
12.5°	3156.9	3156.9	3170.9	3133.8	3138.4	3147.6	3166.2	3147.6	3156.9	3180.2
15°	3106.0	3096.7	3119.8	3092.0	3087.4	3078.1	3096.7	3096.7	3106.0	3092.0
17.5°	3045.5	3031.7	3031.7	3022.4	3017.7	3041.0	3050.3	3054.8	3059.6	3041.0
20°	2971.3	2966.7	2980.6	2966.7	2971.3	2976.0	2976.0	2966.7	3008.4	2957.5
22.5°	2892.3	2906.3	2887.8	2878.5	2887.8	2897.0	2897.0	2901.6	2892.3	2883.0
25°	2813.5	2822.8	2827.3	2799.5	2813.5	2799.5	2832.1	2836.6	2818.0	2827.3
27.5°	2743.8	2730.0	2725.2	2706.7	2715.9	2711.4	2715.9	2715.9	2743.8	2706.7
30°	2637.0	2623.1	2627.7	2613.8	2618.4	2613.8	2618.4	2618.4	2637.0	2632.4
32.5°	2534.9	2521.0	2525.6	2511.7	2511.7	2516.3	2507.0	2507.0	2521.0	2511.7
35°	2437.3	2404.9	2409.5	2404.9	2409.5	2390.9	2390.9	2386.3	2395.6	2372.3
37.5°	2298.1	2284.2	2279.5	2275.0	2279.5	2270.2	2279.5	2265.7	2279.5	2261.0
40°	2172.7	2163.4	2168.1	2140.3	2140.3	2144.8	2135.6	2131.0	2135.6	2154.1
42.5°	2047.5	2028.9	2019.6	2010.3	2014.9	2001.1	1996.3	1987.0	1996.3	1977.8
45°	1898.8	1898.8	1894.2	1870.9	1875.7	1875.7	1857.1	1838.5	1843.1	1843.1
47.5°	1764.3	1755.0	1750.3	1727.2	1722.4	1717.9	1699.1	1685.3	1685.3	1671.3
50°	1615.6	1606.3	1592.5	1569.2	1559.9	1532.1	1518.2	1499.7	1481.1	1481.1
52.5°	1476.4	1443.8	1425.2	1388.1	1374.3	1360.2	1323.1	1309.3	1295.3	1281.4
55°	1309.3	1281.4	1244.3	1202.5	1183.9	1160.6	1123.5	1095.6	1077.1	1081.8
57.5°	1146.8	1100.4	1063.2	1007.5	984.2	970.2	933.1	896.0	877.4	877.4
60°	947.1	910.0	863.6	812.4	793.9	770.8	724.2	701.1	687.0	673.2
62.5°	756.7	728.9	687.0	622.1	608.2	584.9	552.5	524.7	510.7	510.7
65°	566.4	538.5	501.4	455.0	436.4	417.9	390.0	362.2	348.2	343.6
67.5°	399.3	366.7	334.3	297.2	283.2	273.9	246.1	227.5	218.2	213.5
70°	241.3	222.8	199.7	171.8	157.8	148.5	129.9	116.1	111.4	106.8
72.5°	125.4	111.4	92.8	74.3	65.0	55.7	46.4	37.1	32.6	32.6
75°	46.4	37.1	23.3	14.0	9.3	9.3	9.3	9.3	9.3	9.3
77.5°	9.3	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
80°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)