

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C75D010 FEU4C759040 F4LC-DFSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C75D010 FEU4C759040 F4LC-DFSSQ-MW
 Description: 4 INCH 7500 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 4000K, 90CRI LEDS AND F4LC-DFSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 8209.0 lumens
 Efficiency: N/A
 Efficacy: 100.7 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 81.5
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C75D010 FEU4C759040 F4LC-DFSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#

CATALOG NUMBER: FLDSQ4C75D010 FEU4C759040 F4LC-DFSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	111	108	104	101	109	105	102	100	101	99	96		97	95	94		94	92	91	89
2	103	96	91	86	100	94	89	85	91	87	83		88	84	81		85	82	79	77
3	95	86	79	74	93	85	78	73	82	76	72		79	74	71		77	73	69	67
4	88	77	70	64	86	76	69	63	74	67	63		71	66	62		69	65	61	59
5	81	70	62	56	79	69	61	56	67	60	55		65	59	54		63	58	54	52
6	75	63	55	49	73	62	55	49	61	54	49		59	53	48		57	52	48	46
7	70	58	50	44	68	57	49	44	55	49	44		54	48	43		53	47	43	41
8	65	53	45	40	64	52	45	39	51	44	39		50	44	39		49	43	39	37
9	61	49	41	36	60	48	41	36	47	40	36		46	40	35		45	39	35	33
10	57	45	38	33	56	44	37	33	44	37	32		43	37	32		42	36	32	31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	370797	370797	370797
5°	364814	369560	370615
10°	367964	366896	368483
15°	361522	362051	363140
20°	353111	358717	357044
25°	351586	351586	353907
30°	341779	344219	344832
35°	331123	334350	328543
40°	315586	321758	319012
45°	298675	305388	295700
50°	263038	285975	261402
55°	213021	261688	213963
60°	155887	217004	152742
65°	94727	154522	92238
70°	36957	83196	35434
75°	4064	22406	4064
80°	3112	3112	3112
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C75D010 FEU4C759040 F4LC-DFSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	362.7	4.4
10°-20°	1026.4	12.5
20°-30°	1523.0	18.6
30°-40°	1764.7	21.5
40°-50°	1692.0	20.6
50°-60°	1244.0	15.2
60°-70°	537.3	6.5
70°-80°	58.0	0.7
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2912.2	35.5
0°-40°	4676.9	57.0
0°-60°	7612.9	92.7
0°-90°	8209.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8209.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3843	3843	3843	3843	3843	
5°	3766	3805	3816	3821	3826	359
15°	3619	3641	3624	3630	3635	1020
25°	3302	3297	3302	3308	3324	1512
35°	2811	2828	2838	2833	2789	1758
45°	2189	2194	2238	2205	2167	1664
55°	1266	1397	1556	1392	1272	1140
65°	415	518	677	513	404	427
75°	11	16	60	11	11	34
85°	0	0	0	0	0	1
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C75D010 FEU4C759040 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9
2.5°	3815.5	3859.1	3864.7	3837.3	3826.4	3810.1	3848.2	3821.1	3832.0	3821.1	3815.5
5°	3766.5	3815.5	3821.1	3821.1	3810.1	3804.6	3821.1	3815.5	3810.1	3799.2	3815.5
7.5°	3744.7	3771.8	3799.2	3766.5	3782.8	3777.4	3815.5	3799.2	3793.7	3793.7	3782.8
10°	3755.6	3750.0	3771.8	3739.1	3750.0	3739.1	3771.8	3771.8	3760.9	3750.0	3744.7
12.5°	3668.1	3711.7	3711.7	3706.4	3695.5	3679.0	3711.7	3733.8	3700.8	3700.8	3695.5
15°	3619.1	3630.0	3635.3	3635.3	3630.0	3640.9	3657.2	3635.3	3640.9	3613.5	3624.4
17.5°	3564.5	3542.7	3558.9	3548.0	3553.6	3564.5	3586.3	3586.3	3553.6	3548.0	3558.9
20°	3438.9	3504.4	3509.9	3477.2	3482.5	3482.5	3520.8	3488.1	3509.9	3482.5	3493.5
22.5°	3378.8	3422.4	3428.0	3384.3	3411.5	3378.8	3417.1	3367.8	3422.4	3384.3	3400.6
25°	3302.4	3297.0	3313.3	3291.5	3297.0	3297.0	3324.2	3302.4	3318.8	3297.0	3302.4
27.5°	3177.0	3220.6	3215.1	3193.2	3204.2	3198.8	3253.4	3193.2	3226.0	3198.8	3209.7
30°	3067.6	3105.9	3095.0	3073.2	3073.2	3056.7	3116.8	3100.4	3095.0	3095.0	3089.5
32.5°	2958.5	2964.1	2953.2	2958.5	2964.1	2942.2	2991.2	2969.4	2964.1	2969.4	2975.0
35°	2811.1	2811.1	2822.0	2805.7	2827.5	2827.5	2871.2	2843.8	2838.5	2822.0	2838.5
37.5°	2680.1	2663.9	2669.2	2669.2	2680.1	2691.0	2712.9	2701.9	2701.9	2685.7	2696.6
40°	2505.5	2494.6	2510.9	2510.9	2527.3	2527.3	2549.2	2538.2	2554.5	2554.5	2554.5
42.5°	2352.7	2352.7	2341.8	2358.1	2363.6	2358.1	2396.4	2390.8	2396.4	2385.5	2390.8
45°	2188.8	2188.8	2177.9	2172.6	2199.7	2194.4	2238.0	2221.6	2243.4	2232.5	2238.0
47.5°	1965.0	1992.4	1975.9	1992.4	2025.1	2030.7	2057.9	2046.9	2068.8	2052.5	2074.3
50°	1752.3	1752.3	1768.6	1790.4	1823.1	1828.7	1861.4	1883.2	1894.2	1899.5	1905.1
52.5°	1528.5	1522.9	1539.4	1566.6	1593.9	1615.8	1648.5	1681.2	1703.1	1735.8	1719.3
55°	1266.3	1277.3	1293.7	1326.5	1370.1	1397.3	1424.7	1468.3	1506.6	1522.9	1555.6
57.5°	1042.5	1031.6	1042.5	1086.2	1135.4	1157.2	1195.5	1239.2	1293.7	1326.5	1337.4
60°	807.8	813.3	824.3	862.6	900.6	933.4	949.9	1020.7	1069.9	1102.6	1124.5
62.5°	595.1	606.0	616.9	649.6	687.7	715.1	742.3	802.4	846.1	878.8	900.6
65°	414.9	420.3	436.7	453.0	491.3	518.5	540.3	589.5	633.2	660.6	676.8
67.5°	256.6	261.9	272.8	294.9	322.0	343.9	365.7	398.4	436.7	463.9	469.5
70°	131.0	136.5	141.9	158.3	180.2	191.1	207.3	234.7	261.9	283.7	294.9
72.5°	43.7	43.7	49.2	60.1	71.0	82.0	87.3	114.7	136.5	147.4	152.8
75°	10.9	10.9	10.9	10.9	10.9	16.5	16.5	32.7	43.7	54.6	60.1
77.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	10.9	10.9
80°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C75D010 FEU4C759040 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9	3842.9
2.5°	3842.9	3832.0	3826.4	3832.0	3832.0	3826.4	3842.9	3864.7	3891.9	3821.1
5°	3837.3	3826.4	3837.3	3804.6	3821.1	3810.1	3832.0	3826.4	3848.2	3826.4
7.5°	3821.1	3799.2	3804.6	3788.3	3810.1	3782.8	3799.2	3832.0	3810.1	3777.4
10°	3766.5	3755.6	3793.7	3739.1	3728.2	3750.0	3793.7	3760.9	3750.0	3760.9
12.5°	3711.7	3711.7	3728.2	3684.5	3689.9	3700.8	3722.6	3700.8	3711.7	3739.1
15°	3651.8	3640.9	3668.1	3635.3	3630.0	3619.1	3640.9	3640.9	3651.8	3635.3
17.5°	3580.8	3564.5	3564.5	3553.6	3548.0	3575.4	3586.3	3591.7	3597.2	3575.4
20°	3493.5	3488.1	3504.4	3488.1	3493.5	3499.0	3499.0	3488.1	3537.1	3477.2
22.5°	3400.6	3417.1	3395.2	3384.3	3395.2	3406.2	3406.2	3411.5	3400.6	3389.7
25°	3307.9	3318.8	3324.2	3291.5	3307.9	3291.5	3329.8	3335.1	3313.3	3324.2
27.5°	3226.0	3209.7	3204.2	3182.3	3193.2	3187.9	3193.2	3193.2	3226.0	3182.3
30°	3100.4	3084.1	3089.5	3073.2	3078.5	3073.2	3078.5	3078.5	3100.4	3095.0
32.5°	2980.3	2964.1	2969.4	2953.2	2953.2	2958.5	2947.6	2947.6	2964.1	2953.2
35°	2865.6	2827.5	2832.9	2827.5	2832.9	2811.1	2811.1	2805.7	2816.6	2789.2
37.5°	2701.9	2685.7	2680.1	2674.8	2680.1	2669.2	2680.1	2663.9	2680.1	2658.3
40°	2554.5	2543.6	2549.2	2516.4	2516.4	2521.8	2510.9	2505.5	2510.9	2532.7
42.5°	2407.3	2385.5	2374.5	2363.6	2369.0	2352.7	2347.2	2336.2	2347.2	2325.3
45°	2232.5	2232.5	2227.1	2199.7	2205.3	2205.3	2183.5	2161.6	2167.0	2167.0
47.5°	2074.3	2063.4	2057.9	2030.7	2025.1	2019.8	1997.7	1981.5	1981.5	1965.0
50°	1899.5	1888.6	1872.3	1844.9	1834.0	1801.3	1785.0	1763.2	1741.4	1741.4
52.5°	1735.8	1697.5	1675.7	1632.0	1615.8	1599.3	1555.6	1539.4	1522.9	1506.6
55°	1539.4	1506.6	1463.0	1413.8	1391.9	1364.6	1320.9	1288.2	1266.3	1271.9
57.5°	1348.3	1293.7	1250.1	1184.6	1157.2	1140.7	1097.1	1053.4	1031.6	1031.6
60°	1113.6	1069.9	1015.3	955.2	933.4	906.2	851.4	824.3	807.8	791.5
62.5°	889.7	857.0	807.8	731.4	715.1	687.7	649.6	616.9	600.4	600.4
65°	665.9	633.2	589.5	535.0	513.1	491.3	458.6	425.8	409.3	404.0
67.5°	469.5	431.2	393.1	349.4	333.0	322.0	289.3	267.5	256.6	251.0
70°	283.7	261.9	234.7	202.0	185.5	174.6	152.8	136.5	131.0	125.6
72.5°	147.4	131.0	109.1	87.3	76.4	65.5	54.6	43.7	38.3	38.3
75°	54.6	43.7	27.4	16.5	10.9	10.9	10.9	10.9	10.9	10.9
77.5°	10.9	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
80°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)