

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P#

Luminaire Tested: **FLDSQ4C90D010 FEU4C909050 F4LC-DFSSQ-MW**

Issue Date: 12/13/2022

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-08
 Report Number: P#
 Test Lab: INNOVATION CENTER
 Issue Date: 12/13/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: FAIL-SAFE
 Catalog Number: FLDSQ4C90D010 FEU4C909050 F4LC-DFSSQ-MW
 Description: 4 INCH 9000 LUMEN FAIL-SAFE LED DOWNLIGHT WITH, 5000K, 90CRI LEDS AND F4LC-DFSSQ TRIM WITH MW FINISH
 Light Source: -
 Ballast/Driver: -

Summary


Lumens per Lamp: N/A
 Luminaire Lumens: 9638.0 lumens
 Efficiency: N/A
 Efficacy: 99.3 lumens/watt
 Spacing Criteria (0/90/45): 1.19 / 1.2 / 1.29
 Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
 CIE Type: Direct

Input Watts (W): 97.1
 Input Voltage (V):
 Input Current (Ain): NR
 Voltage Rise (V): NR
 Power Factor: NR
 Total Harmonic Distortion (THDi): NR
 Frequency (hertz): 60
 Stabilization Time: NR
 Operation Time: NR
 Ambient Temperature (°C): NR
 Test Distance: 25 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	GONIO 1 IN0055	4/22/2021	10/22/2021
Power Meter	XITRON 2801 IN0197	12/1/2020	12/1/2021
AC Power Source	CHROMA 61505 IN0196	12/1/2020	12/1/2021
DC Power Supply	AGILENT E3634A IN0198	11/30/2020	11/30/2021
Room Thermometer	ONSET IN0143	12/1/2020	12/1/2021

TEST NUMBER: P#
CATALOG NUMBER: FLDSQ4C90D010 FEU4C909050 F4LC-DFSSQ-MW

Luminous Intensity Polar Plot



TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C90D010 FEU4C909050 F4LC-DFSSQ-MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89				89
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77				77
3	95	86	79	74	93	85	78	73	82	76	72	79	74	71	77	73	69	67				67
4	88	77	70	64	86	76	69	63	74	67	63	71	66	62	69	65	61	59				59
5	81	70	62	56	79	69	61	56	67	60	55	65	59	54	63	58	54	52				52
6	75	63	55	49	73	62	55	49	61	54	49	59	53	48	57	52	48	46				46
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41				41
8	65	53	45	40	64	52	45	39	51	44	39	50	44	39	49	43	39	37				37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	35	45	39	35	33				33
10	57	45	38	33	56	44	37	33	44	37	32	43	37	32	42	36	32	31				31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	435339	435339	435339
5°	428323	433892	435132
10°	432012	430758	432629
15°	424454	425073	426362
20°	414576	421158	419197
25°	412781	412781	415517
30°	401275	404138	404863
35°	388758	392551	385743
40°	370529	377771	374547
45°	350664	358552	347171
50°	308821	335751	306900
55°	250114	307243	251208
60°	183020	254769	179334
65°	111211	181417	108288
70°	43389	97668	41612
75°	4772	26320	4772
80°	3612	3612	3612
85°	0	0	0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C90D010 FEU4C909050 F4LC-DFSSQ-MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	425.9	4.4
10°-20°	1205.1	12.5
20°-30°	1788.1	18.6
30°-40°	2071.9	21.5
40°-50°	1986.5	20.6
50°-60°	1460.6	15.2
60°-70°	630.8	6.5
70°-80°	68.1	0.7
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3419.1	35.5
0°-40°	5491.1	57.0
0°-60°	8938.2	92.7
0°-90°	9638.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9638.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	4512	4512	4512	4512	4512	
5°	4422	4467	4480	4486	4492	422
15°	4249	4275	4255	4262	4268	1198
25°	3877	3871	3877	3884	3903	1775
35°	3300	3320	3333	3326	3275	2064
45°	2570	2576	2628	2589	2544	1954
55°	1487	1640	1826	1634	1493	1338
65°	487	609	795	602	474	501
75°	13	19	71	13	13	39
85°	0	0	0	0	0	1
90°	0	0	0	0	0	

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C90D010 FEU4C909050 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8
2.5°	4479.7	4530.9	4537.5	4505.3	4492.5	4473.4	4518.1	4486.2	4499.0	4486.2	4479.7
5°	4422.2	4479.7	4486.2	4486.2	4473.4	4466.9	4486.2	4479.7	4473.4	4460.6	4479.7
7.5°	4396.5	4428.4	4460.6	4422.2	4441.2	4435.0	4479.7	4460.6	4454.1	4454.1	4441.2
10°	4409.3	4402.8	4428.4	4390.0	4402.8	4390.0	4428.4	4428.4	4415.6	4402.8	4396.5
12.5°	4306.6	4357.8	4357.8	4351.6	4338.7	4319.4	4357.8	4383.7	4345.0	4345.0	4338.7
15°	4249.1	4261.9	4268.2	4268.2	4261.9	4274.7	4293.8	4268.2	4274.7	4242.5	4255.3
17.5°	4185.0	4159.4	4178.5	4165.7	4172.2	4185.0	4210.6	4210.6	4172.2	4165.7	4178.5
20°	4037.5	4114.4	4120.9	4082.5	4088.8	4088.8	4133.7	4095.3	4120.9	4088.8	4101.6
22.5°	3966.9	4018.2	4024.7	3973.5	4005.4	3966.9	4011.9	3954.1	4018.2	3973.5	3992.6
25°	3877.2	3871.0	3890.1	3864.4	3871.0	3871.0	3902.9	3877.2	3896.6	3871.0	3877.2
27.5°	3730.0	3781.3	3774.7	3749.1	3761.9	3755.6	3819.7	3749.1	3787.5	3755.6	3768.5
30°	3601.6	3646.6	3633.8	3608.2	3608.2	3588.8	3659.4	3640.1	3633.8	3633.8	3627.3
32.5°	3473.5	3480.0	3467.2	3473.5	3480.0	3454.4	3511.9	3486.3	3480.0	3486.3	3492.9
35°	3300.4	3300.4	3313.2	3294.1	3319.8	3319.8	3371.0	3338.9	3332.6	3313.2	3332.6
37.5°	3146.7	3127.6	3133.8	3133.8	3146.7	3159.5	3185.1	3172.3	3172.3	3153.2	3166.0
40°	2941.7	2928.8	2947.9	2947.9	2967.3	2967.3	2992.9	2980.1	2999.2	2999.2	2999.2
42.5°	2762.3	2762.3	2749.5	2768.6	2775.1	2768.6	2813.5	2807.0	2813.5	2800.7	2807.0
45°	2569.8	2569.8	2557.0	2550.7	2582.6	2576.4	2627.6	2608.3	2633.9	2621.1	2627.6
47.5°	2307.0	2339.2	2319.9	2339.2	2377.6	2384.2	2416.1	2403.3	2428.9	2409.8	2435.4
50°	2057.3	2057.3	2076.4	2102.0	2140.5	2147.0	2185.5	2211.1	2223.9	2230.2	2236.7
52.5°	1794.5	1788.0	1807.4	1839.3	1871.4	1897.0	1935.5	1973.9	1999.5	2038.0	2018.6
55°	1486.8	1499.6	1518.9	1557.4	1608.6	1640.5	1672.7	1723.9	1768.9	1788.0	1826.4
57.5°	1224.0	1211.2	1224.0	1275.2	1333.0	1358.7	1403.6	1454.9	1518.9	1557.4	1570.2
60°	948.4	954.9	967.7	1012.7	1057.4	1095.9	1115.2	1198.4	1256.2	1294.6	1320.2
62.5°	698.7	711.5	724.3	762.7	807.5	839.6	871.5	942.1	993.4	1031.8	1057.4
65°	487.1	493.4	512.8	531.9	576.8	608.7	634.4	692.1	743.4	775.5	794.6
67.5°	301.2	307.5	320.3	346.2	378.1	403.7	429.4	467.8	512.8	544.7	551.2
70°	153.8	160.3	166.6	185.9	211.5	224.3	243.4	275.6	307.5	333.1	346.2
72.5°	51.3	51.3	57.8	70.6	83.4	96.2	102.5	134.7	160.3	173.1	179.4
75°	12.8	12.8	12.8	12.8	12.8	19.3	19.3	38.4	51.3	64.1	70.6
77.5°	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	12.8	12.8
80°	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P#
 CATALOG NUMBER: FLDSQ4C90D010 FEU4C909050 F4LC-DFSSQ-MW

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°
0°	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8	4511.8
2.5°	4511.8	4499.0	4492.5	4499.0	4499.0	4492.5	4511.8	4537.5	4569.4	4486.2
5°	4505.3	4492.5	4505.3	4466.9	4486.2	4473.4	4499.0	4492.5	4518.1	4492.5
7.5°	4486.2	4460.6	4466.9	4447.8	4473.4	4441.2	4460.6	4499.0	4473.4	4435.0
10°	4422.2	4409.3	4454.1	4390.0	4377.2	4402.8	4454.1	4415.6	4402.8	4415.6
12.5°	4357.8	4357.8	4377.2	4325.9	4332.2	4345.0	4370.7	4345.0	4357.8	4390.0
15°	4287.5	4274.7	4306.6	4268.2	4261.9	4249.1	4274.7	4274.7	4287.5	4268.2
17.5°	4204.1	4185.0	4185.0	4172.2	4165.7	4197.8	4210.6	4216.9	4223.4	4197.8
20°	4101.6	4095.3	4114.4	4095.3	4101.6	4108.1	4108.1	4095.3	4152.8	4082.5
22.5°	3992.6	4011.9	3986.3	3973.5	3986.3	3999.1	3999.1	4005.4	3992.6	3979.7
25°	3883.8	3896.6	3902.9	3864.4	3883.8	3864.4	3909.4	3915.7	3890.1	3902.9
27.5°	3787.5	3768.5	3761.9	3736.3	3749.1	3742.8	3749.1	3749.1	3787.5	3736.3
30°	3640.1	3621.0	3627.3	3608.2	3614.5	3608.2	3614.5	3614.5	3640.1	3633.8
32.5°	3499.1	3480.0	3486.3	3467.2	3467.2	3473.5	3460.7	3460.7	3480.0	3467.2
35°	3364.5	3319.8	3326.0	3319.8	3326.0	3300.4	3300.4	3294.1	3306.9	3274.8
37.5°	3172.3	3153.2	3146.7	3140.4	3146.7	3133.8	3146.7	3127.6	3146.7	3121.0
40°	2999.2	2986.4	2992.9	2954.5	2954.5	2960.7	2947.9	2941.7	2947.9	2973.6
42.5°	2826.3	2800.7	2787.9	2775.1	2781.4	2762.3	2755.7	2742.9	2755.7	2730.1
45°	2621.1	2621.1	2614.8	2582.6	2589.2	2589.2	2563.6	2537.9	2544.2	2544.2
47.5°	2435.4	2422.6	2416.1	2384.2	2377.6	2371.4	2345.5	2326.4	2326.4	2307.0
50°	2230.2	2217.4	2198.3	2166.1	2153.3	2114.9	2095.8	2070.1	2044.5	2044.5
52.5°	2038.0	1993.0	1967.4	1916.1	1897.0	1877.7	1826.4	1807.4	1788.0	1768.9
55°	1807.4	1768.9	1717.7	1659.9	1634.3	1602.1	1550.8	1512.4	1486.8	1493.3
57.5°	1583.0	1518.9	1467.7	1390.8	1358.7	1339.3	1288.1	1236.8	1211.2	1211.2
60°	1307.4	1256.2	1192.1	1121.5	1095.9	1064.0	999.6	967.7	948.4	929.3
62.5°	1044.6	1006.2	948.4	858.7	839.6	807.5	762.7	724.3	705.0	705.0
65°	781.8	743.4	692.1	628.1	602.5	576.8	538.4	499.9	480.6	474.3
67.5°	551.2	506.2	461.5	410.3	390.9	378.1	339.7	314.0	301.2	294.7
70°	333.1	307.5	275.6	237.2	217.8	205.0	179.4	160.3	153.8	147.5
72.5°	173.1	153.8	128.1	102.5	89.7	76.9	64.1	51.3	45.0	45.0
75°	64.1	51.3	32.2	19.3	12.8	12.8	12.8	12.8	12.8	12.8
77.5°	12.8	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
80°	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
82.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)