

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P579689

Luminaire Tested: **HC4R10D010-HM40525827-42RMDC**

Issue Date: 9/23/2021

Test Information

Test Method: LM-41-14
Report Number: P579689
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-13)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/23/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC4R10D010-HM40525827-42RMDC
Description: HALO COMMERCIAL 4" ROUND, RETROFIT FRAME, WITH 4" MEDIUM DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1014.4 lumens
Efficiency: N/A
Efficacy: 102.5 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 0.96
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P579689

CATALOG NUMBER: HC4R10D010-HM40525827-42RMDC

Luminous Intensity Polar Plot





TEST NUMBER: P579689

CATALOG NUMBER: HC4R10D010-HM40525827-42RMDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93
2	108	103	99	95	105	101	97	94	98	95	92	95	92	90	92	90	88	86
3	102	95	90	86	100	94	89	86	91	87	84	89	86	83	87	84	82	80
4	97	89	83	79	95	88	82	78	86	81	77	84	80	77	82	78	76	74
5	92	83	77	73	90	82	76	72	80	75	72	78	74	71	77	73	70	69
6	87	78	71	67	85	77	71	67	75	70	66	74	69	66	72	68	65	64
7	82	73	66	62	81	72	66	62	71	65	62	69	65	61	68	64	61	60
8	78	68	62	58	77	68	62	58	67	61	57	65	61	57	65	60	57	56
9	74	64	58	54	73	64	58	54	63	57	54	62	57	54	61	57	53	52
10	70	61	55	51	69	60	54	51	59	54	50	58	54	50	58	53	50	49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	114946
5°	117415
10°	122055
15°	122091
20°	112885
25°	97541
30°	79360
35°	58288
40°	33701
45°	15734
50°	7273
55°	2516
60°	814
65°	555
70°	469
75°	334
80°	0
85°	0



TEST NUMBER: P579689

CATALOG NUMBER: HC4R10D010-HM40525827-42RMDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	91.5	9.0
10°-20°	265.0	26.1
20°-30°	326.3	32.2
30°-40°	238.2	23.5
40°-50°	77.6	7.7
50°-60°	13.0	1.3
60°-70°	2.0	0.2
70°-80°	0.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	682.8	67.3
0°-40°	921.1	90.8
0°-60°	1011.6	99.7
0°-90°	1014.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1014.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	932	
5°	948	91
15°	956	265
25°	717	326
35°	387	238
45°	90	78
55°	12	13
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P579689

CATALOG NUMBER: HC4R10D010-HM40525827-42RMDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	931.9
2.5°	932.6
5°	948.3
7.5°	966.6
10°	974.5
12.5°	971.9
15°	956.1
17.5°	916.9
20°	860.0
22.5°	791.4
25°	716.7
27.5°	639.0
30°	557.2
32.5°	473.5
35°	387.1
37.5°	300.2
40°	209.3
42.5°	136.7
45°	90.2
47.5°	59.5
50°	37.9
52.5°	22.2
55°	11.7
57.5°	4.6
60°	3.3
62.5°	2.6
65°	1.9
67.5°	1.3
70°	1.3
72.5°	0.7
75°	0.7
77.5°	0.7
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)