

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580580

Luminaire Tested: **HC440D010-HM43040835-41WDWB**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P580580
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-10)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC440D010-HM43040835-41WDWB
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" WIDE DISTRIBUTION, WHITE BAFFLE TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4399.8 lumens
Efficiency: N/A
Efficacy: 107.3 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.14 / 1.07
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 41
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P580580

CATALOG NUMBER: HC440D010-HM43040835-41WDWB

Luminous Intensity Polar Plot





TEST NUMBER: P580580

CATALOG NUMBER: HC440D010-HM43040835-41WDWB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90	90	90	90
2	104	98	93	89	102	96	92	88	93	89	86	90	87	84	87	84	82	80	80	80	80
3	98	89	83	78	95	88	82	78	85	80	76	83	78	75	80	77	74	72	72	72	72
4	91	82	75	70	89	81	74	69	78	73	69	76	72	68	74	70	67	65	65	65	65
5	86	75	68	63	84	74	68	63	72	67	62	71	65	61	69	64	61	59	59	59	59
6	80	70	62	57	79	69	62	57	67	61	57	66	60	56	64	59	56	54	54	54	54
7	76	64	57	52	74	64	57	52	62	56	52	61	56	51	60	55	51	49	49	49	49
8	71	60	53	48	70	59	53	48	58	52	48	57	51	47	56	51	47	46	46	46	46
9	67	56	49	44	66	55	49	44	54	48	44	53	48	44	52	47	44	42	42	42	42
10	64	52	46	41	62	52	45	41	51	45	41	50	45	41	49	44	41	39	39	39	39

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	361205
5°	362919
10°	365412
15°	369069
20°	362912
25°	346217
30°	314565
35°	253738
40°	176055
45°	115565
50°	77448
55°	55116
60°	47093
65°	54111
70°	58027
75°	55902
80°	50291
85°	46278



TEST NUMBER: P580580

CATALOG NUMBER: HC440D010-HM43040835-41WDWB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	279.3	6.3
10°-20°	811.9	18.5
20°-30°	1160.0	26.4
30°-40°	1036.3	23.6
40°-50°	531.5	12.1
50°-60°	241.6	5.5
60°-70°	180.2	4.1
70°-80°	122.6	2.8
80°-90°	36.3	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2251.3	51.2
0°-40°	3287.6	74.7
0°-60°	4060.7	92.3
0°-90°	4399.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4399.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2928	
5°	2931	279
15°	2890	812
25°	2544	1160
35°	1685	1036
45°	662	531
55°	256	242
65°	185	180
75°	117	123
85°	33	36
90°	0	



TEST NUMBER: P580580

CATALOG NUMBER: HC440D010-HM43040835-41WDWB

CANDELA DISTRIBUTION (FULL):

0°	
0°	2928.4
2.5°	2917.5
5°	2931.1
7.5°	2931.1
10°	2917.5
12.5°	2903.8
15°	2890.2
17.5°	2849.4
20°	2764.8
22.5°	2661.1
25°	2543.9
27.5°	2396.7
30°	2208.6
32.5°	1968.6
35°	1685.1
37.5°	1382.4
40°	1093.4
42.5°	853.4
45°	662.5
47.5°	518.0
50°	403.6
52.5°	316.2
55°	256.3
57.5°	215.5
60°	190.9
62.5°	185.4
65°	185.4
67.5°	179.9
70°	160.9
72.5°	139.0
75°	117.3
77.5°	92.7
80°	70.8
82.5°	51.8
85°	32.7
87.5°	13.7
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)