

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580784

Luminaire Tested: **HC445D010-HM44560930-41NDC**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P580784
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-1)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC445D010-HM44560930-41NDC
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" NARROW DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3714.6 lumens
Efficiency: N/A
Efficacy: 84.4 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 44
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P580784

CATALOG NUMBER: HC445D010-HM44560930-41NDC

Luminous Intensity Polar Plot





TEST NUMBER: P580784

CATALOG NUMBER: HC445D010-HM44560930-41NDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94			
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	93	91	89	87			
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81			
4	97	90	85	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76			
5	93	84	79	74	91	83	78	74	82	77	73	80	76	73	78	75	72	71			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66			
7	84	75	69	64	82	74	68	64	73	68	64	71	67	64	70	66	63	62			
8	80	70	64	60	78	70	64	60	69	64	60	68	63	60	67	62	59	58			
9	76	66	61	57	75	66	60	57	65	60	56	64	59	56	63	59	56	55			
10	72	63	57	53	71	62	57	53	62	57	53	61	56	53	60	56	53	51			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	547124
5°	546428
10°	535763
15°	498183
20°	428451
25°	344189
30°	268703
35°	188146
40°	96545
45°	48999
50°	24543
55°	9161
60°	3700
65°	2919
70°	1803
75°	1191
80°	1776
85°	0



TEST NUMBER: P580784

CATALOG NUMBER: HC445D010-HM44560930-41NDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	417.2	11.2
10°-20°	1076.9	29.0
20°-30°	1160.2	31.2
30°-40°	762.2	20.5
40°-50°	237.0	6.4
50°-60°	46.5	1.3
60°-70°	9.9	0.3
70°-80°	3.6	0.1
80°-90°	1.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2654.3	71.5
0°-40°	3416.5	92.0
0°-60°	3700.0	99.6
0°-90°	3714.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3714.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4436	
5°	4413	417
15°	3901	1077
25°	2529	1160
35°	1250	762
45°	281	237
55°	43	47
65°	10	10
75°	2	4
85°	0	1
90°	0	



TEST NUMBER: P580784

CATALOG NUMBER: HC445D010-HM44560930-41NDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	4435.7
2.5°	4413.2
5°	4413.2
7.5°	4378.0
10°	4277.6
12.5°	4117.1
15°	3901.3
17.5°	3612.8
20°	3264.1
22.5°	2887.8
25°	2529.0
27.5°	2195.3
30°	1886.6
32.5°	1595.7
35°	1249.5
37.5°	870.6
40°	599.6
42.5°	414.0
45°	280.9
47.5°	190.6
50°	127.9
52.5°	80.3
55°	42.6
57.5°	17.6
60°	15.0
62.5°	12.6
65°	10.0
67.5°	7.5
70°	5.0
72.5°	5.0
75°	2.5
77.5°	2.5
80°	2.5
82.5°	2.5
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)