

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P580801

Luminaire Tested: **HC445D010-HM44560935-41MDC**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P580801
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC445D010-HM44560935-41MDC
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" MEDIUM DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4033.8 lumens
Efficiency: N/A
Efficacy: 91.7 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.96
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 44
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P580801

CATALOG NUMBER: HC445D010-HM44560935-41MDC

Luminous Intensity Polar Plot





TEST NUMBER: P580801

CATALOG NUMBER: HC445D010-HM44560935-41MDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	98	95	105	101	97	94	98	95	92	95	92	90	92	90	88	86			
3	102	95	90	86	100	94	89	86	91	87	84	89	86	83	87	84	82	80			
4	97	89	83	79	95	88	82	78	86	81	77	84	80	77	82	78	76	74			
5	91	83	77	72	90	82	76	72	80	75	72	78	74	71	77	73	70	69			
6	87	78	71	67	85	77	71	67	75	70	66	74	69	66	72	68	65	64			
7	82	73	66	62	81	72	66	62	71	65	62	69	65	61	68	64	61	60			
8	78	68	62	58	77	68	62	58	67	61	57	65	61	57	65	60	57	56			
9	74	64	58	54	73	64	58	54	63	57	54	62	57	54	61	57	53	52			
10	70	61	55	51	69	60	54	51	59	54	50	58	54	50	58	53	50	49			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	467233
5°	475803
10°	490485
15°	485043
20°	445410
25°	384256
30°	313141
35°	231844
40°	133016
45°	64297
50°	30588
55°	10688
60°	3873
65°	2306
70°	1911
75°	1239
80°	0
85°	0



TEST NUMBER: P580801

CATALOG NUMBER: HC445D010-HM44560935-41MDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	369.6	9.2
10°-20°	1053.0	26.1
20°-30°	1285.9	31.9
30°-40°	945.4	23.4
40°-50°	313.3	7.8
50°-60°	55.3	1.4
60°-70°	8.4	0.2
70°-80°	2.8	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2708.6	67.1
0°-40°	3654.0	90.6
0°-60°	4022.6	99.7
0°-90°	4033.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4033.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3788	
5°	3843	370
15°	3798	1053
25°	2823	1286
35°	1540	945
45°	369	313
55°	50	55
65°	8	8
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P580801

CATALOG NUMBER: HC445D010-HM44560935-41MDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	3788.0
2.5°	3790.6
5°	3842.8
7.5°	3900.4
10°	3916.1
12.5°	3879.5
15°	3798.4
17.5°	3631.1
20°	3393.3
22.5°	3116.1
25°	2823.4
27.5°	2517.4
30°	2198.6
32.5°	1879.6
35°	1539.7
37.5°	1194.7
40°	826.1
42.5°	546.4
45°	368.6
47.5°	245.7
50°	159.4
52.5°	94.1
55°	49.7
57.5°	20.9
60°	15.7
62.5°	10.4
65°	7.9
67.5°	5.3
70°	5.3
72.5°	2.6
75°	2.6
77.5°	2.6
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)