

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P581341

Luminaire Tested: **HC460D010-HM44560927-41MDC**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P581341
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC460D010-HM44560927-41MDC
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" MEDIUM DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4110.4 lumens
Efficiency: N/A
Efficacy: 74.7 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.96
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 55
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P581341

CATALOG NUMBER: HC460D010-HM44560927-41MDC

Luminous Intensity Polar Plot





TEST NUMBER: P581341

CATALOG NUMBER: HC460D010-HM44560927-41MDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93
2	108	103	98	95	105	101	97	94	98	95	92	95	92	90	92	90	88	86
3	102	95	90	86	100	94	89	86	91	87	84	89	86	83	87	84	82	80
4	97	89	83	79	95	88	82	78	86	81	77	84	80	77	82	78	76	74
5	91	83	77	72	90	82	76	72	80	75	72	78	74	71	77	73	70	69
6	87	78	71	67	85	77	71	67	75	70	66	74	69	66	72	68	65	64
7	82	73	66	62	81	72	66	62	71	65	62	69	65	61	68	64	61	60
8	78	68	62	58	77	68	62	58	67	61	57	65	61	57	65	60	57	56
9	74	64	58	54	73	64	58	54	63	57	54	62	57	54	61	57	53	52
10	70	61	55	51	69	60	54	51	59	54	50	58	54	50	58	53	50	49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	476102
5°	484854
10°	499791
15°	494250
20°	453863
25°	391551
30°	319080
35°	236256
40°	135544
45°	65519
50°	31182
55°	10881
60°	3947
65°	2335
70°	1911
75°	1287
80°	0
85°	0



TEST NUMBER: P581341

CATALOG NUMBER: HC460D010-HM44560927-41MDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	376.6	9.2
10°-20°	1073.0	26.1
20°-30°	1310.4	31.9
30°-40°	963.3	23.4
40°-50°	319.3	7.8
50°-60°	56.4	1.4
60°-70°	8.5	0.2
70°-80°	2.8	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2760.0	67.1
0°-40°	3723.4	90.6
0°-60°	4099.0	99.7
0°-90°	4110.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4110.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3860	
5°	3916	377
15°	3870	1073
25°	2877	1310
35°	1569	963
45°	376	319
55°	51	56
65°	8	9
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P581341

CATALOG NUMBER: HC460D010-HM44560927-41MDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	3859.9
2.5°	3862.6
5°	3915.9
7.5°	3974.4
10°	3990.4
12.5°	3953.2
15°	3870.5
17.5°	3700.1
20°	3457.7
22.5°	3175.3
25°	2877.0
27.5°	2565.3
30°	2240.3
32.5°	1915.3
35°	1569.0
37.5°	1217.3
40°	841.8
42.5°	556.8
45°	375.6
47.5°	250.4
50°	162.5
52.5°	95.9
55°	50.6
57.5°	21.3
60°	16.0
62.5°	10.6
65°	8.0
67.5°	5.3
70°	5.3
72.5°	2.7
75°	2.7
77.5°	2.7
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)