

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P592570

Luminaire Tested: **HC407D010-HM40525850-41WDH**

Issue Date: 9/9/2021

Test Information

Test Method: LM-41-14
Report Number: P592570
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2106-266-8)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC407D010-HM40525850-41WDH
Description: HALO COMMERCIAL 4" ROUND, NEW CONSTRUCTION FRAME, WITH 4" WIDE DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 5000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 972.7 lumens
Efficiency: N/A
Efficacy: 121.6 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.1
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P592570

CATALOG NUMBER: HC407D010-HM40525850-41WDH

Luminous Intensity Polar Plot





TEST NUMBER: P592570

CATALOG NUMBER: HC407D010-HM40525850-41WDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | 100 | 100 | 100 |
| 1 | 113 | 110 | 107 | 104 | 110 | 108 | 105 | 103 | 103 | 101 | 100 | 100 | 98 | 97 | 96 | 95 | 94 | 92 | 92 | 92 | 92 |
| 2 | 106 | 101 | 96 | 92 | 104 | 99 | 95 | 91 | 96 | 92 | 89 | 93 | 90 | 87 | 90 | 88 | 86 | 84 | 84 | 84 | 84 |
| 3 | 100 | 93 | 87 | 82 | 98 | 91 | 86 | 82 | 88 | 84 | 80 | 86 | 82 | 79 | 84 | 81 | 78 | 76 | 76 | 76 | 76 |
| 4 | 94 | 85 | 79 | 74 | 92 | 84 | 78 | 74 | 82 | 77 | 73 | 80 | 75 | 72 | 78 | 74 | 71 | 69 | 69 | 69 | 69 |
| 5 | 88 | 79 | 72 | 67 | 86 | 78 | 72 | 67 | 76 | 70 | 66 | 74 | 69 | 66 | 72 | 68 | 65 | 63 | 63 | 63 | 63 |
| 6 | 83 | 73 | 66 | 61 | 81 | 72 | 66 | 61 | 70 | 65 | 61 | 69 | 64 | 60 | 68 | 63 | 60 | 58 | 58 | 58 | 58 |
| 7 | 78 | 68 | 61 | 56 | 77 | 67 | 60 | 56 | 65 | 60 | 55 | 64 | 59 | 55 | 63 | 58 | 55 | 53 | 53 | 53 | 53 |
| 8 | 74 | 63 | 56 | 51 | 72 | 62 | 56 | 51 | 61 | 55 | 51 | 60 | 55 | 51 | 59 | 54 | 51 | 49 | 49 | 49 | 49 |
| 9 | 69 | 59 | 52 | 47 | 68 | 58 | 52 | 47 | 57 | 51 | 47 | 56 | 51 | 47 | 55 | 50 | 47 | 45 | 45 | 45 | 45 |
| 10 | 66 | 55 | 48 | 44 | 65 | 54 | 48 | 44 | 53 | 48 | 44 | 53 | 47 | 44 | 52 | 47 | 43 | 42 | 42 | 42 | 42 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|-------|
| | 0° |
| 0° | 81790 |
| 5° | 82400 |
| 10° | 83428 |
| 15° | 85519 |
| 20° | 86160 |
| 25° | 83686 |
| 30° | 76726 |
| 35° | 63122 |
| 40° | 46035 |
| 45° | 29881 |
| 50° | 16829 |
| 55° | 8000 |
| 60° | 3133 |
| 65° | 1955 |
| 70° | 1298 |
| 75° | 858 |
| 80° | 426 |
| 85° | 849 |



TEST NUMBER: P592570

CATALOG NUMBER: HC407D010-HM40525850-41WDH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 63.5 | 6.5 |
| 10°-20° | 188.8 | 19.4 |
| 20°-30° | 280.1 | 28.8 |
| 30°-40° | 258.7 | 26.6 |
| 40°-50° | 135.1 | 13.9 |
| 50°-60° | 37.0 | 3.8 |
| 60°-70° | 7.1 | 0.7 |
| 70°-80° | 2.0 | 0.2 |
| 80°-90° | 0.4 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 532.4 | 54.7 |
| 0°-40° | 791.1 | 81.3 |
| 0°-60° | 963.2 | 99.0 |
| 0°-90° | 972.7 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 972.7 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-----|------|
| 0° | 663 | |
| 5° | 666 | 64 |
| 15° | 670 | 189 |
| 25° | 615 | 280 |
| 35° | 419 | 259 |
| 45° | 171 | 135 |
| 55° | 37 | 37 |
| 65° | 7 | 7 |
| 75° | 2 | 2 |
| 85° | 1 | 0 |
| 90° | 0 | |



TEST NUMBER: P592570

CATALOG NUMBER: HC407D010-HM40525850-41WDH

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|-------|
| 0° | 663.1 |
| 2.5° | 661.2 |
| 5° | 665.5 |
| 7.5° | 667.3 |
| 10° | 666.1 |
| 12.5° | 667.3 |
| 15° | 669.7 |
| 17.5° | 667.3 |
| 20° | 656.4 |
| 22.5° | 638.6 |
| 25° | 614.9 |
| 27.5° | 582.7 |
| 30° | 538.7 |
| 32.5° | 483.3 |
| 35° | 419.2 |
| 37.5° | 352.2 |
| 40° | 285.9 |
| 42.5° | 224.9 |
| 45° | 171.3 |
| 47.5° | 125.5 |
| 50° | 87.7 |
| 52.5° | 58.5 |
| 55° | 37.2 |
| 57.5° | 22.0 |
| 60° | 12.7 |
| 62.5° | 9.1 |
| 65° | 6.7 |
| 67.5° | 4.9 |
| 70° | 3.6 |
| 72.5° | 2.4 |
| 75° | 1.8 |
| 77.5° | 1.3 |
| 80° | 0.6 |
| 82.5° | 0.6 |
| 85° | 0.6 |
| 87.5° | 0.0 |
| 90° | 0.0 |



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)