

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P581986

Luminaire Tested: **HC625D010-HM60525827-61NDC**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P581986
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-1)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC625D010-HM60525827-61NDC
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" NARROW DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2527.9 lumens
Efficiency: N/A
Efficacy: 94.3 lumens/watt
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.88
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 26.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P581986

CATALOG NUMBER: HC625D010-HM60525827-61NDC

Luminous Intensity Polar Plot





TEST NUMBER: P581986

CATALOG NUMBER: HC625D010-HM60525827-61NDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	108	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94			
2	108	103	99	96	106	102	98	95	98	96	93	96	93	91	93	91	89	87			
3	103	97	92	88	101	95	91	87	93	89	86	90	87	84	88	85	83	82			
4	98	90	85	81	96	89	84	80	87	83	79	85	81	79	83	80	78	76			
5	93	85	79	75	91	84	79	75	82	77	74	80	76	73	79	75	73	71			
6	88	80	74	70	87	79	73	69	77	73	69	76	72	68	75	71	68	67			
7	84	75	69	65	83	74	69	65	73	68	64	72	67	64	71	67	64	62			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59			
9	76	67	61	57	75	66	61	57	65	60	57	65	60	57	64	60	56	55			
10	73	63	58	54	72	63	57	54	62	57	54	61	57	53	61	56	53	52			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	150964
5°	151276
10°	153760
15°	154882
20°	141581
25°	111254
30°	81437
35°	57768
40°	27323
45°	10420
50°	4674
55°	1271
60°	548
65°	428
70°	256
75°	339
80°	0
85°	0



TEST NUMBER: P581986

CATALOG NUMBER: HC625D010-HM60525827-61NDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	263.0	10.4
10°-20°	754.3	29.8
20°-30°	839.0	33.2
30°-40°	524.1	20.7
40°-50°	124.5	4.9
50°-60°	17.8	0.7
60°-70°	3.7	0.1
70°-80°	1.5	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1856.2	73.4
0°-40°	2380.4	94.2
0°-60°	2522.7	99.8
0°-90°	2527.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2527.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2754	
5°	2749	263
15°	2729	754
25°	1839	839
35°	863	524
45°	134	125
55°	13	18
65°	3	4
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P581986

CATALOG NUMBER: HC625D010-HM60525827-61NDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	2753.8
2.5°	2742.3
5°	2749.0
7.5°	2758.9
10°	2762.2
12.5°	2760.5
15°	2729.0
17.5°	2622.8
20°	2426.9
22.5°	2151.3
25°	1839.3
27.5°	1540.4
30°	1286.5
32.5°	1075.7
35°	863.2
37.5°	634.1
40°	381.8
42.5°	220.8
45°	134.4
47.5°	86.3
50°	54.8
52.5°	31.6
55°	13.3
57.5°	6.6
60°	5.0
62.5°	5.0
65°	3.3
67.5°	3.3
70°	1.6
72.5°	1.6
75°	1.6
77.5°	1.6
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)