

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P582730

Luminaire Tested: **HC650D010-HM64560830-61WDBB**

Issue Date: 9/16/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P582730  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-11)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/16/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HC650D010-HM64560830-61WDBB  
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" WIDE DISTRIBUTION, BLACK BAFFLE TRIM  
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4603.1 lumens  
Efficiency: N/A  
Efficacy: 95.9 lumens/watt  
Spacing Criteria (0/90/45): 1.32 / 1.32 / 1.14  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct


Input Watts (W): 48  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P582730

CATALOG NUMBER: HC650D010-HM64560830-61WDBB

### Luminous Intensity Polar Plot





TEST NUMBER: P582730

CATALOG NUMBER: HC650D010-HM64560830-61WDBB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	97	95	94	92	92	92	92
2	107	101	97	93	104	100	95	92	96	93	90	93	91	88	90	88	86	85	85	85	85
3	100	93	88	83	98	92	87	83	89	85	81	87	83	80	84	81	79	77	77	77	77
4	95	86	80	75	93	85	79	75	83	78	74	81	77	73	79	75	72	71	71	71	71
5	89	80	73	68	87	79	73	68	77	72	67	75	70	67	73	69	66	65	65	65	65
6	84	74	67	62	82	73	67	62	71	66	62	70	65	61	69	64	61	59	59	59	59
7	79	68	62	57	77	68	61	57	66	61	57	65	60	56	64	59	56	54	54	54	54
8	74	64	57	52	73	63	57	52	62	56	52	61	56	52	60	55	52	50	50	50	50
9	70	59	53	48	69	59	53	48	58	52	48	57	52	48	56	51	48	46	46	46	46
10	66	56	49	45	65	55	49	45	54	48	45	53	48	44	53	48	44	43	43	43	43

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	163474
5°	164670
10°	167549
15°	174189
20°	181491
25°	187971
30°	185453
35°	154519
40°	99086
45°	49478
50°	19633
55°	6671
60°	1919
65°	1362
70°	1122
75°	1483
80°	1105
85°	0



TEST NUMBER: P582730

CATALOG NUMBER: HC650D010-HM64560830-61WDBB

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	286.1	6.2
10°-20°	870.5	18.9
20°-30°	1421.4	30.9
30°-40°	1393.4	30.3
40°-50°	534.2	11.6
50°-60°	78.4	1.7
60°-70°	11.6	0.3
70°-80°	6.0	0.1
80°-90°	1.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2578.0	56.0
0°-40°	3971.4	86.3
0°-60°	4584.0	99.6
0°-90°	4603.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4603.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2982	
5°	2992	286
15°	3069	871
25°	3108	1421
35°	2309	1393
45°	638	534
55°	70	78
65°	10	12
75°	7	6
85°	0	1
90°	0	



TEST NUMBER: P582730

CATALOG NUMBER: HC650D010-HM64560830-61WDBB

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2982.0
2.5°	2975.1
5°	2992.4
7.5°	3002.9
10°	3009.9
12.5°	3034.3
15°	3069.2
17.5°	3097.1
20°	3111.0
22.5°	3114.5
25°	3107.6
27.5°	3058.7
30°	2929.7
32.5°	2685.5
35°	2308.9
37.5°	1845.0
40°	1384.6
42.5°	987.0
45°	638.2
47.5°	390.7
50°	230.2
52.5°	132.5
55°	69.8
57.5°	31.4
60°	17.5
62.5°	13.9
65°	10.5
67.5°	10.5
70°	7.0
72.5°	7.0
75°	7.0
77.5°	3.5
80°	3.5
82.5°	3.5
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P







— 0°-180°







(END OF REPORT)