

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P582923

Luminaire Tested: **HC605D010-HM60525927-61NDH**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P582923
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-2)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC605D010-HM60525927-61NDH
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" NARROW DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 544.3 lumens
Efficiency: N/A
Efficacy: 90.7 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.89
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P582923

CATALOG NUMBER: HC605D010-HM60525927-61NDH

Luminous Intensity Polar Plot





TEST NUMBER: P582923

CATALOG NUMBER: HC605D010-HM60525927-61NDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|---|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | |
| 1 | 113 | 111 | 108 | 106 | 111 | 109 | 106 | 104 | 105 | 103 | 101 | 101 | 99 | 98 | 97 | 96 | 95 | 93 | | | |
| 2 | 108 | 103 | 99 | 96 | 106 | 101 | 98 | 94 | 98 | 95 | 92 | 95 | 93 | 90 | 92 | 90 | 89 | 87 | | | |
| 3 | 102 | 96 | 91 | 87 | 100 | 95 | 90 | 86 | 92 | 88 | 85 | 90 | 86 | 84 | 87 | 85 | 82 | 81 | | | |
| 4 | 97 | 90 | 84 | 80 | 95 | 88 | 83 | 79 | 86 | 82 | 78 | 84 | 81 | 78 | 82 | 79 | 77 | 75 | | | |
| 5 | 92 | 84 | 78 | 74 | 91 | 83 | 77 | 73 | 81 | 76 | 73 | 79 | 75 | 72 | 78 | 74 | 71 | 70 | | | |
| 6 | 88 | 79 | 73 | 68 | 86 | 78 | 72 | 68 | 76 | 71 | 68 | 75 | 71 | 67 | 74 | 70 | 67 | 65 | | | |
| 7 | 83 | 74 | 68 | 64 | 82 | 73 | 68 | 63 | 72 | 67 | 63 | 71 | 66 | 63 | 70 | 66 | 62 | 61 | | | |
| 8 | 79 | 70 | 64 | 59 | 78 | 69 | 63 | 59 | 68 | 63 | 59 | 67 | 62 | 59 | 66 | 62 | 59 | 57 | | | |
| 9 | 75 | 66 | 60 | 56 | 74 | 65 | 59 | 56 | 64 | 59 | 55 | 63 | 59 | 55 | 62 | 58 | 55 | 54 | | | |
| 10 | 72 | 62 | 56 | 52 | 71 | 62 | 56 | 52 | 61 | 56 | 52 | 60 | 55 | 52 | 59 | 55 | 52 | 51 | | | |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|-------|
| | 0° |
| 0° | 33320 |
| 5° | 33183 |
| 10° | 32392 |
| 15° | 30749 |
| 20° | 27413 |
| 25° | 23088 |
| 30° | 18395 |
| 35° | 13124 |
| 40° | 7056 |
| 45° | 3024 |
| 50° | 1382 |
| 55° | 497 |
| 60° | 252 |
| 65° | 195 |
| 70° | 176 |
| 75° | 64 |
| 80° | 95 |
| 85° | 0 |



TEST NUMBER: P582923

CATALOG NUMBER: HC605D010-HM60525927-61NDH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 56.9 | 10.5 |
| 10°-20° | 150.2 | 27.6 |
| 20°-30° | 173.9 | 32.0 |
| 30°-40° | 120.3 | 22.1 |
| 40°-50° | 34.7 | 6.4 |
| 50°-60° | 6.0 | 1.1 |
| 60°-70° | 1.5 | 0.3 |
| 70°-80° | 0.6 | 0.1 |
| 80°-90° | 0.1 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 381.0 | 70.0 |
| 0°-40° | 501.3 | 92.1 |
| 0°-60° | 542.1 | 99.6 |
| 0°-90° | 544.3 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 544.3 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-----|------|
| 0° | 608 | |
| 5° | 603 | 57 |
| 15° | 542 | 150 |
| 25° | 382 | 174 |
| 35° | 196 | 120 |
| 45° | 39 | 35 |
| 55° | 5 | 6 |
| 65° | 2 | 2 |
| 75° | 0 | 1 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P582923

CATALOG NUMBER: HC605D010-HM60525927-61NDH

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|-------|
| 0° | 607.8 |
| 2.5° | 605.2 |
| 5° | 603.0 |
| 7.5° | 596.2 |
| 10° | 581.9 |
| 12.5° | 564.7 |
| 15° | 541.8 |
| 17.5° | 509.5 |
| 20° | 469.9 |
| 22.5° | 425.9 |
| 25° | 381.7 |
| 27.5° | 336.3 |
| 30° | 290.6 |
| 32.5° | 244.9 |
| 35° | 196.1 |
| 37.5° | 145.4 |
| 40° | 98.6 |
| 42.5° | 62.3 |
| 45° | 39.0 |
| 47.5° | 25.1 |
| 50° | 16.2 |
| 52.5° | 9.7 |
| 55° | 5.2 |
| 57.5° | 3.1 |
| 60° | 2.3 |
| 62.5° | 1.9 |
| 65° | 1.5 |
| 67.5° | 1.1 |
| 70° | 1.1 |
| 72.5° | 0.8 |
| 75° | 0.3 |
| 77.5° | 0.3 |
| 80° | 0.3 |
| 82.5° | 0.3 |
| 85° | 0.0 |
| 87.5° | 0.0 |
| 90° | 0.0 |



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)