

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P583074

Luminaire Tested: **HC655D010-HM64560927-61WDH**

Issue Date: 9/16/2021

**Test Information**

Test Method: LM-41-14  
Report Number: P583074  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-8)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 9/16/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: HC655D010-HM64560927-61WDH  
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" WIDE DISTRIBUTION, HAZE TRIM  
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4159.4 lumens  
Efficiency: N/A  
Efficacy: 80.0 lumens/watt  
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.08  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct


Input Watts (W): 52  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P583074

CATALOG NUMBER: HC655D010-HM64560927-61WDH

### Luminous Intensity Polar Plot





TEST NUMBER: P583074

CATALOG NUMBER: HC655D010-HM64560927-61WDH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	103	101	100	100	98	97	96	95	94	92	92	92	92
2	106	101	96	93	104	99	95	92	96	92	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	91	86	82	89	84	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	85	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	89	79	73	68	87	78	72	68	76	71	67	75	70	66	73	69	66	64	64	64	64
6	83	73	67	62	82	73	66	62	71	65	61	70	65	61	68	64	60	59	59	59	59
7	79	68	62	57	77	68	61	57	66	60	56	65	60	56	64	59	56	54	54	54	54
8	74	64	57	52	73	63	57	52	62	56	52	61	56	52	60	55	51	50	50	50	50
9	70	59	53	48	69	59	53	48	58	52	48	57	52	48	56	51	48	46	46	46	46
10	66	56	49	45	65	55	49	45	54	49	45	53	48	45	53	48	44	43	43	43	43

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	162898
5°	163988
10°	165884
15°	169280
20°	170231
25°	164931
30°	149618
35°	121653
40°	80744
45°	44943
50°	25202
55°	13983
60°	7719
65°	5850
70°	4055
75°	2987
80°	1799
85°	1761



TEST NUMBER: P583074

CATALOG NUMBER: HC655D010-HM64560927-61WDH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	284.4	6.8
10°-20°	841.0	20.2
20°-30°	1239.6	29.8
30°-40°	1108.7	26.7
40°-50°	481.0	11.6
50°-60°	141.3	3.4
60°-70°	45.1	1.1
70°-80°	16.0	0.4
80°-90°	2.3	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2365.1	56.9
0°-40°	3473.8	83.5
0°-60°	4096.1	98.5
0°-90°	4159.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4159.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2972	
5°	2980	284
15°	2983	841
25°	2727	1240
35°	1818	1109
45°	580	481
55°	146	141
65°	45	45
75°	14	16
85°	3	2
90°	0	



TEST NUMBER: P583074

CATALOG NUMBER: HC655D010-HM64560927-61WDH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2971.5
2.5°	2963.1
5°	2980.0
7.5°	2985.5
10°	2980.0
12.5°	2980.0
15°	2982.7
17.5°	2965.9
20°	2918.0
22.5°	2836.5
25°	2726.7
27.5°	2572.0
30°	2363.6
32.5°	2116.0
35°	1817.8
37.5°	1477.3
40°	1128.3
42.5°	824.4
45°	579.7
47.5°	413.7
50°	295.5
52.5°	211.0
55°	146.3
57.5°	98.5
60°	70.4
62.5°	56.3
65°	45.1
67.5°	33.7
70°	25.3
72.5°	19.8
75°	14.1
77.5°	11.2
80°	5.7
82.5°	2.8
85°	2.8
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P







— 0°-180°







(END OF REPORT)